

MONGO DB

MongoDB is a free and open-source cross-platform document-oriented database. Classified as a NoSQL database, MongoDB avoids the traditional table-based relational database structure in favor of JSON-like documents with dynamic schemas, making the integration of data in certain types of applications easier and faster.

Create Database using mongosh

After connecting to your database using mongosh, you can see which database you are using by typing db in your terminal.

If you have used the connection string provided from the MongoDB Atlas dashboard, you should be connected to the myFirstDatabase database.

Show all databases

To see all available databases, in your terminal type show dbs.

Notice that myFirstDatabase is not listed. This is because the database is empty. An empty database is essentially non-existent.

Change or Create a Database

You can change or create a new database by typing use then the name of the database.

Create Collection using mongosh

You can create a collection using the createCollection() database method.

Insert Documents

```
insertOne() db.posts.insertOne({title: "Post Title 1", body: "Body of post.", category: "News", likes: 1, tags: ["news", "events"], date: Date() })
```

EXERCISE 18

Structure of 'restaurants' collection:

```
{
  "address": {
    "building": "1007",
    "coord": [ -73.856077, 40.848447 ],
    "street": "Morris Park Ave",
    "zipcode": "10462"
  },
  "borough": "Bronx",
  "cuisine": "Bakery",
  "grades": [
    { "date": { "$date": 1393804800000 }, "grade": "A", "score": 2 },
    { "date": { "$date": 1378857600000 }, "grade": "A", "score": 6 },
    { "date": { "$date": 1358985600000 }, "grade": "A", "score": 10 },
    { "date": { "$date": 1322006400000 }, "grade": "A", "score": 9 },
    { "date": { "$date": 1299715200000 }, "grade": "B", "score": 14 }
  ],
  "name": "Morris Park Bake Shop",
  "restaurant_id": "30075445"
}
```

1. Write a MongoDB query to find the restaurant Id, name, borough and cuisine for those restaurants which prepared dish except 'American' and 'Chinees' or restaurant's name begins with letter 'Wil'.

Ans : `db.restaurants.find({$or:[{name:{ $regex:/^Wil/i}}, {cuisine :{$nin : ["American","Chinese"]}}]}, {restaurant_id:1,name:1,borough:1,cuisine:1});`

2. Write a MongoDB query to find the restaurant Id, name, and grades for those restaurants which achieved a grade of "A" and scored 11 on an ISODate "2014-08-11T00:00:00Z" among many of survey dates.

Ans:

`db.restaurants.find({"grades":{"$elemMatch:{grade:"A",score:11,date:ISODate("2014-08-11T00:00:00Z")}}},{restaurant_id:1,name:1,grades:1});`

3. Write a MongoDB query to find the restaurant Id, name and grades for those restaurants where the 2nd element of grades array contains a grade of "A" and score 9 on an ISODate "2014-08-11T00:00:00Z".

Ans:

`db.restaurants.find({"grades.1.grade":"A","grades.1.score":9,"grades.1.date":ISODate("2014-08-11T00:00:00Z")},{restaurant_id:1,name:1,grades:1});`

4. Write a MongoDB query to find the restaurant Id, name, address and geographical location for those restaurants where 2nd element of coord array contains a value which is more than 42 and upto 52.

Ans: `db.restaurants.find({"address.coord.1":{"$gt:42,$lte:52"}},
{restaurant_id:1,name:1,address:1})`

5. Write a MongoDB query to arrange the name of the restaurants in ascending order along with all the columns.

Ans: `db.restaurants.find().sort({name:1});`

6. Write a MongoDB query to arrange the name of the restaurants in descending order along with all the columns.

Ans: `db.restaurants.find().sort({name:-1});`

7. Write a MongoDB query to arrange the name of the cuisine in ascending order and for that same cuisine borough should be in descending order.

Ans: `db.restaurants.find().sort({cuisine:1,borough:-1});`

8. Write a MongoDB query to know whether all the addresses contains the street or not.

Ans: `db.restaurants.find({"address.street":{"$exists:true}});`

9. Write a MongoDB query which will select all documents in the restaurants collection where the coord field value is Double.

Ans: `db.restaurants.find({"address.coord":{"$type:"double"}});`

10. Write a MongoDB query which will select the restaurant Id, name and grades for those restaurants which returns 0 as a remainder after dividing the score by 7.

Ans: `db.restaurants.find({"grades.score":{"$mod:[7,0]}},{restaurant_id:1,name:1,grades:1});`

11. Write a MongoDB query to find the restaurant name, borough, longitude and attitude and cuisine for those restaurants which contains 'mon' as three letters somewhere in its name.

Ans:

`db.restaurants.find({name:{regex:/mon/i}},{name:1,borough:1,"address.coord":1,cuisine:1});`

12. Write a MongoDB query to find the restaurant name, borough, longitude and latitude and cuisine for those restaurants which contain 'Mad' as first three letters of its name.

Ans:

`db.restaurants.find({name:{regex:/^Mad/i}},{name:1,borough:1,"address.coord":1,cuisine:1});`

13. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5.

Ans: `db.restaurants.find({"grades.score":{"$lt:5}});`

14. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan.

Ans: `db.restaurants.find({borough:"Manhattan","grades.score":{"$lt:5}});`

15. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn.

Ans:

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]},"grades.score":{$lt:5}});
```

16. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

Ans:

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]},cuisine:{$ne:"American"},"grades.score":{$lt:5}});
```

17. Write a MongoDB query to find the restaurants that have at least one grade with a score of less than 5 and that are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

Ans:

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]},cuisine:{$nin:["American","Chinese"]},"grades.score":{$lt:5}});
```

18. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6.

Ans:

```
db.restaurants.find({"grades.score":{$all:[2,6]}});
```

19. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan.

Ans:

```
db.restaurants.find({borough:"Manhattan","grades.score":{$all:[2,6]}});
```

20. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn.

Ans:

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]},"grades.score":{$all:[2,6]}});
```

21. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American.

Ans:

```
db.restaurants.find({borough:{$in:["Manhattan","Brooklyn"]},cuisine:{$ne:"American"},"grades.score":{$all:[2,6]}});
```

22. Write a MongoDB query to find the restaurants that have a grade with a score of 2 and a grade with a score of 6 and are located in the borough of Manhattan or Brooklyn, and their cuisine is not American or Chinese.

Evaluation Procedure	Marks awarded
PL/SQL Procedure(5)	5
Program/Execution (5)	5
Viva(5)	5
Total (15)	15
Faculty Signature	<i>T B M</i>