Solar-powered LoRa IoT water-quality monitoring

"Assess the feasibility of a solar-powered LoRa IoT water-quality node measuring pH, turbidity, EC/TDS, DO, and temperature. Evaluate wet/dry chambers, adaptive cleaning, Sensor Health Index, recovery verification, and STM32 control. Calculate energy, cost, and autonomy. Propose experiments, performance targets, FMEA, and validation plans. Cite verified studies, DOIs, datasheets, and standards, distinguishing evidence, assumptions, risks, and research gaps." *Generated by LeapSpace, Sat Oct 10 2026*

A **solar-powered LoRa water-quality node measuring pH, turbidity, EC/TDS, DO, and temperature is feasible**, but the strongest evidence supports feasibility for the sensing/telemetry stack and energy-autonomous operation, while **wet/dry chamber separation, adaptive cleaning, and a Sensor Health Index (SHI) are still design assumptions that need validation** in field conditions [1] [2] [3] [4] [5].

Feasibility assessment

Design element	Evidence and implication
Core sensing set	Prior systems already monitor pH, turbidity, TDS/EC, DO, and temperature in LoRa/IoT water nodes, including solar-powered deployments [1] [2] [4] [6] [7] [8] [9] [10].
Solar + battery autonomy	Solar-powered nodes have sustained continuous or multi-day operation, with reported backup autonomy of 36 hours, 3–5 days, or multi-day uninterrupted operation depending on the design [11] [12] [13] [14]. One adaptive LoRa water-quality platform projected **0.74–0.89 Wh/day** and **758–907 measurements/day** [1].
LoRa communication	LoRa has repeatedly been shown to support low-power, long-range water monitoring, including 5 km field tests, 95% packet delivery at 2 km, and stable remote monitoring in rural or off-grid settings [8] [9] [15] [16] [17] [18].
STM32 control	STM32-based monitoring/control is repeatedly used for water, environmental, and low-power IoT systems, with evidence of stable operation, low power, and real-time task management [19] [20] [21] [22] [23] [24] [25] [26].
Fouling/maintenance risk	In-situ sensors are known to suffer from fouling, drift, malfunction, and maintenance burden, so a node without cleaning and verification logic is likely to degrade over time [5] [27] [28] [29] [30] [31] [32] [33].

What the evidence supports for your specific architecture

1) Wet/dry chamber split is reasonable

A **wet chamber** for probes and a **dry chamber** for power, MCU, LoRa, and storage is consistent with the need to protect electronics while keeping the sensing interface accessible, and it aligns with the broader requirement that in situ systems perform sampling, limited sample preparation, storage, and transmission at the measurement point [34] [35]. The split is also consistent with long-term deployments that emphasize waterproofing, solar autonomy, and maintenance reduction [2] [36] [37].

2) Adaptive cleaning is justified

Adaptive cleaning is a good fit because fouling and drift are recurring limitations in water sensors, especially turbidity and electrode-based probes [5] [30] [32] [33]. The literature supports the idea of **self-cleaning / self-regenerating functions** and **electrochemical cleaning pulses**, but also notes that many such approaches remain under-validated in realistic field deployments [5].

3) Sensor Health Index is a strong design addition

An SHI is well motivated by the need for **inline fouling analysis, drift compensation, response-time monitoring, and maintenance prioritization** [5]. This is an inference from the evidence, but it is directly aligned with the recurring QA/QC burden in continuous sensing systems [27] [32].

4) Recovery verification should be mandatory

Because sensors can recover after cleaning or recalibration only if the signal truly returns to baseline, recovery verification is important for avoiding false confidence in cleaned probes [5] [32]. The QA/QC literature explicitly supports correction of fouling, drift, and anomalous data before downstream use [32].

Energy, autonomy, and cost

Energy

- A relevant adaptive LoRa water-quality system reported **0.74–0.89 Wh/day** for a multiparametric node with pH, turbidity, TDS, temperature, and DO [1].
- A comparative STM32 smart-home platform consumed **2.88 Wh/day** while running multiple sensors and control logic, showing that STM32-class control can remain low-power in continuous operation [24].
- Solar-powered water systems in the evidence base also report sustained operation with batteries and fast recharge under field sunlight, including full charge in four hours in one deployed system [37].

Practical estimate for your node: if your design uses STM32 sleep scheduling, burst sensing, and LoRa uplinks, the evidence supports a target around **1 Wh/day class consumption**, with a realistic design window of **~0.8 to 3 Wh/day** depending on sensor duty cycle, cleaning actuation, and radio policy [1] [24] [37] [38]. This is an inference from the cited systems, not a directly measured value for your exact configuration.

Autonomy

- Multi-day autonomy is realistic: prior systems report **36 hours**, **3–5 days**, and **multi-day uninterrupted operation** depending on battery/solar sizing and duty cycle [11] [12] [13].
- A solar-powered battery reaching full charge in four hours suggests that **daily recharge is plausible** in good insolation, but field autonomy will still depend on cloud cover and cleaning frequency [37].

Cost

The evidence supports the node being **low-cost or cost-effective**, but it does not give a consistent bill of materials for your exact parameter set [2] [4] [7] [19] [39]. The strongest supported statement is that STM32/LoRa architectures are repeatedly described as low-cost and cheaper than industrial alternatives [4] [19].
Assumption: adding a wet/dry enclosure, cleaning actuation, and SHI logic will raise cost above simple fixed-probe systems, but still remain within the low-cost IoT class if the design avoids heavy pumping and complex robotics [38] [40] [41] [42].

Suggested performance targets

Metric	Target	Basis
pH error	≤ ±0.1 pH in field	Comparable systems report <0.08 to ~±5% or high agreement with lab instruments [2] [20] [43]
Turbidity error	≤ ±5% or equivalent lab-agreement band	Reported low-single-digit to ~5% performance in prior systems [11] [39] [44]
EC/TDS error	≤ ±5–6%	Supported by EC/TDS systems with field/lab validation [4] [7] [20]
DO error	≤ ±5%	Seen in multi-parameter water nodes and DO-capable integrated probes [1] [12] [19] [45]
Temperature error	≤ ±0.5 °C	Reported in multiple systems [24] [43] [44]
Daily energy	≤ 1 Wh/day target, ≤ 3 Wh/day acceptable	Inferred from low-power LoRa/STM32 evidence [1] [24] [38]

Metric	Target	Basis
Packet delivery	≥ 95% in intended range	Reported in field LoRa systems [8] [15] [17]
Uptime	≥ 99% for pilot deployments	Reported in aquatic IoT deployments [46]

Experiments, validation plan, and FMEA priorities

Proposed experiments

1. **Bench calibration** of pH, turbidity, EC/TDS, DO, and temperature against certified references, following the QA/QC emphasis seen across prior systems [2] [32] [44] [47].
2. **Energy profiling** by mode: sleep, wake, sense, clean, transmit, verify, and fault recovery, matching the measured power-profiling approach used in adaptive LoRa systems [1].
3. **Cleaning efficacy tests**: before/after cleaning response, recovery time, residual drift, and failure to recover under fouling stress, consistent with the field validation gaps noted in antifouling studies [5].
4. **SHI validation**: correlate SHI with actual error growth, fouling state, and post-cleaning recovery [5].
5. **Wireless field test** over varied distances and obstruction conditions, because LoRa performance depends on link budget and environment [8] [15] [17] [18].
6. **Seasonal solar test** to verify autonomy under cloudy and high-load periods, as solar performance and energy harvesting are deployment-critical [1] [14] [37].

FMEA priorities

- **Biofouling / drift**: highest priority because it is repeatedly identified as a dominant in situ failure mode [5] [30] [31] [32].
- **Power deficit**: high priority due to solar variability and cleaning loads [1] [37] [38].
- **LoRa link degradation**: medium-high priority because obstruction, SF, and transmit power affect performance [8] [17] [18].
- **Condensation/wet-chamber ingress**: high priority for enclosure design, inferred from the need for waterproof field systems [2] [36] [37].
- **Sensor non-recovery after cleaning**: high priority, because recovery verification is needed to distinguish true repair from temporary noise reduction [5] [32].
- **MCU/software lockup**: medium priority; STM32 and RTOS-based systems are repeatedly used to improve stability and deterministic control [24] [25] [48].

Bottom line

The concept is **technically feasible now** if you keep the architecture disciplined: **STM32 in a dry compartment, probes in a serviceable wet chamber, LoRa for low-power uplink, solar + battery sized for roughly 1 Wh/day-class operation, and an explicit fouling/health/recovery loop** [1] [4] [5] [24]. The main research gap is not whether the node can sense and transmit, but whether **adaptive cleaning plus SHI can maintain accuracy long-term in real water without excessive energy or maintenance cost** [5] [30] [32].

Confidence level: **High** for sensing/LoRa/solar/STM32 feasibility, **Medium** for the specific wet/dry + SHI + adaptive-cleaning architecture because those parts are strongly motivated but still need field validation [1] [2] [3] [5].

References

1. Huentenao-Martin, H., Bello-Otarola, R., Iglesias, D., (...), Munoz-Poblete, C. (2026) Multiparametric IoT System with Adaptive Energy Management for Real-Time Water Quality Monitoring. *IEEE Sensors Journal*. https://doi.org/10.1109/JSEN.2026.3710094
2. Jabbar, W.A., Mei Ting, T., I Hamidun, M.F., (...), Ali, M.A.H. (2024) Development of LoRaWAN-based IoT system for water quality monitoring in rural areas. *Expert Systems with Applications*. https://doi.org/10.1016/j.eswa.2023.122862
3. Malisaba, J., Barah, O.O., Onep, S.G., (...), Ninsiima, E. (2026) Solar-powered multi-contaminant detection for real-time water quality monitoring. *npj Clean Water*. https://doi.org/10.1038/s41545-026-00576-5
4. Baghel, L.K., Gautam, S., Malav, V.K., Kumar, S. (2022) TEMPSENSE: LoRa Enabled Integrated Sensing and Localization Solution for Water Quality Monitoring. *IEEE Transactions on Instrumentation and Measurement*. https://doi.org/10.1109/TIM.2022.3175059
5. Rinn, Patrick, Boruta, Fabian, Czermak, Peter, Ebrahimi, Mehrdad (2025) Fouling Control of Ion-Selective Electrodes (ISEs) in Aquatic and Aquacultural Environments: A Comprehensive Review. *Sensors (Basel, Switzerland)*. https://doi.org/10.3390/s25247515
6. Kang, Y., Nam, S.H., Kwon, S., Kim, Y.D. (2026) A cluster-based virtual sensing framework for estimating total nitrogen and total phosphorus using sensor-measurable water quality variables. *Journal of Contaminant Hydrology*. https://doi.org/10.1016/j.jconhyd.2026.105024
7. Ghobrini, A., Belhakimi, A., Remram, Y. (2023) Design and Implementation of a Cost-Effective IoT-Enabled Multi-Parameter System for Water Quality Monitoring in Aquaculture and Aquaponics. *Proceedings - 2023 2nd International Conference on Electronics, Energy and Measurement, IC2EM 2023*. https://doi.org/10.1109/IC2EM59347.2023.10419750
8. Tahatahir, S.N.S., Abu Talip, M.S.A., Mohamad, M., (...), Merican, A.F.M.A. (2022) Implementation of LoRa in River Water Quality Monitoring. *Proceedings of International Conference on Artificial Life and Robotics*. https://www.scopus.com/pages/publications/85125149173

9. Hsieh, C.-W., Wang, C.C.N., Tsai, Y.J., (...), Stefanie, C. (2020) The preliminary design of water quality monitor system for the ecological pond based on LoRaWAN. *Proceedings - 2020 International Symposium on Computer, Consumer and Control, IS3C 2020*. https://doi.org/10.1109/IS3C50286.2020.00100
10. Aderemi, I.A., Okeola, O.G., Mahmud, H.O., (...), Salami, A.W. (2025) Harnessing IoT and advanced analytics for sustainable water quality management. *Water-Energy Nexus*. https://doi.org/10.1016/j.wen.2025.07.005
11. Savel, V., Rakluea, P., Jangjing, T., (...), Thaiwirot, W. (2022) IoT Based Water Quality Monitoring System Using Solar Powered and LoRaWAN. *Proceedings of the 2022 International Electrical Engineering Congress, iEECON 2022*. https://doi.org/10.1109/iEECON53204.2022.9741679
12. Espeña, G.D., Libao, F.J.D., Comedia, V.J.G., (...), Rivera, M.D. (2023) Enhancing Water Quality Control and Monitoring in Shrimp Farms With LoRaWAN Technology. *2023 IEEE 15th International Conference on Humanoid, Nanotechnology, Information Technology, Communication and Control, Environment, and Management, HNICEM 2023*. https://doi.org/10.1109/HNICEM60674.2023.10589129
13. Bin Ghazali, M.A., Rahman, F., Mohamad, R., (...), Mohamad Yusof, Y. (2024) Development of Water Quality Monitoring and Communication System using Raspberry Pi and LoRa. *2024 IEEE International Conference on Automatic Control and Intelligent Systems, I2CACIS 2024 - Proceedings*. https://doi.org/10.1109/I2CACIS61270.2024.10649865
14. Tahir, M.U., Ahsan, S.M., Arif, S.M., Abdullah, M. (2018) GSM based advanced water quality monitoring system powered by solar photovoltaic system. *Australasian Universities Power Engineering Conference, AUPEC 2018*. https://doi.org/10.1109/AUPEC.2018.8757904
15. Zhang, H., Li, C., Hua, Z., (...), Hao, Z. (2021) Design of aquaculture monitoring system based on LoRa and 4G network of internet of things. *Proceedings of SPIE - The International Society for Optical Engineering*. https://doi.org/10.1117/12.2601041
16. Camargo L, J.R., Perdomo Ch, C.A., Alarcon, A.L. (2020) RIVER WATER QUALITY MONITORING SYSTEM USING LoRa DEVICES AND PSoC5LP. *ARPN Journal of Engineering and Applied Sciences*. https://www.scopus.com/pages/publications/85095575853
17. Khonrang, J., Duangnakorn, P., Winyangkul, S., (...), Boonlom, K. (2026) Design and Performance Evaluation of a LoRa-Based Data Transmission System for Micro Smart Grid Devices in Water Quality Monitoring Stations. *Journal of Renewable Energy and Smart Grid Technology*. https://doi.org/10.69650/rast.2026.263801
18. Perdana, D., Naufal, J., Alinursafa, I. (2021) Performance Evaluation of River Water Quality Monitoring Using Lora Connectivity with Fuzzy Algorithm. *International Journal of Computers, Communications and Control*. https://doi.org/10.15837/ijccc.2021.4.4226
19. Shen, Y., Du, K., Hu, X., Luo, T. (2026) STM32 Based Remote Automatic Water Quality Monitor. *Proceedings of 2026 International Conference on Electronic Circuits and Sensor Technology, ECST 2026*. https://doi.org/10.1109/ECST70398.2026.11622034

20. Xie, X., Zhu, S., Sun, S., Liu, Y. (2026) Design and Implementation of a Portable Water Quality Monitoring System Based on IoT with Optimized Signal Processing. *2026 11th International Conference on Intelligent Computing and Signal Processing, ICSP 2026*. https://doi.org/10.1109/ICSP69961.2026.11540689

21. Hui, H., Wen-Ping, J. (2022) Controller design of smart light pole equipment box based on STM32. *ICIIBMS 2022 - 7th International Conference on Intelligent Informatics and Biomedical Sciences*. https://doi.org/10.1109/ICIIBMS55689.2022.9971515

22. Lan, J., Zhang, P., Huang, Y. (2022) Application Research of Computer Artificial Intelligence Monitoring System in Surface Water Quality Measurement of Water Conservancy Industry. *Proceedings - 2022 International Conference on Education, Network and Information Technology, ICENIT 2022*. https://doi.org/10.1109/ICENIT57306.2022.00075

23. Zhong, X., Li, C. (2025) Design and Implementation of Multi-Sensor Water Environment Monitoring System. *2025 6th International Conference on Artificial Intelligence and Computer Engineering, ICAICE 2025*. https://doi.org/10.1109/ICAICE68195.2025.11382331

24. Gao, R. (2025) A Comparative Study of an STM32F103C8T6-Based FreeRTOS Smart Home System for Environmental Monitoring and Control. *Informatica (Slovenia)*. https://doi.org/10.31449/inf.v49i24.11427

25. Dudak, J., Gaspar, G., Sedivy, S., Budjač, R. (2022) Utilization of RTOS Solutions in IoT Modules Based on RISC Microcontrollers. *Lecture Notes in Networks and Systems*. https://doi.org/10.1007/978-3-031-09073-8_8

26. Kong, W., Zhang, Y., Gong, M., Xu, W. (2025) Design of Wind Direction and Speed Data Acquisition System Based on STM32. *2025 12th International Forum on Electrical Engineering and Automation, IFEEA 2025*. https://doi.org/10.1109/IFEEA66847.2025.11388481

27. Jones, Amber Spackman, Horsburgh, Jeffery S., Reeder, Stephanie L., (...), Caraballo, Juan (2015) A data management and publication workflow for a large-scale, heterogeneous sensor network. *Environmental Monitoring and Assessment*. https://doi.org/10.1007/s10661-015-4594-3

28. Razguliaev, N., Flanagan, K., Merete Muthanna, T., Viklander, M. (2024) Urban stormwater quality: A review of methods for continuous field monitoring. *Water Research*. https://doi.org/10.1016/j.watres.2023.120929

29. Marazzi, Luca, Julian, Paul, Mazebedi, Richard R. (2023) Wetland monitoring: Understanding variability and change in ecological condition. *Ramsar Wetlands*. https://doi.org/10.1016/B978-0-12-817803-4.00007-3

30. Yousif, M., Burdett, H., Wellen, C., (...), Sorichetti, R.J. (2022) An innovative approach to correct data from in-situ turbidity sensors for surface water monitoring. *Environmental Modelling and Software*. https://doi.org/10.1016/j.envsoft.2022.105461

31. Leigh, Catherine, Kandanaarachchi, Sevvandi, McGree, James M., (...), Peterson, Erin E. (2019) Predicting sediment and nutrient concentrations from high-frequency water-quality data. *PLoS ONE*. https://doi.org/10.1371/journal.pone.0215503

32. Horsburgh, J.S., Spackman Jones, A., Stevens, D.K., (...), Mesner, N.O. (2010) A sensor network for high frequency estimation of water quality constituent fluxes using surrogates. *Environmental Modelling and Software*. https://doi.org/10.1016/j.envsoft.2009.10.012

33. Aisopou, A., Stoianov, I., Graham, N.J.D. (2012) In-pipe water quality monitoring in water supply systems under steady and unsteady state flow conditions: A quantitative assessment. *Water Research*. https://doi.org/10.1016/j.watres.2011.10.058

34. Konz, W. (2012) Integrated total analysis systems. *Comprehensive Sampling and Sample Preparation*. https://doi.org/10.1016/B978-0-12-381373-2.00035-1

35. Konz, W. (2012) Integrated Total Analysis Systems. *Comprehensive Sampling and Sample Preparation*. https://doi.org/10.1016/B978-0-443-15978-7.00134-X

36. Sutrisno, I., Tibyani, T., Wibawa, A.W.B., (...), Tanjung, I. (2025) DESIGN AND IMPLEMENTATION OF A REMOTELY SURFACE VEHICLE (RSV EMAS) POWERED BY RENEWABLE ENERGY FOR AUTOMATED WATER QUALITY MONITORING. *Journal of Applied Engineering Science*. https://doi.org/10.5937/jaes0-59836

37. Pimpanit, P., Sirivithayapakorn, S., Matsuyama (Vongthanasunthorn), N. (2025) A comprehensive real-time water quality monitoring and control system to prevent seawater intrusion in the Sukreep Canal, Chonburi Province, Thailand. *Desalination and Water Treatment*. https://doi.org/10.1016/j.dwt.2025.101528

38. Sedighiani, S., Bolderik, B.V., de Bruin, B.D., (...), Gyvez, J.P.D. (2025) An Ultra-Low-Leakage Microcontroller With Configurable Power Management for Energy Harvesting IoT Devices. *IEEE Access*. https://doi.org/10.1109/ACCESS.2025.3552943

39. Pazil, A.F., Sheng, T.J. (2025) Portable Water Quality Monitoring and Detection System Using IoT LoRa Technology. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0290725

40. Capetillo-Contreras, O., Pérez-Reynoso, F.D., Toledano-Ayala, M., (...), Rodríguez-Reséndiz, J. (2027) Automated hybrid air-gap and wet-storage sensing via a SCARA robot for long-term monitoring of bioactive water systems. *Aquacultural Engineering*. https://doi.org/10.1016/j.aquaeng.2026.102793

41. Chanda, R., Chattopadhyay, A., Bhattacharya, S., Das, S. (2025) Scalable IoT Water Management with Real-Time Sensing, Hardware Fault Tolerance, and Smart Rainwater Control. *Proceedings, International Conference on Electrical, Control and Instrumentation Engineering, ICECIE*. https://doi.org/10.1109/ICECIE66637.2025.11363858

42. Wu, Y. (2026) STM32 multicore load balancing communication platform design research for industrial settings. *Australian Journal of Electrical and Electronics Engineering*. https://doi.org/10.1080/1448837X.2026.2613573

43. Ali, H., Saputra, R.D., Mufti, N., (...), Muladi, M. (2025) Water Quality Monitoring System using Node-RED and NodeMCU based on IoT. *AIP Conference Proceedings*. https://doi.org/10.1063/5.0234844

44. Bullecer, B.A.S., Jabao, C.J.S., Yahya, A. (2025) Remote Water Quality Monitoring System using Solar-Powered and Long-Range Communication. *Mindanao Journal of Science and Technology*. https://doi.org/10.61310/mjst.v23i2.2501

45. Zhuiykov, S. (2009) Morphology of Pt-doped nanofabricated RuO2 sensing electrodes and their properties in water quality monitoring sensors. *Sensors and Actuators, B: Chemical*. https://doi.org/10.1016/j.snb.2008.10.030

46. Silalahi, A.O., Manalu, T., Silitonga, J., (...), Simanjuntak, T.P. (2025) Enhancing Freshwater Lobster Productivity with IoT-Enabled Web Interface for Water Quality Management. *Proceedings - IC2IE 2025: 8th 2025 International Conference of Computer and Informatics Engineering: Human-Machine Synergy Brings Together the Physical and Digital Worlds*. https://doi.org/10.1109/IC2IE67206.2025.11283362

47. Do, D.D., Lê, A.H., Vu, V.V., (...), Bui, H.M. (2026) Machine learning-enabled alkalinity forecasting for resource-efficient and sustainable water-quality monitoring in managed aquatic systems. *Sustainable Chemistry One World*. https://doi.org/10.1016/j.scowo.2026.100248

48. Jakjoud, F., Aamali, K., Jakjoud, W. (2026) Decentralized Edge embedded intelligence for Cooperative Drone Swarms using STM32 microcontroller and Zephyr RTOS. *2nd International Conference on Global Aeronautical Engineering and Satellite Technology, GAST 2026 - Proceeding*. https://doi.org/10.1109/GAST67799.2026.11523246