

CDAC DAI CCE Mock Test Solutions - 40 Questions

A1: Answer: B

Explanation: List is mutable; elements can be modified after creation.

A2: Answer: B

Explanation: Division of integers using `/` results in a float in Python.

A3: Answer: A

Explanation: `def` is used to define functions in Python.

A4: Answer: B

Explanation: Both `x` and `y` point to the same list, so changes via `y` affect `x`.

A5: Answer:

Explanation: Use `try-except` to catch `ZeroDivisionError`.

A6: Answer:

Explanation: `break` exits the loop prematurely when a condition is met.

A7: Answer: A

Explanation: `open()` is used to open files for reading or writing.

A8: Answer:

Explanation: List comprehension is a concise way to create lists, while `for` loops are more verbose.

A9: Answer: B

Explanation: Adding 4 to the set makes it `{1,2,3,4}`, so length is 4.

A10: Answer:

Explanation: Define the class with `__init__` and `greet` method as shown.

A11: Answer: C

Explanation: Bubble Sort compares adjacent elements and takes $O(n^2)$ in worst case.

A12: Answer: B

Explanation: Stack follows Last-In-First-Out principle.

A13: Answer: B

Explanation: The last appended element 20 is popped first.

A14: Answer:

Explanation: Binary search divides the sorted array to find the target efficiently.

A15: Answer:

Explanation: A hash table stores key-value pairs for fast lookup, as in Python dictionaries.

A16: Answer: A

Explanation: Queue operates in First-In-First-Out order.

A17: Answer:

Explanation: Recursion is a function calling itself with a base case, like factorial computation.

A18: Answer:

Explanation: A tree is a graph with no cycles; graphs can have cycles.

A19: Answer: C

Explanation: Dijkstra's algorithm finds the shortest path in weighted graphs.

A20: Answer: C

Explanation: get() with default value returns 3 when 'c' is missing.

A21: Answer:

Explanation: Supervised learning trains on labeled data to predict outcomes.

A22: Answer:

Explanation: MSE and MAE are common regression loss functions.

A23: Answer: False

Explanation: Deep learning isn't always superior; depends on data size and problem complexity.

A24: Answer:

Explanation: Overfitting occurs when a model memorizes noise; can be prevented with regularization or more data.

A25: Answer:

Explanation: Splitting helps evaluate model performance on unseen data.

A26: Answer: A

Explanation: Min-Max Scaling adjusts data to a specific range, usually [0,1].

A27: Answer:

Explanation: Learning rate controls how fast or slow the model learns during optimization.

A28: Answer:

Explanation: Classification assigns labels; clustering finds groups without labels.

A29: Answer: C

Explanation: Accuracy measures correct predictions over total predictions.

A30: Answer:

Explanation: `from sklearn.preprocessing import StandardScaler`

A31: Answer:

Explanation: Variance = sum of squared differences from the mean divided by n or (n-1).

A32: Answer:

Explanation: Even numbers are {2,4,6}, so probability = $3/6 = 1/2$.

A33: Answer:

Explanation: Correlation shows how two variables change together in a linear fashion.

A34: Answer:

Explanation: Mean is average; median is the middle sorted value.

A35: Answer: True

Explanation: Probabilities of mutually exclusive events always sum to 1.

A36: Answer: C

Explanation: Matplotlib is used for plotting graphs and charts.

A37: Answer:

Explanation: fit() trains the model using data to find optimal parameters.

A38: Answer:

Explanation: Data preprocessing includes cleaning, normalizing, and transforming data for better modeling.

A39: Answer:

Explanation: Use `pandas.read_csv` to load CSV files into a DataFrame.

A40: Answer:

Explanation: `.loc[]` accesses data by labels, `.iloc[]` by index positions.