Status	Finished
Started	Wednesday, 21 October 2026, 10:33 PM
Completed	Wednesday, 21 October 2026, 10:36 PM
Duration	3 mins 22 secs
Grade	**15.00** out of 15.00 (**100**%)

Question **1**

Correct

Mark 1.00 out of 1.00

What is the purpose of the with statement in Python file handling?

a. To write data to a file
b. To delete a file
c. To automatically close the file after its suite finishes ✓
d. To read data from a file

The correct answer is: To automatically close the file after its suite finishes

Question **2**

Correct

Mark 1.00 out of 1.00

What happens if you try to open a file in write mode ('w') and the file already exists?

a. It does nothing
b. It clears the old data and starts fresh ✓
c. It raises an error
d. It appends data to the file

The correct answer is: It clears the old data and starts fresh

Question **3**

Correct

Mark 1.00 out of 1.00

Select the correct method to write a list of lines to a file

a. writelines(list) ✓
b. write(list)
c. writelist(list)
d. None of the mentioned

The correct answer is: writelines(list)

Question **4**

Correct

Mark 1.00 out of 1.00

What does the following code do?

```
f = open("data.txt", "a")
f.write("Adding new data\n")
f.close()
```

- a. Appends "Adding new data" to the end of the file ✓
- b. Raises an error because the file is opened in append mode
- c. Opens the file in read mode
- d. Overwrites the file with "Adding new data"

The correct answer is: Appends "Adding new data" to the end of the file

Question **5**

Correct

Mark 1.00 out of 1.00

What will the read() method return if used on an empty file?

- a. EOFError
- b. 0
- c. An empty string ✓
- d. None

The correct answer is: An empty string

Question **6**

Correct

Mark 1.00 out of 1.00

Which method is used to read a specific number of characters from a file?

- a. readline()
- b. readchar()
- c. read(size) ✓
- d. readlines()

The correct answer is: read(size)

Question **7**

Correct

Mark 1.00 out of 1.00

What is the default mode in which the open() function opens a file?

a. Read ✓
b. Append
c. Binary
d. Write

The correct answer is: Read

Question **8**

Correct

Mark 1.00 out of 1.00

To open a file a.txt for reading, we use _____

a. infile = open(file = “a.txt”, “r”)
b. infile = open(file, “a.txt”, “r”)
c. infile = open(“a.txt”, “r”) ✓
d. infile = open(file = “a.txt”, “r”)

The correct answer is:
infile = open(“a.txt”, “r”)

Question **9**

Correct

Mark 1.00 out of 1.00

Which of the following modes opens a file for both reading and writing?

a. r
b. w
c. a
d. r+ ✓

The correct answer is: r+

Question **10**

Correct

Mark 1.00 out of 1.00

Which method is used to get the current file position?

a. locate()
b. tell() ✓
c. position()
d. current()

The correct answer is: tell()

Question **11**

Correct

Mark 1.00 out of 1.00

What will be the output of the following code if the file "example.txt" contains "Python Programming"?

```
f = open("example.txt", "r")
print(f.read(6))
f.close()
```

a. Python Programming
b. Python ✓
c. An error is raised
d. Program

The correct answer is: Python

Question **12**

Correct

Mark 1.00 out of 1.00

What does the following code do?

fo = open("foo.txt", "w")

a. Creates a new file for writing ✓
b. Opens a file in binary mode
c. Opens an existing file in read mode
d. Appends to an existing file

The correct answer is: Creates a new file for writing

Question **13**

Correct

Mark 1.00 out of 1.00

Which method is used to truncate a file to a specific size?

a. shrink()
b. resize()
c. reduce()
d. truncate() ✓

The correct answer is: truncate()

Question **14**

Correct

Mark 1.00 out of 1.00

Which method is used to close a file in Python?

a. end()
b. terminate()
c. close() ✓
d. finish()

The correct answer is: close()

Question **15**

Correct

Mark 1.00 out of 1.00

f.seek(5,1) means

a. move the file pointer five characters behind from the current position
b. move the file pointer five characters ahead from the current position ✓
c. moves the file pointer to the end of a file
d. move the file pointer to beginning of the file

The correct answer is:
move the file pointer five characters ahead from the current position