NMAP to discover live host using NMAP

Expno: 8 Date:

Aim:

To discover live hosts using Nmap scans on the TryHackMe Platform Room link.

Subnetworks:

→ A network segment is a group of computers linked through a shared medium, like an Ethernet switch or Wi-Fi access point. A network segment is a physical connection, while a subnetwork is a logical connection.

→ The figure displays two types of subnets.

* /16 Subnets: These have a subnet mask of 255.255.0.0 can accomodate approximately 65 thousand hosts.

* /24 subnets: These feature a subnet mask of 255.255.255.0 and can support around 250 hosts.

Enumering Targets:

Before delving into the details of scanning techniques, it's essential to define the targets we want to scan. Targets can be specified in three ways:

i) List: You can provide a list of specific IP addresses or hostnames, like "MACHINE-IP", scanme.nmap.org" and "example.com", which would result is scanning 3 IP addresses.

PDF Image to PDF

ii) Range: You can specify a range such as "10.11.12.15-20", which will scan 6 IP addresses: 10.11.12.15, 10.11.12.16 and so on, upto 10.11.12.20.

iii) Subnet: You can define a subnet like "MACHINE-11°/30", which will scan 4 IP addresses within that subnet.

UDP Ping:

You can also employ UDP to check if the host if the host is online. Unlike TCP SYN ping, sending a UDP packet to an open port typically doesn't elicit a response. However, when sending a UDP packet to a closed UDP port, you anticipate receiving an ICMP "port unreachable" packet, which indicates the target system is active and reachable