

Four-Core Pipelined Implied Volatility & Greeks Engine (Artix-7 200T @ 100 MHz)

AXI4-Stream Ingress
(256-bit S, K, T, r, C_mkt, TID)

Stage 1: Ingress Registration & Queuing (1 Cycle)

- AXI4-Stream 256-bit Ingress: {S, K, T, r, C_mkt, TID}
- Single-Cycle Register + TID Tag
 - No Ingress Divider (Zero Division Latency)
- Q8.24 Fixed-Point Precision

Contract

Stage 2: Analytical Seeder (Brenner-Subrahmanyam, 64 Cyc)

$$\sigma_0 = \frac{2.5066}{\sqrt{T}} \cdot \frac{C_{mkt}}{(S+K)/2}$$

- Shared Digit-Recurrence $\sqrt{T}$ (29 Cyc)
 - Forwards $\sqrt{T}$ Directly to Stage 3
- Non-Restoring Divider (33 Cyc)
- Liquid Error: $|\sigma_0 - \sigma^*|/\sigma^* \leq 0.5\%$ (≤ 0.08 vol in wings)

$\sigma_0, \sqrt{T}$ (Forward)

Stage 3: Core BS Datapath (126 Cycles, II = 1)

- Scale-Invariant Padé Ratio (S-K)/(S+K)
- 18-Cyc CORDIC Log Fallback (SRL15-Matched)
 - Horner 5th-Order Poly CDF N(d1), N(d2)
- Hyperbolic CORDIC for $\exp(-rT)$ & $\exp(-d1^2/2)$
 - Fully Unrolled 126-Stage Feedforward

C_{BS}, ν
(126 Cyc)

Stage 4: NR Update & Dividers (33 Cycles)

- Convergence: $|C_{BS} - C_{mkt}| \leq \0.01
- **u_nr_divider**: $\Delta\sigma = (C_{BS} - C_{mkt})/\nu$
- **u_gamma_divider**: $\Gamma = \phi(d_1)/(S\sigma\sqrt{T})$
 - Greeks: $\Delta = N(d_1)$, $\nu = S\sqrt{T}\phi(d_1)$
 - TID-Scoreboard Priority Loopback

Converged (97.6%)

Stage 5: Multi-Core Arbiter & 128-Bit Egress (2 Cycles)

- Round-Robin 4-Core Complete Drain
- Packed 128-Bit Single-Flit Bus:
 - [127:122] TID Transaction ID (6b)
 - [121:96] Gamma Greek (26b)
 - [95:64] Vega Greek (32b)
 - [63:32] Delta Greek (32b)
 - [31:0] sigma Implied Vol (32b)

AXI4-Stream Egress
(128-bit σ + Full Greeks)

Context

Zero-BRAM Context Store

- 64 x 32-bit Distributed LUTRAM
- SRL32 Delay Shift Registers
 - 0 Block RAMs (Zero-BRAM)
- Preserves 100% RAMB36/18 for 10GbE MAC & PCIe DMA Subsystems

Loopback
 σ_{n+1} (2.4%)