

Four-Core Pipelined Implied Volatility & Greeks Engine (Artix-7 200T @ 100 MHz)

AXI4-Stream Ingress
(256-bit S, K, T, r, C_mkt, TID)

Stage 1: Ingress Registration
& Queuing (1 Cycle)

- AXI4-Stream 256-bit Ingress: {S, K, T, r, C_mkt, TID}
- Single-Cycle Register + TID Tag
 - No Ingress Divider (Zero Division Latency)
- Q8.24 Fixed-Point Precision

Contract

Stage 2: Analytical Seeder
(Brenner-Subrahmanyam, 64 Cyc)

$$\sigma_0 \approx \frac{2,5066 C_{mkt}}{\sqrt{T} (S + K)/2}$$

- Shared Digit-Recurrence $\sqrt{T}$ (29 Cyc, II = 1)
 - Forwards $\sqrt{T}$ Directly to Stage 3
- Non-Restoring Divider (33 Cyc, II = 1)
- Analytical Initial Estimate (Sec 2.4):

Med Abs Err: 0.1037 vol (1,037 vol-bps) | Rel: 30.52% (11.53% ATTC)

CBS, ν
(126 Cyc)

Stage 4: NR Update & Dividers
(33 Cycles, II = 1)

- Convergence: $|C_{BS} - C_{mkt}| \leq \0.01
- **u_nr_divider**: $\Delta\sigma = (C_{BS} - C_{mkt})/\nu$
- **u_gamma_divider**: $\Gamma = \phi(d_1)/(S\sigma\sqrt{T})$
- Greeks: $\Delta = N(d_1)$, $\nu = S\sqrt{T}\phi(d_1)$
- TID-Scoreboard Priority Loopback

Converged → Egress

Zero-BRAM Context Store

- 64 Context Slots / Core (256 Total)
- 60 Active + 4 Headroom Invariant (Prevents Recirculation Deadlock)
 - Distributed LUTRAM & SRL32
- 0 Block RAM / UltraRAM in Core
- Leaves 365 BRAM36 Free for System

Context

Stage 3: Core Feedforward Datapath
(126 Cycles, II = 1)

- II = 1 Pipeline (Reused Across Passes)
- Scale-Invariant Padé Ratio $(S-K)/(S+K)$
- 18-Cyc CORDIC Log Fallback (SRL15-Matched)
 - Horner 5th-Order Poly CDF $N(d_1)$, $N(d_2)$
- Hyperbolic CORDIC for $\exp(-rT)$ & $\exp(-d_1^2/2)$

$\sigma_0, \sqrt{T}$ (Forward)

Nonconverged → σ_{n+1} Recirculation
(Priority Restore to Stage 3)

Stage 5: Multi-Core Arbiter
& 128-Bit Egress (2 Cycles)

- Round-Robin 4-Core Drain Arbiter
 - 128-Bit Data Payload:
 - [127:122] Local TID (6b)
 - [121:96] Delta Greek (26b, Q2.24)
 - [95:64] Gamma Greek (32b, Q8.24)*
 - [63:32] Vega Greek (32b, Q8.24)*
 - [31:0] sigma Implied Vol (32b, Q8.24)
 - Sideband: Core ID (2b)
- *Carries ν^* , Γ^* for normalized inputs

AXI4-Stream Egress
(128b Payload + 2b Core ID Sideband)