

**ILLINOIS INSTITUTE OF TECHNOLOGY
DEPARTMENT OF COMPUTER SCIENCE**

**Database Organization
Course CS-425 02**

Homework No.6

Optional Homework

SQL Advanced window functions & OLAP queries
SalingDB

Professor:

Gerald Balekaki, Ph.D.

T.A.:

Manoj Kumar Yepuri

Student:

Harlee Ramos

Due Date:

07/19/2024

Summer 2024

Consider a Sailing Club Database with Schema:


Boats-schema = (BID, Bname, fee, location)

Sailors-schema = (SID, Sname, rating, age)

Reserves-schema = (SID, BID, day, deposit)

Captains-schema = (SID, Sname, rating, age)

DATABASE CREATION

SQL CODE	CAPTURE
CREATE DATABASE IF NOT EXISTS SailingDB; USE SailingDB;	

TABLES AND VALUES INSERTION

SQL CODE	CAPTURE																																										
CREATE TABLE sailors (Sname varchar (20), SID int NOT NULL , Rating int , Age int , PRIMARY KEY (SID)); INSERT INTO sailors(Sname,SID,Rating,Age) VALUES('Marx',23,8,52), ('Martin',25,9,51), ('Adams',27,8,36), ('Carrey',33,10,22);	Result Grid Filter Rows: <table><thead><tr><th></th><th>Sname</th><th>SID</th><th>Rating</th><th>Age</th><th></th></tr></thead><tbody><tr><td></td><td>Marx</td><td>23</td><td>8</td><td>52</td><td></td></tr><tr><td></td><td>Martin</td><td>25</td><td>9</td><td>51</td><td></td></tr><tr><td></td><td>Adams</td><td>27</td><td>8</td><td>36</td><td></td></tr><tr><td></td><td>Carrey</td><td>33</td><td>10</td><td>22</td><td></td></tr><tr><td></td><td>NULL</td><td>NULL</td><td>NULL</td><td>NULL</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		Sname	SID	Rating	Age			Marx	23	8	52			Martin	25	9	51			Adams	27	8	36			Carrey	33	10	22			NULL	NULL	NULL	NULL							
	Sname	SID	Rating	Age																																							
	Marx	23	8	52																																							
	Martin	25	9	51																																							
	Adams	27	8	36																																							
	Carrey	33	10	22																																							
	NULL	NULL	NULL	NULL																																							
CREATE TABLE boats(Bname varchar (20), BID int NOT NULL , Fee int , Location text (20), PRIMARY KEY (BID)); INSERT INTO boats(Bname,BID,Fee,Location) VALUES ('Wayfarer',109,120,'Hout Bay'), ('SeaPride',108,500,'Fish Hoek'), ('Yuppie',101,400,'Hout Bay'), ('Joy',104,200,'Hout Bay');	Result Grid Filter Rows: <table><thead><tr><th></th><th>Bname</th><th>BID</th><th>Fee</th><th>Location</th><th></th></tr></thead><tbody><tr><td></td><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>Joy</td><td>104</td><td>200</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>SeaPride</td><td>108</td><td>500</td><td>Fish Hoek</td><td></td></tr><tr><td></td><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>NULL</td><td>NULL</td><td>NULL</td><td>NULL</td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		Bname	BID	Fee	Location			Yuppie	101	400	Hout Bay			Joy	104	200	Hout Bay			SeaPride	108	500	Fish Hoek			Wayfarer	109	120	Hout Bay			NULL	NULL	NULL	NULL							
	Bname	BID	Fee	Location																																							
	Yuppie	101	400	Hout Bay																																							
	Joy	104	200	Hout Bay																																							
	SeaPride	108	500	Fish Hoek																																							
	Wayfarer	109	120	Hout Bay																																							
	NULL	NULL	NULL	NULL																																							

SQL CODE	CAPTURE																																				
<pre>CREATE TABLE reserves(SID INT, BID INT, Day DATE, Deposit DECIMAL(10, 2), PRIMARY KEY (SID, BID), FOREIGN KEY (SID) REFERENCES sailors(SID), FOREIGN KEY (BID) REFERENCES boats(BID)); INSERT INTO reserves (SID, BID, Day, Deposit) VALUES (23, 109, '2014-08-01', 120.00), (23, 108, '2014-08-08', 120.00), (25, 101, '2014-08-08', 0.00), (27, 101, '2014-08-09', 100.00), (27, 109, '2014-08-15', 120.00), (33, 109, '2014-09-04', 0.00), (33, 104, '2014-09-11', 0.00);</pre>	Result Grid Filter Rows: Search <table><tr><th>SID</th><th>BID</th><th>Day</th><th>Deposit</th></tr><tr><td>23</td><td>108</td><td>2014-08-08</td><td>120.00</td></tr><tr><td>23</td><td>109</td><td>2014-08-01</td><td>120.00</td></tr><tr><td>25</td><td>101</td><td>2014-08-08</td><td>0.00</td></tr><tr><td>27</td><td>101</td><td>2014-08-09</td><td>100.00</td></tr><tr><td>27</td><td>109</td><td>2014-08-15</td><td>120.00</td></tr><tr><td>33</td><td>104</td><td>2014-09-11</td><td>0.00</td></tr><tr><td>33</td><td>109</td><td>2014-09-04</td><td>0.00</td></tr><tr><td>NULL</td><td>NULL</td><td>NULL</td><td>NULL</td></tr></table>	SID	BID	Day	Deposit	23	108	2014-08-08	120.00	23	109	2014-08-01	120.00	25	101	2014-08-08	0.00	27	101	2014-08-09	100.00	27	109	2014-08-15	120.00	33	104	2014-09-11	0.00	33	109	2014-09-04	0.00	NULL	NULL	NULL	NULL
SID	BID	Day	Deposit																																		
23	108	2014-08-08	120.00																																		
23	109	2014-08-01	120.00																																		
25	101	2014-08-08	0.00																																		
27	101	2014-08-09	100.00																																		
27	109	2014-08-15	120.00																																		
33	104	2014-09-11	0.00																																		
33	109	2014-09-04	0.00																																		
NULL	NULL	NULL	NULL																																		

```
CREATE TABLE captains (  
  Sname varchar(20),  
  SID int NOT NULL,  
  Rating int,  
  Age int,  
  PRIMARY KEY (SID));
```

Result Grid

Filter Rows:

Sname	SID	Rating	Age
NULL	NULL	NULL	NULL

DATABASE CONTEXT. QUESTIONS

1. Get everything in the Sailors table.

SQL QUERY		CAPTURE				
SELECT * FROM sailors;		Result Grid   Filter Rows: Search				
		Sname	SID	Rating	Age	
		Marx	23	8	52	
		Martin	25	9	51	
		Adams	27	8	36	
Carrey	33	10	22			
NULL	NULL	NULL	NULL			

2. Get sailor ID, rank & age of all sailors, ordered from highest to lowest rank. Rank is 10 times rating.

SQL QUERY	CAPTURE															
SELECT SID, Rating * 10 AS 'Rank', Age FROM sailors ORDER BY Rating DESC ;	Result Grid <table><tr><th>SID</th><th>Rank</th><th>Age</th></tr><tr><td>33</td><td>100</td><td>22</td></tr><tr><td>25</td><td>90</td><td>51</td></tr><tr><td>23</td><td>80</td><td>52</td></tr><tr><td>27</td><td>80</td><td>36</td></tr></table>	SID	Rank	Age	33	100	22	25	90	51	23	80	52	27	80	36
SID	Rank	Age														
33	100	22														
25	90	51														
23	80	52														
27	80	36														

3. Get alphabetical list of sailors with rating less than 10.

9. Get alphabetical list of sailors with rating less than 10.

SQL QUERY	CAPTURE								
SELECT Sname FROM sailors WHERE Rating < 10 ORDER BY Sname;	Result Grid Filter Rows: Search <table><thead><tr><th>Sname</th><th></th></tr></thead><tbody><tr><td>Adams</td><td></td></tr><tr><td>Martin</td><td></td></tr><tr><td>Marx</td><td></td></tr></tbody></table>	Sname		Adams		Martin		Marx	
Sname									
Adams									
Martin									
Marx									

4. Find how much deposit money there is in total and how many tuples are in the reserves table.

SQL QUERY	CAPTURE				
SELECT SUM(Deposit) AS TotalDeposit, COUNT(*) AS TupleCountReserves FROM reserves;	Result Grid Filter Rows: Search <table> <thead> <tr> <th>TotalDeposit</th><th>TupleCountReserv...</th></tr> </thead> <tbody> <tr><td>460.00</td><td>7</td></tr> </tbody> </table>	TotalDeposit	TupleCountReserv...	460.00	7
TotalDeposit	TupleCountReserv...				
460.00	7				

5. Get all info on boats in Fishhoek but I'm not sure how you spell Fishhoek.

SQL QUERY	CAPTURE																			
SELECT * FROM boats WHERE Location LIKE '%Fish Hoek%'	Result Grid   Filter Rows: Search																			
	<table><tr><td>Bname</td><td>BID</td><td>Fee</td><td>Location</td><td></td></tr><tr><td>SeaPride</td><td>108</td><td>500</td><td>Fish Hoek</td><td></td></tr><tr><td>NULL</td><td>NULL</td><td>NULL</td><td>NULL</td><td></td></tr></table>					Bname	BID	Fee	Location		SeaPride	108	500	Fish Hoek		NULL	NULL	NULL	NULL	
	Bname	BID	Fee	Location																
	SeaPride	108	500	Fish Hoek																
NULL	NULL	NULL	NULL																	


6. In what locations are boats kept?

SQL QUERY		CAPTURE							
SELECT DISTINCT Location FROM boats;		Result Grid   Filter Rows: Search  <table><tr><td>Location</td><td></td></tr><tr><td>Hout Bay</td><td></td></tr><tr><td>Fish Hoek</td><td></td></tr></table>		Location		Hout Bay		Fish Hoek	
Location									
Hout Bay									
Fish Hoek									


7. Get the names of all Boats that have a fee value recorded in the database.

SQL QUERY		CAPTURE											
SELECT Bname FROM boats WHERE Fee IS NOT NULL ;		Result Grid   Filter Rows: Search <table><tr><td>Bname</td><td></td></tr><tr><td>Yuppie</td><td></td></tr><tr><td>Joy</td><td></td></tr><tr><td>SeaPride</td><td></td></tr><tr><td>Wayfarer</td><td></td></tr></table>		Bname		Yuppie		Joy		SeaPride		Wayfarer	
Bname													
Yuppie													
Joy													
SeaPride													
Wayfarer													


8. Get ID of all boats that have not been reserved.

SQL QUERY	CAPTURE
#NOTE. THIS QUERY IS SHOWING THE IDs WITH A DEPOSIT EQUAL TO 0 IN THE RESERVATION TABLE. SELECT BID FROM reserves WHERE Deposit =0; #NOTE. THIS QUERY IS RETURNING A BLANK VALUE BECAUSE IT IS TAKING ALL IDs FROM THE RESERVATION VALUE AS RESERVED. SELECT boats.BID FROM boats LEFT JOIN reserves ON boats.BID = reserves.BID WHERE reserves.BID IS NULL;	


9. Get all reservation info, including all details on the boats being reserved.

SQL QUERY	CAPTURE
SELECT * FROM reserves JOIN boats ON reserves.BID = boats.BID;	


10. For all reservations, get the name of the sailor, along with the day and name of the boat booked.

SQL QUERY	CAPTURE
SELECT Sname, Day, Bname FROM sailors JOIN reserves ON sailors.SID = reserves.SID JOIN boats ON reserves.BID = boats.BID;	


11. Get the average deposit paid for each boat.

SQL QUERY	CAPTURE
SELECT BID, ROUND(AVG(Deposit),2) AS 'Avg_Deposit' FROM reserves GROUP BY BID;	

12. Get the average deposit paid for each boat that has been booked by more than one person.

SQL QUERY	CAPTURE
SELECT BID, ROUND(AVG(Deposit),2) AS 'Avg_Deposit' FROM reserves GROUP BY BID HAVING COUNT(DISTINCT SID) > 1;	


13. Get the average firm deposit paid for each boat that has been booked by more than one person, in increasing order of amount. A firm deposit is one which exceeds R10.

SQL QUERY	CAPTURE
SELECT BID, ROUND(AVG(Deposit),2) AS 'Avg_Deposit' FROM reserves WHERE Deposit > 10 GROUP BY BID HAVING COUNT(DISTINCT SID) > 1 ORDER BY 'Avg_Deposit';	


14. Get name & rating of sailors with rating exceeding 7 who made any reservation with 0 deposit.

SQL QUERY	CAPTURE
SELECT Sname, Rating FROM sailors WHERE Rating > 7 AND SID IN (SELECT SID FROM reserves WHERE Deposit = 0);	


15. Get names of boats located in a place other than Hout Bay or Fish Hoek.

SQL QUERY	CAPTURE
SELECT Bname FROM boats WHERE Location NOT IN ('Hout Bay', 'Fish Hoek');	


16. Get names of boats having a fee larger than any boat located in Hout Bay.

SQL QUERY	CAPTURE
SELECT DISTINCT Bname FROM boats WHERE Fee > (SELECT MAX(Fee) FROM boats WHERE Location = 'Hout Bay');	

17. Get names that are in both the sailors and the captains relations.

SQL QUERY	CAPTURE
SELECT sailors.Sname FROM sailors INNER JOIN captains ON sailors.Sname = captains.Sname;	

18. Get names of boats that have exactly 1 reservation.

SQL QUERY	CAPTURE
SELECT Bname FROM boats WHERE BID IN (SELECT BID FROM reserves GROUP BY BID HAVING COUNT(*) = 1);	

19. Get sailor ID and total deposit paid for sailors who have booked more than 1 boat.

SQL QUERY	CAPTURE														
#NOTE. THIS QUERY REPRESENTS ALL RESERVATION INCLUDING THE 0 DEPOSIT. SELECT SID, SUM(Deposit) AS TotalDeposit FROM reserves GROUP BY SID HAVING COUNT(BID) > 1; #NOTE. THIS QUERY REPRESENTS ALL RESERVATION EXCLUDING THE 0 DEPOSIT. SELECT SID, SUM(Deposit) AS TotalDeposit FROM reserves WHERE Deposit > 0 GROUP BY SID HAVING COUNT(DISTINCT BID) > 1;	Result Grid Filter Rows: <table> <thead> <tr> <th>SID</th><th>TotalDeposit</th></tr> </thead> <tbody> <tr> <td>23</td><td>240.00</td></tr> <tr> <td>27</td><td>220.00</td></tr> <tr> <td>33</td><td>0.00</td></tr> </tbody> </table> Result Grid Filter Rows: <table> <thead> <tr> <th>SID</th><th>TotalDeposit</th></tr> </thead> <tbody> <tr> <td>23</td><td>240.00</td></tr> <tr> <td>27</td><td>220.00</td></tr> </tbody> </table>	SID	TotalDeposit	23	240.00	27	220.00	33	0.00	SID	TotalDeposit	23	240.00	27	220.00
SID	TotalDeposit														
23	240.00														
27	220.00														
33	0.00														
SID	TotalDeposit														
23	240.00														
27	220.00														

20. Get all reservation info including details of the boat booked.

SQL QUERY		CAPTURE																																																																																
SELECT * FROM reserves INNER JOIN boats ON reserves.BID = boats.BID;	Result Grid Filter Rows: Search Export: <table><thead><tr><th></th><th>SID</th><th>BID</th><th>Day</th><th>Deposit</th><th>Bname</th><th>BID</th><th>Fee</th><th>Location</th></tr></thead><tbody><tr><td></td><td>25</td><td>101</td><td>2014-08-08</td><td>0.00</td><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td></tr><tr><td></td><td>27</td><td>101</td><td>2014-08-09</td><td>100.00</td><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td></tr><tr><td></td><td>33</td><td>104</td><td>2014-09-11</td><td>0.00</td><td>Joy</td><td>104</td><td>200</td><td>Hout Bay</td></tr><tr><td></td><td>23</td><td>108</td><td>2014-08-08</td><td>120.00</td><td>SeaPride</td><td>108</td><td>500</td><td>Fish Hoek</td></tr><tr><td></td><td>23</td><td>109</td><td>2014-08-01</td><td>120.00</td><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td></tr><tr><td></td><td>27</td><td>109</td><td>2014-08-15</td><td>120.00</td><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td></tr><tr><td></td><td>33</td><td>109</td><td>2014-09-04</td><td>0.00</td><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></tbody></table>		SID	BID	Day	Deposit	Bname	BID	Fee	Location		25	101	2014-08-08	0.00	Yuppie	101	400	Hout Bay		27	101	2014-08-09	100.00	Yuppie	101	400	Hout Bay		33	104	2014-09-11	0.00	Joy	104	200	Hout Bay		23	108	2014-08-08	120.00	SeaPride	108	500	Fish Hoek		23	109	2014-08-01	120.00	Wayfarer	109	120	Hout Bay		27	109	2014-08-15	120.00	Wayfarer	109	120	Hout Bay		33	109	2014-09-04	0.00	Wayfarer	109	120	Hout Bay									
	SID	BID	Day	Deposit	Bname	BID	Fee	Location																																																																										
	25	101	2014-08-08	0.00	Yuppie	101	400	Hout Bay																																																																										
	27	101	2014-08-09	100.00	Yuppie	101	400	Hout Bay																																																																										
	33	104	2014-09-11	0.00	Joy	104	200	Hout Bay																																																																										
	23	108	2014-08-08	120.00	SeaPride	108	500	Fish Hoek																																																																										
	23	109	2014-08-01	120.00	Wayfarer	109	120	Hout Bay																																																																										
	27	109	2014-08-15	120.00	Wayfarer	109	120	Hout Bay																																																																										
	33	109	2014-09-04	0.00	Wayfarer	109	120	Hout Bay																																																																										

21. Get all information on every boat. If a boat has reservations, including all its reservations info.

SQL QUERY	CAPTURE																																																																																
SELECT * FROM boats LEFT JOIN reserves ON boats.BID = reserves.BID;	Result Grid Filter Rows: Search Export: <table><tr><th>Bname</th><th>BID</th><th>Fee</th><th>Location</th><th>SID</th><th>BID</th><th>Day</th><th>Deposit</th></tr><tr><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td><td>25</td><td>101</td><td>2014-08-08</td><td>0.00</td></tr><tr><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td><td>27</td><td>101</td><td>2014-08-09</td><td>100.00</td></tr><tr><td>Joy</td><td>104</td><td>200</td><td>Hout Bay</td><td>33</td><td>104</td><td>2014-09-11</td><td>0.00</td></tr><tr><td>SeaPride</td><td>108</td><td>500</td><td>Fish Hoek</td><td>23</td><td>108</td><td>2014-08-08</td><td>120.00</td></tr><tr><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td><td>23</td><td>109</td><td>2014-08-01</td><td>120.00</td></tr><tr><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td><td>27</td><td>109</td><td>2014-08-15</td><td>120.00</td></tr><tr><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td><td>33</td><td>109</td><td>2014-09-04</td><td>0.00</td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td></td><td></td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	Bname	BID	Fee	Location	SID	BID	Day	Deposit	Yuppie	101	400	Hout Bay	25	101	2014-08-08	0.00	Yuppie	101	400	Hout Bay	27	101	2014-08-09	100.00	Joy	104	200	Hout Bay	33	104	2014-09-11	0.00	SeaPride	108	500	Fish Hoek	23	108	2014-08-08	120.00	Wayfarer	109	120	Hout Bay	23	109	2014-08-01	120.00	Wayfarer	109	120	Hout Bay	27	109	2014-08-15	120.00	Wayfarer	109	120	Hout Bay	33	109	2014-09-04	0.00																
Bname	BID	Fee	Location	SID	BID	Day	Deposit																																																																										
Yuppie	101	400	Hout Bay	25	101	2014-08-08	0.00																																																																										
Yuppie	101	400	Hout Bay	27	101	2014-08-09	100.00																																																																										
Joy	104	200	Hout Bay	33	104	2014-09-11	0.00																																																																										
SeaPride	108	500	Fish Hoek	23	108	2014-08-08	120.00																																																																										
Wayfarer	109	120	Hout Bay	23	109	2014-08-01	120.00																																																																										
Wayfarer	109	120	Hout Bay	27	109	2014-08-15	120.00																																																																										
Wayfarer	109	120	Hout Bay	33	109	2014-09-04	0.00																																																																										

22. Create a new tuple for the boat named "Nino" which has fee R150, BID 110, and is in Fish Hoek.

SQL QUERY	CAPTURE																																										
INSERT INTO boats (Bname, BID, Fee, Location) VALUES ('Nino', 110, 150, 'Fish Hoek'); SELECT * FROM SailingDB.boats;	10/1/201911:11 Result Grid Filter Rows: Search <table><thead><tr><th></th><th>Bname</th><th>BID</th><th>Fee</th><th>Location</th><th></th></tr></thead><tbody><tr><td></td><td>Yuppie</td><td>101</td><td>400</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>Joy</td><td>104</td><td>200</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>SeaPride</td><td>108</td><td>500</td><td>Fish Hoek</td><td></td></tr><tr><td></td><td>Wayfarer</td><td>109</td><td>120</td><td>Hout Bay</td><td></td></tr><tr><td></td><td>Nino</td><td>110</td><td>150</td><td>Fish Hoek</td><td></td></tr><tr><td></td><td>NULL</td><td>NULL</td><td>NULL</td><td>NULL</td><td></td></tr></tbody></table>		Bname	BID	Fee	Location			Yuppie	101	400	Hout Bay			Joy	104	200	Hout Bay			SeaPride	108	500	Fish Hoek			Wayfarer	109	120	Hout Bay			Nino	110	150	Fish Hoek			NULL	NULL	NULL	NULL	
	Bname	BID	Fee	Location																																							
	Yuppie	101	400	Hout Bay																																							
	Joy	104	200	Hout Bay																																							
	SeaPride	108	500	Fish Hoek																																							
	Wayfarer	109	120	Hout Bay																																							
	Nino	110	150	Fish Hoek																																							
	NULL	NULL	NULL	NULL																																							

26. Create a table called Reserves with 3 integer attributes BID, SID & deposit, and a date attribute Day. Allow only deposit to be omitted, and ensure SID and BID values exist in the database. When someone books a boat, it is for the whole day.

SQL QUERY	
<pre>CREATE TABLE reserves (BID INT NOT NULL, SID INT NOT NULL, Day DATE NOT NULL, Deposit INT, PRIMARY KEY (BID, SID), FOREIGN KEY (BID) REFERENCES boats(BID), FOREIGN KEY (SID) REFERENCES sailors(SID));</pre>	

CAPTURES																																																	
	<table border="1"> <thead> <tr> <th colspan="5">Indexes in Table</th> <th>Index I</th> </tr> <tr> <th>Visible</th> <th>Key</th> <th>Type</th> <th>Uniq...</th> <th>Columns</th> <th>Key N</th> </tr> </thead> <tbody> <tr> <td>☒</td> <td>PRIMARY</td> <td>BTREE</td> <td>YES</td> <td>SID, BID</td> <td>Index</td> </tr> <tr> <td>☒</td> <td>BID</td> <td>BTREE</td> <td>NO</td> <td>BID</td> <td>Allow</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th colspan="4">Columns in table</th> </tr> <tr> <th>Column</th> <th>Type</th> <th>Nullable</th> <th>Indexes</th> </tr> </thead> <tbody> <tr> <td>SID</td> <td>int</td> <td>NO</td> <td>PRIMARY</td> </tr> <tr> <td>BID</td> <td>int</td> <td>NO</td> <td>PRIMARY, BID</td> </tr> <tr> <td>Day</td> <td>date</td> <td>YES</td> <td></td> </tr> <tr> <td>Deposit</td> <td>decimal(10,2)</td> <td>YES</td> <td></td> </tr> </tbody> </table>	Indexes in Table					Index I	Visible	Key	Type	Uniq...	Columns	Key N	☒	PRIMARY	BTREE	YES	SID, BID	Index	☒	BID	BTREE	NO	BID	Allow	Columns in table				Column	Type	Nullable	Indexes	SID	int	NO	PRIMARY	BID	int	NO	PRIMARY, BID	Day	date	YES		Deposit	decimal(10,2)	YES	
Indexes in Table					Index I																																												
Visible	Key	Type	Uniq...	Columns	Key N																																												
☒	PRIMARY	BTREE	YES	SID, BID	Index																																												
☒	BID	BTREE	NO	BID	Allow																																												
Columns in table																																																	
Column	Type	Nullable	Indexes																																														
SID	int	NO	PRIMARY																																														
BID	int	NO	PRIMARY, BID																																														
Day	date	YES																																															
Deposit	decimal(10,2)	YES																																															

27. Add a new attribute NEEDSREPAIR to the Boats table. It is usually "N".

SQL QUERY	CAPTURE
<pre>ALTER TABLE boats ADD NeedsRepair CHAR(1) DEFAULT 'N'; SELECT * FROM SailingDB.boats;</pre>	

28. We should not be ageist. Remove the Age attribute.

SQL QUERY	CAPTURE
<pre>ALTER TABLE sailors DROP COLUMN Age; SELECT * FROM SailingDB.boats;</pre>	

29. Remove the Captains relation altogether so that nobody can try insert or use Captains in future.

SQL QUERY	CAPTURE
<pre>DROP TABLE captains;</pre>	

RELATION ALGEBRA

#2 Get sailor ID, rank & age of all sailors, ordered from highest to lowest rank. Rank is 10 times rating.

SQL QUERY	RELATION ALGEBRA
SELECT SID, Rating * 10 AS 'Rank', Age FROM sailors ORDER BY Rating DESC ;	$\pi_{SID, (Rating \times 10) 'Rank', Age} \sigma ((sailors))$

#8 Get ID of all boats that have not been reserved.

SQL QUERY	RELATION ALGEBRA
SELECT BID FROM reserves WHERE Deposit <=0; SELECT boats.BID FROM boats LEFT JOIN reserves ON boats.BID = reserves.BID WHERE reserves.BID IS NULL;	$\pi_{BID} (\sigma_{Deposit \leq 0} ((reserves)))$ $\pi_{BID} (\sigma_{reserves.BID \text{ IS NULL}} (boats \bowtie_{boats.BID=reserves.BID} reserves))$

#9 Get all reservation info, including all details on the boats being reserved.

SQL QUERY	RELATION ALGEBRA
SELECT * FROM reserves JOIN boats ON reserves.BID = boats.BID;	$reserves \bowtie_{reserves.BID = boats.BID} (boats)$

#10 For all reservations, get the name of the sailor, along with the day and name of the boat booked.

SQL QUERY	RELATION ALGEBRA
SELECT Sname, Day, Bname FROM sailors JOIN reserves ON sailors.SID = reserves.SID JOIN boats ON reserves.BID = boats.BID;	$\pi_{Sname, Day, Bname} ((sailors \bowtie_{sailors.ID = reserves.ID} (reserves)) \bowtie_{reserves.BID = boats.BID} (boats))$

#17 Get names that are in both the sailors and the captains relations.

SQL QUERY	RELATION ALGEBRA
SELECT sailors.Sname FROM sailors INNER JOIN captains ON sailors.Sname = captains.Sname;	$\pi_{sailors.Sname} (sailors \bowtie_{sailors.Sname = captains.Sname} (captains))$

#20

SQL QUERY	RELATION ALGEBRA
SELECT * FROM reserves INNER JOIN boats ON reserves.BID = boats.BID;	$reserves \bowtie_{reserves.BID = boats.BID} (boats)$