Site Reliability Engineer HandBook

Introduction

Operating System

Linux Boot Process

Filesystems

RAID

IPC.

Sockets

RPC

Signals

POSIX signals

Threads

Streams

Caching

Scheduler

Write-through, write-around, write-b...

Tempfiles

System Calls

PID Definition

**Shared Memory** 

Zombie process

What's in an inode?

What are the common run levels in li...

What is the difference between soft ...

What happens when a process forks?

How-To Compile Linux Kernel from ...

Understanding Sticky-Bit, SUID and ...

Understanding User and Kernel Mode

Understanding Linux CPU Load - wh...

## More about /proc/PID/file & procfs File System

/proc (or procfs) is a pseudo-file system that it is dynamically generated after each reboot. It is used to access kernel information. procfs is also used by Solaris, BSD, AIX and other UNIX like operating systems. Now, you know how many file descriptors are being used by a process. You will find more interesting stuff in /proc/\$PID/file directory:

- /proc/PID/cmdline : process arguments
- /proc/PID/cwd: process current working directory (symlink)
- /proc/PID/exe : path to actual process executable file (symlink)
- /proc/PID/environ : environment used by process
- /proc/PID/root: the root path as seen by the process. For most processes
  this will be a link to / unless the process is running in a chroot jail.
- /proc/PID/status: basic information about a process including its run state and memory usage.
- /proc/PID/task: hard links to any tasks that have been started by this (the parent) process.