



See how your visitors are really using your website.

TRY IT FOR FREE

Custom Search

COURSES

Login

HIRE WITH US




## Hierholzer's Algorithm for directed graph

Given a directed Eulerian graph, print an **Euler circuit**. Euler circuit is a path that traverses every edge of a graph, and the path ends on the starting vertex.


Examples:

Input : Adjacency list for the below graph



Output : 0 -> 1 -> 2 -> 0

Input : Adjacency list for the below graph



**Euler Circuit : 0 -> 6 -> 4 -> 5 -> 0 -> 1 -> 2 -> 3 -> 4 -> 2 -> 0**

Output : 0 -> 6 -> 4 -> 5 -> 0 -> 1  
-> 2 -> 3 -> 4 -> 2 -> 0

Explanation:

In both the cases, we can trace the Euler circuit by following the edges as indicated in the output.

**Recommended: Please try your approach on [{IDE}](#) first, before moving on to the solution.**



See how your visitors are really using your website.

TRY IT FOR FREE

is  $O(E)$ . Using Hierholzer's Algorithm, we can find the circuit/path in  $O(E)$ , i.e., linear time.


Below is the Algorithm: ref ( [wiki](#) ). Remember that a directed graph has an Eulerian cycle if following conditions are true (1) All vertices with nonzero degree belong to a single strongly connected component. (2) In degree and out degree of every vertex is same. The algorithm assumes that the given graph has Eulerian Circuit.

- Choose any starting vertex  $v$ , and follow a trail of edges from that vertex until returning to  $v$ . It is not possible to get stuck at any vertex other than  $v$ , because indegree and outdegree of every vertex must be same, when the trail enters another vertex  $w$  there must be an unused edge leaving  $w$ .  
The tour formed in this way is a closed tour, but may not cover all the vertices and edges of the initial graph.
- As long as there exists a vertex  $u$  that belongs to the current tour but that has adjacent edges not part of the tour, start another trail from  $u$ , following unused edges until returning to  $u$ , and join the tour formed in this way to the previous tour.

Thus the idea is to keep following unused edges and removing them until we get stuck. Once we get stuck, we back-track to the nearest vertex in our current path that has unused edges, and we repeat the process until all the edges have been used. We can use another container to maintain the final path.

Let's take an example:


Let the initial directed graph be as below



Let's start our path from 0.


Thus,  $\text{curr\_path} = \{0\}$  and  $\text{circuit} = \{\}$

Now let's use the edge  $0 \rightarrow 1$



Now,  $\text{curr\_path} = \{0, 1\}$  and  $\text{circuit} = \{\}$

similarly we reach up to 2 and then to 0 again as




Now,  $\text{curr\_path} = \{0, 1, 2\}$  and  $\text{circuit} = \{\}$

Then we go to 0, now since 0 haven't got any unused edge we put 0 in circuit and back track till we find



See how your visitors are really using your website.

TRY IT FOR FREE



We then have  $\text{curr\_path} = \{0,1,2\}$  and  $\text{circuit} = \{0\}$   
 Similarly when we backtrack to 2, we don't find any unused edge. Hence put 2 in circuit and backtrack again.

$\text{curr\_path} = \{0,1\}$  and  $\text{circuit} = \{0,2\}$

After reaching 1 we go to through unused edge 1->3 and then 3->4, 4->1 until all edges have been traversed.

The contents of the two containers look as:  
 $\text{curr\_path} = \{0,1,3,4,1\}$  and  $\text{circuit} = \{0,2\}$

now as all edges have been used, the  $\text{curr\_path}$  is popped one by one into circuit.  
 Finally we've  $\text{circuit} = \{0,2,1,4,3,1,0\}$

We print the circuit in reverse to obtain the path followed.  
 i.e., **0->1->3->4->1->1->2->0**

Below is the C++ program for the same.

```

// A C++ program to print Eulerian circuit in given
// directed graph using Hierholzer algorithm
#include <bits/stdc++.h>
using namespace std;

void printCircuit(vector< vector<int> > adj)
{
    // adj represents the adjacency list of
    // the directed graph
    // edge_count represents the number of edges
    // emerging from a vertex
    unordered_map<int,int> edge_count;

    for (int i=0; i<adj.size(); i++)
    {
        //find the count of edges to keep track
        //of unused edges
        edge_count[i] = adj[i].size();
    }

    if (!adj.size())
        return; //empty graph

    // Maintain a stack to keep vertices
    stack<int> curr_path;

    // vector to store final circuit
    vector<int> circuit;

    // start from any vertex
    curr_path.push(0);
  
```



See how your visitors are really using your website.

TRY IT FOR FREE

```

    // If there's remaining edge
    if (edge_count[curr_v])
    {
        // Push the vertex
        curr_path.push(curr_v);

        // Find the next vertex using an edge
        int next_v = adj[curr_v].back();

        // and remove that edge
        edge_count[curr_v]--;
        adj[curr_v].pop_back();

        // Move to next vertex
        curr_v = next_v;
    }

    // back-track to find remaining circuit
    else
    {
        circuit.push_back(curr_v);

        // Back-tracking
        curr_v = curr_path.top();
        curr_path.pop();
    }
}

// we've got the circuit, now print it in reverse
for (int i=circuit.size()-1; i>=0; i--)
{
    cout << circuit[i];
    if (i)
        cout<<" -> ";
}

// Driver program to check the above function
int main()
{
    vector< vector<int> > adj1, adj2;

    // Input Graph 1
    adj1.resize(3);

    // Build the edges
    adj1[0].push_back(1);
    adj1[1].push_back(2);
    adj1[2].push_back(0);
    printCircuit(adj1);
    cout << endl;

    // Input Graph 2
    adj2.resize(7);
    adj2[0].push_back(1);
    adj2[0].push_back(6);
    adj2[1].push_back(2);
    adj2[2].push_back(0);
    adj2[2].push_back(3);
    adj2[3].push_back(4);
    adj2[4].push_back(2);
    adj2[4].push_back(5);
    adj2[5].push_back(0);
    adj2[6].push_back(4);
    printCircuit(adj2);
}

```



See how your visitors are really using your website.

TRY IT FOR FREE

Output:

```
0 -> 1 -> 2 -> 0
0 -> 6 -> 4 -> 5 -> 0 -> 1 -> 2 -> 3 -> 4 -> 2 -> 0
```

**Time Complexity** :  $O(V+E)$ .

This article is contributed by **Ashutosh Kumar**. The article contains also inputs from **Nitish Kumar**. If you like GeeksforGeeks and would like to contribute, you can also write an article using [contribute.geeksforgeeks.org](https://contribute.geeksforgeeks.org) or mail your article to [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org). See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.

### Recommended Posts:

Convert the undirected graph into directed graph such that there is no path of length greater than 1

Euler Circuit in a Directed Graph

Detect Cycle in a Directed Graph using BFS

Clone a Directed Acyclic Graph

Check if a directed graph is connected or not

Detect Cycle in a Directed Graph

All Topological Sorts of a Directed Acyclic Graph

Shortest Path in Directed Acyclic Graph

Longest Path in a Directed Acyclic Graph

Detect Cycle in a directed graph using colors

Longest Path in a Directed Acyclic Graph | Set 2

Find if there is a path between two vertices in a directed graph

Shortest path with exactly k edges in a directed and weighted graph

Number of shortest paths in an unweighted and directed graph

Check if a given directed graph is strongly connected | Set 2 (Kosaraju using BFS)

**Article Tags :** Graph Euler-Circuit

**Practice Tags :** Graph



2

☐ To-do ☐ Done

3.5

Based on 13 vote(s)



See how your visitors are really using your website.

TRY IT FOR FREE

Please write to us at [contribute@geeksforgeeks.org](mailto:contribute@geeksforgeeks.org) to report any issue with the above content.Writing code in comment? Please use [ide.geeksforgeeks.org](https://ide.geeksforgeeks.org), generate link and share the link here.6 Comments   **GeeksforGeeks**

Login ▾

Recommend 2   Tweet   Share

Sort by Newest ▾



Join the discussion...

LOG IN WITH

OR SIGN UP WITH DISQUS

**Rohit Agarwal** • 5 months agoWhy do you need edge\_count when clearly we are destroying the input graph? Can't we test it directly by `adj[i].size()` ?

• Reply • Share &gt;

**Deepak chaudhary** • 2 years ago • edited

A simple code to print euler tour

```
#include<bits/stdc++.h>
using namespace std;
vector<vector<int>> >v(1007);
int main()
{
    int next=0,curr;
    v[0].push_back(1);
    v[1].push_back(2);
    v[2].push_back(0);
```

```
vector<int> ans;
ans.push_back(next);
while(1){
    if(v[next].empty())
        break;
    curr = v[next].back();
    ans.push_back(curr);
```

[see more](#)

2 • Reply • Share &gt;

**Nishan Tamng** → Deepak chaudhary • a year ago

Nice and easy implementation! Thanks

• Reply • Share &gt;

**Sudhanshu Monga** • 2 years ago<http://ideone.com/pANMWg>

simple recursive code, please report bugs, if any.

1 • Reply • Share &gt;

**Anas Mahmoud** • 2 years ago



Here you pushed vertex 0 TWICE to curr\_path for the first run of the algorithm (at line 1 and line 5), or did I miss something ?

```
// start from any vertex
1- curr_path.push(0);
2- int curr_v = 0; // Current vertex

3- while (!curr_path.empty())
{
// If there's remaining edge
4- if (edge_count[curr_v])
{
// Push the vertex
5- curr_path.push(curr_v);
}
}
```

^ | v • Reply • Share ›



**Kfir Berger** → Anas Mahmoud • 2 years ago

yes, same question here...

^ | v • Reply • Share ›

[Subscribe](#) [Add Disqus to your site](#) [Add Disqus](#) [Add Disqus](#) [Disqus' Privacy Policy](#) [Privacy Policy](#) [Privacy Policy](#)

A computer science portal for geeks

5th Floor, A-118,  
Sector-136, Noida, Uttar Pradesh - 201305  
[feedback@geeksforgeeks.org](mailto:feedback@geeksforgeeks.org)

#### COMPANY

[About Us](#)  
[Careers](#)  
[Privacy Policy](#)  
[Contact Us](#)

#### PRACTICE

[Courses](#)  
[Company-wise](#)  
[Topic-wise](#)  
[How to begin?](#)

#### LEARN

[Algorithms](#)  
[Data Structures](#)  
[Languages](#)  
[CS Subjects](#)  
[Video Tutorials](#)

#### CONTRIBUTE

[Write an Article](#)  
[Write Interview Experience](#)  
[Internships](#)  
[Videos](#)

@geeksforgeeks, Some rights reserved







