

1

PHP include file

CS380

include() example

3

```
<a href="/default.php">Home</a>
<a href="/tutorials.php">Tutorials</a>
<a href="/references.php">References</a>
<a href="/examples.php">Examples</a>
<a href="/contact.php">Contact Us</a>
```

PHP

```
<html>
<body>

<div class="leftmenu">
<?php include("menu.php"); ?>
</div>

<h1>Welcome to my home page.</h1>
<p>I have a great menu here.</p>

</body>
</html>
```

PHP

PHP Include File

2

- Insert the content of one PHP file into another PHP file before the server executes it
- Use the
 - ▣ `include()` generates a warning, but the script will continue execution
 - ▣ `require()` generates a fatal error, and the script will stop

CS380

4

PHP File Input/Output

CS380

PHP file I/O functions

5

function name(s)	category
file , file_get_contents , file_put_contents	reading/writing entire files
basename , file_exists , filesize , fileperms , filemtime , is_dir , is_readable , is_writable , disk_free_space	asking for information
copy , rename , unlink , chmod , chgrp , chown , mkdir , rmdir	manipulating files and directories
glob , scandir	reading directories

CS380

Reading/writing files

6

contents of foo.txt	file("foo.txt")	file_get_contents("foo.txt")
Hello how are you? I'm fine	array("Hello\n", #0 "how are\n", #1 "you?\n", #2 "\n", #3 "I'm fine\n" #4)	"Hello\n how are\n you?\n \n I'm fine\n"

- `file` returns lines of a file as an array
- `file_get_contents` returns entire contents of a file as a string

CS380

Reading/writing an entire file

7

```
# reverse a file
$text = file_get_contents("poem.txt");
$text = strrev($text);
file_put_contents("poem.txt", $text);
```

PHP

- `file_get_contents` returns entire contents of a file as a string
- `file_put_contents` writes a string into a file, replacing any prior contents

CS380

Appending to a file

8

```
# add a line to a file
$new_text = "P.S. ILY, GTG TTYL!~";
file_put_contents("poem.txt", $new_text,
FILE_APPEND);
```

PHP

old contents

Roses are red,
Violets are blue.
All my base,
Are belong to you.

new contents

Roses are red,
Violets are blue.
All my base,
Are belong to you.
P.S. ILY, GTG TTYL!~

CS380

The file function

9

```
# display lines of file as a bulleted list
$lines = file("todolist.txt");
foreach ($lines as $line) {
    ?>
    <li> <?= $line ?> </li>
<?php
}
?>
```

PHP

- file returns the lines of a file as an array of strings
 - each string ends with \n
 - to strip the \n off each line, use optional second parameter:

```
$lines = file("todolist.txt", FILE_IGNORE_NEW_LINES);
```

PHP

Fixed-length files, file and list

11

```
Xenia Mountrouidou
(919) 685-2181
570-86-7326
```

contents of file personal.txt

```
list($name, $phone, $ssn) = file("personal.txt");
```

PHP

- reads the file into an array of lines and unpacks the lines into variables
- Need to know a file's exact length/format

CS380

Unpacking an array: list

10

```
list($var1, ..., $varN) = array;
```

PHP

```
$values = array("mundruid", "18", "f", "96");
...
list($username, $age, $gender, $iq) = $values;
```

PHP

- the list function accepts a comma-separated list of variable names as parameters
- use this to quickly "unpack" an array's contents into several variables

CS380

Splitting/joining strings

12

```
$array = explode(delimiter, string);
$string = implode(delimiter, array);
```

PHP

```
$class = "CS 380 01";
$class1 = explode(" ", $s); # ("CS", "380", "01")
$class2 = implode("...", $a); # "CSE...380...01"
```

PHP

- explode and implode convert between strings and arrays

CS380

Example explode

13

```
Harry Potter, J.K. Rowling  
The Lord of the Rings, J.R.R. Tolkien  
Dune, Frank Herbert
```

contents of input file books.txt

```
<?php foreach (file("books.txt") as $book) {  
    list($title, $author) = explode("", $book);  
    ?>  
    <p> Book title: <?= $title ?>, Author: <?= $author ?> </p>  
<?php  
}  
?>
```

PHP

CS380

Reading directories

14

function	description
<u>scandir</u>	returns an array of all file names in a given directory (returns just the file names, such as "myfile.txt")
<u>glob</u>	returns an array of all file names that match a given pattern (returns a file path and name, such as "foo/bar/myfile.txt")

CS380

Example for glob

15

```
# reverse all poems in the poetry directory  
$poems = glob("poetry/poem*.dat");  
foreach ($poems as $poemfile) {  
    $text = file_get_contents($poemfile);  
    file_put_contents($poemfile, strrev($text));  
    print "I just reversed " .  
basename($poemfile);  
}
```

PHP

- ❑ glob can match a "wildcard" path with the * character
- ❑ the basename function strips any leading directory from a file path

CS380

Example for glob

16

```
# reverse all poems in the poetry directory  
$poems = glob("poetry/poem*.dat");  
foreach ($poems as $poemfile) {  
    $text = file_get_contents($poemfile);  
    file_put_contents($poemfile, strrev($text));  
    print "I just reversed " .  
basename($poemfile);  
}
```

PHP

- ❑ glob can match a "wildcard" path with the * character
- ❑ the basename function strips any leading directory from a file path

CS380

Example for scandir

17

```
<ul>
<?php
$folder = "taxes/old";
foreach (scandir($folder) as $filename) {
    ?>
    <li> <?= $filename ?> </li>
<?php
}
?>
</ul>
```

PHP

- .
- ..
- 2009_w2.pdf
- 2007_1099.doc

output

Exceptions

19

- Used to change the normal flow of the code execution if a specified error (exceptional) condition occurs.
- What normally happens when an exception is triggered:
 - current code state is saved
 - code execution will switch to a predefined (custom) exception handler function
 - the handler may then
 - resume the execution from the saved code state,
 - terminate the script execution or
 - continue the script from a different location in the code

PHP Exceptions

18

CS380

Exception example

20

```
<?php
//create function with an exception
function checkStr($str)
{
    if(strcmp($str, "correct") != 0)
    {
        throw new Exception("String is not correct!");
    }
    return true;
}

//trigger exception
checkStr("wrong");
?>
```

PHP

CS380

Exception example (cont.)

21

```
<?php
//create function with an exception
function checkStr($str)
{
    ...
}

//trigger exception in a "try" block
try
{
    checkStr("wrong");
    //If the exception is thrown, this text will not be shown
    echo 'If you see this, the string is correct';
}

//catch exception
catch(Exception $e)
{
    echo 'Message: ' . $e->getMessage();
}

?>
```

PHP

23

PHP cookies and sessions

CS380

PHP larger example

22

□ Display a random quote of the day:

- I don't know half of you half as well as I should like; and I like less than half of you half as well as you deserve.

J. R. R. Tolkien (1892 - 1973), *The Fellowship of the Ring*

- I have not failed. I've just found 10,000 ways that won't work.

Thomas A. Edison (1847 - 1931), (attributed)

- I am among those who think that science has great beauty. A scientist in his laboratory is not only a technician: he is also a child placed before natural phenomena which impress him like a fairy tale.

Marie Curie (1867 - 1934)

- I love deadlines. I like the whooshing sound they make as they fly by.

Douglas Adams

- Statistics: The only science that enables different experts using the same figures to draw different conclusions.

Evan Esar

Cookies

24

□ Problem: HTTP is stateless

□ What is a cookie?

- ▣ tiny bits of information that a web site could store on the client's machine
- ▣ they are sent back to the web site each time a new page is requested by this client.



CS380

Bad Cookies?

25

- Urban myth: tracking, violate privacy
- Reality:
 - cookies are relatively harmless
 - can only store a small amount of information

CS380

Sessions

26

- What is a session?
 - a combination of a server-side cookie and a client-side cookie,
 - the client-side cookie contains only a reference to the correct data on the server.
- when the user visits the site:
 - their browser sends the reference code to the server
 - the server loads the corresponding data.

CS380

Cookies vs Sessions

27

- Cookies can be set to a long lifespan
- Cookies work smoothly when you have a cluster of web servers
- Sessions are stored on the server, i.e. clients do not have access to the information you store about
- Session data does not need to be transmitted with each page; clients just need to send an ID and the data is loaded from the local file.
- Sessions can be any size you want because they are held on your server,

Create a cookie

28

```
setcookie(name, value, expire, path, domain);
```

PHP

```
<?php  
setcookie("user", "Harry Potter", time()+3600);  
?>  
  
<html>  
.....
```

PHP

CS380

Retrieve a Cookie Value

29

```
<?php
// Print a cookie
echo $_COOKIE["user"];

// A way to view all cookies
print_r($_COOKIE);
?>
```

PHP

CS380

Delete a Cookie

30

```
<?php
// set the expiration date to one hour ago
setcookie("user", "", time()+3600);
?>
```

PHP

CS380

Start/end a session

31

```
bool session_start ( void )
bool session_destroy ( void )
```

PHP

- All your session data is stored in the session superglobal array, `$_SESSION`

```
$_SESSION['var'] = $val;
$_SESSION['FirstName'] = "Jim";
```

PHP

CS380