



Darshan
UNIVERSITY

Data Mining

Lab - 6

Name: Harmik Rathod

Enrollment No: 24010101680

Dimensionality Reduction using NumPy

What is Data Reduction?

Data reduction refers to the process of reducing the amount of data that needs to be processed and stored, while preserving the essential patterns in the data.

Why do we reduce data?

- To reduce computational cost.
- To remove noise and redundant features.
- To improve model performance and training time.
- To visualize high-dimensional data in 2D or 3D.

Common data reduction techniques include:

- Principal Component Analysis (PCA)
- Feature selection
- Sampling

What is Principal Component Analysis (PCA)?

PCA is a **dimensionality reduction technique** that transforms a dataset into a new coordinate system. It identifies the **directions (principal components)** where the variance of the data is maximized.

Key Concepts:

- **Principal Components:** New features (linear combinations of original features) capturing most variance.
- **Eigenvectors & Eigenvalues:** Used to compute these principal directions.
- **Covariance Matrix:** Measures how features vary with each other.

PCA helps in **visualizing high-dimensional data**, **noise reduction**, and **speeding up algorithms**.



NumPy Functions Summary for PCA

Function	Purpose
<code>np.mean(X, axis=0)</code>	Compute mean of each column (feature-wise mean).
<code>X - np.mean(X, axis=0)</code>	Centering the data (zero mean).
<code>np.cov(X, rowvar=False)</code>	Compute covariance matrix for features.
<code>np.linalg.eigh(cov_mat)</code>	Get eigenvalues and eigenvectors (for symmetric matrices).
<code>np.argsort(values)[::-1]</code>	Sort values in descending order.
<code>np.dot(X, eigenvectors)</code>	Project original data onto new axes.

Step 1: Load the Iris Dataset

```
In [2]: import pandas as pd
import numpy as np
import matplotlib.pyplot as plt
```

```
In [3]: df=pd.read_csv('iris.csv')
```

```
In [4]: df
```

Out[4]:

	sepal_length	sepal_width	petal_length	petal_width	species
0	5.1	3.5	1.4	0.2	setosa
1	4.9	3.0	1.4	0.2	setosa
2	4.7	3.2	1.3	0.2	setosa
3	4.6	3.1	1.5	0.2	setosa
4	5.0	3.6	1.4	0.2	setosa
...
145	6.7	3.0	5.2	2.3	virginica
146	6.3	2.5	5.0	1.9	virginica
147	6.5	3.0	5.2	2.0	virginica
148	6.2	3.4	5.4	2.3	virginica
149	5.9	3.0	5.1	1.8	virginica

150 rows × 5 columns

```
In [6]: x=df.drop(columns="species")
y=df["species"]

x.shape
```

Out[6]: (150, 4)

Step 2: Standardize the data (zero mean)

```
In [7]: x_meaned=x-np.mean(x, axis=0)
x_meaned[:5]
```

Out[7]:

	sepal_length	sepal_width	petal_length	petal_width
0	-0.743333	0.442667	-2.358	-0.999333
1	-0.943333	-0.057333	-2.358	-0.999333
2	-1.143333	0.142667	-2.458	-0.999333
3	-1.243333	0.042667	-2.258	-0.999333
4	-0.843333	0.542667	-2.358	-0.999333

Step 3: Compute the Covariance Matrix

```
In [8]: cov_mat=np.cov(x_meaned,rowvar=False)
cov_mat
```

```
Out[8]: array([[ 0.68569351, -0.042434 ,  1.27431544,  0.51627069],
               [-0.042434 ,  0.18997942, -0.32965638, -0.12163937],
               [ 1.27431544, -0.32965638,  3.11627785,  1.2956094 ],
               [ 0.51627069, -0.12163937,  1.2956094 ,  0.58100626]])
```

Step 4: Compute eigenvalues and eigenvectors

```
In [13]: eigenvalues, eigenvectors=np.linalg.eigh(cov_mat)

#eigenvalue
eigenvalues
```

```
Out[13]: array([0.02383509, 0.0782095 , 0.24267075, 4.22824171])
```

```
In [14]: eigenvectors
```

```
Out[14]: array([[ 0.31548719,  0.58202985,  0.65658877, -0.36138659],
               [-0.3197231 , -0.59791083,  0.73016143,  0.08452251],
               [-0.47983899, -0.07623608, -0.17337266, -0.85667061],
               [ 0.75365743, -0.54583143, -0.07548102, -0.3582892 ]])
```

Step 5: Sort eigenvalues and eigenvectors

```
In [19]: sorted_index=np.argsort(eigenvalues)[::-1]
sorted_eigenvalues=eigenvalues[sorted_index]
sorted_eigenvectors=eigenvectors[:,sorted_index]
```

Step 6: Select the top k eigenvectors (top 2)

```
In [20]: k=2

eigenvector_subset=sorted_eigenvectors[:,0:k]
```

Step 7: Project the data onto the top k eigenvectors


```
In [25]: x_reduce=np.dot(x_meaned, eigenvector_subset)
x_reduce.shape
```

Out[25]: (150, 2)

Step 8: Plot the PCA-Reduced Data

```
In [43]: plt.figure(figsize=(8,6))
plt.scatter(x_reduce[:,0], x_reduce[:,1],cmap='viridis')
plt.xlabel('Principle Component 1')
plt.ylabel('Principle Component 2')
plt.title('PCA-IRIS Dataset')
plt.grid(True)
plt.show()
```

C:\Users\HP\AppData\Local\Temp\ipykernel_19868\4018771003.py:2: UserWarning: No data for colormapping provided via 'c'. Parameters 'cmap' will be ignored
 plt.scatter(x_reduce[:,0], x_reduce[:,1],cmap='viridis')



Extra - Bining Method

5,10,11,13,15,35,50,55,72,92,204,215.

Partition them into three bins by each of the following methods: (a) equal-frequency (equal-depth) partitioning (b) equal-width partitioning

In [23]:

```
Sorted Data: [5, 10, 11, 13, 15, 35, 50, 55, 72, 92, 204, 215]
```

(a) Equal-Frequency Bins:

Bin 1: [5, 10, 11, 13]

Bin 2: [15, 35, 50, 55]

Bin 3: [72, 92, 204, 215]

(b) Equal-Width Bins:

Bin 1: [5, 10, 11, 13, 15, 35, 50, 55, 72]

Bin 2: [92]

Bin 3: [204, 215]

In []: