# Contents A. Al Agent--I...

Α.	Al AgentI	<u>'</u>
Co	onfigure OpenAI with localAI2	<u>)</u>
Co	onfiguring AI Agent:	<u>)</u>
В.	System Message Template:	ļ
C.	Making chat public on a URL5	5
D.	SMTP node-I	7
E.	SMTP nodeII	)
F.	SMTP nodeIII	3
G.	N8n memory error	5
H.	N8n on docker with PostgreSQL on machine	5
l.	Al agent and postgres	)
J.	Data transformation	L
K.	Sub-workflows in n8n	L
L.	Using webhook in n8n	L
M.	Slack	L
W	hat are Slack channels:24	ļ
N.	Pinecone vector store:	5
M	etadata25	5
0.	Simple RAG with n8n	3
P.	RAG with Pinecone	3
Sc	rapping web-pages and summarization35	5
Q.	Send SMS using Twilio	3
D	Slack ADI	`

# A. Al Agent--I

# Refer <u>this video</u>

# Configure OpenAI with localAI Our workflow:




Figure 1: We will use LocalAI instead of OpenAI

## Configuring Al Agent:

You also have to write a user prompt:




Figure 2: Write user prompt also

#### Here is an expanded view of AI Agent:




Figure 3: A User prompt is required

#### This is OpenAI chat model:




Figure 4: Base URL of localai is: http://localhost:8080/v1. Note it is NOT https




Figure 5: On our machines gemma-3-4b-it works well. Under <u>Add options</u>, you can also write System Message (see below)

#### B. System Message Template:

A recommended *System Message* template is below. See <u>this link</u> also.




Figure 6: Broad System Message format

# C. Making chat public on a URL

See this diagram again and make workflow *Active*:




Figure 7: Make workflow **Active**. Then, double click to open the Chat message trigger and proceed to next diagram.

Double Click on the first node (When chat message received) to open it:




Figure 8: Click on Make chat public and then get the URL

And here is the web-page with the copied URL:




Figure 9: Chat message that triggers n8n workflow

#### D. SMTP node-I

Refer here and here

Follow these steps to send an email to your Gmail account:

- a. In your Gmail account, set-up two step verification. See <u>this link</u> as to how to set-up two-step verification account.
- b. To generate an app password:
  - a. In your Google account, go to App passwords.
  - b. Enter an App name for your new app password, like 'n8n credential'.
  - c. Select Create.
  - d. Copy the generated app password. You'll use this in your n8n credential.
- c. Here is how you setup SMTP node:




Figure 10: Set up SMTP account as below. From email should correspond to your app-password. This message will be

#### Here is how you setup SMTP account credentials.




Figure 11: Setup SMTP credentials: <u>User</u> is your email address. <u>Password</u> is App-password. <u>Host</u> is always: smtp.gmail.com. <u>Port</u> is always: **465**. <u>Client Host</u> name is NULL.




Figure 12: On click Execute step an email will be sent to the send account. This email does not carry calculator output. It has fixed message. See below

#### Send calculator output:




Figure 13: Use Text fomat. And drag the output to here from left panel. In <a href="mailto:ashok@fsm.ac.in">ashok@fsm.ac.in</a> check All Mail as also Inbox

#### E. SMTP node--II

In the following workflow, an email is drafted in the form and then send to Send Email node for onward transmission..




Figure 14: On form submission, the email is sent to desired address.




Figure 15: The form. Its elements are: email, text and text

#### These are the form elements:




Figure 16: Form fields




Figure 17: Form elements to be submitted to SMTP node--Pinned

Send Email INPUT OUTPUT Settings Docs ☑ Credential to connect with SMTP account Operation Send 2025-07-13T22:48:59.634-04:00 fx ccma@fsm.acin A formMode Variables and co To Email fx {{ \$ison.emailAddress }} Subject fx { Email I Text fx { \$json.body }} Th Ор Add option

Set up credentials of SMTP service as before. And fill up fields as below.

Figure 18: Left panel contains data submitted from **form**. Drag fields from left panel to the Central panel instead of writing json code. For example, drag **emailAddress** from left panel and drop it in **To:Email** field; similarly for **subject** and other fields. You can press <shift><ENTER> to enter a new line.

On Execute workflow, an email goes to <a href="mailto:ashok@fsm.ac.in">ashok@fsm.ac.in</a>.

#### F. SMTP node--III

You can make the above workflow a little more complex by introducing a switch and in the form element writing an email.




Figure 19: Configuration for switch node is as below.




Figure 20: Input element of email is tested in the two rules. Upper rule tests for <a href="mailto:ashok@fsm.ac.in">ashok@fsm.ac.in</a> and the lower rule tests for <a href="mailto:ashok@fsm.ac.in">ccma@fsm.ac.in</a> and the lower rule tests for <a href="mailto:ashok@fsm.ac.in">ccma@fsm.ac.in</a> and the lower rule tests for <a href="mailto:ashok@fsm.ac.in">ashok@fsm.ac.in</a> and ashok@fsm.ac.in</a> an



Figure 21: Switch node details

#### G. N8n memory error

n8n keeps data in memory while the workflows are running. Creating sub-workflows is a good idea as after a sub-workflow is executed, its memory is released. At times n8n breaks and gives memory error. Error message is about JavaScript heap memory being exceeded. Memory needs to be increased. See <a href="this link">this link</a> and <a href="this link">this link</a>.

One can assign more memory by changing the environment variable --max-old-space-size. This can be done while starting docker, as:

```
docker run -d --name n8n -p 5678:5678 -e NODE_OPTIONS="--max-old-space-size=8000" docker.n8n.io/n8nio/n8n
```

And, if n8n is directly installed, run n8n as:

```
NODE OPTIONS="--max-old-space-size=8000" npx n8n
```

To check memory usage, issue top command. Specifically for user ashok, issue top -u ashok:

	:33:57 up								
	52 total,						stoppe		zombie , 0.0 si, 0.0 st
cpu(s):	0.5 us,	٥.	ı sy	, 6.6 n	1, 99.4	1a, 0.	o wa,	0.0 ni	, 0.0 51, 0.0 51
PID	USER	PR	NI	VIRT	RES	SHR S	%CPU	%MEM	TIME+ COMMAND
1486	ashok	20	0	38.6g	6.9g	56640 S	14.0	22.9	1:46.01 node
1605	ashok	20	0	7800	3680	3040 S	0.3	0.0	0:00.31 top
1	root	20	0	167152	11356	7836 S	0.0	0.0	0:00.81 systemd
2	root	20	0	3060	1760	1760 S	0.0	0.0	0:00.00 init-systemd(Ub
6	root	20	0	3076	1820	1760 S	0.0	0.0	0:00.00 init
61	root	19	-1	47804	14080	13280 S	0.0	0.0	0:00.11 systemd-journal
90	root	20	0	23028	5888	4608 S	0.0	0.0	0:00.10 systemd-udevd
127	systemd+	20	0	26200	14240	9120 S	0.0	0.0	0:00.05 systemd-resolve
128	systemd+	20	0	89364	7040	6240 S	0.0	0.0	0:00.05 systemd-timesyn
209	root	20	0	4308	2560	2400 S	0.0	0.0	0:00.00 cron
211	message+	20	0	8588	4000	3680 S	0.0	0.0	0:00.13 dbus-daemon
223	root	20	0	30088	18400	9920 S	0.0	0.1	0:00.08 networkd-dispat
226	syslog	20	0	222404	4800	4160 S	0.0	0.0	0:00.02 rsyslogd
232	root	20	0	15336	6880	6240 S	0.0	0.0	0:00.08 systemd-logind
253	root	20	0	3240	2080	2080 S	0.0	0.0	0:00.00 agetty
257	root	20	0	3196	1920	1920 S	0.0	0.0	0:00.00 agetty
258	root	20	0	15436	9120	7520 S	0.0	0.0	0:00.00 sshd
322	root	20	0	107164	20960	13120 S	0.0	0.1	0:00.07 unattended-upgr
359	postgres	20	Θ	215808	29600	27040 S	0.0	0.1	0:00.05 postgres
441	postgres	20	Θ	215808	7448	4800 S	0.0	0.0	0:00.00 postgres
442	postgres	20	0	215808	8568	5920 S	0.0	0.0	0:00.04 postgres
443	postgres	20	0	215808	11448	8800 S	0.0	0.0	0:00.01 postgres
444	postgres	20	0	216376	10168	7200 S	0.0	0.0	0:00.00 postgres

Figure 22: top command output. RES shows total memory usage by user 'ashok' and the process is node (ie nodejs).




Figure 23: Output of command: top -u ashok. You can also see total memory as also free memory

H. N8n on docker with PostgreSQL on machine

#### Steps:

- a. Reconfigure PostgreSQL security:
  - o Configure /etc/postgresql/16/main/postgresql.conf. Here '/16/' is the version number. Check the line:

```
cat /etc/postgresql/16/main/postgresql.conf | grep listen
You will get:
#listen_addresses = 'localhost'
```

o Modify the *listen\_addresses* parameter to allow connections from external interfaces. To allow connections from all interfaces, set it to '\*'.

```
listen_addresses = '*'
```

Configure /etc/postgresql/16/main/pg\_hba.conf. For broader access (e.g., from a specific IP range), you can use a CIDR notation. In google you can raise a query: 'how to write 172.30.109.200 with netmask of 255.255.240.0 in cidr notation'. Or see this link for calculation:

host all all 172.30.96.0/20 md5

Restart postgresql

sudo systemctl restart postgresql

Create a user, say kumar, and assign him necessary privileges: (See this file (at line no 170-211) for all the quick code):

```
sudo useradd -m kumar
sudo passwd kumar
sudo -u postgres psql -c 'create database kumar;'
sudo -u postgres psql -c 'create user kumar;'
sudo -u postgres psql -c 'grant all privileges on database kumar
to kumar; ' -d kumar
sudo -u postgres psql -c "alter user kumar with encrypted
password 'kumar';
sudo -u postgres psql -c " GRANT ALL ON SCHEMA public TO kumar;"
-d kumar
sudo -u postgres psql -c " CREATE EXTENSION vector;" -d kumar
# Add a table and a record
sudo -u kumar psql -c "CREATE TABLE acars ( brand VARCHAR(255),
model VARCHAR(255), year INT);" -d kumar
sudo -u kumar psql -c "INSERT INTO acars (brand, model, year)
VALUES ('Ford', 'Mustang', 1964);" -d kumar
```

o OR as: Create a table in database kumar, as:

```
$sudo su kumar
$psql kumar
kumar=> \c kumar
You are now connected to database "kumar" as user "kumar".
kumar=> CREATE TABLE acars ( brand VARCHAR(255), model VARCHAR(255), year INT);
kumar=> INSERT INTO acars (brand, model, year) VALUES ('Dzire', 'Maruti', 1994);
kumar=> INSERT INTO acars (brand, model, year) VALUES ('Swift', 'Maruti', 1984);
kumar=> select * from acars;
```

b. In n8n create the following very simple network:




Figure 24: Double click to open it. In Query write: select \* from acars; OR select \* from employees;

#### Create PostgreSQL credentials, as:




Figure 25: User: kumar; password: kumar; database: kumar




Figure 26: Query: select \* from acars; The result is on the right.

# Extend the above workflow further, step-by-step:




Figure 27; Workflow using different postgres nodes: Execute SQL Query, Insert rows, Delete table of rows





Figure 28: Delete table rows settings

# I. Al agent and postgres

#### Postgres with ai agent

https://n8n.io/workflows/1954-ai-agent-chat/



#### System prompt of AI agent:

You are DB assistant. You need to run queries in DB aligned with user requests. Run custom SQL query to aggregate data and response to user. Make sure every table has schema prefix to it in sql query which you can get from `Get DB Schema and Tables List` tool. Fetch all data to analyse it for response if needed.

#### ## Tools

- Execute SQL query- Executes any sql query generated by AI
- Get DB Schema and Tables List Lists all the tables in database with its schema name
- Get Table Definition Gets the table definition from db using table name and schema name"

#### **Create tables**

(See this file (at line no 170-211) for all the quick code):

#### **INSERT Data:**

```
INSERT INTO departments (department_id,department_name) values
(1, 'Human Resources'),
(10,'Finance'),
(20,'IT'),
(30, 'Operations');

INSERT INTO employees (employee_id,employee_name, age, departmentId) values
(1,'Alice', 30.4, 10),
(2,'Bob',50.8, 10),
(3,'sudha', 39.0, 20),
(4,'Charlie',34.0, 30);
```

- J. Data transformation
- K. Sub-workflows in n8n
- L. Using webhook in n8n
- M. Slack

How to get slack api or token from slack. Here are the steps:



Figure 29: Sign in using your email.




Figure 30: Create a new Workspace of your own where your team will work




Figure 31: Create a Workspace



Figure 32: Fill in some details about your workspace. Name your team and click Next




Figure 33: Add team members




Figure 34: No. Start with a limited free version




Figure 35: Three channels, one app

#### What are Slack channels:

A Slack channel is a dedicated space within a Slack workspace where teams can collaborate, communicate, and share information related to a specific topic, project, or team. Channels can be public, allowing anyone in the workspace to join, or private, requiring explicit invitation. Key features of channels are:

Collaboration: Channels facilitate communication, file sharing, and even video/audio calls.

**Searchability:** Messages and files within a channel are searchable, making it easy to find past conversations and information.

**Customization:** Channels can be created for various purposes, such as project updates, team discussions, or specific topics.

A company might have a public channel for general announcements (#general), a private channel for sensitive HR matters (#hr-private), and a project-specific channel for a new product launch (#product-launch).

What is an app

Apps connect other software that you use (such as Google Calendar, OneDrive or one of your company's internal tools) to Slack. With all your tools in one place, you can streamline work and help people in your workspace collaborate more effectively.

#### What you need to know

- There are a few different types of apps that you may see in Slack built by Slack, third parties or your own team. How an app was built determines how it can be installed and managed in a workspace, as well as where and how you'll be able to interact with it.
- By default, any workspace member can <u>install apps</u>, but owners and admins can choose to <u>restrict this permission</u>. Once an app is installed to a workspace, any member can connect their account to use it.
- Before installing an app from the Slack Marketplace, you can review its privacy policy and security and compliance information (if submitted by the app's developer) from the app page. We recommend only choosing services that you trust when installing apps to Slack.

#### N. Pinecone vector store:

- 1. Create a free account (say, using google)
- 2. Create an API key
- 3. Create a (vector) index

#### **Understanding Pinecone indexes:**

In Pinecone, an index is the primary organizational unit for storing and querying vector data. Think of it as a table in a database, but specifically designed for efficient similarity searches on vectors. Indexes can accept, store, and serve queries on vectors, as well as perform other vector operations. Here's a more detailed breakdown:

#### **Storage and Organization:**

Indexes hold the vector embeddings of your data, allowing you to store and manage them in a structured way.

#### **Key Parameters dimension etc:**

When creating an index, you'll need to define its name, the dimensionality of the vectors it will store, and the similarity metric (e.g., cosine, Euclidean).

#### Types of Indexes for scaling out:

Pinecone offers <u>serverless</u> and <u>pod-based</u> indexes, with different options for scaling and performance.

#### Namespaces:

Within an index, you can further organize data using namespaces, allowing you to isolate queries to specific subsets of your data.

#### **Similarity Search:**

Pinecone indexes are built for efficient similarity searches, meaning you can quickly find vectors that are similar to a given query vector.

#### **Highest Level:**

It's the top-level container for your vector data within Pinecone, similar to a table in a relational database.

#### **Creation and Management:**

Indexes can be created via the Pinecone UI or programmatically using their API.

#### Metadata:

Pinecone indexes can store associated metadata with each vector, enabling filtering and more complex search conditions.

#### Metadata

Every <u>record</u> in an index must contain an ID and a vector. In addition, you can include metadata key-value pairs to store additional information or context. When you query the index, you can then include a <u>metadata filter</u> to limit the search to records matching a filter expression. Searches without metadata filters do not consider metadata and search the entire namespace.

See LlamaIndex example for Chromadb as to how metadata filter works.




Figure 36: Click Create Index to begin creating an index





Figure 37: Select an index and select a Configuration for index (such as Vector Dimension: 768, 1024 etc). See figure below

# Configuration



# Index configured for Ilama-text-embed-v2:

Modality	Text
Vector type	Dense
Max input	2,048 tokens
Starter limits	5M tokens
Dimension	1024
Metric	cosine

Figure 38: Set vector Dimension as per your embedder (click Down-arrow). For example, nomic-embed-text has a vector dimension of 768 AND NOT of 1024. We have used 768




Figure 39: Create index. Records will come from n8n workflow

Note that selected embedder will also decide max input tokens. The character splitter chunk size will affect the amount of **input tokens** you're trying to get. For the embedding model of. *mxbai-embed-large*, max input token limit is 512.

Our dataset is students.json on GitHub, at site: LLMs/install\_ai\_tools/mongodb//datasets/

```
{"id":0,"name":"aimee Zank", "scores":[{"score":1.463179736705023,"type":"exam"},{"score":11.78273309957772,"type":"quiz"},{"score":35.8740349954354,"type":"homework"}]}
{"id":1,"name":"Aurelia Menendez", "scores":[{"score":60.06045071030959, "type":"exam"},{"score":52.79790691903873, "type":"quiz"},{"score":71.76133439165544, "type":"homework"}]}
{"id":2,"name":"Corliss Zuk", "scores":[{"score":60.03077096065002, "type":"exam"},{"score":63.03851677835235, "type":"quiz"},{"score":62.28344683278382, "type":"homework"}]}
{"id":3,"name":"Bao Ziglar", "scores":[{"score":71.64343899778332, "type":"exam"},{"score":24.80221293650313, "type":"quiz"},{"score":42.26147058804812, "type":"homework"}]}
{"id":4,"name":"Zachary Langlais", "scores":[{"score":78.68385091304332, "type":"exam"},{"score":90.2963101368042, "type":"quiz"},{"score":34.41620148042529, "type":"homework"}]}
{"id":5,"name":"Venette Flanders", "scores":[{"score":44.87186330181261, "type":"exam"},{"score":25.72395114668016, "type":"quiz"},{"score":63.4228310628662, "type":"homework"}]}
{"id":7,"name":"Salena Olmos", "scores":[{"score":90.37826509157176, "type":"exam"},{"score":42.48780666956811, "type":"quiz"},{"score":96.52986171633331, "type":"homework"}]}
{"id":8,"name":"Daphne Zheng", "scores":[{"score":22.13583712862635, "type":"exam"},{"score":14.63969941335069, "type":"quiz"},{"score":75.94123677556644, "type":"homework"}]}
```

Figure 40: Extract from file students.json

#### Here are two rows from the data:

```
{"_id":0,"name":"aimee
Zank","scores":[{"score":1.463179736705023,"type":"exam"},{"score":11.78273309957772,"type":"q
uiz"},{"score":35.8740349954354,"type":"homework"}]}

{"_id":1,"name":"Aurelia
Menendez","scores":[{"score":60.06045071030959,"type":"exam"},{"score":52.79790691903873,"type
":"quiz"},{"score":71.76133439165544,"type":"homework"}]}
```

#### O. Simple RAG with n8n

File: 'Simple RAG flow.json'

We use 'n8n Form trigger' node as file uploader. The vector store is in-memory vector store: Simple Vector Store.




Figure 41: Full workflow

#### Its two sub-workflows are as follows:




Figure 42: Creating a vector store

## Upload files node (n8n form):




Figure 43: File upload with n8n form. Allow both pdf and txt files upload. Easy to upload Paul Graham essay on Good Wrining.

#### Simple vector store




Figure 44: Simple Vector store configuration

#### Default Data loader




Figure 45: Default data loader. Type of data is Binary. Text splitting is Simple

Al Agent has no special system prompt. Default is OK. But you should change. See below the suggested system message.




Figure 46: No special System prompt in AI Agent

#### System message in Al Agent:

You are an expert in answering questions after extracting information from the provided 'Simple Vector Store1' on the game of football. You only answer from the extracted context and not from your own knowledge. In case the extracted contextual information from 'Simple Vector Store1' does not answer the user's query, you simply say 'I do not know'.

#### Retriever tool description

Retrieves information pertaining to the game of football

#### Simple vector store below AI Agent




Figure 47: Simple vector store on AI Agent side




Figure 48: Querying a vector store

System message of AI Agent and vector tool description are as follows:

System message in Al Agent:

You are an expert in answering questions after extracting information from the provided 'Simple Vector Store1' on the game of football. You only answer from the extracted context and not from your own knowledge. In case the extracted contextual information from 'Simple Vector Store1' does not answer the user's query, you simply say 'I do not know'.

Retriever tool description

Retrieves information pertaining to the game of football

Figure 49: System message for AI Agent

#### P. RAG with Pinecone

N8n model files: n8n/2025/Rag Flow-I.json and Rag Flow-II.json

Dataset files: Try this

See <u>this link</u> for the detailed blog. Vectorization may take a very long time depending upon the input size. As vectorization of files may take a long time, a smaller json file is on GitHub <u>at this link</u>. This file has 35 json records.




Figure 50: Our workflow to save data to vector store. 47 items possibly means that 47 chunks were processed till now. Chunk size for Recursive text splitter is 512 as selected embedder is:




Figure 51: Reading vector data from Pinecone vector store

a. Here are the models used:

Embedding: nomic-embed-text (ollama)
Chat ollama: mistral-nemo (ollama)

b. Questions asked:

## Questions

1. This question fails:

Who scored the max quiz marks?

Possibly the query is compared with data in vector store and 10 matching results are taken out. The LLM then compares marks from among 10 and gives the reply. Try to load this data in csv format to get proper answer.

- 2. These questions succeed:
  - a. What are the scores of Edgar in Quiz?
  - b. Compare the scores of Edgar with that of Rudolph.
  - c. Find the student with maximum of score in quiz. Examine all the data before answering that is examine data from \_id of 0 to \_id of 199.


c. Al Agent System message:


You are a helpful assistant. You answer questions on scores of students and not from your own training data.


d. Tool Agent Description


You answer questions regarding scores of students in exam, quiz and homework


Scrapping web-pages and summarization











n8n how to decide css selector in html node

Thinking

Kicking off 7 searches

Looking at 105 sites

Putting it all together

Deciding on the correct CSS selector in n8n's HTML node (formerly HTML Extract node) is crucial for accurately extracting the data you need from a web page. Here's a breakdown of how to approach this, including recommended practices and tools:

1. Using Browser Developer Tools (Inspect Element)

The easiest and most common way to identify the correct CSS selector is by using your web browser's developer tools.

- Navigate to the web page: Open the web page containing the data you want to scrape in your browser.
- **Inspect the element:** Right-click on the specific element (text, image, link, etc.) you want to extract and select "Inspect" or "Inspect Element". This will open the browser's developer tools and highlight the element's HTML code.
- Copy the CSS Selector/Path: In the developer tools (usually under the "Elements" tab), right-click on the highlighted HTML element and choose "Copy" > "Selector". This will copy the CSS selector to your clipboard

Using the CSS selector in the n8n HTML node

- Add an HTML node to your workflow: According to n8n Docs and, the node is called "HTML" (it replaced the older "HTML Extract" node).
- **Set Source Data:** Choose "JSON" if the HTML content is in the JSON output of a previous node (like an HTTP Request node), or "Binary" if the HTML is in a binary file.
- **Specify JSON Property (if applicable):** Enter the name of the JSON property containing the HTML.
- Add Extraction Value: Click "Add Value" to define what you want to extract.
- **Key:** Enter a name for the extracted value (e.g., "title", "price").
- CSS Selector: Paste the CSS selector you identified in the previous steps.

- **Return Value:** Choose the type of data to return: "Attribute" (e.g., "href" for links), "HTML", "Text", or "Value" (for input elements).
- **Return Array (if applicable):** If you expect multiple elements to match the selector, enable "Return Array" to get an array of values.

#### Example:

If you want to extract the text "Medium" from a <span> element within a table, the copied CSS selector might look like:

body > table:nth-child(2) > tbody:nth-child(1) > tr:nth-child(1) > td:nth-child(2) > span:nth-child(1)

#### **Understanding CSS Selector Syntax:**

Familiarize yourself with basic CSS selector syntax (e.g., . for classes, # for IDs, > for direct children, nth-child() for selecting elements based on their position) to create or modify selectors manually if needed.

#### Q. Send SMS using Twilio

- 1. Open <u>Twilio home</u> page:
- 2. Click on 'Start for free' button at the top-right
- 3. At the bottom of this page, click on Sign up with Google
- 4. After signing in, you have to enter your mobile number so as to verify the destination SMS address. Click the button *Send code via SMS*
- 5. You will receive a verification code on your mobile by SMS. Enter the code and click Verify button.
- 6. You will get a recovery code. Copy and Save it somewhere (maybe your email): XYTMNTY5PGJLS7FA52S5MY3YHP
- 7. Click Continue button
- Fill up some survey information.
   Which channel are you interested in? ==> Select SMS
- 9. You are taken to following screen. This screen has two parts: Top and Bottom.

In the top part, you are invited to get a free telephone number from where you will get an SMS. Note down this number.




Figure 52: Click the button 'Get Phone Number'

In the bottom part of the page, you get *Account information* and *Auth token*. Save this information also.




Figure 53: Copy each and every information from this page into your email

#### R. Slack API

To work with Slack API, click <u>on this link</u> or in Google, search for Slack API. <u>Click here</u> OR <u>here</u>.



Figure 54: Click on Create an App




Figure 55: Click From Scratch




Figure 56: Fill it up and click Create App




Figure 57: Not sure if to note down these or not.




Figure 58: Click Install Apps




Figure 59: Click Install to FORE School. But first Give permissions




Figure 60: Allow your App permissions on your Workspace




Figure 61: A token will be generated. Note this down. This token is important.

#### xoxb-9192442410912-9192645536416-cKpr88MQ0FNbrOhGKa8Llkpp




Figure 62: An App FORE Service is now visible

## YouTube video

