Crewai Creating Raw Python Environment

Last amended: 17th May, 2026
My folder: D:\Documents\OneDrive\Documents\crewai
Reference: Crewai documentation here
Reference introductory videos on crewai here AND here.

Quick code for single python file:

Here is a quick 4-line code. But you can read on for explanation:

```
cd ~/
uv venv my_env                          # Create an env by name of my_env
source my_env/bin/activate              # Activate it
# Note it is NOT 'pip install' but 'uv pip install'.
uv pip install crewai crewai[tools] langchain  langchain-openai langchain-ollama
langchain-community langchain-classic langchain-experimental langchain-cli
```

Now you can create a python file in this environment and call crewai packages using '`from crewai import…`'.

`pip install vs uv pip install`:

By default, '*`uv pip install`*' requires an activated **virtual environment** and will refuse to install into the system Python unless you explicitly use the --system flag. '*`pip install`*' will often install globally if no environment is active.

Quick code for standard crewai install:

Here is a quick 5+1-line code for standard crewai-CLI install with python packages added:

```
cd ~/
uv tool install crewai  # Only if crewai was not earlier installed
crewai create crew my_project
cd my_project
crewai install
uv add crewai crewai[tools] langchain  langchain-openai langchain-ollama
langchain-community langchain-classic langchain-experimental langchain-cli
```

::Q1:: How to create a raw python environment for crewai using uv?

To create a raw Python environment for **crewAI** using `uv`, you can initialize a new project, create a virtual environment, and then install the crewAI packages directly using `uv`'s high-speed package management commands.

Details

1. Install uv

If you haven't installed `uv` yet, use the following commands based on your operating system:

- **macOS/Linux**: `curl -LsSf https://astral.sh/uv/install.sh | sh`
- **Windows (PowerShell)**: `powershell -c "irm https://astral.sh/uv/install.ps1 | iex"`

2. Initialize Your Project

Navigate to your desired folder and initialize a basic Python project structure:

```
mkdir my-crew-project
cd my-crew-project
uv init
```

The `uv init` command **sets up a new Python project by creating a standard folder structure and configuration files**. It eliminates the hassle of manually creating virtual environments, `.gitignore` files, and metadata configurations. Astral Docs +1

Depending on how you use it, `uv init` generates different types of project setups: Python Developer Tooling Handbook

1. Application Setup (`uv init`)

Running the command by itself (or with a directory name) creates a default application project perfect for web apps, scripts, and command-line tools. It automatically generates: Astral Docs +2

- `pyproject.toml` : Manages project configuration and metadata.
- `README.md` : A placeholder for project documentation.
- `main.py` : A basic sample script to test your setup.
- `.python-version` : Specifies your target Python version.
- `.git` and `.gitignore` : Initializes version control. Astral Docs +4

3. Create the Virtual Environment:

Create a managed virtual environment. For crewAI, it is recommended to use **Python 3.10 to 3.12**.

```
# Create environment with your system's default Python
uv venv

# OR specify a version (e.g., 3.12)
uv venv --python 3.12
```

To activate the environment:

- **macOS/Linux**: `source .venv/bin/activate`
- **Windows**: `.venv\Scripts\activate`

4. Install crewAI Packages:

Install the core library and any additional tools you might need using the `uv pip` interface:

```
# Install the main crewAI package in the virtual env
uv pip install crewai

# Install crewAI with built-in tools (recommended)
uv pip install 'crewai[tools]'
```

5. Verify Installation

Check that the environment is set up correctly by verifying the installed package version:

```
uv pip list | grep crewai
```

::Q2::After creating the virtual environment should I work in *`my-crew-project`* folder or *`my-crew-project/.venv`* folder

You should always work inside the **my-crew-project** folder. Here is why and how to handle both folders:

Where to Work

- **Keep your files here**: Write your code, configuration files, and script files directly inside **my-crew-project**.
- **Run commands here**: Execute your terminal commands (like python main.py) from this root folder.

What is the **.venv** Folder?

- **It is a system folder**: The .venv directory contains the Python interpreter, standard libraries, and downloaded dependencies (like crewai).
- **Do not modify it**: You should never manually add, edit, or delete files inside the `.venv` folder.
- **Hide it from Git**: Ensure .venv is added to your .gitignore file so you do not upload external dependencies to your repository.

::Q3:: Installation of crewai CLI does not install python packages?

That is completely correct. **`uv tool install crewai` only installs the standalone CrewAI Command-Line Interface (CLI)**. It isolates the `crewai` binary globally so you can use commands like `crewai create crew`. It intentionally **does not** inject the Python libraries into your workspace. To actually write `from crewai import Agent` in a script, you must add the library package to your local environment.

How to Use the CrewAI Workflow Correctly?

You can resolve this by following the workflow that matches your development preference:

Option A: The Automated CrewAI Project Workflow (Recommended)

If you want to use CrewAI's structured template with pre-configured agents and tasks, use the CLI tool you just installed to generate the environment for you:

1. **Generate the project structure:**
   ```
   crewai create crew my_project
   ```
2. **Navigate into the new folder:**
   ```
   cd my_project
   ```
3. **Lock and install all Python libraries automatically:**
   ```
   crewai install
   ```

(This command runs `uv pip install` *behind the scenes inside a local virtual environment it creates for you).*

4. **Add any other python packages with uv add:**

```
uv add crewai crewai[tools] langchain  langchain-openai langchain-ollama
langchain-community langchain-classic langchain-experimental langchain-cli
```

`uv add` uses `uv pip install` behind the scenes.

5. **Point VS Code to this new environment:**

Open the **Command Palette** (`Ctrl+Shift+P` / `Cmd+Shift+P`), **Python: Select Interpreter** select the `.venv` folder created inside `my_project`.

When you use the CrewAI CLI to create a project, it generates a standard structure centered around a `pyproject.toml` file. LinkedIn · Fikayo Adepoju +3

1. pyproject.toml: This file tracks your project's dependencies. When you run `uv add`, it automatically updates this file.
2. **Virtual Environment:** CrewAI automatically manages a virtual environment for your project. Using `uv` ensures that packages are installed specifically into this isolated environment rather than your global Python installation.
3. **Execution:** After installing new packages, you can run your project using `crewai run`, which executes the crew within the managed environment. CrewAI Documentation +3

Option B: The Quick Script Workflow (For single `.py` files)

If you just want to run a loose script without a formal project folder structure, you need to manually add the package to a local virtual environment:

6. **Create a local virtual environment in your workspace:**

```
uv venv          # Default env below: .venv
OR
uv venv my_env   # Env name: my_env
```

7. **Activate the environment:**

`source .venv/bin/activate`

OR

`source my_env/bin/activate`

8. **Once, activated, install the Python package directly into this environment:**

```
uv pip install crewai crewai[tools]
```

9. **Match your VS Code Interpreter:**

   Ensure your VS Code Python Interpreter is pointing to the `.venv` (or `my_env`) file you just spun up in this folder.

10. **Quick three lines code:**

```
uv venv my_env
source my_env/bin/activate
pip install --upgrade pip
uv pip install crewai crewai[tools] langchain  langchain-openai langchain-ollama langchain-community langchain-classic langchain-experimental langchain-cli
```

11. **Remove my_env**

```
rm -rf my_env
```

If you decide to go with **Option A**, let me know if you run into any dependency errors when running `crewai install`!

#########