

Cloudflare Secure Worker-to-Worker POC

Overview

Secure Worker-to-Worker communication using Cloudflare Access and HMAC signing.

Architecture

vendor-worker-a → Cloudflare Access → protected-worker-b → HMAC Validation

Components

Worker A: vendor-worker-a
Worker B: protected-worker-b
Hostname: api.volblut.com
Service Token: Vendor-Test

Step 1 — Create Worker B

Deploy protected-worker-b and attach api.volblut.com.

Step 2 — Configure Access

Create Self-hosted Access application Worker B Protected API.

Step 3 — Create Service Token

Create Vendor-Test token and save Client ID and Secret.

Step 4 — Configure Service Auth Policy

Policy Action: Service Auth
Include: Service Token → Vendor-Test

Step 5 — Configure DNS

AAAA api → 100:: → Proxied

Step 6 — Configure Route

api.volblut.com/*

Worker A Fetch Example

```
const path = "/vendor/vendor-a";

const response = await fetch(
  "https://api.volblut.com/vendor/vendor-a",
  {
    method: "POST",
    headers: {
      "CF-Access-Client-Id": env.CF_ACCESS_CLIENT_ID,
      "CF-Access-Client-Secret": env.CF_ACCESS_CLIENT_SECRET
    }
  }
);
```

Successful Response

```
{
  "success": true,
  "message": "Authenticated request accepted",
  "path": "/vendor/vendor-a"
}
```