

RRT Sampling-Based Motion Planning

```
In [11]: # The autoreload extension will automatically load in new code as you edit files,
# so you don't need to restart the kernel every time
%load_ext autoreload
%autoreload 2

import numpy as np
import matplotlib.pyplot as plt
from P2_rrt import *

plt.rcParams['figure.figsize'] = [8, 8] # Change default figure size
```

The autoreload extension is already loaded. To reload it, use:

```
%reload_ext autoreload
```

Set up workspace


```
In [12]: MAZE = np.array([
    (( 5, 5), (-5, 5)),
    ((-5, 5), (-5,-5)),
    ((-5,-5), ( 5,-5)),
    (( 5,-5), ( 5, 5)),
    ((-3,-3), (-3,-1)),
    ((-3,-3), (-1,-3)),
    (( 3, 3), ( 3, 1)),
    (( 3, 3), ( 1, 3)),
    (( 1,-1), ( 3,-1)),
    (( 3,-1), ( 3,-3)),
    ((-1, 1), (-3, 1)),
    ((-3, 1), (-3, 3)),
    ((-1,-1), ( 1,-3)),
    ((-1, 5), (-1, 2)),
    (( 0, 0), ( 1, 1))
])

# try changing these!
x_init = [-4,-4] # reset to [-4,-4] when saving results for submission
x_goal = [4,4] # reset to [4,4] when saving results for submission
```

Geometric Planning

```
In [13]: grrt = GeometricRRT([-5,-5], [5,5], x_init, x_goal, MAZE)
grrt.solve(1.0, 2000)
```


```
Out[13]: True
```



Adding shortcutting

```
In [14]: grrt.solve(1.0, 2000, shortcut=True)
```

```
Out[14]: True
```




Dubins Car Planning

```
In [28]: x_init = [-4,-4,0]
x_goal = [4,4,np.pi/2]

drirt = DubinsRRT([-5,-5,0], [5,5,2*np.pi], x_init, x_goal,
MAZE, .5)
drirt.solve(1.0, 1000, shortcut=True)
```

Out[28]: True



```
In [26]: x1=[2.99, 3, 0]
x2=[3., 3., 0]
eps=1.0
drirt.steer_towards(x1,x2,eps)

[(2.99, 3.0, 0.0)]
```

Out[26]: [3.0, 3.0, 0]

In []: