


Homework Ten

Jeremy Harper  
STA4702  
03.14.12

6.1



Yes, the result that point  $\delta = 0$  falls outside of the confidence region is consistent with the  $T^2$  - test that  $\delta \neq 0$ , as the region does not contain  $\delta = 0$ .

6.6a

	y1		y2		x1		x2
s1							
	3	3	2	3	2	4	3
2	1	-1.5					
	1	6	5	1			
-1.5	3						
	2	3	3	1			
			2	3			
			s2		n1	n2	spool
			2	-1.333333	3	4	1.6
-1.4			-1.333333	1.333333			-1.4

6.6b  $T^2 = 3.87$ . Compared to  $\frac{(n_1 + n_2 - 2)p}{(n_1 + n_2 - p - 1)} F_{p, n_1 + n_2 - p - 1}$ , or  $(10/4)F_{2,4}(.01) = 45$ . As  $3.87 < 45$ , there is no evidence against the hypothesis  $H_0 = \mu_1 - \mu_2 = 0$ .

6.6c The 99% simultaneous confidence intervals for the differences  $\mu_{1i} - \mu_{2i}$  for  $i = 1, 2$  are

$$(\bar{x}_{11} - \bar{x}_{21}) \pm \sqrt{\frac{(n_1 + n_2 - 2)p}{n_1 + n_2 - p - 1} F_{p, n_1 + n_2 - p - 1}(\alpha)} \sqrt{\left(\frac{1}{n_1} + \frac{1}{n_2}\right) \mathbf{S}_{11, \text{pooled}}}$$

$$(2 - 3) \pm \text{sqrt}(45 * (1/3 + 1/4) * 1.6) = -1 \pm 6.481$$

and

$$(\bar{x}_{12} - \bar{x}_{22}) \pm \sqrt{\frac{(n_1 + n_2 - 2)p}{n_1 + n_2 - p - 1} F_{p, n_1 + n_2 - p - 1}(\alpha)} \sqrt{\left(\frac{1}{n_1} + \frac{1}{n_2}\right) \mathbf{S}_{22, \text{pooled}}}$$

$$(4 - 2) \pm \text{sqrt}(45 * (1/3 + 1/4) * 2) = 2 \pm 7.246$$

#### CODE

```
/* 6.1a */

data t61;
  infile "\
\psf\Home\Documents\University\Spring_2012\STA4702\Datasets\T6-1.dat";
  input x1 x2 x3 x4;
  boddiff = x1-x3;
  SSdiff  = x2-x4;
run;

title '95% Confidence Ellipse for the (SSdiff, BODdiff) Mean Vector';
proc sgscatter data = T61;
  compare y = boddiff x = SSdiff / ellipse = (type=mean);
run; title '';

/* Program to graph the confidence ellipse for the mean vector */
%let inputdata = T61; /* this line must be edited */
%let var1      = SSdiff ; /* this line must be edited */
%let var2      = boddiff ; /* this line must be edited */
%let conf      = 95 ; /* Confidence level desired*/
proc corr data=&inputdata noprint nocorr cov outp=covout(type=cov);
  var &var1 &var2;
run;
data covonly;
```

```

        set covout;
        if _type_='COV';
        keep &var1 &var2;
run;
data meanonly;
    set covout;
    if _type_='MEAN';
    keep &var1 &var2;
run;
data nonly;
    set covout;
    if _type_='N';
    keep &var1 &var2;
run;
proc iml;
    use covonly;
    read all into S;
    p = ncol(S);
    use meanonly;
    read all into xbar;
    xbar = xbar`;
    use nonly;
    read all into n;  n=n[1,1];
    A = S/n;
    Evec = Eigvec(A);
    Eval = diag(Eigval(A));
    EvecS = Eigvec(S);
    EvalS = diag(Eigval(S));
    try1 = Evec*Eval*Evec`;
    center = xbar;
    F = finv(&conf/100, p, n-p);
    one = (p*(n-1));
    two = (n*(n-p));
    diff = ((p*(n-1))/(n*(n-p)))*F;
    diffT = sqrt(((p*(n-1))/(n-p))*finv(&conf/100, p, n-p));
    ss = sqrt(diag(S)/n);
    distances = sqrt(diag(EvalS))*sqrt(((p*(n-1))/(n*(n-p)))*finv(&conf/100, p,
n-p));
    distance = sqrt((n-1)*p*finv(&conf/100, p, n-p) / (n-p));
    T2distminus = xbar - sqrt(((p*(n-1))/(n-p))*finv(&conf/100, p, n-
p))*sqrt(diag(S)/n);
    T2distplus = xbar + sqrt(((p*(n-1))/(n-p))*finv(&conf/100, p, n-
p))*sqrt(diag(S)/n);
    print xbar distance distances center EvecS EvalS F one two diff diffT S
T2distminus T2distplus ss;

npoints = 1000;
free xbig;
do r = 1 to npoints;
    angle = 2*3.14159265 * (r/npoints);
    w1 = sin(angle);
    w2 = cos(angle);
    w = w1//w2;
    x = Evec*sqrt(Eval)*distance*w + center;

```

```

        xbig = xbig//x`;
end;
create plotdata from xbig;
append from xbig;
quit;
goptions ftext=SWISS ctext=BLACK htext=1 cells;
axis1 width=1 offset=(3 pct) label=(a=90 r=0) ;
axis2 width=1 offset=(3 pct) ;
symbol1 c=BLUE ci=BLUE v=none height=1 cells
        interpol=spline l=1 w=1;
proc gplot data=Work.Plotdata(rename=(Col1=&var1 Col2=&var2)) ;
    title "&conf% Confidence Ellipse for the (&var1, &var2) Mean Vector";
    plot &var2 * &var1 /
        caxis = BLACK
        ctext = BLACK
        cframe = CXF7E1C2
        href=0
        vref=0
        hminor = 0
        vminor = 0
        vaxis = axis1
        haxis = axis2
        ;
    run;
quit;
goptions ftext= ctext= htext=;
symbol1;
axis1; axis2;
title;

/* 6.6a */

proc iml;
    y1 = {3 3, 1 6, 2 3};
    y2 = {2 3, 5 1, 3 1, 2 3};
    x1 = mean(y1);
    x2 = mean(y2);
    n1 = nrow(y1);
    n2 = nrow(y2);
    s1 = cov(y1);
    s2 = cov(y2);
    spool = (((n1-1)/(n1+n2-2))*s1) + (((n2-1)/(n1+n2-2))*s2);
    print y1 y2 x1 x2 s1 s2 n1 n2 spool; quit;
run;

/* 6.6b */

proc iml;
    y1 = {3 3, 1 6, 2 3};
    y2 = {2 3, 5 1, 3 1, 2 3};
    x1t = mean(y1);
    x2t = mean(y2);
    x1 = (x1t)`;
    x2 = (x2t)`;
    n1 = nrow(y1);

```

```
n2 = nrow(y2);
s1 = cov(y1);
s2 = cov(y2);
spool = (((n1-1)/(n1+n2-2))*s1) + (((n2-1)/(n1+n2-2))*s2);
t2 = (x1-x2)`*inv(((1/n1)+(1/n2))*spool)*(x1-x2);
print spool t2; quit;
run;
```