



Mercury Outboard Maintenance Planner

Owner checklist and service record for your Mercury outboard.

ENGINE MODEL / HP

SERIAL NUMBER

CURRENT HOURS

NO UNIVERSAL 20-HOUR SERVICE: Use the schedule for your exact engine and serial number.

SAFETY AND READINESS

Before every outing

- Check FourStroke engine oil, or the oil supply on an oil-injected two-stroke.
- Test the lanyard stop switch and inspect the cord and clip.
- Inspect fuel lines, fittings and primer bulb for leaks or deterioration.
- Check motor-to-transom security. Inspect steering and hydraulic fittings for binding or leaks.
- Check the propeller for damage and confirm battery connections are secure.
- Confirm the required safety gear is aboard.

COMMON ON MANY FOURSTROKES

Annual or 100 hours

- Change engine oil and filter where fitted, using the exact grade and quantity.
- Inspect fuel filter(s); replace as the manual or condition requires.
- Drain and refill gearcase lube. Check the old oil for water or metal.
- Remove the propeller; inspect the shaft, sleeve and fishing line; lubricate as specified.
- Inspect mounting fasteners, anodes, battery, controls, steering, hoses and connections.
- Record the date, engine hours, parts and fluids used.

CONDITION-BASED

After use and in season

- Flush after use. Salt, polluted water, silt or restricted flow may require more attention.
- Inspect promptly after known fishing-line contact or propeller impact.
- Watch anodes and corrosion. Use the correct anode material for the water and application.
- Log engine hours, alarms, overheating and reduced-water-flow events.

OFTEN 300 HOURS / 3 YEARS

Expanded interval

- Many current models use a 300-hour or 3-year interval - check yours.
- Common items include the water-pump impeller and spark plugs.
- Depending on model: trim fluid, driveshaft splines, wiring, belts, filters, thermostats and seals.
- Inspect earlier after overheating, low water pressure, sand, silt or heavy-duty use.

MODEL-SPECIFIC

Storage preparation

- Follow the long-term-storage section - usually two months or longer.
- Treat fresh fuel promptly. Ethanol fuel may require draining depending on the engine and fuel system.
- Complete due oil, filter, gear-lube and corrosion-protection work before storage.
- Use the specified drainage position, commonly vertical or full-down, and follow the battery procedure.
- Rather not DIY? Book fall winterization at hbw.wiki/service.

FREE HBW TOOL

Capacity and filter lookup

- Search by model, year, serial break and gearcase.
- Use reference capacities only as a starting point.
- Confirm the final level with the dipstick procedure.



SCAN THE QR CODE



Maintenance and Service Record

Keep this page with your engine records and receipts.



ENGINE MODEL / HP	SERIAL NUMBER	BOAT / OWNER
GEARCASE / DRIVE	MANUAL / DOC #	NEXT SERVICE DUE

IDENTIFY THE ENGINE BEFORE ORDERING PARTS

Photograph the transom label and serial number before ordering a filter, impeller, kit or lubricant. Horsepower alone is not fitment.

DATE	HOURS	WORK COMPLETED	PARTS / FLUIDS	BY

Need local Mercury service?

If the boat can come to Harris Boat Works in Gores Landing, submit the serial number, current hours and symptoms at hbw.wiki/service.

Prefer to talk? Call (905) 342-2153 or text (647) 952-2153.

Keep invoices, part numbers and fluid specifications with this record.

START A SERVICE REQUEST
hbw.wiki/service