



Mercury Outboard Maintenance Planner

Owner checklist and service record. Your serial-number manual controls.

ENGINE MODEL / HP

SERIAL NUMBER

CURRENT HOURS

NO UNIVERSAL 20-HOUR SERVICE:

Use the schedule for your exact engine and serial number.

SAFETY AND READINESS

Before every outing

- Check FourStroke engine oil, or the oil supply on an oil-injected two-stroke.
- Test the lanyard stop switch and inspect the cord and clip.
- Inspect fuel lines, fittings and primer bulb for leaks or deterioration.
- Check motor-to-transom security. Inspect steering and hydraulic fittings for binding or leaks.
- Check the propeller for damage and confirm battery connections are secure.
- Confirm the required safety gear is aboard.

COMMON ON MANY FOURSTROKES

Annual or 100 hours

- Change engine oil and filter where fitted, using the exact grade and quantity.
- Inspect fuel filter(s); replace as the manual or condition requires.
- Drain and refill gearcase lube. Check the old oil for water or metal.
- Remove the propeller; inspect the shaft, sleeve and fishing line; lubricate as specified.
- Inspect mounting fasteners, anodes, battery, controls, steering, hoses and connections.
- Record the date, engine hours, parts and fluids used.

CONDITION-BASED

After use and in season

- Flush exactly as the manual directs. Salt, polluted water, silt or restricted flow may require more attention.
- Inspect promptly after known fishing-line contact or propeller impact.
- Watch anodes and corrosion. Use the correct anode material for the water and application.
- Log engine hours, alarms, overheating and reduced-water-flow events.

OFTEN 300 HOURS / 3 YEARS

Expanded interval

- Many current manuals use a 300-hour or 3-year interval. Your exact manual decides.
- Common items include the water-pump impeller and spark plugs.
- Depending on model: trim fluid, driveshaft splines, wiring, belts, filters, thermostats and seals.
- Inspect earlier after overheating, low water pressure, sand, silt or heavy-duty use.

MODEL-SPECIFIC

Storage preparation

- Follow the exact long-term-storage section, often defined as two months or longer.
- Treat fresh fuel promptly. Ethanol fuel may require draining depending on the engine and fuel system.
- Complete due oil, filter, gear-lube and corrosion-protection work before storage.
- Use the drainage position in the serial-number manual so water is not trapped, and follow the battery procedure.

FREE HBW TOOL

Capacity and filter lookup

- Search by model, year, serial break and gearcase.
- Use reference capacities only as a starting point.
- Confirm the final level by the exact manual and dipstick procedure.



SCAN OR CLICK THE QR CODE



Maintenance and Service Record



Keep this page with your engine records and receipts.

ENGINE MODEL / HP	SERIAL NUMBER	BOAT / OWNER
GEARCASE / DRIVE	MANUAL PUBLICATION	NEXT SERVICE DUE

IDENTIFY THE ENGINE BEFORE ORDERING PARTS
Photograph the transom label and serial number before ordering a filter, impeller, kit or lubricant. Horsepower alone is not fitment.

DATE	HOURS	WORK COMPLETED	PARTS / FLUIDS	BY

Need local Mercury service?

If the boat can come to Harris Boat Works in Gores Landing, submit the serial number, current hours and symptoms at hbw.wiki/service.

Keep invoices, part numbers and fluid specifications with this record.

START A SERVICE REQUEST
hbw.wiki/service