

Mercury Outboard Maintenance Planner

A model-aware owner checklist and service record. Free, no email gate.

MODEL / HP

SERIAL NUMBER

CURRENT HOURS

BEFORE EVERY OUTING

ROUTINE

- ☐ Check four-stroke engine oil level, or injector-oil level on a two-stroke.
- ☐ Check fuel level and inspect fittings, hose and primer bulb for leakage or damage.
- ☐ Confirm battery security and tight, clean connections.
- ☐ Move steering, throttle and shift through a smooth, unobstructed range.
- ☐ Inspect the propeller and confirm required safety gear is aboard.

ANNUAL OR 100 HOURS

MOST FOURSTROKES

- ☐ Change engine oil and filter where fitted, using the exact grade and quantity.
- ☐ Change gearcase lubricant and inspect the drain for water or metal.
- ☐ Service the fuel filters listed for the engine and boat installation.
- ☐ Inspect propeller, prop shaft, fasteners, battery, steering, throttle, shift and hoses.
- ☐ Lubricate specified points and record the date, hours, fluids and part numbers.

AFTER USE AND IN SEASON

ROUTINE

- ☐ Flush only by the method in the exact manual. Salt, brackish and silty use can require more frequent flushing.
- ☐ Inspect the prop and prop shaft for fishing line; grease the shaft as specified.
- ☐ Inspect sacrificial anodes. Correct material and replacement point depend on the application.
- ☐ Track engine hours, alerts and completed work instead of relying on memory.

EXPANDED INTERVAL

MODEL-SPECIFIC

- ☐ The serial-number manual decides the interval and the parts list.
- ☐ Possible items include spark plugs, water-pump service, filters, thermostats, belts, seals and additional inspections.
- ☐ Do not treat a generic 300-hour kit as proof that every included item fits every Mercury.
- ☐ Bring inspection forward after overheating, restricted cooling flow, sand, silt or heavy-duty use.

STORAGE PREPARATION

MODEL-SPECIFIC

- ☐ Follow the exact long-term storage procedure for this engine family.
- ☐ Use fresh fuel and the specified stabilizer procedure. Tank level depends on the fuel-system design.
- ☐ Complete due oil, filter and gear-lube work before storage.
- ☐ Protect the battery, corrosion points and drainage position as specified.

CAPACITY LOOKUP

Search model, year, serial break and gearcase.



Scan for the HBW lookup

Reference capacities are approximate.
Final fill comes from the dipstick and exact manual.

Mercury Outboard Maintenance Planner

A model-aware owner checklist and service record. Free, no email gate.

MODEL / HP	SERIAL NUMBER	GEARCASE / DRIVE
_____	_____	_____
OWNER / BOAT _____		

DATE	HOURS	WORK COMPLETED	PARTS / FLUIDS	BY

THE IDENTIFICATION CHECK THAT SAVES THE RETURN TRIP

Before ordering an oil filter, maintenance kit, impeller or gear lubricant, photograph the transom-bracket label and record the serial number. Horsepower alone is not a fitment key.

Local service: If the boat can come to HBW in Gores Landing, submit the serial number and hours at hbw.wiki/service.