


# The Design and Implementation of a Low-Cost Bitcoin Vending Machine



Harrison Fernandez<sup>1</sup> and Dr. Guan-Hua Tu<sup>2</sup>

<sup>1</sup>Department of Computer Science and Information Security, John Jay College <sup>2</sup>Department of Computer Science and Engineering, Michigan State University

#### Introduction

#### What is Bitcoin?

• Bitcoin (BTC) is a virtual and decentralized cryptocurrency and currency trading platform [1].

#### Why is it important?

• The odds of experiencing a data breach are 1 in 4 [2].

#### How is Bitcoin flawed?

- The average timing for BTC transactions is 10 minutes [1].
- Current solutions reduce the transaction time, but use expensive components in terms of computation power and monetary cost [3], [4].

## **Research Question**

Can a low-cost vending machine be designed and implemented to support Bitcoin transactions?

#### **System Overview**



a. Vending machine

b. WiFi-enabled computing device

c. Full Ethereum node, etherscan.io

Figure 1: Design of Bitcoin vending machine system

#### **Fast Transactions**

- Ethereum's (ETH) smart contract functionality will be used to speed up BTC transactions.
- The average time for one ETH transaction confirmation is 15 seconds [5].
- Twelve confirmations will be the base for a secure transaction [5].

#### System Architecture

- The vending machine setup shown in figure 2.
  - Board cost: \$31 (2018), operating on 3.3 volts.
  - Each module cost: < \$12, operating on 5 volts.
- The vending machine interfaces with a server of any computing caliber.
- Using etherscan.io is much more inexpensive than hosting our own Ethereum node.




Figure 2: Vending machine architecture and modules

## **Transaction Process**



Figure 3: Design and visualization of the transaction process.

Steps 2 to 4 are completed on the server:

- Step 2 and 3 are interfaced with the Ethereum node.
- Step 4 is interfaced with the Arduino board.

#### **Discussion**

BTC hasn't been adapted for use in time-constrained environments. Current solutions are costly in terms of money and power consumption. Our design is low-cost and more viable, allowing future work to be more feasible.

#### Conclusion

By adapting BTC payments for timeconstrained transactions, society is able to move away from third party trust. In a world where hacking and data breaches happen every day, Bitcoin is important for keeping our information out of the wrong hands.

#### **Future Work**

- Same design; no server.
- Timing and security analyses.
- Implementation in grocery stores, retailers, bus stations, and more.

### Acknowledgements

- Summer Research Opportunities Program (SROP).
- Michigan State University.
- Computer Science and Engineering Department.
- Dr. Guan-Hua Tu's Network System and Security Lab.

#### References

- [1] S. Nakamoto, "Bitcoin: A peer-to-peer electronic cash system", 2008.
- [2] Ponemon Institute, "2017 Cost of Data Breach Study", 2017.
- [3] T. Bamert, "Have a snack, pay with bitcoins", 13th IEEE International Conference on Peer-to-Peer Computing, Italy, 2013.
- [4] M. Asplund, J. Lovhall, S. Nadjm-Tehrani, "In-store payments using bitcoin", 2018, 9th IFIP Conference.
- [5] V. Buterin, "A Next-Generation Smart Contract and Decentralized Application Platform", 2013.
- EM: harrison.fernandez@jjay.cuny.edu|LinkedIn.com/in/harrison-fernandez