Environment configuration contract

Every deployment supplies a complete immutable environment binding. Values below are parameter names, not credentials or real IDs.

Parameter	Local	Preview	Staging	Production	Rule
`SEMESTER_ENV`	`local`	`preview`	`staging`	`production`	Exact allowlist
`DEPLOYMENT_PROJECT_ID`	local identifier	preview project	staging project	production project	Must match manifest
`SUPABASE_PROJECT_REF`	local service	PR/preview branch	staging project	production project	No accidental production ref
`AUTH_ISSUER`	local issuer	preview issuer	staging issuer	production issuer	Exact token issuer
`AUTH_AUDIENCE`	local audience	preview audience	staging audience	production audience	Exact token audience
`AI_QUEUE_NAMESPACE`	local queue	preview queue	staging queue	production queue	Never shared
`AI_STORAGE_NAMESPACE`	local storage	preview storage	staging storage	production storage	Never shared
`AI_DATA_MODE`	synthetic	synthetic	synthetic/approved test	authorized	Nonproduction rejects production records
`AI_PRODUCTION_DATA_INCLUDED`	false	false	false	false unless explicit approved migration process	Branch include-data is forbidden by default
`AI_STUDENT_RECORD_EGRESS`	false	false	false	false	Must be false everywhere
`AI_RAW_CONTENT_LOGGING`	false	false	false	false	Metadata only by default
`AI_SHARED_PROVIDER_CACHE`	false	false	false	false	Cache is permission/context-bound only
`AI_PROVIDER_MODE`	mock	mock	mock/approved test	approved live route	Exact approved mode
`AI_LIVE_PROVIDER_APPROVAL`	false	false	explicit review	explicit review	Required for live route
`AI_TIMEOUT_MS`	bounded	bounded	bounded	bounded	1–30,000 in reference
`AI_POLICY_VERSION`	fixture	fixture	release candidate	approved version	Included in every decision

Parameter	Local	Preview	Staging	Production	Rule
`AI_EGRESS_ALLOWLIST_ID`	test list	preview list	staging list	reviewed list	Gateway only
`AI_AUDIT_SINK_ID`	local test	preview audit	staging audit	production audit	Failure blocks dispatch

Vercel environments have independently scoped variables; a preview deployment does not affect production, but staged production deployments can use production variables and therefore must not be treated as an isolated test environment. [web:114][web:115]

Supabase branches start without production data or storage objects by default. Include-data branches copy production data and must be treated with production-level controls; this gateway contract disallows them for ordinary AI preview/testing. [web:112]