Admin/member/viewer navigation matrix and gates

Application roles are database assignments, not PostgreSQL superuser/authenticated/anon roles. All logged-in application roles execute as authenticated. Admin does not mean bypass RLS; viewer does not mean free tier.

Every reference route evaluates authentication + tenant/resource authorization + optional feature entitlement + module readiness + quota. Subscription payment never grants role authority. Paid personal features do not gate required enrolled-course access or published own grades.

Screen family	Admin	Member	Viewer	Anonymous	Tier gate
Public site/pricing	Public	Public	Public	Public	None
Sign-in/invite	Identity flow	Identity flow	Identity flow	Identity flow	None
Student home/course/assignment	Own education scope	Own education scope	Own education scope, actions individually authorized	Denied	No personal upgrade for required coursework
Faculty studio/gradebook	Assigned teaching only	Assigned teaching only	Read only if separately granted	Denied	Teaching permission, not Pro
Notes/planner	Own	Own	Own personal workspace (viewer refers to organization role)	Denied	Core Free; premium extras gated
Advanced study/search/sync	Personal/sponsor eligibility	Personal/sponsor eligibility	Personal/sponsor eligibility	Denied	Plus or Pro
Research/automation	Personal/sponsor eligibility	Personal/sponsor eligibility	Personal/sponsor eligibility	Denied	Pro; tool actions independently authorized
Institution directory/settings	Explicit admin capabilities	Assigned domain	Explicit read grant	Denied	Contracted module readiness
Institution integration setup	Integration admin	Assigned operator	Authorized status only	Denied	Contract + readiness
CRM/company workflows	Company domain role	Assigned company workflows	Granted read projection	Denied	Employee authorization, not student subscription
Documents	Author/audience/reviewer only	Author/audience/reviewer only	Explicit audience	Denied	Document classification and assignment
Subscription/invoices	Explicit account billing authority	Own/explicit account authority	Explicit billing read only	Denied	Ownership/ACL, not admin label

Screen family	Admin	Member	Viewer	Anonymous	Tier gate
Ledger/refund approvals	Finance-specific role	Assigned financial role	Explicit ledger read	Denied	Separation of duties
People/legal records	Restricted people/legal role	Assigned scope	Explicit restricted read	Denied	Not generic admin
Operations/audit	Technical/security scope	Assigned operator	Sanitized explicit read	Denied	Not billing tier

This family matrix extends the prior 69-screen inventory; it does not silently assign all permissions to generic admin/member/viewer bundles. Use per-screen capability predicates from that inventory. Add specific read permissions rather than turning role names into broad shortcuts.

FeatureGate returns unauthenticated/forbidden/upgrade-required/institution-approval/quota-exhausted/backend-error separately. Checkout UI displays proposed approved price/cadence and confirms backend tier after webhook reconciliation, never URL parameters. Membership helper is private and exposed through a sanitized /me/membership server projection, not public private-schema RPC exposure.