Object-level Semantic Mapping with Language Models from Egocentric Video



Harry Graves

St Anne's College

University of Oxford

A thesis submitted in partial completion of the degree of

MEng Engineering Science

Trinity 2025

Acknowledgements

I would like to extend my gratitude to my supervisor, Professor Maurice Fallon, who's support over the last year has been instrumental in both the completion of this undergraduate thesis and in the development of my career. I also owe a great deal of thanks to Christina Kassab, Matías Mattamala, Jianeng Wang, Tobit Flatscher, and all other members of the DRS-P group for the advice and assistance afforded to me throughout this project.

I wish to acknowledge the generous financial support provided by Institute of Engineering and Technology through their Launch Scholarship. The assistance that this funding has provided throughout my degree has allowed me to fully dedicate myself to my work and pursue opportunities that would have otherwise been inaccessible.

My final thanks goes to my parents. For giving me the opportunity to pursue a university education, and to further support me throughout its most challenging moments, none of this would have been possible without them.

Abstract

Closing the gap between machine and human perception is a key requirement for more natural human-computer interaction. Meta's Project Aria Augmented Reality research glasses are a platform designed to close this gap. By capturing an individual's actions from an *Egocentric* perspective, unique insights into their daily experiences can be obtained; yet the complexity of human movement and the richness of real-world environments pose challenges for machine perception. In this thesis, we approach egocentric video understanding from a robotics perspective. By exploiting spatial priors obtained from simultaneous localisation and mapping, we improve object recognition accuracy compared to purely visual methods. We explore how physical actions, such as hand gestures or eye-gaze direction, can be used as a signal for the detection of interactions between a hand and object, and assess how existing work from the DRS-P group, using vision-language models for semantic place recognition, can be employed in an egocentric setting. The result is an *active memory*, encoding semantic information about objects the user interacted with, as well as the times and 3D locations at which these interactions occurred. Finally, the performance of each aspect of our system is evaluated using both public datasets and self-collected data, demonstrating a repeatable method for registration of Aria SLAM graphs into a prior map for benchmarking.

Contents

1 Introduction **1**
- 1.1 Motivation . . . 1
- 1.2 Challenges . . . 2
- 1.3 Objectives . . . 2
- 1.4 Contributions . . . 2

2 Related Work **4**

3 Project Aria **10**
- 3.1 The Device . . . 11
- 3.2 Machine Perception Services . . . 11
- 3.3 Open Datasets . . . 13

4 Methods **14**
- 4.1 Hand-Object Interaction Detection . . . 14
  - 4.1.1 Problem Formulation . . . 15
  - 4.1.2 Model . . . 18
  - 4.1.3 Training . . . 18
- 4.2 Active Memory . . . 20
  - 4.2.1 Active Memory Formulation . . . 20
  - 4.2.2 Object Identification and Tracking . . . 21
  - 4.2.3 Location Segmentation . . . 27

5 Experiments **30**
- 5.1 Hand-Object Interaction Detection . . . 31
  - 5.1.1 Frame-wise Prediction . . . 31
  - 5.1.2 Interaction Segmentation . . . 35
- 5.2 Active Memory . . . 37
  - 5.2.1 Object Tracking . . . 37
  - 5.2.2 Object Identification and Matching . . . 39
  - 5.2.3 Location Identification . . . 41
- 5.3 Runtime Analysis . . . 47

6 Conclusion **48**

References **49**

If you want a system that is socially aware in a sense, one that perceives the space like people do, you need to look at the world from a human point of view.

— Renzo de Nardi, technical lead, *Project Aria*

1 Introduction

1.1 Motivation

As wearable technology becomes increasingly integrated into daily life, there is a growing need for systems that can understand and recall human experiences in a natural and intuitive way. From purely virtual AI assistants to physically embodied agents, many applications could benefit from memory-like capabilities that allow machines to answer human-centred questions such as "Where is my wallet?" or "What did I do this morning?". Such capabilities lie at the heart of human cognition and are essential for building more seamless and intelligent human-computer interaction.

Meta's Project Aria glasses represent a significant step forward in wearable augmented reality (AR) technology. Platforming a suite of egocentric data sources, including multiple cameras and IMUs, a microphone and GPS receiver, this device is capable of capturing a person's daily experiences from a first-person perspective. This data has enormous potential for enabling context-aware systems that can not only perceive the current environment, but also remember and reason about past interactions in a meaningful way.

1.2 Challenges

Applying traditional computer vision techniques to the problem of long-form egocentric video understanding is ill conditioned; neither the viewpoint nor scene is static, and the constant motion of the head-mounted camera introduces frequent occlusions, motion blur, and dramatic perspective changes that violate the assumptions of many standard vision pipelines. Moreover, these methods do not scale well to egocentric video, where thousands of frames must be processed over extended periods, requiring both temporal abstraction and computational efficiency.

1.3 Objectives

Whilst egocentric video understanding has attracted significant attention from academia, it has thus far largely been framed as a computer vision problem. This is, in part, due to hardware constraints historically faced by this area of research, whereby egocentric video datasets were captured using a simple head-mounted camera setup [1, 2].

Instead, this thesis aims to approach the problem from a robotics perspective. Meta's Project Aria glasses are a significant enabler for such an approach, allowing for fusion of data from multiple sensors and providing access to high-fidelity SLAM trajectories, hand-tracking and eye-tracking data. Leveraging such data sources allows focus to be shifted from slow, non-causal visual object trackers towards real-time, spatiotemporal object tracking that can be used in an online manner, pushing toward more intelligent, memory-augmented AR systems.

1.4 Contributions

In this thesis, we present a framework for long-form egocentric video understanding through the construction of an *Active Memory*, using data collected from Meta's Project Aria AR research glasses. We evaluate the performance of our system's modalities on both publicly available Project Aria datasets and self-collected data. In summary, the contributions of this thesis are as follows:

1. A method for robust hand-object interaction detection, using an LSTM network trained to detect hand-object interactions from a combination of hand-tracking and eye-tracking data.

2. Spatially grounded object reidentification, supporting disambiguation between similar-looking object instances and multiple sightings of the same object instance.

3. A lightweight object tracking mechanism that maintains consistent object positions over time, even in the presence of motion, occlusions, or multiple re-visitations.

4. Online construction of an *Active Memory*, encoding semantic labels, interaction timestamps, and 3D positions of both objects that are interacted with and rooms that are visited.

The system is designed to operate incrementally on streaming sensor data, laying the groundwork for future deployment on real-time AR hardware. Each module processes incoming frames causally and with low computational overhead, enabling scalable memory construction in dynamic environments.




Figure 1.1: An overview of our active memory system. The system captures hand-object interactions (solid segments), and objects remain static whilst not being interacted with (dashed segments).

2
Related Work

The following chapter reviews the current state-of-the-art for long-form egocentric video understanding. This is broadly broken down into the following constituent parts; the ability to identify and track dynamic objects, the ability to understand human-object interactions, the ability to maintain a human-centric memory, and the ability to query this memory using a large language model.

Object Tracking in Egocentric Video

The problem of object tracking in egocentric video is non-trivial. This was first explored with the EgoTracks dataset [3], whereby classic single object trackers (SOTs) were shown to exhibit poor performance on first-person video. In this context, the ability to *re-associate* objects with ones previously seen is more critical than in other tasks due to the frequent occlusions characteristic of egocentric video. To this end, the authors of EgoTracks propose the fine-tuning of STARK [4], a transformer-based visual-object tracking method, on their dataset. Although this significantly improved results on traditional tracking metrics, their approach remains fundamentally image-based, relying heavily on visual continuity and appearance features.

Spatially-Informed Egocentric Object Tracking

Driven by the need to create more robust methods for object re-identification, several recent works have demonstrated that the 3D location of objects can act as valuable spatial priors for object matching. Such methods take inspiration from object permanence, a key concept of human cognition, that has largely remained unexploited by object tracking methods.

With this in mind, Out of Sight, Not Out of Mind (OSNOM) [5] improves over purely visual object-tracking methods by computing a cost function using both visual features and relative 3D locations of objects in the world coordinate frame. These 3D locations are obtained from object bounding box annotations using three key steps; first, a Structure from Motion (SfM) pipeline, in this instance COLMAP [6], is used to obtain estimates for the camera pose at each frame. A multi-view stereopsis pipeline [7] is then used to extract scene geometry in the form of a dense 3D point-cloud. Finally, the depth of the object centroid is estimated at each frame using a monocular depth estimate [8], which is rescaled to align with the scene geometry estimate. Combining the global camera pose and object depth at each frame, 2D detections are lifted to 3D, as shown in Figure 2.1. Objects then remain static in this coordinate frame whilst out of view.




Figure 2.1: A visualisation of how 2D object masks are lifted to 3D locations in [5].

3D-Aware Instance Segmentation and Tracking [9] starts with predictions from a 2D video object segmentation model, and refines them using the 3D locations of objects obtained in an identical manner to OSNOM. Crucially, their cost function also compares the initial object ID and semantic label obtained from the 2D object segmentation model between frames, rather than just visual features and locations of objects, to achieve state-of-the-art tracking consistency on egocentric data.

It is clear from these studies that leveraging 3D information is crucial for robust long-term object tracking in egocentric video. However, both OSNOM and 3D-Aware Instance Segmentation and Tracking rely heavily on bulky post-processing pipelines that limit their applicability in real-time or streaming contexts. Specifically, the use of COLMAP involves batch processing over large sets of images, and obtaining and aligning per-frame monocular depth estimates with dense scene reconstructions from the multi-view stereopsis pipeline, making online operation impractical.

Furthermore, both methods adopt a track-everything paradigm, in which objects are tracked continuously across all images, regardless of whether they are static in the world coordinate frame. Maintenance of an exhaustive scene state in this way captures significant redundant information with large computational overhead.

Hand-Object Interaction Detection

A fundamental prerequisite for a human-centric memory system is the ability to accurately perceive and interpret human-object interactions. These interactions provide essential structure for organizing egocentric experience, as they represent the primary mode through which users engage with their surroundings.




Figure 2.2: An example output from InteractNet [10]. This consists of bounding boxes for the human and the knife with which they are interacting, as well as the verb "cut" to denote the nature of their interaction with the knife.

Traditional approaches to human-object interaction detection rely on visual input, training neural networks to detect interaction based on spatial proximity and human pose. One particularly relevant example is InteractNet [10], which introduced a human-centric Faster-RCNN (FRCNN) [11] model for predicting ⟨human, verb, object⟩ triplets from images, as shown in Figure 2.2.

As can be seen, such approaches rely on the pose of the full body to infer which object is being interacted with and how. In egocentric video, this information is not

captured, shifting the focus to finer-grained cues at the point of contact between the human and their environment. In this context, the hands play a particularly critical role as the primary instruments of manipulation. Consequently, detecting when and how the hands engage with objects - hereby referred to as hand-object interaction (HOI) detection - has become a central problem in egocentric video understanding.

Understanding Human Hands in Contact at Internet Scale [12] again attempts to solve this problem visually by fine-tuning a model on annotations from their 100 Days of Hands (100DoH) dataset. This FRCNN model not only predicts bounding boxes for the hands and objects that are in contact, but also outputs the specific contact state of each hand $\in$ (none / self / other person / non-portable object / portable object), shown in Figure 2.3.




Figure 2.3: An example output of the HOI detector from [12]. O represents the object bounding box, R and L represent the hand bounding boxes, and P and N represent positive and negative contact states respectively.

Whilst achieving strong performance on large-scale data, this method still relies purely on frame-by-frame visual input, which is costly and sensitive to occlusions, clutter and changes in lighting characteristic of egocentric video.

In this work, we present a novel method for hand-object interaction detection that does not require an explicit visual object tracker. To our knowledge, no existing method has explored the application of raw hand-tracking data in this context, nor incorporation of eye-gaze data as a further signal for detection. We therefore seek to address this gap in this thesis.

Active Memory

AMEGO: Active Memory from long EGOcentric videos [13] employs the fine-tuned SOT model from [3] in combination with the hand-object interaction detector of [12], to create what they define as an *active memory*. This semantic free representation consists of a series of location and object segments. Locations are defined by the image features of the whole camera frame whilst the wearer is interacting with an

object, and is represented simply as the location ID and the start and end time that the wearer is in that location. Object segments are represented as tuples, consisting of the start and end times of hand-object interactions, the sequence of 2D bounding boxes representing the active object in each frame, the hand that was used to interact with the object, and the assigned instance ID.

At the start of each hand-object interaction, the cosine similarity is calculated between the image features of the new candidate object and that of each object already in the memory, to identify the most visually similar object. If this maximum visual similarity is above some threshold, they are identified as being the same object. This explicit matching mechanism enables AMEGO to better re-identify objects across interactions, though the sole reliance on visual similarity for object re-identification makes their method vulnerable to errors when interacting with visually similar objects (e.g., two identical-looking mugs) or in the presence of occlusions.

This paper also marks the first benchmarking of long-form egocentric video understanding. The *Active Memories Benchmark* presents more than 20,000 multiple-choice visual queries, covering three key levels of reasoning: sequencing, concurrency, and temporal grounding. Providing both semantic and semantic-free baselines, this benchmark provides a quantitative measure for which to evaluate memory representations in egocentric video, pushing the field toward more human-aligned metrics of understanding.

Semantic Parsing with LLMs

Recent advances in Large Language Models (LLMs) have significantly influenced video understanding, particularly through approaches that transform visual content into natural language for downstream reasoning. A notable method is that of LLoVi [14], which takes the approach of splitting the video into multiple shorter videos, and using a short-term captioning model to generate captions for each one, before passing these captions to an LLM for interpretation. This training-free approach has gained traction due to its modularity and zero-shot flexibility,

enabling systems to leverage the general-purpose reasoning capabilities of models like GPT-4 without domain-specific fine-tuning.

Whilst effective for short video clips (up to eight seconds long), this approach does not generalise to longer videos, particularly those captured from an egocentric perspective. Such videos contain high levels of redundancy, and hence a naive sampling of frames from such videos will result in the LLM being overloaded with inessential information during periods of repeated or uneventful visual input, degrading efficiency and long-range reasoning ability.

VideoMindPalace [15] organises key moments from egocentric video into a topologically-grounded, three-layer graph representation; nodes in each layer represent human-object interactions, activity zones, and room layers respectively; edges encode spatiotemporal, interaction, and proximity relationships. Converting this semantic graph into JSON format, it can then be interpreted by an LLM to allow for greater human-centric reasoning, supporting both spatially- and temporally-grounded text queries. This human-aligned reasoning ability is benchmarked in the *Video MindPalace Benchmark*, with both multiple-choice and open-ended queries for sequences from the EPIC-KITCHENS [1] and Ego-4D [16] datasets.

Interactions, encoded by the nodes and edges of this graph, are captured in an identical manner to [13], and suffers many of the same limitations. All objects are naively tracked using an SOT model, forgoing any spatially-informed object disambiguation as in [5], or object category penalty as in [9]. Although locations are determined using both visual similarity and 3D proximity, camera poses are obtained from ground-truth trajectories from the EPIC-Fields dataset [17]. Importantly, it does not address the challenges of real-time operation or online augmentation of the graph as new sensor data is delivered.

3
Project Aria

To understand the design and implementation of the methods presented in this work, it is first necessary to introduce the capabilities of the Project Aria glasses, and the associated datasets that are at our disposal. The hardware and data formats used by Aria differ significantly from what is traditionally used in computer vision and robotics, and these differences strongly influence the methodology discussed in this thesis.



Figure 3.1: Project Aria glasses.

3.1 The Device

Fundamentally, Project Aria is a multimodal sensor platform in the form of a pair of lightweight glasses (Figure 3.1). Designed to be worn for extended periods of time in a socially-acceptable form factor, this setup is less obtrusive than previous egocentric data collection platforms (e.g. head-mounted GoPros), resulting in more genuine, real-world insight into the wearer's daily experiences.

The device is fitted with a 2.5 W h battery, facilitating 1.5 hours of continuous recording plus 30 hours standby in the default recording profile, and 4 GB of onboard RAM. The sensors most significant to our work are a pair of IMUs, running at 800 and 1000 Hz respectively, and the visual sensors detailed in table 3.1. All sensor data may be streamed via WiFi or USB to one or more devices, or written to a single file per recording. This file is in the VRS format, designed for the recording and playback of multiple streams of sensor data, themselves of varying format.

Camera	HFOV (°)	VFOV (°)	IFOV (°/pix)	Max Res. (pix)	Max FPS	Shutter
Mono Scene (x2)	150	120	0.26	640×480	30	global
RGB (x1)	110	110	0.038	2880×2880	30	rolling
Eye Tracking (x2)	64	48	0.2	640×480	90	global

Table 3.1: Project Aria camera specifications.

3.2 Machine Perception Services

On top of this raw sensor data, Meta provide access to a set of *Machine Perception Services (MPS)*. These are a set of foundational machine perception capabilities, including Simultaneous Localisation and Mapping (SLAM), eye-tracking and hand-tracking, shown in Figure 3.2 and detailed in the following section.

SLAM services include 1 kHz open- and closed-loop trajectories, online intrinsic and extrinsic camera calibration, and semi-dense point-cloud data. In the case of multiple recordings in the same environment, simultaneous processing of these recordings generates the aforementioned trajectories and point clouds in one unified coordinate frame.

Eye-gaze data is obtained using the two onboard eye-tracking cameras, to provide an estimate of the gaze vector from each pair of simultaneous eye-tracking images. This is calculated as the vector running from the origin of the Central Pupil Frame (CPF) to the point at which the left and right eye-gaze vectors intersect, thereby also providing an estimate of the depth of the eye-gaze point.

Hand-Tracking services make use of the two mono scene cameras to estimate the positions of each hand in the device coordinate frame. This includes the position of each palm and wrist, as well as the direction of their normal vectors to indicate orientation.

MPS is currently offered as post-processing of the VRS files via a cloud service; whilst this means that use of the data provided by MPS is not strictly *online*, the Project Aria Tools API effectively accesses this data as though it were queued sensor data. This means that, as this technology progresses, any algorithms developed that use MPS data will run online as MPS processing transitions from offline to online, with Aria Gen 2 already supporting on-device MPS[1].




Figure 3.2: A visualisation of MPS data from a sequence recorded in the George building. The device outline is shown in light blue, with the eye-gaze vector marked as a green line originating from the centre of the glasses. The wrist and palm positions from hand-tracking are marked as the red points below the glasses, and the device trajectory is shown in dark blue.

[1]Meta blog post on Aria Gen 2

3.3 Open Datasets

Alongside the hardware platform, Meta have also released a number of datasets specific to Project Aria. In this work, we heavily use the **HOT3D** [18] dataset, a benchmark dataset to evaluate 3D hand- and object-tracking from egocentric video. The Aria headset is used to capture a number of egocentric recordings of a person who is interacting with a number of commonly encountered, holdable objects. Recorded in a motion-capture environment, small optical markers placed on the hands and objects allow for the provision of ground-truths for their 6-DoF poses and 2D bounding boxes, which are then time-synchronised with all standard Aria and MPS data. This dataset is used for both training and evaluation purposes throughout this thesis.




Figure 3.3: An overview of the data available in the HOT3D dataset. The left shows the RGB and mono scene camera image streams from the Aria headset, as well as ground-truth hand and object bounding boxes. The right depicts the ground-truth hand and object poses, on top of all standard MPS data.

4
Methods

Chapter 4 describes the system developed to construct an active, semantic memory from long-form egocentric video recorded using the Project Aria glasses. The goal is to detect and record meaningful human-object interactions in a way that is grounded in space, time, and semantic content, enabling the possibility of downstream natural-language querying.

Our system consists of two key components: a lightweight method for hand-object interaction detection from eye-gaze and hand-tracking cues, and a pipeline for the iterative construction of an active memory, storing spatio-temporal information about detected hand-object interactions and areas of activity. The methodology of these components are detailed in the following two sections.

4.1 Hand-Object Interaction Detection

Detecting when a user is actively interacting with an object is a fundamental component of our system. The successful detection of the start of a hand-object interaction serves as the trigger for object tracking and memory updates; likewise, the successful detection of the end of a hand-object interaction serves as the trigger to cease object tracking, ensuring objects remain static unless manipulated by the user. As such, a robust yet lightweight method to detect such events is required.

4.1.1 Problem Formulation

Previous works ([13], [15]) have defined the hand-object interaction detection task as a binary classification problem over video frames. Specifically, these works employ the hand-object interaction detector from [12] to provide a set of active object and hand bounding boxes at each frame. If a hand and object bounding box exhibit strong spatial overlap for some number of consecutive frames, then a hand-object interaction is deemed to be occurring for that hand, thereby lifting per-frame predictions into a temporal interval for which an interaction is consistently active. The interaction ends when the bounding boxes no longer overlap for some number of consecutive frames, including if this is a result of occlusion.

In this section, we wish to explore how the user's physical behaviour, in the form of hand gestures and eye gaze, can be used as cues for hand-object interaction detection, and whether this can be used to overcome the limitations of purely vision-based detectors. We therefore define the hand-object interaction detection task as a binary classification problem over temporal sequences of hand-tracking and eye-gaze data. At each timestamp t, we aim to predict the true binary label $y_t^h \in \{0, 1\}$ for each hand $h \in \{\text{left}, \text{right}\}$, where $y_t^h = 1$ indicates hand h holding or interacting with an object at time t, and $y_t^h = 0$ otherwise. We then determine the start of a hand-object interaction if, within a sliding window of length W ending at time t, some proportion $k \in [0, 1]$ of the predicted labels $\hat{y}_{t-W+1}^h, \ldots, \hat{y}_t^h$ are equal to 1 for a given hand h. This hand-object interaction then remains active until at least $k \cdot W$ of the predicted labels for this hand are equal to 0.

Our predictions are made based on hand-tracking and eye-tracking data provided by Aria MPS. Hand-tracking data is given by the vector

$$\mathbf{h}_t = \left[c_t^L, \mathbf{p}_t^{L,wrist}, \mathbf{p}_t^{L,palm}, c_t^R, \mathbf{p}_t^{R,wrist}, \mathbf{p}_t^{R,palm}, \mathbf{n}_t^{L,wrist}, \mathbf{n}_t^{L,palm}, \mathbf{n}_t^{L,wrist}, \mathbf{n}_t^{L,palm}\right] \quad (4.1)$$

where, for hand h at time t,

- $c_t^h \in [0.0, 1.0]$ (or -1.0 where data is missing) is the tracking confidence,

- $\mathbf{p}_t^{h,wrist} \in \mathbb{R}^3$ and $\mathbf{p}_t^{h,palm} \in \mathbb{R}^3$ are the 3D positions of the wrist and palm in the device coordinate frame
- $\mathbf{n}_t^{h,wrist} \in \mathbb{R}^3$ and $\mathbf{n}_t^{h,palm} \in \mathbb{R}^3$ are the 3D positions of the wrist and palm normals in the device coordinate frame.

Similarly, eye-tracking data is given by the vector

$$\mathbf{g}_t = \left[\theta_t^L, \theta_t^R, \phi_t, d_t, \theta_t^{L,\text{low}}, \theta_t^{R,\text{low}}, \phi_t^{\text{low}}, \theta_t^{L,\text{high}}, \theta_t^{R,\text{high}}, \phi_t^{\text{high}}, \mathbf{e}_t^L, \mathbf{e}_t^R\right] \tag{4.2}$$

where:

- θ_t^L and θ_t^R are the yaw angles (in radians) of the left and right eyes respectively,
- ϕ_t is the shared pitch angle of both eyes,
- d_t is the absolute depth of the 3D gaze point in meters,
- $\theta_t^{L,\text{low}}$, $\theta_t^{R,\text{low}}$, $\theta_t^{L,\text{high}}$ and $\theta_t^{R,\text{high}}$ are the lower and upper bounds of the yaw confidence intervals for the left and right eyes,
- ϕ_t^{low} and ϕ_t^{high} are the lower and upper bound of the shared pitch confidence interval,
- $\mathbf{e}_t^L \in \mathbb{R}^3$ and $\mathbf{e}_t^R \in \mathbb{R}^3$ are the 3D positions of the left and right eyes in the CPF frame respectively.

These two vectors are concatenated to form the frame-level feature vector $\mathbf{x}_t = [\mathbf{h}_t \,\|\, \mathbf{g}_t]$ of combined length 42, before taking a sliding window approach, concatenating the last N of these vectors to create the overall feature vector:

$$\mathbf{X}_t = \left[\mathbf{x}_{t-N+1}, \mathbf{x}_{t-N+2}, \ldots, \mathbf{x}_t\right]^\top \tag{4.3}$$

To map this feature vector to a predicted probability for each hand, we employ a learnable function $f_\theta(\cdot)$ parametrised by a neural network, such that

$$\hat{\mathbf{y}}_t = f_\theta(\mathbf{X}_t) \tag{4.4}$$

where $\hat{\mathbf{y}}_t = \left[\hat{y}_t^L, \hat{y}_t^R\right]^\top$ represents the predicted probabilities that the left and right hands are interacting with an object at time t, respectively. The above process is summarised in Algorithm 1.

Algorithm 1: Hand-Object Interaction Detection and Segmentation

Input: Hand-tracking data stream $\mathbf{h}$; eye-gaze data stream $\mathbf{g}$
Output: Interaction intervals for left and right hands
Initialise: empty feature vector $\mathbf{X}$, left window $\mathbf{w}_L$; right window $\mathbf{w}_R$
Set: max window size N, smoothing window size W, thresholds $k_{\text{on}}, k_{\text{off}}$
foreach *frame* t **do**
  if *hand or eye tracking data missing* **then**
    continue
  end
  if $|\mathbf{X}| = N$ **then**
    remove first element from $\mathbf{X}$
  end
  if $|\mathbf{w}_L| = W$ **then**
    remove first element from $\mathbf{w}_L$
  end
  if $|\mathbf{w}_R| = W$ **then**
    remove first element from $\mathbf{w}_R$
  end
  $\mathbf{x}_t \leftarrow [\mathbf{h}_t \| \mathbf{g}_t]$
  append $\mathbf{x}_t$ to $\mathbf{X}$
  if $|\mathbf{X}| = N$ **then**
    $\hat{\mathbf{y}}_t = f_\theta(\mathbf{X})$; `// LSTM inference`
  end
  foreach *hand* $h \in \{L, R\}$ **do**
    append $\hat{y}_t^h$ to $\mathbf{w}_h$
    if $|\mathbf{w}_h| = W$ **then**
      $p \leftarrow$ proportion of 1s in $\mathbf{w}_h$
      if $p \geq k_{on}$ ***and*** h *not currently interacting* **then**
        Call `process_interaction_start()`
        Mark h as currently interacting
      end
      if $p \leq k_{off}$ ***and*** h *is currently interacting* **then**
        Call `process_interaction_end()`
        Mark h as not interacting
      end
    end
  end
end

4.1.2 Model

We implement this learnable function $f_\theta(\cdot)$ as a Long Short-Term Memory (LSTM), a type of Recurrent Neural Network (RNN). The LSTM is well suited to the modelling of sequential data through the maintenance and updating of a hidden internal state over time. This makes this architecture particularly useful in the context of hand gesture comprehension, where the actions of each hand cannot be fully understood from a single frame. Instead, the model must learn from sequences of hand motion, capturing cues such as deceleration before grasp, dwell time during manipulation, and coordinated movement between the wrist and palm.

The LSTM has an input size of $N \times 42$. Hidden layer capacity is studied in section 5.1, and a fully connected layer maps the final hidden layer to two outputs, each undergoing sigmoid activation to produce the output vector $\hat{\mathbf{y}}_t = \left[\hat{y}_t^L, \hat{y}_t^R\right]^\top$.

4.1.3 Training

We train our model in a supervised fashion. In this section, we detail our label generation process, loss function, and choice of hyperparameters.

Dataset

In order to obtain annotations for hand-object interactions $\mathbf{y}_t$ at each MPS hand-tracking timestamp t, we use the ground-truth positions of objects in the HOT3D dataset. We use the first-order central difference method to calculate the velocity of each object at each motion capture timestamp t_{mc} as:

$$v_t^i = \frac{\|\mathbf{p}_{t+1}^i - \mathbf{p}_{t-1}^i\|}{2\delta t_{mc}} \tag{4.5}$$

where $\mathbf{p}_t^i \in \mathbb{R}^3$ is the position of object i at timestamp t, and δt_{mc} is the inverse of the frequency at which the motion capture system captures ground-truth object positions (30 Hz).

We then assert that, since all objects in the dataset are static unless moved by the participant's hands, a hand-object interaction is occurring at timestamp t_{mc} if at least one object has a velocity above some small threshold $v_{thresh} = 3\,\mathrm{cm\,s^{-1}}$. If

two objects succeed this threshold velocity, then both hands are given the binary label 1 at that timestamp, indicating that they are both interacting with an object. If only one object succeeds this threshold velocity, it is left to determine which hand is being used to interact with this object; we simply pick the hand who's palm has the smallest euclidean distance to the object centroid, assign a 1 for that hand, and a 0 for the other.

Since MPS hand-tracking timestamps t and motion capture timestamps t_{mc} are not synchronised, we obtain $\mathbf{y}_t$ at each MPS timestamp t using the value at the nearest t_{mc}. Finally, we split the dataset up into non-overlapping windows, length N, of frame-level feature vectors as in Equation 4.3 to form our training and validation feature vectors. Each feature vector is paired with the ground-truth label $\mathbf{y}_t$ of the final timestamp in the window, such that the model predicts $\hat{\mathbf{y}}_t$ in a causal manner, based on the window of previous hand-tracking and eye-tracking data $[\mathbf{x}_{t-N+1} \cdots \mathbf{x}_t]$.

Loss Function

For the loss criterion, we employ the binary cross-entropy loss. Specifically, for $y_t^h \in \{0, 1\}$, the ground-truth HOI status of hand h at time t, and $\hat{y}_t^h \in [0, 1]$, the predicted probability after sigmoid activation of hand h interacting with an object at time t, the binary cross-entropy is given by

$$\text{BCE}(y_t^h, \hat{y}_t^h) = -\left(y_t^h \cdot \log(\hat{y}_t^h) + (1 - y_t^h) \cdot \log(1 - \hat{y}_t^h)\right) \tag{4.6}$$

We calculate the binary cross-entropy for each hand $h \in \{L, R\}$ separately, before averaging between the two, giving an overall loss function of

$$\mathcal{L}_{\text{BCE}} = \frac{1}{2}\left(\text{BCE}(y_t^L, \hat{y}_t^L) + \text{BCE}(y_t^R, \hat{y}_t^R)\right) \tag{4.7}$$

Treating the prediction for each hand as a separate binary decision is preferable over the four-class classification problem of selecting one of the four labels $[0, 0], [0, 1], [1, 0], [1, 1]$ and using cross-entropy loss. This is because no constraints are placed on the relative probabilities for each hand, allowing each label (i.e. the probability for each hand) to be learned independently.

4.2 Active Memory

The ability to identify and recall objects across space and time is a cornerstone of human cognition. *Object permanence*, the understanding that an object continues to exist even when not being perceived, is the first developmental step towards this ability, emerging in infants between 4 and 7 months of age. This evolves into the capacity to maintain a persistent mental representation of one's experiences - where objects are located, what they looked like, and how we used them. Mirroring this ability in an artificial system is, however, a significant challenge, one which we will explore in this section.

To address this challenge, we propose an *active memory*. This concept is inspired by the prior work of AMEGO, where the notion of active memory was introduced. We use a semantic representation of both objects and locations, and 3D localisation for improved object tracking and pose-graph segmentation. This representation is capable of capturing not only *what* was interacted with and *when*, but also *where* in the physical environment these events occurred. We develop our methods around real-time active memory population, therefore permitting queries without the need for post-processing.

4.2.1 Active Memory Formulation

Following the nomenclature of AMEGO, we define our memory $\mathcal{E}$ as a set of objects $\mathcal{O}$ and locations $\mathcal{L}$. Each object $o_i \in \mathcal{O}$ is characterised by the tuple

$$o_i = (\text{ID}, \text{label}, \text{position}, \text{features}, \text{segments}) \tag{4.8}$$

where

- ID is a unique object identifier,
- label is a semantic object label (e.g., "mug", "phone"),
- position $\in \mathbb{R}^3$ are the last known object coordinates in the world frame,
- features are a visual feature embedding,

- segments $= \{(t_j^s, t_j^e, h)\}_{j=1}^n$ is the list of n interaction segments, each defined by the start and end time of the jth interaction with that object, along with the hand $h \in \{\text{L}, \text{R}\}$ that was used during that interval.

Similarly, each location $l_i \in \mathcal{L}$ is characterised by the tuple

$$l_i = (\text{ID}, \text{label}, \text{segments}) \tag{4.9}$$

where

- ID is a unique location identifier,
- label is a semantic location label (e.g., "office", "living room"),
- segments $= \{(t_j^s, t_j^e)\}_{j=1}^n$ is the list of n location intervals, each defined by the start and end time of the jth interval during which the user was present in that location.

4.2.2 Object Identification and Tracking

Populating this object memory $\mathcal{O}$ is a compound problem, drawing on elements from object detection, tracking, and instance segmentation. Our pipeline consists of three key steps: (1) proposing a candidate object at the moment of interaction, (2) comparing it to previously seen objects to identify potential matches, and (3) updating the object memory to reflect either this newly identified object or a new interaction with an existing object.

Step 1 - Object Candidate Proposal

At the start of each hand-object interaction segment, we generate a candidate object o_c, which mirrors the structure defined in Equation 4.8, excluding the ID and segments fields. This candidate object's properties are obtained as follows:

Given the palm position $\mathbf{p}_t^{h,palm} \in \mathbb{R}^3$ and point along the palm normal $\mathbf{n}_t^{h,palm} \in \mathbb{R}^3$, both in the device frame for the interacting hand $h \in L, R$ at time t, we reconstruct the unit palm normal vector as

$$\mathbf{v}_t^h = \frac{\mathbf{q}_t^h - \mathbf{p}_t^h}{|\mathbf{q}_t^h - \mathbf{p}_t^h|} \tag{4.10}$$

We then estimate the 3D coordinates of the object's centroid in the device frame as a point at distance $\lambda = 5\,\text{cm}$ along this vector

$$\mathbf{c}_t^{\text{device}\leftarrow o} = \mathbf{p}_t^h + \lambda \cdot \mathbf{v}_t^h \tag{4.11}$$

From this, we construct the 4x4 homogeneous transformation matrix for the object's centroid in the device frame as

$$T_t^{\text{device}\leftarrow o} = \begin{bmatrix} \mathbf{I}_{3\times 3} & \mathbf{c}_t^{\text{device}\leftarrow o} \\ \mathbf{0}_{1\times 3} & 1 \end{bmatrix} \tag{4.12}$$

To obtain the object's transformation matrix in the world frame, we simply matrix multiply this with the 4x4 homogeneous transformation matrix for the device in the world frame $T_t^{\text{world}\leftarrow\text{device}}$

$$T_t^{\text{world}\leftarrow o} = T_t^{\text{world}\leftarrow\text{device}} \cdot T_t^{\text{device}\leftarrow o} \tag{4.13}$$

before extracting its centroid coordinates in the world frame as the translation component of $T_t^{\text{world}\leftarrow o}$:

$$\mathbf{c}_t^{\text{world}\leftarrow o} = T_t^{\text{world}\leftarrow o}[0:3,3] \tag{4.14}$$

where $T[0:3,3]$ denotes the first three elements of the fourth column of the matrix. This is the vector that is stored in the position field of the candidate object.

In order to obtain visual features and a semantic label for the candidate object, we must first obtain its pixel coordinates $\mathbf{u}_t \in \mathbb{Z}^2$ in the RGB camera image. This is obtained by projecting $\mathbf{c}_t^{\text{device}\leftarrow o}$ onto the image plane using the FisheyeRadTanThinPrism projection model and the camera's online intrinsic calibration provided by MPS.

Using this pixel coordinate $\mathbf{u}_t = (u_t, v_t)$ we define the candidate object's 2D bounding box $\mathcal{B}_t$ as a square, centered at $\mathbf{u}_t$, with side length s pixels:

$$\mathcal{B}_t = \left(u_t - \frac{s}{2},\ v_t - \frac{s}{2}, s, s\right) \tag{4.15}$$

from which we crop the RGB camera image to obtain the object's image patch $\mathcal{I}_t$ for processing.

We employ a pretrained CLIP [19] model to obtain a visual feature embedding as well as semantic label for the candidate object. CLIP consists of a joint image-text embedding space where both images and text are projected into a shared semantic space. We make use of both the image and text encoders as follows:

Given the image patch of the candidate object $\mathcal{I}_t$, CLIP's image encoder produces a feature vector $\mathbf{f}^{\mathcal{I}} \in \mathbb{R}^d$ capturing the high-level visual appearance of the object:

$$\mathbf{f}^{\mathcal{I}} = \text{CLIP}_{\text{image}}(\mathcal{I}_t) \tag{4.16}$$

This embedding is then stored in the features field of the candidate object.

A predefined list of possible object labels $\{\ell_1, \ell_2, \ldots, \ell_K\}$ are embedded into this same feature space using CLIP's text encoder:

$$\mathbf{f}_k^{\ell} = \text{CLIP}_{\text{text}}(\ell_k), \quad k = 1, \ldots, K \tag{4.17}$$

from which the candidate object's label field can be calculated as the label whose text embedding has the highest cosine similarity with the image embedding:

$$\ell = \arg\max_k \ \text{S}_\text{c}(\mathbf{f}^{\mathcal{I}}, \mathbf{f}_k^{\ell}) \tag{4.18}$$

where cosine similarity is defined by

$$\text{S}_\text{c}(\mathbf{f}^{\mathcal{I}}, \mathbf{f}^{\ell}) = \frac{\mathbf{f}^{\mathcal{I}} \cdot \mathbf{f}^{\ell}}{||\mathbf{f}^{\mathcal{I}}||\,||\mathbf{f}^{\ell}||} \tag{4.19}$$

Step 2 - Object Matching

With our proposed candidate object o_c, we next determine whether this candidate corresponds to an object instance that is already in our object memory $\mathcal{O}$, or is a novel instance that must be added. To achieve this, we calculate the similarity between o_c and each existing object $o_i \in \mathcal{O}$ according to the similarity score defined below.

First, the visual similarity $S_v(o_c, o_i)$ is measured using a Cauchy distribution of the squared L^2 distance between their visual feature embeddings:

$$S_v(o_c, o_i) = \frac{1}{1 + \beta_v \left\| \mathbf{f}_c - \mathbf{f}_i \right\|_2^2} \tag{4.20}$$

Second, the spatial proximity term $S_s(o_c, o_i)$ is modelled as an exponential decay of the Euclidean distance between their centroids in the world coordinate frame:




Figure 4.1: A visualisation of the similarity distributions over L^2 distance in physical and visual embedding space.

$$S_s(o_c, o_i) = \exp\left(-\beta_s \left\| \mathbf{c}_c^{\text{world}} - \mathbf{c}_i^{\text{world}} \right\|_2\right) \tag{4.21}$$

where β_v and β_s are hyperparameters controlling the rate of decay of visual and spatial similarity respectively. These distributions are shown in Figure 4.1. The final similarity score is then computed as a weighted average of the two:

$$S(o_c, o_i) = \frac{1}{\alpha_v + \alpha_s} \left(\alpha_v S_v(o_c, o_i) + \alpha_s S_s(o_c, o_i)\right) \tag{4.22}$$

where α_v and α_s are hyperparameters used to control the relative weighting of each term in the cost function, resulting in an overall normalised similarity score $S(o_c, o_i) \in [0, 1]$.

To associate the candidate object o_c to an existing memory entry, we compute the similarity $S(o_c, o_i)$ for each $o_i \in \mathcal{O}$, and select the memory object with maximum similarity:

$$i^* = \arg\max_i \; S(o_c, o_i) \tag{4.23}$$

If $S(o_c, o_{i^*}) > \tau$ for some similarity threshold $\tau \in [0, 1]$, we associate o_c to the existing object o_{i^*}; otherwise, we create a new object instance for o_c.

Our formulation of the similarity distributions takes inspiration from the cost functions defined in [5] and [9]. These methods use such cost functions to apply frame-by-frame Hungarian matching across all objects to globally optimise assignment.

However, our use case requires only the association of a single candidate object to existing memory entries, making Hungarian matching redundant. We therefore opt to use the same distributions, but negated as normalised similarity scores rather than association costs, resulting in a simpler threshold-based matching procedure better suited to online and incremental memory construction.

Step 3 - Interaction Tracking

Having assigned o_c to a memory entry $o_i \in \mathcal{O}$, we track the hand-object interaction for it's duration to populate the segment for the jth interaction with this object, (t^s, t^e, h).

t^s and h are simply set as the timestamp t at which the hand-object interaction detected, and the hand $h \in \{\text{L}, \text{R}\}$ for which it was detected. t^e is set as the timestamp at which our hand-object interaction detection model indicates that an interaction is no longer active for this hand; at this point, the object's position in the world frame is obtained again using equation 4.14, and is then saved to the object's *position* field. The above three steps are summarised in Algorithms 2, 3 and 4 respectively.

Algorithm 2: Object Candidate Proposal

Input: Hand pose $\mathbf{p}_t^h$, $\mathbf{q}_t^h$; device pose $T_t^{\text{world}\leftarrow\text{device}}$; RGB image $\mathcal{I}$; calibration $\mathcal{K}$; CLIP model; precomputed label embeddings $\{\mathbf{f}_k^\ell\}$

Output: Candidate object o_c

$\mathbf{v}_t^h \leftarrow \frac{\mathbf{q}_t^h - \mathbf{p}_t^h}{\|\mathbf{q}_t^h - \mathbf{p}_t^h\|}$

$\mathbf{c}_t^{\text{device}\leftarrow o} \leftarrow \mathbf{p}_t^h + \lambda \cdot \mathbf{v}_t^h$

$T_t^{\text{device}\leftarrow o} \leftarrow \begin{bmatrix} \mathbf{I}_{3\times3} & \mathbf{c}_t^{\text{device}\leftarrow o} \\ \mathbf{0}_{1\times3} & 1 \end{bmatrix}$

$T_t^{\text{world}\leftarrow o} \leftarrow T_t^{\text{world}\leftarrow\text{device}} \cdot T_t^{\text{device}\leftarrow o}$

$\mathbf{c}_t^{\text{world}} \leftarrow T_t^{\text{world}\leftarrow o}[0\!:\!3, 3]$

$\mathbf{u}_t \leftarrow \text{Project}(\mathbf{c}_t^{\text{device}\leftarrow o}, \mathcal{K})$

$\mathcal{I}_t \leftarrow$ crop image patch centered at $\mathbf{u}_t$

$\mathbf{f}^{\mathcal{I}} \leftarrow \text{CLIP}_{\text{image}}(\mathcal{I}_t)$

$\ell \leftarrow \arg\max_k \frac{\mathbf{f}^{\mathcal{I}} \cdot \mathbf{f}_k^\ell}{\|\mathbf{f}^{\mathcal{I}}\| \cdot \|\mathbf{f}_k^\ell\|}$

return $o_c = (\ell, \mathbf{c}_t^{world}, \mathbf{f}^{\mathcal{I}})$

Algorithm 3: Object Matching

Input: Candidate object $o_c = (\ell_c, \mathbf{c}_c^{\text{world}}, \mathbf{f}_c)$; object memory $\mathcal{O}$; hyperparameters $\alpha_v, \alpha_s, \beta_v, \beta_s, \tau$

Output: Matched object index i^* or `None`

for $i \leftarrow 1$ **to** $|\mathcal{O}|$ **do**
  $\mathbf{f}_i \leftarrow \mathcal{O}[i]$.features
  $\mathbf{c}_i \leftarrow \mathcal{O}[i]$.position
  $S_v \leftarrow \frac{1}{1+\beta_v \|\mathbf{f}_c - \mathbf{f}_i\|^2}$
  $S_s \leftarrow \exp(-\beta_s \|\mathbf{c}_c^{\text{world}} - \mathbf{c}_i\|)$
  $S_i \leftarrow \frac{1}{\alpha_v + \alpha_s}(\alpha_v S_v + \alpha_s S_s)$
end
$i^* \leftarrow \arg\max_i S_i$
if $S_{i^*} > \tau$ **then**
  return i^*
end
else
  return *None*
end

Algorithm 4: Interaction Tracking

Input: Assigned object index i^*; object memory $\mathcal{O}$ current timestamp t; interacting hand h; Hand pose $\mathbf{p}_t^h$, $\mathbf{q}_t^h$

Output: Updated memory object o_i with new segment and final position

$t^s \leftarrow t$
while *IsInteracting*(h, t) **do**
  $t \leftarrow t + 1$
end
$t^e \leftarrow t$
Append (t^s, t^e, h) to $\mathcal{O}[i]$.segments
$\mathbf{v}_t^h \leftarrow \frac{\mathbf{q}_t^h - \mathbf{p}_t^h}{\|\mathbf{q}_t^h - \mathbf{p}_t^h\|}$
$\mathbf{c}_t^{\text{device}\leftarrow o} \leftarrow \mathbf{p}_t^h + \lambda \cdot \mathbf{v}_t^h$
$T_t^{\text{device}\leftarrow o} \leftarrow \begin{bmatrix} \mathbf{I}_{3\times 3} & \mathbf{c}_t^{\text{device}\leftarrow o} \\ \mathbf{0}_{1\times 3} & 1 \end{bmatrix}$
$T_t^{\text{world}\leftarrow o} \leftarrow T_t^{\text{world}\leftarrow \text{device}} \cdot T_t^{\text{device}\leftarrow o}$
$\mathcal{O}[i]$.position $\leftarrow T_t^{\text{world}\leftarrow o}[0:3, 3]$
return $o_i = (\ell, \mathbf{c}_t^{world}, \mathbf{f}^{\mathcal{I}}, \mathbf{c}^{world})$

4.2.3 Location Segmentation

The second component of our memory $\mathcal{E} = \{\mathcal{O}, \mathcal{L}\}$ concerns the identification of the set of semantic locations that the user visits, as well as when they were present in each one. This can be seen as a problem of semantic scene understanding and place recognition - open areas of research in the field of robotics, from which we take inspiration.

Building on methods presented in LEXIS [20], our pipeline consists of three key steps: (1) room identification and pose-graph segmentation, (2) pose-graph refinement, and (3) room instance clustering, and we further demonstrate the downstream application of these methods to point-cloud segmentation.

Step 1 - Room Identification & Pose-graph Segmentation

First, a room label is identified for the room within which the user is present at time t. To do this, a similar procedure to section 4.2.2 is used; the same pre-trained CLIP model is reused to generate an image embedding, this time for the entire RGB camera image at time t, and its cosine similarity is calculated with a list of possible room label embeddings, such that the label with the highest cosine similarity is selected.

This process is repeated at regular intervals along the device's trajectory, splitting the pose-graph into segments of length $\delta = 1\,\text{m}$, each with an associated semantic label ℓ^{room}. We represent the n segments in order as a list of tuples:

$$\mathcal{S} = \left\{ (t_j^s, t_j^e, \ell_j^{\text{room}}, \mathbf{p}_j^{\text{avg}}) \right\}_{j=1}^{n} \tag{4.24}$$

where t_j^s and t_j^e are the start and end timestamps for the jth segment, and $\mathbf{p}_j^{\text{avg}}$ is the average position of the poses within that segment.

Step 2 - Pose-graph Refinement

Labels generated by step 1 are identified purely by the RGB images at a discrete set of timestamps; it lacks any temporal context and hence room label misclassification is common when transitioning between rooms or moving through areas that lack

distinct semantic content (see Section 5.2.3). This problem is exacerbated by the frequent occlusions and rapid camera motion characteristic of egocentric video.

To mitigate this label noise, a smoothing step is performed to refine this sequence of pose-graph segment labels. This refinement step is inspired by the label propagation algorithm [21], which considers the K-nearest neighbours of each segment, and identifies the most common label within this range. If the central segment's label differs from this most common label, it is overwritten, with the process repeating until convergence. The approach here remains largely the same, differing by the fact that we only perform one forward pass for every m new segments created.

Step 3 - Room Instance Clustering

It does not suffice to simply label each room in order to identify unique room instances. For example, if the user walks between multiple office rooms, our active memory must be capable of distinguishing one office from the other, despite them having the same semantic label.

To achieve this, a clustering step is finally performed. Each segment with a room label not yet encountered forms its own cluster $\mathcal{C}$. Each subsequent segment $s_j = (t_j^s, t_j^e, \ell_j^{\text{room}}, \mathbf{p}_j^{\text{avg}})$ is added to the kth cluster $\mathcal{C}_k$ with the same label if

$$\left\| \mathbf{p}_j^{\text{avg}} - \bar{\mathbf{p}}_k \right\|_2 < \delta_r \tag{4.25}$$

where $\bar{\mathbf{p}}_k$ is the mean of all segment centroids currently in cluster $\mathcal{C}_k$, and δ_r is a spatial radius threshold. Clustering in this way allows for the assignment of a unique location ID to each cluster and the collapse the sequential representation $\mathcal{S}$ in Equation 4.24 to our location memory form $\mathcal{L}$ of Equation 4.9.

The above steps are based on methods presented in sections III.B and III.C of LEXIS [20]. The applications of these methods to our work are summarised in Algorithms 5, 6 and 7, respectively.

Algorithm 5: Room Identification and Pose-graph Segmentation

Input: Device poses $\{\mathbf{p}_t\}$; RGB frames $\{\mathcal{I}_t\}$, room label embeddings $\{\mathbf{f}_k^\ell\}$
Output: Initial segment set $\mathcal{S}$

Initialise: segment index $j = 0$, last sampled pose $\mathbf{p}_{\text{sampled}}$
Set: distance threshold δ
foreach *frame* t **do**
  if $\|\mathbf{p}_t - \mathbf{p}_{sampled}\|_2 \geq \delta$ **then**
    $j = j + 1$
    $t_{j-1}^e \leftarrow t$
    append $(t_{j-1}^s, t_{j-1}^e, \ell_{j-1}^{\text{room}}, \mathbf{p}_{j-1}^{\text{avg}})$ to $\mathcal{S}$
    $\mathbf{f}^I \leftarrow \texttt{CLIP}_{\text{image}}(\mathcal{I}_t)$
    $\ell_t^{\text{room}} \leftarrow \arg\max_k \frac{\mathbf{f}^I \cdot \mathbf{f}_k^\ell}{\|\mathbf{f}^I\| \cdot \|\mathbf{f}_k^\ell\|}$
    Create new segment $(t_j^s, _, \ell_t^{\text{room}}, \mathbf{p}_j^{\text{avg}})$
    $\mathbf{p}_{\text{sampled}} \leftarrow \mathbf{p}_t$
  end
end

Algorithm 6: Pose-graph Refinement

Input: Initial segment set $\mathcal{S}$
Output: Refined segments with corrected labels

Set: number of neighbours K
foreach *m segments created* **do**
  foreach $s_j \in \mathcal{S}$ **do**
    $\mathcal{N}_j \leftarrow$ K-nearest neighbours of s_j
    $\ell_{\text{mode}} \leftarrow$ most common label in $\mathcal{N}_j$
    if $\ell_j^{room} \neq \ell_{mode}$ **then**
      $\ell_j^{\text{room}} \leftarrow \ell_{\text{mode}}$
    end
  end
end

Algorithm 7: Room Instance Clustering

Input: Refined segments $\mathcal{S}$
Output: Location memory $\mathcal{L}$ with labeled room segments

Set: cluster distance threshold δ_c
foreach $s_j = (t_j^s, t_j^e, \ell_j^{room}, \mathbf{p}_j^{avg}) \in \mathcal{S}$ **do**
  if *cluster* $\mathcal{C}_k$ *exists with same label and* $\|\mathbf{p}_j^{avg} - \bar{\mathbf{p}}_k\|_2 < \delta_c$ **then**
    Assign s_j to $\mathcal{C}_k$
  else
    Create new cluster $\mathcal{C}_{\text{new}}$ with s_j
  end
end

5
Experiments

There is no single evaluation mode or unified metric that fully captures the performance of our system. Instead, our evaluation is structured to reflect the modular stages of our pipeline, with separate experiments conducted to assess each component independently using task-specific benchmarks and metrics. As in Chapter 4, we break down our experiments into an evaluation of our hand-object interaction detection system, and our active memory:

5.1 Hand-Object Interaction Detection

1. Frame-wise Prediction - An ablation over model capacity and input data modality on detection performance and inference speed.
2. Interaction Segmentation - Evaluation of our method for segmenting interaction intervals from frame-wise predictions using temporal smoothing.

5.2 Active Memory

1. Object Tracking - Measurement of our system's ability to estimate the 3D location of interacted objects over time.
2. Object Identification and Matching - Evaluation of object identification and matching performance, ablating over spatial and visual matching weightings.
3. Location Identification - Evaluation applied to room segmentation, via alignment of Aria trajectories to ground-truth building maps.

5.1 Hand-Object Interaction Detection

Our first set of experiments are focussed on the evaluation of our hand-object interaction detection method. Forming the initial stage of our pipeline, robust detection is critical, as downstream tasks such as object identification and tracking depend on correctly identifying the temporal bounds of interaction events. We assess performance of the model on the frame-wise detection problem, and test how well these predictions are grouped to form temporally consistent interaction segments, which serve as the atomic units of memory storage in the active memory module.

5.1.1 Frame-wise Prediction

To better understand the impact of key design decisions on our hand-object interaction detection model's performance, we conduct an ablation study over three core aspects of our LSTM design: (1) network architecture, (2) temporal window size, and (3) input data modality. As detailed in Section 4.1.3, we train our model in a supervised manner using the HOT3D dataset [18].

The dataset $\mathcal{D}$ is split as follows: by default, a number of sequences do not have ground-truth hand and object poses. These sequences form the test set, $\mathcal{D}_{\text{Test}}$. For all sequences that fall outside of this test set, we randomly split them into 80% training sequences $\mathcal{D}_{\text{Train}}$ and 20% validation sequences $\mathcal{D}_{\text{Val}}$, as per standard procedure.

Metrics

By the nature of our choice of labelling $y_t^h \in \{0, 1\}$ for hand h, the majority of our labels are 0 due to the fact that participants in the HOT3D dataset tend to spend more time with their hands *not* interacting with an object. This class imbalance problem is exacerbated by the fact that the majority of the population is right-handed, with the majority of hand-object interactions in the dataset using the right hand. The result is a significant imbalance towards the 0 label for the left hand in particular, making appropriate choice of metric critical.

Precision is calculated as the number of correct positive predictions out of the total number of positive predictions:

$$\text{Precision} = \frac{TP}{TP + FP} \tag{5.1}$$

where TP and TN represent the number of true positives and true negatives, and FP and FN represent the number of false positives and false negatives, respectively. **Recall** is calculated as the number of the number of correct positive predictions out of the total number of data points that should've been predicted as positive:

$$\text{Recall} = \frac{TP}{TP + FN} \tag{5.2}$$

***F*1 score** is computed as the harmonic mean of precision and recall:

$$F1 = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \tag{5.3}$$

which is particularly valuable in imbalanced classification problems, as it penalises both false positives and false negatives. In our case, this ensures the model is not only cautious in predicting interactions (high precision), but also sufficiently sensitive to detect them when they occur (high recall).

We finally note the training setup, for which we control over each ablation experiment. We use PyTorch [22] to train our model for 20 epochs with a batch size of 32. We use the Adam optimiser [23] with a constant learning rate of 1^{-3}, and set the LSTM dropout rate to 0.3. The $F1$ score reported for each training run is given by the model's peak performance on the validation set during that run.

Model Capacity

We start with an assessment of the trade-off between model complexity and performance. We do so by comparing model performance across different numbers of hidden layers, as well as different hidden state sizes, in the LSTM. Specifically, we study all combinations of the number of layers $L \in \{1, 2, 3\}$ and hidden layer size $H \in \{32, 64, 128\}$. Our results are given in Table 5.1.

A monotonic improvement in $F1$ scores is observed as both the number of LSTM layers L and the hidden state size H increase. However, these gains taper as

		Number of Layers (L)		
		1	**2**	**3**
Hidden Size (H)	**32**	0.7221 / 0.8348	0.8017 / 0.8720	0.8290 / 0.8882
	64	0.8244 / 0.8873	0.8953 / 0.9322	0.9064 / 0.9407
	128	0.9102 / 0.9440	0.9364 / 0.9612	**0.9369 / 0.9634**

Table 5.1: $F1$ score for each hand across different model architectures. Each cell reports Left / Right hand $F1$ score.

the model capacity increases, with marginal performance increase between $L = 2$ and $L = 3$ at $H = 128$. Each successive increase in model capacity also increases inference time and power consumption, which are both constrained when operating online. For this reason, the architecture with $L = 2$, $H = 128$ is chosen as the preferred model for further experiments.

Another key observation is the consistent underperformance in left hand $F1$ score compared to right. This asymmetry reflects the class imbalance toward right-hand interactions in the dataset, as previously noted.

Window Size

In this experiment, we investigate how the length of the sliding window N in equation 4.3 affects model performance. This parameter determines how many past timestamps of hand-tracking the LSTM observes when making a prediction at time t. Intuitively, a longer window may provide the model with more temporal context, potentially improving its ability to detect interactions that evolve gradually over time. However, excessively long windows could introduce noise or lead to overfitting, particularly given our dataset's class imbalance.

We report the model's performance for $N \in \{6, 15, 30, 60\}$ corresponding to $\{0.2, 0.5, 1, 2\}$ seconds of hand-tracking data at 30 Hz respectively. Our results are given in Table 5.2.

These results show a similar pattern to the previous ablation study: model performance increases consistently with increasing window size, suggesting that longer temporal context is indeed beneficial for our model's performance. Returns diminish for temporal window sizes beyond 1-2 seconds, however it is noted that

Window Size N	***F*1 Score** L / R	**Inference Time** ms
6	0.8619 / 0.9065	**0.79**
15	0.9070 / 0.9394	0.94
30	0.9313 / 0.9575	1.19
60	**0.9409 / 0.9600**	1.82

Table 5.2: Model performance and inference time across varying temporal window sizes N.

inference time does not vary proportionally with window size, with even the largest window size falling well within latency constraints. Consequently, experiments are continued with a window size $N = 60$.

Input Data Modality

Our final model ablation study investigates the contribution of different physical signal modalities to hand-object interaction detection: hand-tracking and eye-tracking data. Each modality offers distinct cues - hand motion may signal physical interaction, while gaze behavior can indicate intent or attention. To understand how each modality contributes to the model's predictive performance, we compare three different input configurations: (1) hand-tracking data only, (2) eye-tracking data only, and (3) a combination of both. Our results are given in Table 5.3.

Input Modality	***F*1 Score** L / R
Hand-Tracking	0.9364 / **0.9612**
Eye-Tracking	0.9116 / 0.9473
Hand + Eye Tracking	**0.9409** / 0.9600

Table 5.3: Left / Right hand $F1$ score across different input data modalities.

Obtaining eye-gaze data requires the inclusion of two eye-tracking cameras in the frame of the glasses. For the provision of such a simple and unambiguous signal, this is a bulky and obstructive addition to the device. Yet, eye-gaze data alone proves to be a rich and informative source of information for detecting object interactions, demonstrated by the competitive performance of the model conditioned solely on eye-gaze data. This highlights the strong correlation that exists between visual attention and intention to

act, though physical motion of the hand remains the strongest individual modality, outperforming eye-tracking across both hands.

Despite the strong performance of each of these single-modality models, using a combination of both modalities by concatenating the data into one larger feature vector results in marginal improvement for the left hand, and a degradation in performance for the right hand. These small discrepancy may be within the bounds of statistical variation, but it could also point to the model relying primarily on hand-tracking data when the hands are clearly visible, and defaulting to eye-tracking data only when hand-tracking confidence is low or features are ambiguous - especially relevant for the lesser-used left hand.

With this in mind, our final hand-object interaction detector is selected as the combined hand- and eye-tracking model. This model offers the best trade-off between left- and right-hand performance and demonstrates the strongest robustness to class imbalance across modalities.

5.1.2 Interaction Segmentation

Having assessed our ability to predict frame-wise hand-object interaction statuses, we now investigate our ability to form consistent interaction intervals, or segments, from this signal. In order to quantitatively measure our performance on this task, we compute the average Intersection over Union (IoU) between predicted and ground-truth intervals for which a hand-object interaction is active. We further report the difference in the number of predicted and ground-truth segments, ΔN, as a measure of segmentation noise.

The predicted intervals are obtained as per Section 4.1.1, whereby the start of a hand-object interaction is detected for hand h at time t if at least some proportion $k \in [0, 1]$ of the predicted labels in a sliding window of length W, i.e. $[\hat{y}^h_{t-W+1}, \ldots, \hat{y}^h_t]$, are positive ($= 1$). This segment ends when the proportion of negative predictions in this window exceeds this same threshold. The ground-truth segments are obtained in the same way as the ground-truth labels in Section 4.1.3.

Figure 5.1 illustrates the predicted versus ground-truth interaction segments for a sequence in the validation set. From this, several observations can be made; first, our dataset's class imbalance for the left hand is evident in the lack of time spent using the left hand to interact with objects. This results in sparse predictions which fail to align with ground-truth interactions. Segmentation for the right hand is better, suggesting increased training data has a significant impact on performance, though segments are often fragmented, likely due to transient confidence drops.




Figure 5.1: Ground-truth and predicted segments from a sequence in the HOT3D validation set. Here, $k = 0.75$ and $W = 5$.

It should be noted that, when our thresholds is set as $k = 1$, smoothing collapses to a strict consecutive frame thresholding scheme, where an interaction is initiated only after W consecutive positive predictions, and terminated immediately after W negative predictions. Experiments showed that setting $k = 0.75$ gave best performance consistently across window different window sizes, for which results are shown in Table 5.4.

It is observed that larger smoothing windows more effectively attenuate noise caused by incorrect predictions from the LSTM. This is evidenced by the monotonic decrease in ΔN with increasing W, showing that over-segmentation is reduced with a larger smoothing window. Despite this, there is a noticeable drop in IoU for both hands as the window length increases. This is likely because larger windows delay

Window Length (W)	Left IoU	Right IoU	ΔN
5	**0.1070**	**0.2458**	14.375
10	0.1001	0.2447	11.050
15	0.0959	0.2408	10.525
30	0.0846	0.2387	**9.650**

Table 5.4: Average IoU for each hand and ΔN across different window lengths W.

the model's response to changes in the interaction state — the temporal smoothing suppresses short interactions or introduces lag in their detection, reducing alignment with ground-truth intervals.

5.2 Active Memory

In the following section, we evaluate our system's ability to accurately construct and update our *active memory*. As per Section 4.2, this includes our ability to identify both objects and locations, as well as track objects and match repeat observations over time.

5.2.1 Object Tracking

Given a hand-object interaction, our ability to then localize this object in space is critical - not only for the purpose of storing its last known location in our object memory for downstream querying, but also in our object matching cost function (Equation 4.22). In a wider context, this capability underpins real-world applications such as assistive robotics, where accurate knowledge of object positions enables efficient interaction and navigation. In this section, we evaluate our system's ability to estimate and maintain accurate 3D object locations in the world coordinate frame.

Standalone Performance

The performance of our object tracking method is affected by the performance of the upstream hand-object interaction detection; if we do not detect a hand-object interaction, we do not update the location of an object. We therefore seek to avoid

compounding detector error, and decouple the results of our hand-object interaction segmentation pipeline from our object tracking algorithm.

To achieve this, we follow a similar approach to OSNOM [5], who make use of annotations from VISOR [24] to start from a point where they have reliable 2D bounding boxes for objects. We instead make use of ground-truth data from the HOT3D dataset [18]. We determine the start of a hand-object interaction when an object starts moving, according to equation 4.5; we determine the conclusion when this velocity falls back to zero. Furthermore, when a hand-object interaction starts, we use the ground-truth bounding box for the corresponding object to generate visual features, bypassing errors that arise from improper object cropping.

We adopt the **Percentage of Correct Locations (PCL)** metric, introduced in OSNOM [5], as our principal evaluation measure. This metric reports the proportion of objects whose predicted 3D location lies within a fixed radius R of their ground-truth location at each time step. It thus directly quantifies spatial accuracy across time, and is particularly suitable for long-horizon egocentric tracking. Following convention, we set $R = 30\,\text{cm}$, approximately corresponding to the width of a typical kitchen cabinet, as this reflects a practically acceptable tolerance for locating objects in household environments.

We report the average PCL across all sequences in our HOT3D validation set, split into 5 second evaluation intervals. Our results are shown in Figure 5.2.




Figure 5.2: PCL over time across all sequences in the validation set.

From this graph, it can be seen that our method produces a 100% score towards the end of all recordings. All sequences in the HOT3D dataset conclude with the participant setting down all objects, before ending the recording. As a result, all objects are static in the last few seconds of each recording, and during this period, we score 100% PCL across all objects. This shows that, if one can reliably predict the *end* time of hand-object interactions, then the method of employing hand-tracking to infer the object's last known location, and not updating that location until the object is interacted with again, can be useful.

PCL score is slightly lower throughout the main section of the sequences, when objects are being picked up and manipulated by the participants' hands. During these periods, objects are in motion and their precise positions vary rapidly, making tracking inherently more challenging. Our method updates the estimated object position at each timestamp based on the tracked hand pose; if said hand is occluded, then the object's location is not updated, resulting in periods of lower PCL.

The primary concern of our active memory, however, is not tracking objects whilst they are in hand, but accurately storing their last known location for downstream object matching and querying. These results demonstrate that this final position is estimated with high reliability, supporting our design choice to prioritise endpoint accuracy over continuous object tracking.

5.2.2 Object Identification and Matching

For the evaluation of our object identification and matching pipeline, we wish to assess how reliably our system assigns the correct object instance to each hand-object interaction segment. Therefore, following the approach of AMEGO [13], we compute the intersection over union between predicted and ground-truth segments, on a per-object basis. Specifically, we report the following: AIoU P, average Intersection over Union between each predicted object instance's segments and its best-matching ground truth object instance's segments, as a measure of precision, and AIoU GT, average Intersection over Union between each ground truth object instance's segment and its best-matching predicted object instance's segments, as a measure

of recall. We also report ΔN, the difference between the number of predicted and ground-truth object instances, to measure how frequently repeat interactions with the same object fail to be matched.

Standalone Performance

In the same way as the object location accuracy experiments, the IoU between an object's predicted and ground-truth segments depend not only on how well our system assigns object instances to each segment, but also on the performance of our hand-object interaction segmentation pipeline. Furthermore, due to the nature of our similarity score (Equation 4.22), our results here also depend on our ability to accurately localise objects in the world frame. Again, we seek to avoid compounding upstream errors and evaluate our object identification and matching methods in isolation.

We therefore take a similar approach as in Section 5.2.1, using ground-truth data from the HOT3D dataset to detect the start and end of interactions. However, we further make use of ground-truth 3D object positions, rather than estimated ones, in our similarity scoring function.

Our main objective in this ablation is to study the effect of incorporating spatial information into our similarity score (Equation 4.22). We therefore vary the relative importances of the two terms in this function by varying α_s in the range $\{0, 0.25, 0.5, 0.75, 1\}$ and setting $\alpha_v = 1 - \alpha_s$, before calculating the average IoUs over all object instances. Our results are shown in Table 5.5.

$\boldsymbol{\alpha_s}$	**AIoU P**	**AIoU GT**	ΔN
0.00	0.0644	0.1858	21.88
0.25	0.2288	0.2135	20.77
0.50	0.0443	0.1644	18.44
0.75	0.0378	0.1575	12.22
1.00	0.0353	0.1558	-0.4166

Table 5.5: Effect of spatial and visual similarity weighting α_s on average Intersection over Union. AIoU P = predicted-to-ground-truth matching (precision), AIoU GT = ground-truth-to-predicted matching (recall).

It is observed that incorporating a modest spatial component to the similarity function, i.e. setting $\alpha_s = 0.25$, significantly improves both AIoU P and AIoU GT over the purely visual baseline. This demonstrates that integrating even a small

amount of spatial reasoning substantially enhances the reliability of object matching, helping to disambiguate visually similar but spatially distinct object instances.

The negative ΔN observed for $\alpha_s = 1$, meaning that on average, the number of predicted object instances was less than the true number of object instances. This indicates that the system is estimating multiple objects as the same instance due to their close proximity to one another. On the other hand, increasing the visual weighting leads to a monotonic increase in ΔN, a result of occlusions at the start of interactions causing object crops that lack any distinct semantic content. This shows that visual matching alone can be brittle, and suggests a need for some confidence awareness when adding new object instances to the active memory.

5.2.3 Location Identification

The second key aspect of our active memory is to identify the locations within which the user, and hence objects, were present over time. This is performed using our room segmentation pipeline 4.2.3, whereby we identify semantic labels for the rooms within which the user was present over a series of temporal intervals, which we then used for downstream pose-graph segmentation.

Experimental Setup

In order to evaluate the performance of our location identification methods, some set of annotations is required to compare against - either temporal intervals during which the user was known to be in a particular room, or a set of device poses who's positions are known to fall into ground-truth room bounding boxes. Unfortunately, no such dataset exists for Project Aria data, meaning this annotation must be done manually.

Again approaching this problem from a robotics perspective, we make use of existing ground-truth maps of the Oxford Robotics Institute's George Building. Specifically, a point-cloud generated by a survey-grade Terrestrial Laser Scanner (TLS), and bounding boxes for the rooms within the building, both in the same coordinate frame. Following the approach of LEXIS [20], accuracy of the room

labelling method can be calculated by comparing the predicted room labels of nodes in our pose-graph with the labels of the room bounding boxes within which they fall.

In order for this to be possible, MPS SLAM trajectories must first be aligned with the coordinate frame of this ground-truth map. This is a rigid alignment problem, for which, in principle, there are several options for solving.

Coordinate Frame Alignment

The simplest is manual alignment - overlaying the trajectory and point-cloud and adjusting the transformation until they appear to align. Whilst being simple and quick, this method is inherently imprecise and must be done manually for each trajectory that is in a new unknown coordinate frame.

A second option is using Iterative Closest Points (ICP) or a similar algorithm for registration between the TLS and MPS point-clouds. However, these two point-clouds differ significantly in density and surface coverage (Figures 5.5 and 3.2), and the success of ICP depends heavily on good initialisation, which is not available here.

Given these limitations, we instead opt for the more repeatable approach of visual fiducial registration using AprilTags [25, 26]. We placed a series of tags (Figure 5.3) in known, repeatable locations around the George Building, and marked their 6-DoF poses in the ground-truth map coordinate frame (Figure 5.4). We then recorded a sequence with the Aria glasses, walking around the building past these tags before calculating the transformation as follows.



Figure 5.3: Example AprilTag placements around the George building.




Figure 5.4: 6-DoF AprilTag poses in the ground-truth map coordinate frame.

AprilTags are first detected in the RGB camera images. For each detection of tag i at time t, the relative pose of the tag in the camera frame is estimated as $T_i^{\text{cam}\leftarrow\text{tag}}(t)$ using the standard AprilTag detection pipeline, which fits a perspective transform to the detected tag corners and recovers the 6-DoF pose via a Perspective-n-Point algorithm. The pose of the tag in the MPS SLAM frame is then computed as

$$T_i^{\text{SLAM}\leftarrow\text{tag}}(t) = T^{\text{SLAM}\leftarrow\text{cam}}(t) \cdot T_i^{\text{cam}\leftarrow\text{tag}}(t) \tag{5.4}$$

For each tag i, all such detections across time are collected, and a robust estimate of the tag's pose in the MPS SLAM frame is computed by taking the component-wise median of 3D positions and Euler angles across all detections:

$$\bar{\mathbf{p}}_i = \underset{t}{\text{median}}\left(\mathbf{p}_i(t)\right), \quad \bar{\mathbf{q}}_i = \underset{t}{\text{median}}\left(\mathbf{q}_i(t)\right) \tag{5.5}$$

where $\mathbf{p}_i(t)$ and $\mathbf{q}_i(t)$ are the positional and rotational components of $T_i^{\text{SLAM}\leftarrow\text{tag}}(t)$. This yields a final estimated pose $\hat{T}_i^{\text{SLAM}\leftarrow\text{tag}}$ for each tag in the MPS SLAM frame.

Finally, a single rigid-body transformation $T^{\text{GT}\leftarrow\text{SLAM}} \in SE(3)$ is computed using point-based registration; the 3D positions of matched AprilTags from both coordinate systems, $\mathbf{p}_i^{\text{SLAM}} \in \mathbb{R}^3$ and $\mathbf{p}_i^{\text{GT}} \in \mathbb{R}^3$ are used to compute the rigid transform $T^{\text{GT}\leftarrow\text{SLAM}}$ that minimizes the mean squared error between these matched 3D points:

$$\min_{R,\mathbf{t}} \sum_{i=1}^{N} \left\| \mathbf{p}_i^{\text{GT}} - \left(R \cdot \mathbf{p}_i^{\text{SLAM}} + \mathbf{t} \right) \right\|^2 \tag{5.6}$$

This problem has a closed-form solution using the Umeyama algorithm [27], which recovers the optimal R and $\mathbf{t}$ in a least-squares sense. The final transformation is then applied to all estimated camera and tag poses, bringing the full SLAM trajectory into the coordinate frame of the ground-truth map. An example output of this process is shown in Figure 5.5.




Figure 5.5: An MPS trajectory aligned with the coordinate frame of the ground-truth map, TLS point-cloud and room bounding boxes. The trajectory is split into segments, coloured based on predicted room label.

An important feature of MPS is the ability to process multiple recordings simultaneously into a shared SLAM graph, known as Multi-SLAM. When sequences are jointly processed in this manner, they are all registered into a common coordinate frame. As a result, the rigid-body transformation $T^{\text{GT}\leftarrow\text{SLAM}}$ computed

via AprilTag registration in a single sequence is valid for all sequences that were jointly processed with it.

This greatly improves the practicality and scalability of our alignment procedure. Once a single reference sequence that was recorded with AprilTags is aligned with the ground-truth map, all jointly-processed sequences recorded in the same environment can also be aligned, even sequences recorded when AprilTags were not present. This allows us to re-record sequences around the George Building and recover their global alignment using only the shared SLAM graph, which we leverage to evaluate over multiple recording sessions.

Recordings

We used the Aria glasses to record five sequences around the George building for use as evaluation data. The building features three floors of offices, meeting rooms, and a kitchen, offering a realistic indoor environment with varied spatial layouts and semantic labels.

To evaluate the robustness of our method under different movement conditions, these sequences were designed to fall into two categories: controlled and natural. Controlled sequences involved smooth camera motion with minimal interaction, simulating structured mapping runs typical in robotics. In contrast, natural sequences captured everyday human activity such as making coffee, washing up, and informal conversations - introducing rapid head movement, occlusions, and more dynamic camera trajectories. This distinction enables us to assess the system's performance both in ideal conditions and in more challenging, real-world use cases.

Results

Overall accuracy of each category is calculated for both the baseline room identification case without smoothing, and after smoothing with K set as the value that gave highest overall accuracy. To contextualise our performance, we also report the accuracy that was achieved by LEXIS [20] in the George building, but on recordings that were made using a hand-held camera setup. These results act as an upper bound for our approach. Our results are shown in Table 5.6.

Method	Accuracy		
	Natural	Controlled	LEXIS
Baseline	0.5742	0.6098	0.6809
Smoothed	0.6548	0.6895	0.7922

Table 5.6: Room labelling accuracy for sequences in the George building with and without smoothing. Results from LEXIS in the same building are shown for comparison.

As expected, performance of our method on natural sequences is worse than the results obtained by LEXIS in the same building. However, the proposed method also underperforms LEXIS on controlled sequences, though this is likely due to the choice of $\delta = 0.25\,\text{m}$ in LEXIS giving higher spatial resolution, compared to the $\delta = 1\,\text{m}$ that was used here to decrease the frequency of CLIP model calls. Setting $K = 2$ was shown to effectively suppress classification noise in both controlled and natural sequences, increasing accuracy by around 8 percentage points in both cases.

In order to understand the system's failure modes, Figure 5.6 highlights segments of the trajectory that were misclassified. Errors frequently occur when transitioning between rooms; despite standing inside office 1 and looking through the door to the corridor, the RGB camera captures only the corridor, leading to misclassification. Areas of low or ambiguous semantic content, such as staircases or the George building kitchen (which contains whiteboards and tables as well as kitchen appliances), cause periods of misclassification that are too large to be suppressed by smoothing.




Figure 5.6: A plan view of the ground floor (left) and first floor (right) of the George building, with an Aria trajectory aligned and coloured by segment room label.

5.3 Runtime Analysis

As a final study, the runtime performance of our system's three key algorithms are given in Table 5.7. Experiments were conducted on a laptop with 8 Intel Xeon E3-1505M v6 CPUs and an Intel HD Graphics P630 integrated graphics unit.

Algorithm(s)	**Trigger Condition**	**Avg Runtime**
Hand-Object Interaction Detection 1	Every frame (30 Hz)	1.76 ms
Object Identification & Matching 2 + 3	Every new HOI segment	649.47 ms
Room Identification 5	Every $\delta = 1$ m walked	466.16 ms

Table 5.7: Average inference time for our three key models.

It is observed that the core HOI detection model, which is run every frame at 30Hz, falls well within real-time latency. Object and location identification modules are significantly more computationally expensive, with runtimes of 649.47 ms and 466.16 ms respectively, though these algorithms are triggered only upon detected hand-object interactions or per meter walked. Forward passes of the CLIP model that is used to gather image features for the objects and rooms are responsible for the majority of this runtime. Object identification must additionally compare the object candidate with each object already in memory, where the cost of this step scales with the number of objects in the memory, hence the larger runtime than location identification. Future work may focus on reducing latency for these modules via model quantisation or more efficient similarity search.

While our runtime analysis captures the computational cost of our own algorithms, it is noted that the performance of the overall system also depends on upstream models provided by Meta's Machine Perception Services (MPS), including SLAM, hand-tracking, and eye-tracking. These models are currently closed-source and only available to research partners as a post-processing service. A full end-to-end benchmark would require a study of these perception models, though we assume capability for real-time operation.

6 Conclusion

This thesis has presented a novel framework for object-level semantic mapping from egocentric video using Meta's Project Aria augmented reality research platform. Key contributions include the assessment of the use of hand motion and eye-gaze as cues for hand-object interaction detection using an LSTM, and the online construction of an *active memory*. This memory is populated online with both objects, using hybrid visual-spatial methods for instance segmentation, and locations, building on previous semantic scene understanding techniques from the DRS-P group.

Performance is benchmarked on a modern egocentric dataset, demonstrating how, using this dataset, training and evaluation data that previously required manual annotation to obtain can be generated at scale. A repeatable method for registration of Aria SLAM data using AprilTags is provided and leveraged to conduct further experiments on self-collected data.

Experiments yield promising performance, particularly for room segmentation with a vision-language model, and the use of SLAM and hand-tracking data as a proxy for 3D object tracking. Limitations exist, particularly for bi-manual object handling, suggesting future research towards a more complex representation of how hands are used to interact with objects.

References

[1] Dima Damen et al. “Scaling Egocentric Vision: The EPIC-KITCHENS Dataset”. In: *European Conference on Computer Vision (ECCV)*. 2018.

[2] Dima Damen et al. “Rescaling Egocentric Vision: Collection, Pipeline and Challenges for EPIC-KITCHENS-100”. In: *International Journal of Computer Vision (IJCV)* 130 (2022), pp. 33–55.

[3] Hao Tang et al. “EgoTracks: A Long-term Egocentric Visual Object Tracking Dataset”. In: *Conference on Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track*. 2023.

[4] Boyu Chen et al. *Backbone is All Your Need: A Simplified Architecture for Visual Object Tracking*. 2022. arXiv: `2203.05328 [cs.CV]`.

[5] Chiara Plizzari et al. “Spatial Cognition from Egocentric Video: Out of Sight, Not Out of Mind”. In: *International Conference on 3D Vision (3DV)*. 2025.

[6] Johannes Lutz Schönberger and Jan-Michael Frahm. “Structure-from-Motion Revisited”. In: *Conference on Computer Vision and Pattern Recognition (CVPR)*. 2016.

[7] Yasutaka Furukawa and Jean Ponce. “Accurate, Dense, and Robust Multiview Stereopsis”. In: *IEEE Transactions on Pattern Analysis and Machine Intelligence* 32.8 (2010), pp. 1362–1376.

[8] Lihe Yang et al. “Depth Anything: Unleashing the Power of Large-Scale Unlabeled Data”. In: *Conference on Computer Vision and Pattern Recognition (CVPR)*. 2024.

[9] Yash Bhalgat et al. “3D-Aware Instance Segmentation and Tracking in Egocentric Videos”. In: *Asian Conference on Computer Vision*. IEEE. 2024.

[10] Georgia Gkioxari et al. “Detecting and Recognizing Human-Object Interactions”. In: *Conference on Computer Vision and Pattern Recognition (CVPR)*. 2018, pp. 8359–8367.

[11] Shaoqing Ren et al. “Faster R-CNN: Towards Real-Time Object Detection with Region Proposal Networks”. In: *Advances in Neural Information Processing Systems (NeurIPS)*. Vol. 28. 2015.

[12] Dandan Shan et al. “Understanding Human Hands in Contact at Internet Scale”. In: *Conference on Computer Vision and Pattern Recognition (CVPR)*. 2020.

[13] Gabriele Goletto et al. “AMEGO: Active Memory from long EGOcentric videos”. In: *European Conference on Computer Vision (ECCV)*. 2024.

[14] Ce Zhang et al. *A Simple LLM Framework for Long-Range Video Question-Answering*. 2024. arXiv: `2312.17235 [cs.CV]`.

[15] Zeyi Huang et al. *Building a Mind Palace: Structuring Environment-Grounded Semantic Graphs for Effective Long Video Analysis with LLMs*. 2025. arXiv: 2501.04336 [cs.CV].

[16] Kristen Grauman et al. *Ego4D: Around the World in 3,000 Hours of Egocentric Video*. 2022. arXiv: 2110.07058 [cs.CV].

[17] Vadim Tschernezki et al. "EPIC Fields: Marrying 3D Geometry and Video Understanding". In: *Conference on Neural Information Processing Systems (NeurIPS)*. 2023.

[18] Prithviraj Banerjee et al. *HOT3D: Hand and Object Tracking in 3D from Egocentric Multi-View Videos*. 2024. arXiv: 2411.19167 [cs.CV].

[19] Alec Radford et al. *Learning Transferable Visual Models From Natural Language Supervision*. 2021. arXiv: 2103.00020 [cs.CV].

[20] Christina Kassab et al. "Language-EXtended Indoor SLAM (LEXIS): A Versatile System for Real-time Visual Scene Understanding". In: *International Conference on Robotics and Automation (ICRA)* (2024).

[21] Xiaojin Zhu and Zoubin Ghahramani. *Learning from Labeled and Unlabeled Data with Label Propagation*. 2003.

[22] Jason Ansel et al. "PyTorch 2: Faster Machine Learning Through Dynamic Python Bytecode Transformation and Graph Compilation". In: *International Conference on Architectural Support for Programming Languages and Operating Systems (ASPLOS)*. 2024.

[23] Diederik Kingma and Jimmy Ba. "Adam: A Method for Stochastic Optimization". In: *International Conference on Learning Representations (ICLR)* (2014).

[24] Ahmad Darkhalil et al. "EPIC-KITCHENS VISOR Benchmark: VIdeo Segmentations and Object Relations". In: *Conference on Neural Information Processing Systems (NeurIPS) Datasets and Benchmarks Track*. 2022.

[25] Edwin Olson. "AprilTag: A robust and flexible visual fiducial system". In: *Proceedings of the IEEE International Conference on Robotics and Automation (ICRA)*. 2011, pp. 3400–3407.

[26] John Wang and Edwin Olson. "AprilTag 2: Efficient and robust fiducial detection". In: *IEEE/RSJ International Conference on Intelligent Robots and Systems (IROS)*. 2016.

[27] S. Umeyama. " Least-Squares Estimation of Transformation Parameters Between Two Point Patterns ". In: *IEEE Transactions on Pattern Analysis & Machine Intelligence* 13.04 (1991), pp. 376–380.