

CSS III

Harry J. Wang, Ph.D.

University of Delaware

Review and Sample Code

- Some review and sample code are from the follownig courses
 - <https://www.codecademy.com/learn/learn-css>

CSS Box Model

- The box model comprises a set of properties used to create space around and between HTML elements.
- The height and width of a content area can be set in pixels or percentage.
- Borders surround the content area and padding of an element. The color, style, and thickness of a border can be set with CSS properties.
- Padding is the space between the content area and the border. It can be set in pixels or percent.
- Margin is the amount of spacing outside of an element's border.
- Horizontal margins add, so the total space between the borders of adjacent elements is equal to the sum of the right margin of one element and the left margin of the adjacent element.
- Vertical margins collapse, so the space between vertically adjacent elements is equal to the larger margin.
- `margin: 0 auto` horizontally centers an element inside of its parent content area, if it has a width.
- The `overflow` property can be set to `display`, `hide`, or `scroll`, and dictates how HTML will render content that overflows its parent's content area.
- The `visibility` property can hide or show elements.

Remote Fonts

- You can link to the remotely hosted fonts, such as Google Fonts

```
<head>
  <link href="https://fonts.googleapis.com/css?
family=Raleway" type="text/css" rel="stylesheet"
>
</head>
```


```
h1 {
  font-family: Raleway, Georgia, serif;
}
```

- For font name with spaces

```
<link href="https://fonts.googleapis.com/css?
family=Playfair+Display" type="text/css"
rel="stylesheet">
```

The Box Model

- All HTML elements live within a box. Elements on a web page are understood by the browser as “living” inside of a container, or a box.



Exercise (news.html and news.css)

- Change basic background and font
- Change unordered list to navigation menu
 - `float`: float to the left/right of the container (Elements after a floating element will flow around it. To avoid this, use the `clear` property)
 - `list-style-type`
- Change text into the following:

LOCAL NATIONAL THE TERMINAL GLOBAL OPED DONATE



- Change the text to the following (`div` and `span`):

WRITTEN BY: JAMES JAYCE

AWS Exercise

- Follow the instruction and upload two news.html and news.css