

**A 2D SIMULATION-BASED DECISION SUPPORT SYSTEM FOR FLOOD
EVACUATION PLANNING**

CAPSTONE PROJECT

JOHN HAROLD A. ALEJO
CYRUS KIRBY GAOR
BRADLEY KJIEL PASALO
JOSHEARIE KRISTOFFER LANDICHO



**Department of Information Technology
COLLEGE OF COMPUTING AND INFORMATION SCIENCES
Mariano Marcos State University
City of Batac 2906 Ilocos Norte**

August 2026

A 2D SIMULATION-BASED DECISION SUPPORT SYSTEM FOR FLOOD EVACUATION PLANNING

A Capstone Project Presented to the Faculty of College
of Computing and Information Sciences - Department of Information Technology

In Partial Fulfillment of the Requirements for the Degree
Bachelor of Science in Information Technology

By

JOHN HAROLD A. ALEJO
CYRUS KIRBY GAOR
BRADLEY KJIEL PASALO
JOSHEARIE KRISTOFFER LANDICHO

August 2026

APPROVAL SHEET

This capstone project titled, "**A 2D SIMULATION-BASED DECISION SUPPORT SYSTEM FOR FLOOD EVACUATION PLANNING**", prepared and submitted by JOHN HAROLD A. ALEJO, CYRUS KIRBY GAOR, BRADLEY KJIEL PASALO, JOSHEARIE KRISTOFFER LANDICHO in partial fulfillment of the requirements for the degree Bachelor of Science in Information Technology, has been examined and recommended for acceptance and approval for the oral examination.

ADVISER A. ADVISER
Adviser

PANEL OF EXAMINERS

Approved by the Committee on Oral Examination in partial fulfillment of the requirements for the degree Bachelor of Science in Information Technology on May 5, 2026.

PANEL A. ONE
Chairman

PANEL B. TWO
Member

PANEL C. THREE
Member

Accepted in partial fulfillment of the requirements for the degree of BACHELOR OF SCIENCE IN INFORMATION TECHNOLOGY.

Date

SATURNINA F. NISPEROS
Dean

ACKNOWLEDGMENT

The Researchers

ABSTRACT

Table of Contents

Title Page	i
Approval Sheet	ii
Acknowledgment	iii
Abstract	iv
Table of Contents	v
List of Figures	vii
List of Tables	viii
List of Algorithms	ix
1 Introduction	1
1.1 Project Context	1
1.2 Purpose and Description	3
1.3 Objectives of the Study	4
1.4 Significance of the Study	5
1.5 Scope and Delimitations of the Study	5
1.6 Operational Definition of Terms	6
2 Review of Related Literature	8
2.1 Introduction	8
2.2 Flood-Aware Road Accessibility and Geospatial Decision Support	9
2.3 Shelter Capacity and Population Allocation	14
2.4 Evacuation Simulation and Related Systems	21
2.5 Terrain Processing and Evacuation Behavior	28
2.6 Synthesis and Research Gap	30
3 Methodology	31
3.1 Research Design	31
3.2 Data Gathering Tools	31
3.3 Research Instruments	31
3.4 Data Gathering Procedures	31
3.5 Statistical Treatment of Data	31

4	Results and Discussion	32
4.1	System Development and Scenario-Analysis Results	32
4.2	System Evaluation Results	32
5	Conclusions and Recommendations	33
5.1	Conclusion	33
5.2	Recommendation	33
	References	34
	Appendices	38
	Appendix A Detailed Tables	39
	Appendix B Questionnaires	40

List of Figures

List of Tables

List of Algorithms

1 Introduction

Flooding can disrupt road access, increase evacuation demand, and constrain the use of evacuation centers. During a flood event, disaster planners and responders must determine which routes remain feasible, which centers can accommodate affected residents, and how available vehicles and other resources can be distributed. These decisions become more difficult when road conditions, shelter capacity, affected population, and resource availability change across possible flood situations.

Maps and geographic information can show locations, roads, and hazard areas, but static representations alone provide limited support for testing how changing conditions affect evacuation options. A scenario-based decision-support system can integrate relevant geographic and operational information so that planners can configure conditions, examine their consequences, and compare alternative evacuation plans before an event occurs.

This study develops *OverFlow*, a geospatial decision-support system for flood-evacuation planning. The system is intended to help authorized local disaster planners and responders configure and compare scenarios involving rainfall, affected population, road or bridge closures, evacuation-center status and capacity, and available resources. It provides decision-support information on flood-affected areas, feasible and alternative evacuation routes, center allocation, estimated evacuation time, and resource allocation. The system supplements, rather than replaces, the judgment and authority of disaster-management personnel.

1.1 Project Context

Flooding can change the conditions under which an evacuation plan must operate. Roads and bridges may become unavailable, the number of people requiring assistance may vary

between areas, evacuation centers may have limited capacity, and available vehicles and other resources may be insufficient for every possible situation. Local disaster planners must consider these conditions together when determining which routes remain usable, where affected residents can be accommodated, and what alternatives are available when an expected route or center cannot be used.

Maps can identify roads, boundaries, waterways, facilities, and hazard-related locations, but a map by itself does not show the consequences of changing several planning conditions at once. An evacuation plan may need to be reconsidered when rainfall conditions change, a road is manually closed, an evacuation center becomes unavailable or reaches capacity, the affected population increases, or fewer resources are available. Examining these conditions as configurable scenarios gives planners a structured way to compare possible evacuation arrangements before selecting or revising a plan.

This project develops *OverFlow*, a localized two-dimensional simulation-based decision-support system for flood evacuation planning. The system is intended for authorized local disaster planners and responders. It combines terrain, road, boundary, evacuation-center, population, and resource information in an interactive planning environment. Users configure rainfall intensity and duration, affected population, road or bridge closures, evacuation-center status and capacity, and available resources. The system then presents flood-affected conditions and analyzes feasible and alternative routes, center allocation, estimated evacuation time, and resource distribution for comparison with other scenarios.

The flood component uses a digital elevation model as its terrain input. D8 flow direction and flow accumulation represent how terrain directs and concentrates water, while a simplified rainfall overlay and threshold classify areas for scenario analysis. Drainage infrastructure may be displayed as a reference layer but is not included in the flood compu-

tation. The rainfall-to-indicator formula, classification threshold, and validation procedure still require final definition; therefore, the output must be treated as a relative scenario representation rather than a calibrated hydraulic result or exact flood forecast.

OverFlow is intended to supplement the planning process by organizing relevant conditions and showing how changes in those conditions affect evacuation options. It does not make autonomous emergency decisions, guarantee that a route will remain safe during an actual event, or replace the authority and judgment of disaster-management personnel. The final locality, geographic coverage, operating organization, accessible datasets, routing and allocation methods, and evaluation design remain subject to confirmation.

1.2 Purpose and Description

The purpose of this study is to develop *OverFlow*, a localized, scenario-based decision-support system for flood-evacuation planning. A planner configures rainfall intensity and duration, affected population by barangay, evacuation-center status, center capacity, manual road or bridge closures, and available resources. Using the geographic and terrain data for the selected study area, the system represents the resulting flood and evacuation conditions in an interactive two-dimensional planning environment.

For each scenario, the system identifies flood-affected areas and analyzes evacuation options under the configured constraints. It is intended to identify feasible and alternative routes, assign affected groups to available evacuation centers, estimate evacuation time, and present resource-allocation information. The planner can compare the results of different scenarios and use them as a reference in preparing or revising an evacuation plan.

The output is decision-support information, not an autonomous emergency decision or a guarantee of actual road safety. Results depend on the completeness, accuracy, resolution,

and currency of the underlying data, as well as on the selected scenario inputs. The simplified terrain-based flood computation is suitable for comparing relative conditions, but it does not model detailed hydraulic behavior, flow velocity, infiltration, or drainage pipes and canals.

1.3 Objectives of the Study

The general objective of this study is to develop and evaluate a localized two-dimensional simulation-based decision-support system for creating and comparing flood-evacuation planning scenarios.

Specifically, it aims to:

1. integrate validated local map, road, hazard, evacuation-center, population, and resource data for the selected study area;
2. represent flood-affected areas from DEM-based terrain accumulation using rainfall intensity and duration, together with road disruption, evacuation demand, center capacity, and resource availability;
3. analyze feasible evacuation routes, center allocation, estimated evacuation time, and resource distribution under configured scenario constraints;
4. present scenario results through an interactive two-dimensional map and comparison interface; and
5. evaluate the developed system using methods and metrics to be selected for the final study.

1.4 Significance of the Study

The study is intended to provide an interactive way of examining localized flood-evacuation scenarios. By showing flood-affected areas together with road accessibility, evacuation demand, center capacity, and resources, *OverFlow* may help users compare the consequences of alternative planning conditions before an emergency occurs.

For local disaster planners and responders, the system may provide a supplementary reference for preparing and revising evacuation plans. It can support the examination of feasible routes, alternate routes, center allocation, estimated evacuation time, and resource requirements under different scenario conditions. It does not replace existing disaster-management procedures or the judgment of authorized personnel.

For local engineering and planning personnel, barangay responders, and evacuation-center managers, the system may support coordination by presenting relevant geographic and capacity information in one planning environment. Community residents are intended indirect beneficiaries when better-informed preparedness and evacuation plans are developed. The study may also provide future researchers and developers with a reference for localized, terrain-based flood-evacuation decision-support systems.

1.5 Scope and Delimitations of the Study

This study covers the development of *OverFlow*, a localized two-dimensional flood-evacuation planning and decision-support system. It includes configurable scenario inputs for rainfall intensity and duration, affected population by barangay, evacuation-center status and capacity, manual road or bridge closures, and available rescue resources. The system uses DEM data to compute terrain-based flood-affected areas through D8 flow direction, flow accu-

mulation, rainfall overlay, and threshold-based classification. It represents roads, bridges, barangay boundaries, evacuation centers, population information, and resource conditions to support analysis and comparison of evacuation scenarios.

The system produces decision-support outputs that include flood-affected areas, recommended and alternative evacuation routes, center allocation, estimated evacuation time, resource-allocation information, dynamic maps, and scenario comparisons. Drainage infrastructure may be included only as a reference map layer. The final study area, deployment organization, and availability of local datasets remain subject to confirmation; the system's implemented coverage and features will be bounded by data that can be legitimately obtained and validated during the study.

The study excludes real-time flood forecasting, public navigation, emergency dispatch control, and direct control of physical infrastructure. It does not implement a calibrated hydraulic model and does not claim exact flood depth, velocity, or prediction of actual flood behavior. The model does not represent detailed hydraulic processes such as soil infiltration, drainage pipes and canals, or multi-directional flow spreading. Its outputs are intended for relative scenario comparison and human planning support, not as absolute emergency instructions.

1.6 Operational Definition of Terms

Affected Population. Refers to the number of people assigned to a barangay or area within a configured evacuation scenario.

D8 Flow Direction. Refers to a terrain-processing method that assigns each DEM cell a downhill flow direction toward its steepest neighboring cell among eight possible neighbors.

Decision-Support System. Refers to a system that helps a human decision-maker

evaluate options. In *OverFlow*, it presents processed information for examining flood-evacuation scenarios; it does not make autonomous emergency decisions.

Digital Elevation Model (DEM). Refers to a two-dimensional grid in which each cell stores ground elevation. It is the primary terrain input for the flood computation in *OverFlow*.

Drainage Infrastructure. Refers to pipes, canals, and other structures that collect or convey water. In *OverFlow*, available drainage information is a reference map layer and is not used to compute flooding.

Evacuation-Center Allocation. Refers to the assignment of affected groups to evacuation centers while considering accessibility and available capacity.

Evacuation Route. Refers to a road-network path considered usable between an affected area and an evacuation center under a scenario's constraints.

Flood Scenario. Refers to a configured set of conditions, including rainfall, affected population, road closures, center status and capacity, and available resources, used to examine a possible evacuation situation.

Flow Accumulation. Refers to a grid operation that counts or estimates the upstream area draining into a DEM cell, indicating locations where water may collect.

OverFlow. Refers to the proposed localized two-dimensional, simulation-based decision-support system for flood-evacuation planning developed in this study.

Terrain-Based Flood Computation. Refers to the simplified computation of flood-affected areas from rainfall input and DEM terrain data using D8 flow direction, flow accumulation, rainfall overlay, and threshold-based flood classification. It is not a hydraulic model.

2 Review of Related Literature

2.1 Introduction

This review examines the studies and systems that provide the main research and methodological foundations for a simulation-based decision support system for flood evacuation planning. The reviewed works address four connected concerns: the effect of flooding on road accessibility, the assignment of affected populations to evacuation centers, the simulation and comparison of evacuation scenarios, and the use of terrain and behavioral information in evacuation analysis. Recent studies from 2022 to 2026 are emphasized to reflect current geospatial and optimization approaches. Earlier works are retained where they establish a foundational method, document an influential related system, or provide locally relevant evidence that remains directly applicable to the study.

Taken together, the literature shows that flood evacuation planning is not adequately represented by a static map or a shortest route calculated under normal road conditions. A useful planning system must relate the flood condition to the road network, determine which destinations remain reachable, respect shelter capacity and other operational constraints, and allow planners to compare the consequences of different assumptions. These requirements correspond to the objectives of OverFlow: to integrate terrain, road, population, evacuation-center, and resource information; identify feasible routes and center allocations; and present alternative scenarios through an interactive geospatial interface.

2.2 Flood-Aware Road Accessibility and Geospatial Decision Support

Li et al. synthesized 211 publications and technical documents on urban flood evacuation, organizing the field around flood simulation, hazard assessment, shelter identification, route development, and the movement of pedestrians and vehicles [1]. Their comparison covered 23 experimental studies of instability in floodwater, 20 route-planning algorithms, and seven evacuee-movement models. The review found that metaheuristic algorithms are effective for complex evacuation routing and identified movement speed, evacuee psychology, multimodal evacuation, and overhead power-line hazards as areas requiring further investigation.

This synthesis provides a useful structure for evaluating the narrower studies in this review because it shows that routing, shelter choice, and movement assumptions depend on the preceding hazard assessment. It also cautions against treating any single algorithm as a complete evacuation plan. For OverFlow, the review supports a workflow in which the terrain-based hazard representation constrains the road network before routes and center allocations are compared. The breadth of Li et al.'s evidence does not validate OverFlow's specific D8 thresholds or local travel assumptions, which still require separate definition and testing.

Alabbad et al. developed a web-based decision support framework that evaluates road and bridge accessibility under multiple flood conditions and provides shortest-path, facility-allocation, and service-area analyses [2]. Its tests in Cedar Rapids and Charles City showed that inundation can disconnect parts of a road network, lengthen routes, and change which critical facility is nearest and reachable. The study is particularly relevant because it treats flood extent as an operational constraint on a graph rather than as a visual overlay alone.

It also demonstrates that flood-related network analysis can be delivered through a web interface to users who do not operate specialist GIS software.

The framework supports OverFlow's proposed integration of flood-affected areas with road routing and its use of an accessible map-based interface. Its scope, however, is centered on transportation accessibility and emergency-facility placement. It does not provide a complete evacuation-planning model that jointly accounts for affected populations, shelter capacities, available resources, and estimated evacuation time. Its use of prepared inundation maps and two Iowa case areas also means that its results cannot be transferred directly to a Philippine locality without locally appropriate terrain, road, and population data. OverFlow can adopt the study's flood-constrained graph principle while evaluating it within a localized planning workflow.

Suwanno et al. combined GIS-based flood susceptibility analysis with road-network analysis to identify suitable evacuation areas and routes in Nakhon Si Thammarat, Thailand [3]. Elevation, slope, land use, proximity to water, and other spatial criteria were used to locate flood-prone areas and assess evacuation alternatives under normal and flooded conditions. Because the case is situated in Southeast Asia, it provides a closer geographic and environmental comparison than studies based only in North America. It also confirms that the safety of a destination and the accessibility of its connecting route must be evaluated together.

The study offers strong support for using GIS layers to screen evacuation centers and calculate routes, but its result is principally a set of suitable areas and paths derived from the selected criteria and weights. Such an approach is valuable for preparedness, yet it provides limited support for repeated what-if comparisons involving road closures, changing demand, center status, and resource availability. For OverFlow, the study informs the selection and

spatial validation of routes and centers, while the proposed scenario mechanism extends the analysis by allowing planners to change operational conditions and compare the resulting plans.

Parajuli et al. similarly combined flood-susceptibility mapping with evacuation-route analysis in Siraha Municipality, Nepal [4]. They used a GIS-based Analytical Hierarchy Process to combine nine flood-conditioning factors, then applied closest-facility and service-area analyses to connect assembly points with shelters. Their route costs accounted for the effects of slope and flooding on pedestrian speed, while a flood map derived from 2019 synthetic-aperture-radar imagery was used to check the susceptibility result. The study classified approximately 48.6% of the municipality as flood susceptible, placed 22 candidate shelters in the safe zone, and found that 12 evacuation routes could be completed within 30 minutes. It also reported that 74.03% of the historically inundated area fell within zones classified as highly susceptible.

The study strengthens the methodological case for validating a hazard classification before using it to constrain evacuation routes. It also demonstrates that travel time can be more informative than distance when terrain and flood conditions reduce movement speed. However, its AHP result depends on expert-assigned criteria and secondary spatial data, and the authors identify damaged roads, collapsed bridges, changing flood depth, and different walking abilities as matters for further work. OverFlow can use the same general sequence of hazard screening followed by network analysis, but its D8-based classification and route estimates require separate local validation rather than adoption of the Nepalese criteria or reported travel times.

Bolanio et al. provide a Philippine example that joins evacuation-center assessment with web-based geospatial access [5]. In Las Nieves, Agusan del Norte, the researchers

used weighted overlay and multicriteria analysis to assess slope, elevation, land cover, road access, proximity to water and electrical sources, and proximity to fuel stations. They also evaluated 11 existing evacuation centers against a 100-year flood layer and developed a web mapping application for center status, spatial capacity, and other flood-related information. The suitability analysis classified 85.1% of the municipality as moderately suitable, 0.3% as highly suitable, and 14.6% as having low suitability. Ten existing centers were moderately suitable, while the Maningalao Evacuation Center was considered unsuitable because it was exposed to the modeled flood.

This case is relevant to OverFlow because it shows that a local-government web application can combine spatial suitability, center information, and flood exposure in a Philippine setting. It also supports checking existing centers rather than assuming that every listed facility is safe. Its weighted-overlay output, however, represents suitability under selected criteria and weights; it does not simulate population assignment, route congestion, or changes across repeated operational scenarios. OverFlow can extend this type of local geospatial inventory through scenario comparison, provided that center capacity, status, and flood exposure are confirmed from authoritative local data.

Abuzo et al. evaluated vulnerable routes in Cagayan de Oro City under normal and flood conditions by combining baseline road and traffic data, travel-condition and perception profiles, spatial analysis, and traffic-flow simulation [6]. Their comparison identified changes in road performance and produced maps and mitigation strategies for managing affected routes. One evaluated alternative route had floodwater affecting 60% of its links, illustrating how a route that exists in the ordinary network may lose much of its practical value during a flood.

This Philippine case strengthens the local basis for comparing a baseline road network

with a flood-constrained version instead of reporting a route without a reference condition. It also suggests that evaluation should cover network-wide effects and alternate-route vulnerability, not only whether one origin can still reach one destination. Because the results depend on Cagayan de Oro's road, flood, and travel conditions, they do not establish performance values for OverFlow. They instead support a methodology in which the system records which links become affected, recalculates accessibility, and presents the change between normal and configured flood scenarios.

Ogawa et al. designed a route-search method for dynamic inundation in Obihiro City, Japan, by modifying Dijkstra's algorithm with road weights based on distance from the present flooded area and the flood extent predicted ten minutes later [7]. Across different levee-breach and shelter conditions, the method directed evacuees farther from the expanding hazard and produced more successful simulated evacuations than the conventional route model. In one tested condition, the number of successful evacuees was 2.16 times that of the comparison model.

The study advances flood-aware routing beyond removing links already marked as flooded: future hazard movement also changes the cost of roads that remain open. This is relevant to OverFlow's scenario logic because a currently passable shortest path may lead toward an accumulating hazard. However, the reported improvement depends on a time-varying inundation model and the study's simulation assumptions. OverFlow's terrain-based accumulation cannot claim the same predictive horizon unless hazard progression is implemented and validated; its present contribution is to make hazard exposure visible and allow route results to change when the configured affected area changes.

Jeon et al. developed a map-API-based guidance system that combines predicted water levels, flood-risk extent, user location, shelter and terrain data, and pedestrian routing

through the T-Map application programming interface [8]. In a South Korean testbed near Yeojubo, the prototype identified the user's position, displayed warnings and the expected hazard area, calculated a route to a shelter, and canceled and recalculated that route when flooding affected the path or destination.

The prototype demonstrates a clear interaction pattern for an evacuation interface: the hazard state, current location, destination, and reason for rerouting should be visible together. This supports OverFlow's planned geospatial presentation and recalculation of feasible routes when roads or centers become unavailable. The study verifies that the prototype functions under its test conditions, but it does not provide field evidence that the guidance reduces casualties or remains reliable during an actual flood. OverFlow should likewise distinguish functional system evaluation from validation of hazard accuracy, route safety, and real-world evacuation outcomes.

2.3 Shelter Capacity and Population Allocation

Qiu et al. integrated a two-dimensional shallow-water model, entropy-weighted flood-risk assessment, multi-objective shelter selection, and agent-based evacuation simulation [9]. The model selected 26 shelters that covered the affected population in the study area. In the subsequent simulation, the evacuation rate rose from 97.4% to 98.4%, the modeled death rate fell from 1.94% to 0.98%, and casualties decreased by 133 compared with the original shelter arrangement.

The study strengthens the case for evaluating proposed shelter locations through a separate evacuation model rather than accepting an optimization result without testing. Its reported reductions are simulation outputs for one modeled urban flood and therefore cannot be interpreted as expected outcomes for OverFlow. The applicable methodological lesson

is to keep hazard assessment, allocation, and evaluation distinct: OverFlow should report whether its selected centers cover demand under the configured constraints and validate the resulting assignments against defined scenarios and local expert review.

Sharbaf et al. proposed a risk-based shelter-network design model that integrates population exposure, shelter risk, evacuation risk, pedestrian accessibility, and flood conditions in a single optimization framework [10]. Applied in Haiti, the model seeks to maximize coverage of vulnerable populations while reducing the risks associated with shelter locations and evacuation paths. Its contribution is the recognition that a nearby shelter is not automatically an appropriate assignment: both the facility and the route leading to it may be exposed to flooding. The study therefore provides a current basis for treating evacuation-center allocation as a constrained risk problem rather than a nearest-facility lookup.

This model directly supports OverFlow’s objective of assigning affected populations to accessible centers while respecting safety and capacity considerations. Nevertheless, Sharbaf et al. focus on strategic shelter-network design and pedestrian evacuation, whereas OverFlow is intended to help local planners test operational scenarios involving existing centers, road interruptions, and available resources. The difference suggests that OverFlow should not claim to reproduce the study’s optimization model unless the same objective function, constraints, and validation procedures are implemented. Instead, the study supplies criteria against which OverFlow’s allocation method can be defined and evaluated, including capacity satisfaction, population coverage, and route exposure.

Wang et al. examined pedestrian evacuation planning for a dam-break flood by assessing road difficulty, disaster risk, and pedestrian demand, then applying fuzzy VIKOR and a staged dual-objective planning method to route and shelter decisions [11]. Their Hurricane

Katrina-based New Orleans case identified high-risk roads near Lake Pontchartrain and selected 22 and 18 shelters from 34 candidates in two simulated planning scenarios. The alternative results reflect different trade-offs rather than a single solution that is best under every objective.

The study supports evaluating shelter assignments together with the risks and demand carried by their connecting roads. It also provides a reason for OverFlow to disclose competing measures such as coverage, route exposure, travel cost, and capacity instead of hiding them behind one score. Its dam-break representation, indicator weights, and New Orleans data are specific to the case, so the selected shelters and performance values cannot be transferred to the project. The usable contribution is the multi-criteria planning structure and the comparison of feasible alternatives under stated priorities.

De Veluz et al. developed a scenario-based, multi-objective location-routing model for pre-disaster planning in Quezon Province, Philippines [12]. The study represented 1,242 barangays and 11,868 road links under eight typhoon scenarios, used Project NOAH risk maps and consultation with the provincial disaster-risk office, and sought trade-offs among facility cost, travel time, and the number of vehicles. A multi-objective particle-swarm method generated alternative plans for distribution hubs, evacuation centers, facility capacities, routes, and vehicle requirements and was compared with other optimization approaches.

This work provides locally relevant evidence that evacuation-center placement, road routing, capacity, and logistics should be examined as one scenario-dependent planning problem. Its Pareto solutions also show why planners may need to choose among several defensible plans according to available facilities, vehicles, and acceptable travel time. The province-scale optimization requires risk, demand, capacity, cost, and fleet data that

OverFlow has not yet confirmed. Accordingly, the study guides the system's comparison measures and its presentation of trade-offs, while the project's actual allocation procedure must be limited to the local data and objectives established in the methodology.

Gama et al. formulated a multi-period shelter location-allocation model that determines when shelters should open, when evacuation orders should be issued, and how evacuees should be assigned as flood and road conditions change over time [13]. The model accounts for limited shelter capacities, time-dependent travel conditions, and the gradual availability of facilities. It is older than the preferred five-year review period, but it remains important because it connects the temporal development of a flood with capacity-constrained allocation and demonstrates why a single static assignment may be insufficient.

The authors also report that exact optimization becomes computationally demanding for realistic problem sizes and therefore use a simulated-annealing heuristic. This limitation is relevant to the design of OverFlow: a planning tool must return understandable results within a practical interaction time, even when an exact optimum is expensive to compute. The study supports scenario comparison and time-sensitive allocation, while also indicating that OverFlow must define its problem size, objective function, and acceptable solution time before describing any route or allocation as optimal.

Bera et al. integrated multi-hazard susceptibility mapping with shelter location-allocation for a mountainous community in the Western Ghats of India [14]. Random Forest models implemented through Google Earth Engine were used to map flood and landslide susceptibility, after which schools were treated as candidate shelters and households as demand points. A P-median model sought shelter arrangements that reduce household travel distance, while a maximal-covering model measured how many households could reach a shelter within specified time limits. When the framework recreated the conditions

of a destructive 2005 rainstorm, the existing shelters could not serve all households within either 30 or 60 minutes.

The result shows why shelter planning must consider both hazard exposure and the portion of the population that can actually reach a facility within an operational limit. It complements Sharbaf et al. by offering a GIS-oriented approach that is easier to interpret, although its single-objective location models simplify the competing demands that arise in an actual evacuation. For OverFlow, household or barangay demand, route accessibility, center capacity, and a stated travel-time cutoff should be evaluated together. The study does not establish that a P-median or maximal-covering formulation is automatically appropriate for the project; the chosen allocation rule must reflect available data and the decisions local planners need to make.

Rendana et al. mapped both flood risk and potential shelter suitability in Palembang, Indonesia, using an integrated GIS and Analytical Hierarchy Process approach [15]. Their criteria included elevation, population, slope, land cover, distance from rivers, drainage density, distance from roads and settlements, and soil type. The resulting flood-risk map classified 30.3% of the area as high risk, 60.5% as moderate risk, and 9.2% as low risk. The shelter-suitability assessment was more restrictive: only 4.1% of the area was highly suitable, while 19.4% was moderately suitable, 60.5% had low suitability, and 16.1% had very low suitability. The best locations were concentrated in higher northern and northwestern areas farther from the river.

These findings distinguish a low-risk location from a practically suitable shelter location: road access, proximity to settlements, terrain, and supporting conditions still affect whether the site can serve evacuees. This distinction is useful for OverFlow's separation of hazard screening from center allocation. Nevertheless, AHP-based suitability remains sensitive

to the chosen factors and weights, and an area-level suitability class does not confirm the condition, ownership, capacity, or availability of a specific building. Candidate centers in OverFlow should therefore be verified as facilities and treated as configurable resources rather than inferred solely from a suitability surface.

Yin et al. proposed a system-level method for citywide coastal-flood evacuation that gives specific attention to elderly residents with special needs [16]. Their comparison of Shanghai and New York City combined exposed population, evacuation zones, shelter locations and capacities, and origin-to-destination transfers. Shanghai exhibited a shelter-capacity shortfall of approximately 230,000 spaces for the modeled conditions, while the potential demand among vulnerable elderly residents was approximately 520,000. The authors found that risk-informed shelter deployment could meet this demand and improve transfer efficiency by a factor of three.

The study shows that aggregate evacuation planning can obscure the needs of residents who require additional time, assistance, or specialized transport. It also demonstrates that shelter sufficiency depends on spatial distribution and transfer feasibility rather than citywide capacity alone. OverFlow can reflect this principle by keeping affected-population groups, center capacities, and resource requirements visible in each scenario. However, the project cannot claim equivalent improvements without local demographic, mobility, capacity, and transport data, and its initial allocation method must state how vulnerable groups are represented.

Janatabadi and Ermagun combined coastal flood risk and emergency-shelter access in a national assessment of communities across 27 coastal states in the United States [17]. Their Flood-Access Integrated Risk approach used census block groups, road-network travel, shelter locations, flood-risk indicators, and bivariate spatial clustering. Of roughly 80,000

square miles classified as high flood risk, 98% had low shelter access, and 17.8 million people lived in the resulting priority areas. Racial and ethnic minorities, older adults, people with disabilities, and households with mobility constraints were disproportionately represented.

This evidence broadens shelter evaluation from capacity and distance to accessibility and equity. A route may be computationally feasible while remaining impractical for residents without private vehicles or with limited mobility. For OverFlow, the study supports reporting uncovered demand and access differences instead of presenting a single route set as equally usable by all residents. Its national indicators and 30-minute driving threshold are context-specific, so a Philippine deployment would require locally appropriate population categories, transport assumptions, and accessibility limits.

Chen et al. addressed shelter capacity through an urban-scale evacuation simulation and spatial optimization model [18]. They constructed an origin-destination cost matrix from population-demand points, available shelters, and the road network, then assigned evacuees while enforcing shelter capacities. Remaining evacuees who could not be accommodated were redistributed to nearby plots where new fixed or temporary shelter space could be developed. In their application, 680 of 2,334 demand points could not be completely evacuated through the existing arrangement, and only 218 of 888 fixed shelters remained below capacity. The optimization consequently recommended 487 additional fixed shelters and 360 temporary shelters across the analyzed districts.

Although the model is designed for general urban emergency-shelter planning rather than a specific flood event, it provides direct evidence that aggregate citywide capacity can conceal local service gaps. It also offers a useful method for recording unassigned demand instead of forcing every population group into an already full center. OverFlow

can adopt this transparency by reporting unmet demand, remaining center capacity, and alternative destinations for each scenario. The scale of Chen et al.’s recommendations is specific to their case, and their model does not establish the safety of routes under changing flood conditions, so capacity allocation in OverFlow must remain coupled with flood-aware network analysis.

2.4 Evacuation Simulation and Related Systems

Aketa et al. developed a GIS-based evacuation action analysis system that links flood analysis with network analysis for multiple evacuees and shelters [19]. The system simulates evacuation movement, considers walking speed, and searches routes across a road network to support route and shelter planning. Although published well outside the recent review window, it is retained as an early related system that demonstrates the feasibility of coupling flood conditions with network-based evacuation behavior in one geospatial environment.

Its age and brief reported evaluation limit its value as evidence for current web architecture or modern local-government deployment. More significantly, the system emphasizes route and shelter analysis but does not establish the broader scenario controls, resource-allocation outputs, or comparative planning interface proposed for OverFlow. Its relevance is therefore conceptual: it shows that flood and evacuation analyses should interact, while the present study must establish a current implementation and evaluate whether planners can use its combined outputs effectively.

Mizumura et al. tested a routing strategy called Evacuating Inundated Areas via the Shortest Possible Route, which first minimizes movement within the inundated area before directing an evacuee toward a shelter [20]. The authors linked time-series depths from a Rainfall–Runoff–Inundation model to an Artisoc multi-agent pedestrian simulation and

used A* search on an OpenStreetMap-derived road network in Kuki City, Japan. Across the tested rainfall and departure conditions, the method reduced distance traveled on flooded roads and increased travel on safer road segments compared with ordinary shortest-path routing.

The study demonstrates that minimizing total distance and minimizing exposure to floodwater are different routing objectives. The safer route could also increase total travel distance or time for some evacuees, so the method was not uniformly preferable under every condition. This trade-off is directly relevant to OverFlow: route comparisons should disclose distance, estimated time, and flood exposure rather than label the shortest path as inherently safest. Because Mizumura et al. used hydraulic depth estimates and a calibrated simulation environment, OverFlow must not imply the same safety precision from terrain-based accumulation alone.

The United States Army Corps of Engineers' LifeSim 2.0 is a more comprehensive related system for simulating population redistribution, warnings, evacuation traffic, flood exposure, and potential life loss [21]. Its agent-based model represents interactions among evacuees, roads, vehicles, and an advancing hazard; it can reroute groups when roads flood and uses repeated simulations to represent uncertainty. LifeSim demonstrates the analytical value of treating evacuation as a dynamic process and of comparing alternative warning, road, and hazard scenarios rather than relying on a single deterministic result.

LifeSim also clarifies the intended boundary of OverFlow. Reproducing an agent-based traffic and life-loss model would require behavioral, vehicle, warning, hazard-intensity, and validation data beyond the confirmed scope of the project. OverFlow can apply the more limited but relevant principle of configurable scenario comparison without presenting its terrain-based accumulation output as a calibrated hydraulic forecast or its planning estimates

as life-loss predictions. LifeSim therefore serves both as a design reference and as evidence for clearly documenting model assumptions and uncertainty.

González-Villa et al. presented an evacuation management system that combines a real-time GIS decision-support interface, damaged-area information, shelter and assembly-point routing, and stochastic pedestrian and vehicle models [22]. In a case based on the 2019 Gran Canaria wildfire, the system handled 13 urban areas and four simultaneous evacuations and satisfied the three operational requirements defined for the demonstration. Processing demand was influenced mainly by the number of evacuees and their interactions on roads rather than by the number of routes alone.

Although the case concerns wildfire rather than flooding, the system is relevant as an architectural comparison for coordinating scenario data, network analysis, simulation, and map-based decisions in one application. Its demonstration also indicates that an interactive tool must balance analytical detail with response time as the affected population grows. The evaluation was functional and simulation-based, and observed evacuation times were unavailable, so it does not establish real-world outcome accuracy. For OverFlow, it supports measuring usability and processing performance separately from the validity of flood and evacuation estimates.

Du et al. developed an integrated socio-hydrological framework that couples the MIKE 21 hydrodynamic model, an agent-based model, and the MATSim large-scale traffic simulator [23]. Applied to a simulated 100-year flood in China's Xiong'an New Area, the framework tested all 31 combinations of five possible shelters, different levels of variation in household preparation time, and both individual shortest-route and system-level optimized routing. The flood simulation inundated 66.5% of the study area and affected an estimated 508,986 residents. The experiments showed that shelter location and distribution

mattered more than simply increasing the number of shelters; after three suitably distributed shelters, additional sites produced only marginal reductions in average evacuation time.

The route experiment is especially relevant to the interpretation of OverFlow's outputs. System-level routing reduced modeled clearance time from 27.5 to 15.5 hours and reduced the share of agents on the road at the traffic peak from 60.4% to 43.1%, showing that individually shortest routes may collectively create congestion. The integrated framework is substantially more data- and computation-intensive than OverFlow's confirmed scope, and it does not enforce shelter capacity in the reported shelter experiment. It nevertheless supports comparing complete scenarios at the system level and cautions against labeling independent shortest paths as the best evacuation plan for the population as a whole.

Butters and Dawson adapted an agent-based flood-evacuation model for Kibera, Kenya, using open building, population, road, footpath, flood, and shelter data [24]. They compared shelter locations, river crossings, response conditions, and population samples through repeated simulations. Shelters in the northwestern, northern, and northeastern parts of the study area performed best, while a southern exit, bridge, and riverside path repeatedly developed congestion. The authors also found that a 1% population sample produced unstable estimates of agents at risk, whereas a 10% sample was more informative for the tested model.

This application shows that useful evacuation experiments can be assembled in a data-constrained settlement with open sources, which is relevant to the practical setting of OverFlow. At the same time, its sampling result and acknowledged data limitations show that accessible data do not automatically produce reliable estimates. OverFlow should therefore document the completeness and resolution of its population, road, terrain, and center inputs, repeat scenarios where stochastic variation is present, and avoid treating

uncalibrated model outputs as precise predictions of community behavior.

Yang et al. developed an agent-based Dynamic Coastal Flood Evacuation model that couples high-resolution inundation, human response, GIS transportation networks, infrastructure failure, and shelter systems [25]. In a Shanghai scenario based on a 1,000-year storm event, only 24.2% of the affected population evacuated within 24 hours without early warning. A 24-hour warning allowed the same number of people to evacuate within nine hours and kept approximately 28% from being overtaken by inundation, yet the overall success rate increased by only 11.2% because shelter capacity remained restrictive. Optimized decisions approximately doubled modeled evacuation efficiency.

These results show that advance warning alone cannot overcome inadequate destination capacity or unequal shelter distribution. They also show the analytical value of allowing hazard progression, road availability, behavior, and facility limits to interact during a scenario. OverFlow can use warning time, center status, road closures, and affected population as comparative planning inputs, but its confirmed terrain-based model is less detailed than the two-dimensional inundation model used by Yang et al. Consequently, OverFlow's results should be presented as scenario comparisons rather than forecasts of actual evacuation success.

Bustami et al. used AnyLogic to construct a micro-scale agent-based evacuation model for compound wind and storm-surge hazards in Westbrook, Connecticut [26]. Household and vehicle characteristics, survey-based evacuation behavior, shelter capacities, a GIS road network, surge-related road closures, and stochastic wind disruptions were combined in hurricane scenarios. Under the most demanding compound conditions, townwide clearance increased from approximately 6.3 hours in the baseline Category 3–4 scenario to nearly 19 hours, while failure exceeded 90% in several population groups. Adding one shelter in a

highly constrained block group reduced its modeled failure rate from 90.7% to 63.3% and its clearance time from 19.6 to 3.26 hours.

The results illustrate how interacting hazards and uneven local access can produce severe neighborhood differences that citywide averages conceal. They also show how simulation can test a specific intervention, such as adding a shelter, before resources are committed. This model uses detailed behavioral, demographic, hydraulic, infrastructure, and stochastic inputs beyond OverFlow's present scope, and its percentages are scenario outputs rather than transferable forecasts. For OverFlow, the methodological lesson is to compare interventions at both overall and local levels and to state which hazards and behaviors the model does and does not represent.

Santana-Robles et al. linked evacuation planning with post-disaster aid distribution in their study of the 2021 Tula River flood in Hidalgo, Mexico [27]. An integer-linear-programming model selected temporary shelters and evacuation assignments, while a vehicle-routing model evaluated the delivery of humanitarian supplies. Using road distances obtained from Google Maps, the researchers generated evacuation routes from 13 affected areas to 34 possible shelters and compared the original demand with scenarios in which demand increased or decreased by 10%. They also calculated aid-distribution costs under alternative collection strategies involving state and municipal authorities.

The study expands the meaning of evacuation planning beyond moving people to a destination: the selected centers must also be supportable after evacuees arrive. This is relevant to OverFlow's proposed resource-distribution output and its controls for changing population and resource availability. However, the model minimizes defined logistics costs and uses a case-specific transport structure; it does not simulate flood propagation or determine whether each road remains safe during travel. OverFlow should therefore present

resource allocation as a scenario-dependent planning estimate and explicitly document the objective, available units, center demand, and road constraints used to generate it.

Woo and Kang integrated shelter selection, private-car and bus evacuation, congestion-aware destination choice, and relief-supply routing in a bi-level optimization model [28]. Their Ulsan flood scenario used a dynamic virtual-link method for user-equilibrium traffic assignment and a metaheuristic evolutionary algorithm refined through shelter-addition, removal, and swap operations. Relative to manually selecting the nearest shelters, the optimized plan reduced total modeled cost by 9.4%. Ignoring congestion underestimated evacuation time by as much as 41%, while the local-search procedure improved cost efficiency by a further 7%.

This work shows that shelter placement, vehicle availability, traffic, and post-arrival supply cannot always be optimized independently. It is particularly relevant to residents who depend on public or designated transport, since the sensitivity analysis found that smaller bus fleets increased clearance time, workload, and required shelter capacity. The model nevertheless depends on detailed demand, traffic-capacity, fleet, cost, and logistics data that are not yet confirmed for OverFlow. Its appropriate contribution is to guide the project's scenario variables and evaluation measures rather than to justify implementing the complete bi-level model.

Insani et al. formulated an integrated vehicle-routing model for evacuating vulnerable residents and delivering relief supplies before floodwater reaches the affected area [29]. The model permits vehicle reuse, multiple trips, split deliveries, uncertain evacuation demand, and closing time windows. An exact solver and a modified genetic algorithm were evaluated through synthetic instances and a case study in Bontoala, Indonesia. The integrated approach required fewer vehicles than comparable separated operations, while

the genetic algorithm produced optimal or near-optimal solutions for smaller instances approximately 92.5% faster than the exact method and remained usable when the exact approach became impractical for larger cases.

The study supports considering evacuation and relief distribution as linked uses of limited vehicles and time. It also demonstrates why a practical decision-support system may need a well-evaluated heuristic when exact optimization cannot respond quickly enough. However, the model addresses the early stage before inundation reaches demand points and relies on assumptions about demand, time windows, and vehicle operation. OverFlow should adopt these concepts only if the required local data and objectives are confirmed; otherwise, it should report resource allocation as a bounded scenario estimate and retain unmet needs explicitly.

2.5 Terrain Processing and Evacuation Behavior

O’Callaghan and Mark introduced the method now commonly called D8, in which each cell in a digital elevation model directs flow toward its steepest downslope neighbor, allowing drainage direction and accumulated contributing area to be derived from gridded terrain [30]. This is a classic methodological source rather than a recent evacuation study, and it provides the foundation for OverFlow’s confirmed terrain-based accumulation approach. D8 offers a computationally straightforward way to identify likely flow paths and areas of accumulation from elevation data.

The method does not by itself calculate flood depth, velocity, drainage-system behavior, or the timing of inundation. Consequently, terrain-derived accumulation should be used in OverFlow to classify scenario-specific flood-affected areas according to an explicitly documented threshold and should not be described as a calibrated hydraulic model. This

distinction affects the methodology: the study must validate the digital elevation model, document preprocessing and threshold choices, and test how the resulting flood classification changes the set of usable road links.

Lim et al. examined the route choices of households affected by flooding in Bagong Silangan, Quezon City, using three binary logit models based on hazard, socioeconomic, and evacuation-related variables [31]. Their Philippine case shows that evacuees do not necessarily select routes solely by minimum distance; departure timing, familiarity, perceived conditions, and household characteristics can influence movement. The study provides local evidence that a mathematically shortest route and an actual human route are not always equivalent.

This finding is critical for interpreting OverFlow's outputs. A feasible or recommended path should be presented as a planning option derived from the available network and scenario constraints, not as a prediction of the route every resident will follow. The study also identifies a methodological opportunity for evaluation: proposed routes can be reviewed by local disaster personnel and, where data are available, compared with known routes, accessibility conditions, and community practices. Behavioral modeling may remain outside the initial implementation, but its absence should be stated as a limitation when evacuation-time estimates are interpreted.

Borowska-Stefańska et al. examined how self-evacuation from flood-hazard areas changes regional traffic conditions in Greater Poland [32]. They surveyed 500 residents about evacuation knowledge, transport choice, ability to self-evacuate, and mobility limitations, then incorporated the responses into six scenarios using a calibrated multimodal regional traffic model and the RoadLoad application. The scenarios represented different stages of planned and emergency self-evacuation, including road-management measures and

road sections made unavailable by flooding. This combination of household evidence and network simulation allowed the authors to compare flood evacuation traffic with ordinary regional travel.

The simulations found that self-evacuation substantially redistributed traffic across the road network, including areas beyond the immediate flood zone, while its effect on average speed was smaller because the modeled network retained spare capacity. Delayed and spontaneous evacuation produced the most difficult conditions, and the authors emphasized staged evacuation and current route information as planning measures. These findings reinforce Lim et al.'s evidence that evacuation movement depends on behavior and context rather than geometric distance alone. For OverFlow, manual closures and demand changes can support useful pre-event comparisons, but reliable congestion or clearance-time claims would require locally calibrated traffic demand, departure behavior, vehicle availability, and road-capacity data.

2.6 Synthesis and Research Gap

3 Methodology

3.1 Research Design

3.2 Data Gathering Tools

3.3 Research Instruments

3.4 Data Gathering Procedures

3.5 Statistical Treatment of Data

4 Results and Discussion

4.1 System Development and Scenario-Analysis Results

4.2 System Evaluation Results

5 Conclusions and Recommendations

5.1 Conclusion

5.2 Recommendation

References

- [1] Chuannan Li et al. “An Overview of Flood Evacuation Planning: Models, Methods, and Future Directions”. In: *Journal of Hydrology* 656 (2025), p. 133026. DOI: 10.1016/j.jhydrol.2025.133026.
- [2] Yazeed Alabbad et al. “A Web-Based Decision Support Framework for Optimizing Road Network Accessibility and Emergency Facility Allocation During Flooding”. In: *Urban Informatics* 3.1 (2024), p. 10. DOI: 10.1007/s44212-024-00040-0.
- [3] Piyapong Suwanno et al. “GIS-Based Identification and Analysis of Suitable Evacuation Areas and Routes in Flood-Prone Zones of Nakhon Si Thammarat Municipality”. In: *IATSS Research* 47.3 (2023), pp. 416–431. DOI: 10.1016/j.iatssr.2023.08.004.
- [4] Gaurav Parajuli et al. “A GIS-Based Evacuation Route Planning in Flood-Susceptible Area of Siraha Municipality, Nepal”. In: *ISPRS International Journal of Geo-Information* 12.7 (2023), p. 286. DOI: 10.3390/ijgi12070286.
- [5] K. P. Bolanio et al. “Mapping and Assessment of Flood Evacuation Sites in a Geospatial Environment: A Case in Las Nieves, Agusan del Norte, Philippines”. In: *The International Archives of the Photogrammetry, Remote Sensing and Spatial Information Sciences* XLVIII-4/W6-2022 (2023), pp. 473–482. DOI: 10.5194/isprs-archives-XLVIII-4-W6-2022-473-2023.
- [6] Anabel Abuzo et al. “Evaluation of Vulnerable Routes and Simulation Under Normal and Flood Conditions in Cagayan De Oro City, Philippines”. In: *Journal of the Eastern Asia Society for Transportation Studies* 15 (2024), pp. 1805–1823. DOI: 10.11175/easts.15.1805.
- [7] Kohei Ogawa et al. “A Route Search System to Avoid the Danger to Life in Dynamic Inundation”. In: *Water* 15.7 (2023), p. 1417. DOI: 10.3390/w15071417.
- [8] Sungwoo Jeon et al. “Map API-Based Evacuation Route Guidance System for Floods”. In: *Applied Sciences* 13.16 (2023), p. 9141. DOI: 10.3390/app13169141.
- [9] Jiale Qiu et al. “Selection of Urban-Flood-Shelter Locations Based on Risk Assessment”. In: *Water-Energy Nexus* 7 (2024), pp. 151–162. DOI: 10.1016/j.wen.2024.04.003.
- [10] Maedeh Sharbaf et al. “Risk-Based Shelter Network Design in Flood-Prone Areas: An Application to Haiti”. In: *Omega* 131 (2025), p. 103194. DOI: 10.1016/j.omega.2024.103194.

- [11] Wei Wang et al. “Pedestrian Evacuation Planning Under Dam-Break Flood Disaster Considering Road Risk and Road Pedestrian Demand”. In: *International Journal of Disaster Risk Reduction* 104 (2024), p. 104355. doi: 10.1016/j.ijdr.2024.104355.
- [12] Maria Rossana D. de Veluz et al. “Scenario-Based Multi-Objective Location-Routing Model for Pre-Disaster Planning: A Philippine Case Study”. In: *Sustainability* 15.6 (2023), p. 4882. doi: 10.3390/su15064882.
- [13] Melissa Gama, Bruno Filipe Santos, and Maria Paola Scaparra. “A Multi-Period Shelter Location-Allocation Model with Evacuation Orders for Flood Disasters”. In: *EURO Journal on Computational Optimization* 4.3–4 (2016), pp. 299–323. doi: 10.1007/s13675-015-0058-3.
- [14] Somnath Bera et al. “Assessment of Shelter Location-Allocation for Multi-Hazard Emergency Evacuation”. In: *International Journal of Disaster Risk Reduction* 84 (2023), p. 103435. doi: 10.1016/j.ijdr.2022.103435.
- [15] Muhammad Rendana et al. “Flood Risk and Shelter Suitability Mapping Using Geospatial Technique for Sustainable Urban Flood Management: A Case Study in Palembang City, South Sumatera, Indonesia”. In: *Geology, Ecology, and Landscapes* 9.2 (2025), pp. 452–462. doi: 10.1080/24749508.2023.2205717.
- [16] Jie Yin et al. “Strategic Storm Flood Evacuation Planning for Large Coastal Cities Enables More Effective Transfer of Elderly Populations”. In: *Nature Water* 2.3 (2024), pp. 274–284. doi: 10.1038/s44221-024-00210-z.
- [17] Fatemeh Janatabadi and Alireza Ermagun. “Limited Shelter Access Exacerbates Coastal Flood Risks for Vulnerable Communities”. In: *Applied Geography* 181 (2025), p. 103686. doi: 10.1016/j.apgeog.2025.103686.
- [18] Wei Chen et al. “The Spatial Optimization of Emergency Shelters Based on an Urban-Scale Evacuation Simulation”. In: *Applied Sciences* 11.24 (2021), p. 11909. doi: 10.3390/app112411909.
- [19] Osamu Aketa, Takafumi Amano, and Hirotake Uchida. “Development of the GIS-Based Evacuation Action Analysis System Against Flood Disasters”. In: *Theory and Applications of GIS* 15.1 (2007), pp. 23–28. doi: 10.5638/thagis.15.23.
- [20] Takuyou Mizumura, Hiroyuki Taguchi, and Hitoshi Nakamura. “Confirming the Safety Improvement and Evacuation Time Reduction Effects by the Method for Evacuating Inundated Areas via the Shortest Possible Route”. In: *International Journal of Disaster Risk Reduction* 101 (2024), p. 104252. doi: 10.1016/j.ijdr.2024.104252.

- [21] U.S. Army Corps of Engineers, Risk Management Center. *LifeSim 2.0 Technical Reference Manual*. LifeSimCPD-97a. U.S. Army Corps of Engineers, Institute for Water Resources. Aug. 2021. URL: <https://iwrlibrary.sec.usace.army.mil/resource/c1dae7c1-c83f-4e9d-82e9-f311fa67f2ef> (visited on 09/23/2026).
- [22] Javier González-Villa et al. “Evacuation Management System for Major Disasters”. In: *Applied Sciences* 12.15 (2022), p. 7876. doi: 10.3390/app12157876.
- [23] Enyan Du et al. “Development of an Integrated Socio-Hydrological Modeling Framework for Assessing the Impacts of Shelter Location Arrangement and Human Behaviors on Flood Evacuation Processes”. In: *Hydrology and Earth System Sciences* 27.8 (2023), pp. 1607–1626. doi: 10.5194/hess-27-1607-2023.
- [24] Olivia Butters and Richard J. Dawson. “Flood Evacuation in Informal Settlements: Application of an Agent-Based Model to Kibera Using Open Data”. In: *Urban Science* 9.1 (2025), p. 12. doi: 10.3390/urbansci9010012.
- [25] Yuhan Yang et al. “Dynamic Flood Evacuation Modelling for Coastal Cities: A Case Study of Shanghai”. In: *International Journal of Disaster Risk Reduction* 125 (2025), p. 105591. doi: 10.1016/j.ijdrr.2025.105591.
- [26] Omar Bustami et al. “Micro-Scale Agent-Based Modeling of Hurricane Evacuation Under Compound Wind–Surge Hazards: A Case Study of Westbrook, Connecticut”. In: *Sustainability* 18.7 (2026), p. 3182. doi: 10.3390/su18073182.
- [27] Francisca Santana-Robles et al. “Quick-Response Model for Pre- and Post-Disaster Evacuation and Aid Distribution: The Case of the Tula River Flood Event”. In: *Logistics* 8.1 (2024), p. 8. doi: 10.3390/logistics8010008.
- [28] Seong-Jong Woo and Seungmo Kang. “Optimising Shelter Locations for Bus Evacuation and Relief Supply Under Traffic Congestion”. In: *IET Intelligent Transport Systems* 19.1 (2025), e70020. doi: 10.1049/itr2.70020.
- [29] Nur Insani, Sona Taheri, and Mali Abdollahian. “A Mathematical Model for Integrated Disaster Relief Operations in Early-Stage Flood Scenarios”. In: *Mathematics* 12.13 (2024), p. 1978. doi: 10.3390/math12131978.
- [30] John F. O’Callaghan and David M. Mark. “The Extraction of Drainage Networks from Digital Elevation Data”. In: *Computer Vision, Graphics, and Image Processing* 28.3 (1984), pp. 323–344. doi: 10.1016/S0734-189X(84)80011-0.
- [31] Hector R. Lim Jr., Ma. Bernadeth B. Lim, and Mongkut Piantanakulchai. “Modeling Route Choice Behavior of Evacuees in Highly Urbanized Area: A Case Study of Bagong Silangan, Quezon City, Philippines”. In: *Asia Pacific Management Review* 24.2 (2019), pp. 98–105. doi: 10.1016/j.apmr.2017.03.004.

- [32] Marta Borowska-Stefańska et al. “The Impact of Self-Evacuation from Flood Hazard Areas on the Equilibrium of the Road Transport”. In: *Safety Science* 157 (2023), p. 105934. doi: 10.1016/j.ssci.2022.105934.

APPENDICES

A Detailed Tables

B Questionnaires