MINDASSESS: A Clinical-Grade Mental Health Assessment and Monitoring Platform Using MERN Stack Architecture

Milan Harsh 22EAICS177
Kavya Bhavsar 22EAICS142
Department of Computer Science Engineering
Arya College of Engineering, Jaipur

***Abstract*—The increasing prevalence of mental health disorders has created an urgent need for accessible, scalable, and clinically reliable digital assessment systems. Existing platforms often lack standardized evaluation methodologies, structured scoring mechanisms, and longitudinal monitoring capabilities. This paper presents MINDASSESS, a full-stack mental health assessment and monitoring platform designed to provide clinically grounded screening using validated psychological instruments.**

MINDASSESS is implemented using the MERN stack architecture (MongoDB, Express.js, React.js, and Node.js) and follows a Single Page Application (SPA) paradigm for enhanced responsiveness. The system integrates adaptive assessment using validated tools including PHQ-9, GAD-7, and ASRS v1.1, mapped across five core clinical categories. A linear weighting model is applied to quantify psychological burden and generate interpretable insights.

The platform incorporates JWT-based authentication, modular RESTful APIs, and real-time dashboard visualization. Performance evaluation demonstrates efficient API response times and scalability under concurrent conditions. The proposed system provides a robust foundation for future integration of AI-driven recommendations and large-scale cloud deployment.

Index Terms—Mental Health Assessment, MERN Stack, PHQ-9, GAD-7, ASRS, Single Page Application, JWT

I. Introduction

Mental health disorders have become a significant global concern, affecting individuals across all demographics. The World Health Organization estimates that a substantial portion of the population experiences anxiety, depression, or related psychological conditions. Despite this, access to structured and reliable mental health assessment remains limited.

Existing digital mental health platforms often provide either informational resources or basic self-assessment tools without standardized scoring frameworks. These limitations hinder accurate evaluation and long-term monitoring.

To address these challenges, this paper introduces MINDASSESS, a clinical-grade mental health assessment platform built using the MERN stack. The system integrates validated psychological screening tools, adaptive questionnaires, and a scalable full-stack architecture to deliver reliable and accessible mental health evaluation.

The key contributions of this work include:

- Integration of clinically validated screening tools (PHQ-9, GAD-7, ASRS v1.1)
- Development of an adaptive assessment engine using weighted scoring
- Implementation of scalable MERN-based architecture
- Secure authentication and protected routing using JWT

II. Literature Review and Gap Analysis

Digital mental health solutions can be categorized into self-assessment tools, therapy platforms, and informational systems. While these systems provide value, they exhibit several limitations.

Self-assessment tools often lack clinical validation and structured scoring mechanisms. Therapy platforms focus on professional consultation but do not offer automated preliminary screening. Informational platforms emphasize awareness but lack diagnostic capabilities.

These systems fail to provide:

- Clinically validated assessment models
- Quantitative scoring frameworks
- Continuous monitoring and analytics

MINDASSESS addresses these gaps by integrating validated screening instruments with a scalable full-stack architecture and real-time analytics.

III. System Architecture

The proposed MINDASSESS platform is designed as a modular, full-stack web-based clinical assessment system that integrates frontend presentation, backend logic, NoSQL data storage, JWT-based authentication, and longitudinal monitoring mechanisms into a unified healthcare framework. The architecture follows a layered design model to ensure scalability, clinical data integrity, and secure role-based interaction.

A. Overall Architectural Design

MINDASSESS adopts a three-tier architecture consisting of a presentation layer, application layer, and data layer. The presentation layer is implemented using React.js and follows the Single Page Application (SPA) paradigm, enabling dynamic component rendering for a seamless user experience during assessments. The application layer is developed using Node.js with the Express.js framework, exposing RESTful APIs for communication between the client and server. The data layer is

powered by MongoDB, a document-oriented NoSQL database that supports flexible schema representation for heterogeneous clinical assessment data.

User requests initiated through the frontend are transmitted to the backend via HTTP requests. The backend processes the clinical scoring logic, validates authentication tokens, interacts with the database, and returns structured JSON responses. The integration of stateless REST APIs ensures horizontal scalability and modular expansion as the user base grows.



Fig. 1. General MINDASSESS System Architecture

B. MERN Stack Justification

The selection of the MERN stack (MongoDB, Express.js, React.js, and Node.js) provides architectural coherence through a unified JavaScript-based ecosystem. This consistency reduces development complexity and enhances maintainability across system components.

Node.js enables non-blocking, event-driven server execution, allowing efficient handling of concurrent user requests during peak usage. Express.js simplifies middleware integration, routing, and modular API construction. React.js supports component-based interface design, improving user accessibility and enabling real-time feedback during psychological screening. MongoDB offers the schema flexibility required for representing diverse clinical structures ranging from simple PHQ-9 Likert scales to complex longitudinal behavioral metrics. The unified stack ensures seamless data exchange in JSON format, minimizing transformation overhead and improving system efficiency.

C. Database Design and Schema Flexibility

A key architectural requirement of MINDASSESS is the ability to represent heterogeneous assessment levels within a single database system. Unlike relational databases requiring rigid schema definitions, MongoDB supports document-based storage, enabling dynamic field adaptation for various mental health instruments.

For example, depression-level screening (PHQ-9) may include frequency-based metadata, whereas ADHD assessments (ASRS) require specific symptom-frequency mapping and functional impact metrics. The document-oriented model allows flexible embedding of such varied attributes without schema restructuring. Collections within the database are organized into



Fig. 2. MERN Stack Architecture for Mental Health Data Handling

primary entities including *Users*, *Assessments*, *Responses*, and *Clinical Records*. Relationships are managed using reference identifiers and indexed fields to optimize query performance.

D. RESTful API Architecture

The backend exposes categorized REST endpoints structured around modular resource handling. Major API groups include:

- **Authentication APIs:** Handles secure login, registration, and JWT token validation.
- **Assessment Engine APIs:** Manages question delivery and multi-dimensional response submission.
- **Scoring and Analytics APIs:** Processes raw data through the linear weighting algorithm to generate clinical insights.
- **Administrative Control APIs:** Allows authorized management of assessment parameters and user data logs.

Each request is processed in a stateless manner, with JSON Web Tokens attached in headers to validate session identity. This design supports scalability and enables potential horizontal deployment across distributed servers.

E. Integrated System Modules

Beyond core CRUD operations, the architecture integrates specialized modules:

- **Assessment Engine Module:** Dynamically renders validated psychological tools (PHQ-9, GAD-7) based on user progress.
- **Role-Based Access Control (RBAC):** Restricts sensitive health data access based on user roles (User, Clinician, Administrator).
- **Visualization Module:** Converts raw assessment scores into longitudinal trend charts for user self-monitoring.
- **Security Module:** Handles data encryption and secure session persistence using JWT.

The modular structure ensures that each component operates independently while maintaining coordinated interaction through the centralized API layer.

IV. Clinical Assessment Model

A. Standardized Psychological Instruments

The assessment framework is based on validated clinical screening tools including the PHQ-9 for depression [1], GAD-7

for anxiety [2], and ASRS v1.1 for adult ADHD [3]. The system utilizes a curated set of 15 adaptive questions derived from these instruments to maintain clinical reliability while reducing respondent fatigue.

B. Clinical Categories and Dimensions

MINDASSESS evaluates the user across five distinct domains. Table I illustrates the mapping of these clinical categories to their specific psychological dimensions.

TABLE I
CLINICAL CATEGORIES AND EVALUATED DIMENSIONS

Clinical Category	Evaluation Dimensions
Anxiety Markers	Persistent worry, irritability, and physiological symptoms of restlessness.
Depression Markers	Anhedonia, sleep disturbances, and persistent low mood or fatigue.
Focus and ADHD	Executive dysfunction, difficulty in task completion, and attention span.
Trauma and Stress	Emotional reactivity and psychological burden from external stressors.
Functional Impact	Impairment in social, occupational, or daily life activities.

C. Weighting Algorithm

A linear weighting matrix is applied to quantify user responses. Each response option is assigned a numeric value w representing the psychological load:

- Strongly Agree: +2 (High Symptom Presence)
- Agree: +1 (Moderate Symptom Presence)
- Disagree: −1 (Low Symptom Presence)
- Strongly Disagree: −2 (Negligible Symptom Presence)

D. Score Computation and Severity Mapping

The Global Psychological Index (GPI) is calculated by aggregating the weights of all 15 responses ($n = 15$). The mathematical expression for the total score S is:

$$S = \sum_{i=1}^{n} w_i$$

where $w_i \in \{-2, -1, 1, 2\}$. The resulting score ranges from a minimum of −30 to a maximum of +30.

1) Case Study: Representative Assessment: To demonstrate the scoring logic, consider a user responding to a three-question subset:

1) **Question (Anxiety):** "I feel overwhelmed by daily tasks." → *User selects "Strongly Agree"* (+2)
2) **Question (Focus):** "I find it hard to concentrate on one thing." → *User selects "Agree"* (+1)
3) **Question (Impact):** "I feel energetic and productive today." → *User selects "Strongly Disagree"* (+2)*

**Note: For positive-framed questions, the system applies inverse scoring to maintain burden consistency.*

Summing these individual weights generates a cumulative score. In a full 15-question test, if a user finishes with a total score of +18, the system maps this to the "Moderate-to-High Severity" range.

2) Severity Thresholds: The system categorizes the GPI into four actionable tiers:

- **-30 to -10 (Resilient):** Indicates stable mental health with minimal symptom presence.
- **-9 to +5 (Mild/Sub-clinical):** Normal range with occasional stressors.
- **+6 to +20 (Moderate):** Presence of significant clinical markers; monitoring recommended.
- **+21 to +30 (Severe):** High clinical load; urgent professional consultation advised.

V. IMPLEMENTATION MODULES

This section describes the functional realization of MINDASSESS through its major operational modules. While the previous section presented architectural design principles, the following subsections detail how key system components are implemented to enable clinical screening, practitioner-led monitoring, and secure access control.

A. Practitioner and Clinical Supervision Module

A core innovation of MINDASSESS is the integration of a clinical supervision framework within a structured self-assessment environment. Unlike basic screening tools, MINDASSESS enables qualified mental health practitioners to apply for professional status and oversee anonymized patient trends under administrative supervision.

The practitioner onboarding process follows a multi-step workflow:

1) Practitioner submits application with clinical credentials and license details.
2) Administrator reviews and verifies the professional background.
3) Approved practitioners gain role-based access to the monitoring dashboard.
4) Practitioners define custom threshold alerts for specific patient demographics.
5) Assessment data undergoes periodic validation to ensure clinical relevance.

This hybrid structure preserves strict quality control while maintaining the flexibility of a scalable digital health platform.

B. Assessment and Report Generation Workflow

MINDASSESS integrates a structured diagnostic subsystem to manage the assessment lifecycle and generate detailed clinical reports. The workflow is designed to ensure data integrity and automated profile updates.

The assessment process proceeds as follows:

1) User selects a screening module based on symptoms (e.g., Anxiety, ADHD).
2) The adaptive assessment engine presents clinically validated questions.
3) Responses are processed via the backend scoring algorithm in real-time.
4) Upon completion, a comprehensive PDF-based clinical report is generated.

5) Longitudinal monitoring records are updated to track progress over time.

Assessment data is stored within a dedicated NoSQL collection linking user identifiers, test timestamps, and weighted scores. This structure supports historical trend analysis, risk detection, and audit tracking for clinical accuracy.

C. Role-Based Access Control (RBAC)

To ensure secure and structured interaction with sensitive health data, MINDASSESS implements Role-Based Access Control (RBAC) using JSON Web Tokens (JWT). Users are assigned one of three primary roles: *Standard User*, *Clinical Practitioner*, and *Administrator*.



Fig. 3. JWT Authentication and Authorization Flow

Upon successful authentication, the backend generates a signed JWT containing encoded role information and expiration metadata. This token is attached to subsequent API requests through authorization headers. Middleware functions validate the token signature and verify specific role permissions before granting access to protected clinical endpoints. For example:

- Only **Practitioners** can access aggregate patient trend data.
- Only **Administrators** can modify the weighting constants of assessment tools.
- **Standard Users** can access their own reports but cannot view others' sensitive data.

D. Clinical Lifecycle and Adaptive Rendering

The platform organizes psychological assessments according to severity levels and specific diagnostic categories. The SPA frontend dynamically renders assessment components based on metadata retrieved from the backend.

This dynamic rendering allows consistent interface logic across varying instruments (PHQ-9 vs GAD-7) while adapting content structure appropriately to the user's emotional state (e.g., simplified UI for high-anxiety scores). The modular implementation ensures that additional clinical scales or AI-driven diagnostic tracks can be incorporated without architectural restructuring.

VI. Performance Evaluation

To validate the architectural efficiency and clinical reliability of MINDASSESS, controlled performance evaluation experiments were conducted under simulated concurrent usage conditions. The primary objective was to measure API responsiveness, database latency, and frontend rendering efficiency within the MERN-based framework, specifically focusing on the diagnostic assessment engine's stability.

A. Experimental Setup

The system was deployed on a local development environment to establish a performance baseline with the following configuration:

- **Processor:** Quad-Core CPU (2.4 GHz)
- **RAM:** 8 GB DDR4
- **Backend Runtime:** Node.js v18.x
- **Database:** MongoDB Community Edition
- **Frontend:** React.js (Vite-based SPA architecture)

Concurrent user requests were simulated using automated API testing tools to evaluate backend response consistency and database throughput during active assessment sessions.

B. API Response Performance and Metrics

API performance was measured across core functional endpoints including user authentication, adaptive question retrieval, clinical score calculation, and PDF report generation. Average response times were calculated over repeated requests under concurrent load conditions to ensure clinical utility.

TABLE II
Performance Metrics Under Simulated Load

Metric	Observed Value
Average API Response Time	120–180 ms
Database Query Latency	25–45 ms
Concurrent Assessment Sessions	150+ Users
Initial Dashboard Load Time	1.1–1.4 s
Clinical Score Computation	< 50 ms
PDF Report Generation Time	400–650 ms

The results indicate that the event-driven Node.js backend efficiently handles asynchronous diagnostic requests without blocking execution threads. MongoDB indexing significantly optimized query retrieval for frequently accessed collections.

C. SPA Responsiveness and User Experience

The Single Page Application (SPA) design significantly improves the user experience, which is vital when dealing with individuals in psychological distress. Unlike traditional multi-page applications, the React-based frontend dynamically updates only relevant components. While the initial page load incurs a minor cost due to bundled assets, subsequent navigation occurs with minimal latency. This architectural choice reduces bandwidth usage and improves perceived responsiveness, ensuring engagement throughout the clinical evaluation.

VII. Comparative Feature Analysis

To evaluate the positioning of MINDASSESS within the existing Digital Mental Health (mHealth) ecosystem, a structured feature-based comparison was conducted against representative self-screening applications and traditional clinical institutional

platforms. The analysis focuses on diagnostic continuity, practitioner oversight, clinical validation, and architectural scalability.

The comparative results highlight a distinct architectural gap. Consumer-facing self-screening platforms often prioritize accessibility but frequently lack clinically validated instruments and longitudinal monitoring. Conversely, traditional clinical institutional systems offer professional credibility but remain largely inaccessible for preliminary screening and lack real-time feedback.

MINDASSESS differentiates itself by bridging these domains into a unified diagnostic lifecycle. By combining clinically validated instruments (PHQ-9, GAD-7, and ASRS), decentralized practitioner participation, and a scalable MERN-based full-stack architecture, the platform provides a comprehensive screening framework. This hybrid integration establishes MINDASSESS as a clinical-grade monitoring system rather than a standalone assessment tool.

VIII. Discussion

The development of MINDASSESS demonstrates the feasibility of integrating a clinically grounded diagnostic lifecycle within a unified full-stack web architecture. The system successfully combines decentralized practitioner oversight, standardized clinical governance, and a scalable API-driven design within a single modular framework. The MERN-based implementation ensures architectural consistency, flexible data modeling for varied psychological instruments, and efficient client-server interaction.

One of the primary strengths of the proposed system lies in its document-oriented database design. By leveraging MongoDB's schema flexibility, the platform accommodates heterogeneous clinical structures ranging from simple frequency-based Likert scales (PHQ-9) to multi-dimensional adult ADHD metrics (ASRS). This adaptability would be significantly more complex within rigid relational schemas, which often struggle with the sparse and varied nature of psychological data. Additionally, the stateless REST architecture combined with JWT-based authentication enables secure, scalable session handling and simplifies horizontal deployment strategies, which is paramount when handling sensitive protected health information (PHI).

The integration of a governed practitioner module represents another architectural advantage. Unlike purely self-help applications that lack professional accountability, MINDASSESS incorporates administrative validation within the practitioner onboarding workflow. This hybrid model balances user autonomy with structured professional oversight, supporting both widespread accessibility and clinical integrity.

Despite these strengths, certain limitations remain. The current performance evaluation was conducted in a controlled local deployment environment, and large-scale cloud-native testing has not yet been performed. While the architecture is designed to support horizontal scaling, real-world performance under thousands of concurrent assessment sessions would require distributed infrastructure and advanced load-balancing mechanisms. Furthermore, the accuracy of long-term monitoring depends on sustained user engagement beyond the initial technical interface.

Another notable limitation involves the absence of integrated artificial intelligence-based recommendation systems. Although the modular design allows for future integration of adaptive learning analytics, the present implementation focuses primarily on architectural unification and standardized scoring rather than personalized predictive algorithms. Overall, while MINDASSESS successfully addresses diagnostic fragmentation at the architectural level, further expansion into cloud scalability, AI-driven sentiment analysis, and cross-platform mobile support would significantly strengthen its real-world clinical applicability.

IX. Conclusion and Future Work

This paper presented MINDASSESS, a unified clinical-grade mental health assessment and monitoring platform designed to address structural fragmentation within the current digital health ecosystem. Existing platforms typically operate in isolation, focusing either on unregulated self-screening or high-barrier institutional management. This segmentation limits diagnostic continuity and hinders longitudinal monitoring for the general population.

To address these limitations, MINDASSESS was developed using a modular MERN stack architecture, integrating a React-based frontend, Node.js API services, and a flexible MongoDB data layer. The system supports a comprehensive diagnostic lifecycle by incorporating validated clinical instruments (PHQ-9, GAD-7, ASRS), a governed practitioner oversight module, and secure Role-Based Access Control (RBAC) using JWT-based authentication.

Performance evaluation demonstrated stable API responsiveness, efficient clinical score computation, and reliable PDF report generation under simulated concurrent conditions. The stateless RESTful design and schema flexibility further validate the system's potential for large-scale healthcare deployment. Comparative analysis confirmed that the proposed architecture uniquely integrates clinical validation, professional governance, and architectural scalability within a single unified platform.

While the current implementation establishes architectural feasibility, several opportunities exist for future enhancement:

- **AI-Driven Insights:** Integration of artificial intelligence and machine learning recommendation engines to support predictive diagnostics and personalized mental health pathways.
- **Cloud-Native Deployment:** Transitioning to distributed cloud infrastructure (e.g., AWS or Azure) to enable global scalability and advanced load-balancing.
- **Mobile Expansion:** Development of cross-platform mobile applications to increase accessibility and facilitate real-time "in-the-moment" mood tracking.
- **Advanced Analytics:** Implementation of comprehensive dashboards for practitioners to monitor aggregate population health trends and institutional performance.

In conclusion, MINDASSESS contributes to the mHealth domain by proposing and validating a unified diagnostic archi-

tecture that bridges the gap between user-centric accessibility and professional clinical governance. The system provides a robust, scalable foundation for future expansion toward intelligent, cloud-enabled, and globally accessible mental health monitoring platforms.

Future enhancements include:

- AI-based recommendation systems
- Cloud-native deployment
- Mobile application development

References

[1] K. Kroenke, R. L. Spitzer, and J. B. W. Williams, "The PHQ-9: Validity of a brief depression severity measure," *Journal of General Internal Medicine*, vol. 16, no. 9, pp. 606–613, 2001.

[2] R. L. Spitzer, K. Kroenke, J. B. W. Williams, and B. Löwe, "A brief measure for assessing generalized anxiety disorder: The GAD-7," *Archives of Internal Medicine*, vol. 166, no. 10, pp. 1092–1097, 2006.

[3] R. C. Kessler et al., "The World Health Organization Adult ADHD Self-Report Scale (ASRS): A short screening scale," *Psychological Medicine*, vol. 35, no. 2, pp. 245–256, 2005.

[4] S. Tilkov and S. Vinoski, "Node.js: Using JavaScript to build high performance network programs," *IEEE Internet Computing*, vol. 14, no. 6, pp. 80–83, 2010.

[5] J. Banks, "Architecting Single Page Applications with React," *IEEE Software*, vol. 35, no. 3, pp. 95–100, 2018.

[6] K. Chodorow, *MongoDB: The Definitive Guide*. Sebastopol, CA, USA: O'Reilly Media, 2013.

[7] R. T. Fielding, "Architectural styles and the design of network-based software architectures," Ph.D. dissertation, Univ. California, Irvine, 2000.

[8] M. Jones, J. Bradley, and N. Sakimura, "JSON Web Token (JWT)," IETF RFC 7519, 2015.

[9] R. Sandhu, D. Ferraiolo, and R. Kuhn, "The NIST model for role-based access control: Towards a unified standard," in *Proc. ACM Workshop on Role-Based Access Control*, 2000, pp. 47–63.

[10] OWASP Foundation, "OWASP Top 10 Web Application Security Risks," 2021. [Online]. Available: https://owasp.org

[11] A. Mesbah and A. van Deursen, "Migrating multi-page web applications to single-page AJAX interfaces," in *Proc. European Conf. Software Maintenance*, 2007, pp. 181–190.

[12] X. Chen, M. Xie, and D. Zou, "A review of AI-based adaptive learning systems," *IEEE Access*, vol. 8, pp. 153–162, 2020.

[13] P. Mell and T. Grance, "The NIST definition of cloud computing," NIST Special Publication 800-145, 2011.