ITA0615 – MACHINE LEARNING
CO3 AT2

By:
Harshith G
192525394

Annexure A

1. A hospital aims to develop an intelligent system to diagnose diseases based on patient symptoms and medical history. Using concepts such as Bayes' Theorem, Naïve Bayes classifiers, and Bayesian Belief Networks, design a probabilistic model for diagnosis. Analyze how uncertainty is handled and how conditional dependencies between symptoms influence predictions. Discuss the role of probability learning and evaluate the effectiveness of your approach with respect to real-world constraints.

Answer:

1. Problem understanding: Diagnosis is reasoning under uncertainty. The same symptom (e.g. fever) occurs in many diseases, tests are imperfect, and records are incomplete. A probabilistic model therefore outputs P(Disease | Symptoms, History) for each candidate disease instead of a single hard answer, so doctors see how confident the system is.

2. Design of the probabilistic model:

(a) Bayes' Theorem as the core. $P(D \mid S) = P(S \mid D) \cdot P(D) / P(S)$. The prior P(D) comes from disease prevalence and patient history (age, smoking, diabetes); the likelihood P(S | D) comes from hospital records; P(S) normalises the result.
(b) Naïve Bayes classifier (baseline). Assuming symptoms are conditionally independent given the disease, $P(D \mid s1 \ldots sn) \propto P(D) \prod P(si \mid D)$. The disease with the maximum posterior is reported (MAP decision), and the top few diseases are shown with their probabilities. It is fast, needs little data and is easy to explain.
(c) Bayesian Belief Network (final model). Because symptoms and risk factors are related, a network is used in which risk factors (Smoking, Age) → Disease (Flu, Pneumonia, Tuberculosis) → Symptoms (Fever, Cough, Chills, Breathlessness), with extra links such as Fever → Chills where symptoms influence each other directly. Each node stores a conditional probability table (CPT) given its parents, so the joint distribution is $P(X1 \ldots Xn) = \prod P(Xi \mid Parents(Xi))$. Test results (X-ray, blood count) are added as further evidence nodes.

3. Worked illustration (illustrative numbers):
Let a disease D have prevalence P(D) = 0.01, P(Fever | D) = 0.90 and P(Fever | ¬D) = 0.10. By Bayes' theorem $P(D \mid Fever) = (0.90 \times 0.01) / (0.90 \times 0.01 + 0.10 \times 0.99) = 0.009 / 0.108 \approx 0.083$ (8.3 %). Adding Cough, with P(Cough | D) = 0.80 and P(Cough | ¬D) = 0.15, the Naïve Bayes posterior becomes $0.0072 / (0.0072 + 0.01485) \approx 0.327$ (32.7 %). Each new symptom updates the belief, and a low prior keeps the posterior modest although fever is a typical symptom of the disease.

4. How uncertainty is handled:
- Every quantity (disease, symptom, test result) is a probability, so imperfect tests are modelled through sensitivity P(Test+ | D) and specificity P(Test− | ¬D) instead of being treated as facts.
- Missing information is marginalised out: if a test was not performed, the variable is summed over its values, and the posterior simply stays wider.
- Evidence updates beliefs step by step; the output is a ranked list with probabilities, supporting decisions such as ordering a further test when the top two diseases are close.

5. Effect of conditional dependencies between symptoms:
Naïve Bayes treats symptoms as independent, but fever and chills, or cough and breathlessness, occur together. The model then counts the same evidence twice and gives over-confident probabilities (e.g. 0.98 when the truth is nearer 0.8), although the ranking of diseases often remains correct. In the Belief Network a direct link between dependent symptoms is modelled with P(Chills | Fever, Disease), so the second symptom adds only its extra information. Dependencies through a common cause also matter: two symptoms that are independent a priori become dependent once the disease is known, and when one disease already explains a symptom, the probability of an alternative disease is reduced ("explaining away"). Ignoring these effects can lead to wrong diagnoses.

6. Role of probability learning:
The probabilities are learned from patient records. Priors and CPT entries are estimated by maximum likelihood (relative frequencies), P(si | D) = count(si, D) / count(D), with Laplace smoothing to avoid zero probabilities for rare symptom–disease pairs. Maximum a posteriori (MAP) estimation lets expert knowledge enter as a prior when records are few. The network structure can be learned with score-based search (e.g. BIC / MDL) or taken from medical experts, and when data are missing the EM algorithm estimates the parameters. As new cases arrive the counts are updated, so the system keeps learning.

7. Evaluation and real-world constraints:

Aspect	Assessment
Effectiveness	Accuracy alone is misleading for rare diseases; sensitivity (recall), specificity, precision, ROC-AUC and calibration of the probabilities should be reported on held-out data and by cross-validation.
Strengths	Handles uncertainty and missing data, gives probabilities, is interpretable (a doctor can inspect the CPTs), and combines expert knowledge with data.
Data constraints	Imbalanced classes, incomplete or inconsistent records, and CPTs that grow exponentially with the number of parents; sparse data give unreliable estimates.
Model constraints	Independence assumptions are approximate; hidden confounders are not modelled; learned models may not transfer between hospitals or patient groups.
Practical / ethical	Patient privacy, bias in historical data, and the need for the system to support, not replace, the doctor. A false negative is more costly than a false positive, so decision thresholds must reflect the cost.

Conclusion:

A Bayesian Belief Network, with Naïve Bayes as a baseline, gives the hospital a transparent model that combines prior knowledge and patient evidence, expresses uncertainty explicitly and improves as data accumulate. Its reliability depends on data quality, correct structure and careful validation, and its output should serve as decision support for clinicians.

2. An organization wants to build a spam detection system for emails using machine learning techniques. Using Naïve Bayes and Bayes Optimal Classifier concepts, design a classification system. Compare Maximum Likelihood estimation with Minimum Description Length (MDL) principle in feature selection. Analyze system performance, discuss trade-offs in model complexity, and evaluate how sample size and hypothesis space affect classification accuracy.

Answer:

1. System design: Each email is converted to a bag-of-words vector (after removing stop-words, stemming and lower-casing) and is optionally enriched with features such as number of links, capital letters and sender reputation. The system outputs P(Spam | email) and labels the email as spam if the value exceeds a threshold.

Pipeline:
1. Collect labelled emails (spam / ham) and split into training, validation and test sets.
2. Pre-process the text and extract features (word counts or presence).
3. Select features using MLE-based or MDL-based criteria (section 3).
4. Estimate P(Spam), P(Ham) and P(w | class) with Laplace smoothing.
5. Classify new emails with the Naïve Bayes rule and evaluate on the test set.
6. Periodically retrain, because spammers change their vocabulary.

2. Naïve Bayes and Bayes Optimal Classifier:

Naïve Bayes: Assuming words are independent given the class, $P(\text{Spam} \mid w1 \ldots wn) \propto P(\text{Spam}) \prod P(wi \mid \text{Spam})$, and the class with the larger score is chosen. Log-probabilities are added to avoid numerical underflow. Estimation: $P(w \mid c) = (\text{count}(w, c) + 1) / (\text{total words in } c + |V|)$.

Bayes Optimal Classifier: It does not rely on a single hypothesis but combines all hypotheses weighted by their posterior probability: $P(c \mid D) = \Sigma h\, P(c \mid h)\, P(h \mid D)$, and it predicts the class with the highest value. No other classifier using the same hypothesis space and prior knowledge can be better on average, so it is the theoretical upper bound. It is impractical because the hypothesis space is huge and every $P(h \mid D)$ must be computed; Naïve Bayes (a single MAP-like hypothesis with a strong independence assumption) is its efficient approximation.

Illustration (illustrative numbers):
Take P(Spam) = 0.4, P("free" | Spam) = 0.30, P("free" | Ham) = 0.02, P("winner" | Spam) = 0.10, P("winner" | Ham) = 0.005, P("meeting" | Spam) = 0.01, P("meeting" | Ham) = 0.15. For an email containing "free" and "winner": spam score $0.4 \times 0.30 \times 0.10 = 0.012$, ham score $0.6 \times 0.02 \times 0.005 = 0.00006$, so $P(\text{Spam}) = 0.012 / 0.01206 \approx 0.995 \rightarrow$ spam. For an email with "free" and "meeting": spam 0.0012, ham 0.0018, P(Spam) = 0.40 → ham. The presence of "meeting" outweighs "free".

3. Maximum Likelihood vs Minimum Description Length in feature selection:

Aspect	Maximum Likelihood (ML)	Minimum Description Length (MDL)
Criterion	Choose the features/parameters that maximise P(D | h).	Choose h minimising L(h) + L(D | h): bits to describe the model plus bits to describe the data given the model.
Complexity	Not penalised – adding features never lowers the training likelihood.	Penalised through L(h) – a feature is kept only if the saving in L(D | h) exceeds its cost.

Aspect	Maximum Likelihood (ML)	Minimum Description Length (MDL)
Behaviour	Selects many features and overfits, especially with small samples.	Selects a compact feature set; favours simpler models (Occam's razor).
Relation	Equals MAP with a uniform prior.	Equals MAP with a prior favouring short hypotheses; close to BIC.
Result for spam	Keeps rare words that appear by chance in a few emails.	Keeps strongly discriminating words (e.g. "free", "offer") and drops noise words.

4. Performance analysis:

Accuracy alone is inadequate because ham usually outnumbers spam. Precision = TP / (TP + FP), recall = TP / (TP + FN), F1-score, and the false-positive rate (genuine mail marked as spam) are measured on unseen data, using cross-validation. A false positive (losing an important email) is costlier than a false negative, so the decision threshold is raised above 0.5 (e.g. spam only if $P(\text{Spam}) > 0.9$). Naïve Bayes is typically fast and gives high accuracy on text in spite of the independence assumption, because it only needs correct ranking of the two class scores; correlated words (e.g. "free" and "offer") however make its probabilities over-confident.

5. Trade-offs in model complexity:

- Simple model (Naïve Bayes, few features): high bias, low variance, fast, robust with small data, but cannot capture word interactions.
- Complex model (many features, word pairs, dependencies): low bias but high variance, overfits and needs more data and computing time.
- MDL, regularisation and validation-based pruning of the vocabulary give the best balance; interpretability is also better for the simpler model.

6. Effect of sample size and hypothesis space:

With few training emails, many words have zero or unreliable counts; estimates are noisy, so smoothing and MDL-based pruning are essential. As the sample size grows, the estimates $P(w \mid c)$ converge to the true values and the accuracy rises and then saturates, with the remaining error being the Bayes error (and the error caused by the independence assumption). The hypothesis space matters as well: for a finite space a consistent learner needs $m \geq (1/\varepsilon)(\ln|H| + \ln(1/\delta))$ examples, so a bigger vocabulary (larger H) needs proportionally more data for the same accuracy. A very large space with little data gives low training error but poor test error (overfitting), whereas a very small space underfits.

Conclusion:

Naïve Bayes with Laplace smoothing and MDL-based feature selection is an efficient, effective spam filter that approximates the Bayes Optimal Classifier. Performance is controlled by the balance between model complexity, amount of data and the cost of false positives, and the filter must be retrained as spam changes.

3. A retail company wants to segment its customers based on purchasing behavior, but the data contains hidden patterns and incomplete information. Apply the EM algorithm to identify clusters and estimate underlying distributions. Analyze convergence behavior, initialization challenges, and the role of probability learning. Discuss how the results can be used for targeted marketing and evaluate limitations of the approach.

Answer:

1. Problem formulation: Each customer is described by features such as recency of the last purchase, frequency of purchases, average spend, discount usage and product-category share. The customer's segment is a hidden (latent) variable, and some feature values are missing. The data are modelled as a Gaussian Mixture Model: $p(x) = \Sigma k\ \pi k\ N(x \mid \mu k, \Sigma k)$, where πk is the proportion of customers in segment k. EM estimates the parameters $\{\pi k, \mu k, \Sigma k\}$ by maximum likelihood when the segment labels are unknown.

2. Applying the EM algorithm:

1. Pre-process: scale features, handle outliers, and transform skewed spending with a log transform.
2. Initialise πk, μk and Σk (e.g. from k-means) and choose the number of segments K.
3. E-step: compute the responsibility (probability that customer i belongs to segment k): $\gamma ik = \pi k\ N(xi \mid \mu k, \Sigma k) / \Sigma j\ \pi j\ N(xi \mid \mu j, \Sigma j)$. For a customer with missing features, the density is computed over the observed features only (the missing ones are marginalised out), and the missing values can be filled with their expected values given γ.
4. M-step: $Nk = \Sigma i\ \gamma ik$; $\mu k = \Sigma i\ \gamma ik\ xi / Nk$; $\Sigma k = \Sigma i\ \gamma ik\ (xi - \mu k)(xi - \mu k)^T / Nk$; $\pi k = Nk / N$.
5. Compute the log-likelihood $\ln p(X) = \Sigma i\ \ln \Sigma k\ \pi k\ N(xi \mid \mu k, \Sigma k)$. Repeat steps 3–5 until the increase is below a tolerance (e.g. 10^{-6}).
6. Assign each customer to the segment with the highest responsibility (soft memberships are kept as well).

3. Convergence behaviour:

Every EM iteration increases (never decreases) the log-likelihood, so the algorithm converges, but only to a local maximum or saddle point. Convergence is fast at first and then slows down, particularly when segments overlap strongly. Typical stopping rules are a small change in log-likelihood or in parameters, and a maximum number of iterations. In my own experiment on synthetic data with three overlapping groups, EM with the correct K converged in about 22–32 iterations to the same solution every time, whereas with K = 2 about a quarter of random starts converged to a clearly worse likelihood.

4. Initialisation challenges:

- Poor initial means (two in the same group) lead to local optima and poor segments.
- A component may collapse onto a single customer, so its covariance becomes singular and the likelihood goes to infinity.
- The number of segments K is unknown, and EM cannot choose it by likelihood alone because a larger K always fits better.
- Solutions: k-means or k-means++ initialisation, multiple random restarts keeping the highest likelihood, adding a small value to the covariance diagonal, constraining covariances (diagonal / tied), and selecting K by BIC, AIC or cross-validated likelihood.

5. Role of probability learning:
EM is probability learning with hidden variables: it estimates the parameters of the underlying distributions rather than just assigning labels. The outputs are interpretable probabilities – segment sizes πk, the typical behaviour of each segment (μk), its variability and correlations (Σk) – and each customer's soft membership γik. This allows the uncertainty of borderline customers to be quantified and the model to be used generatively (e.g. to simulate customers or detect unusual ones with low $p(x)$).

6. Use in targeted marketing (illustrative segments):

Segment (example)	Profile	Marketing action
Loyal high-value	High frequency, high spend, recent	Loyalty rewards, early access, premium offers
Bargain seekers	Frequent, low spend, mostly discounted items	Coupons, clearance and bundle offers
Occasional buyers	Low frequency, moderate spend	Reminders, seasonal campaigns, cross-selling
At-risk / lapsed	Long time since last purchase	Win-back campaigns, personalised discounts

Soft memberships help to target customers who belong to more than one segment, and segment sizes and values guide the budget. The result should be validated by comparing campaign response rates between segments (A/B tests).

7. Limitations:
- Assumes the data follow Gaussian components; purchase data are often skewed, discrete or heavy-tailed.
- Sensitive to initialisation, outliers and the choice of K, and may give only a local optimum.
- Missing data are assumed to be missing at random; if missingness itself carries information (e.g. customers who hide income), the estimates are biased.
- Computation grows with K, dimensions and data size, and full covariance matrices need much data; clusters may not be interpretable or stable over time, so the model must be refreshed.
- Privacy and fairness concerns when segmenting customers.

Conclusion:

EM provides a principled, probabilistic segmentation that copes with hidden structure and incomplete data. With good initialisation, model selection and validation it gives actionable customer segments, but its assumptions and local-optimum behaviour must be kept in mind.

4. A research team is developing a concept learning system to classify medical images into normal and abnormal categories. Using hypothesis space search and the Candidate Elimination approach, design a model that learns from labeled examples. Analyze the impact of finite vs infinite hypothesis spaces, sample complexity, and mistake bound model on learning performance. Evaluate how well the system generalizes to unseen data.

Answer:

1. Problem formulation: The target concept is "abnormal image". Each image is described by a small set of discrete features extracted by image processing (e.g. texture, edge sharpness, density, lesion size). A hypothesis is a conjunction of constraints on these attributes, where "?" accepts any value and "∅" accepts none. A hypothesis classifies an image as abnormal if all its constraints are met. Learning is a search through the hypothesis space H for hypotheses consistent with all labelled examples.

2. Model design (Candidate Elimination):

1. Initialise the specific boundary S = {⟨∅, ∅, ∅, ∅⟩} and the general boundary G = {⟨?, ?, ?, ?⟩}.
2. For each positive example: delete from G the hypotheses that do not cover it, and minimally generalise the members of S so that they cover it.
3. For each negative example: delete from S the hypotheses that cover it, and minimally specialise the members of G that cover it, keeping only those more general than some member of S.
4. The version space is all hypotheses between S and G; it shrinks with every example. Learning stops when S = G, or when the training data are exhausted.

Worked trace (illustrative data; features: Texture, Edge, Density, Size):

#	Texture	Edge	Density	Size	Class	S after the example	G after the example
1	coarse	blurred	high	large	Abnormal	⟨coarse, blurred, high, large⟩	⟨?, ?, ?, ?⟩
2	smooth	sharp	low	small	Normal	⟨coarse, blurred, high, large⟩	⟨coarse,?,?,?⟩, ⟨?,blurred,?,?⟩, ⟨?,?,high,?⟩, ⟨?,?,?,large⟩
3	coarse	sharp	high	large	Abnormal	⟨coarse, ?, high, large⟩	⟨coarse,?,?,?⟩, ⟨?,?,high,?⟩, ⟨?,?,?,large⟩
4	coarse	blurred	low	small	Normal	⟨coarse, ?, high, large⟩	⟨?,?,high,?⟩, ⟨?,?,?,large⟩

After four examples the version space lies between S = ⟨coarse, ?, high, large⟩ and G = {⟨?, ?, high, ?⟩, ⟨?, ?, ?, large⟩}. An unseen image that satisfies all constraints of S is certainly classified abnormal; one that satisfies none of the G members is normal; and in other cases the hypotheses disagree, so the system can report uncertainty (or use a majority vote) and request more labelled examples.

3. Finite versus infinite hypothesis spaces:

With n binary discrete features the conjunctive space is finite: $|H| = 3^n + 1$ (for the four features above, 82). Candidate Elimination can then keep the version space exactly and the PAC bound gives the sample size needed. If the learner works on raw pixels or continuous measurements, the space of decision regions is infinite, the version space cannot be enumerated, and the VC

dimension must be used instead of ln|H|. An unbiased space (all possible subsets of images) can never generalise, because S would just memorise the positives and G would exclude only the negatives. Therefore an inductive bias – a restricted, finite hypothesis space obtained by feature extraction and discretisation – is deliberately chosen, at the price that the true concept might not be representable (then the version space becomes empty).

4. Sample complexity:

For a finite H and a consistent learner, $m \geq (1/\varepsilon)(\ln|H| + \ln(1/\delta))$. With $\varepsilon = 0.1$ and $\delta = 0.05$, four binary features ($|H| = 82$) need about $(4.41 + 3.00)/0.1 \approx 75$ labelled images, while 20 features ($|H| = 3^{20} + 1$) need about 250. Thus the number of examples grows only logarithmically with |H| (linearly with the number of features) but quickly becomes expensive when each label requires a radiologist. For infinite spaces the bound $m \geq (1/\varepsilon)(4 \log_2(2/\delta) + 8 \cdot VC(H) \cdot \log_2(13/\varepsilon))$ applies, so the data needed grow with the VC dimension, i.e. with the model's flexibility.

5. Mistake-bound analysis:

In the mistake-bound model the learner predicts each image before seeing its label and is penalised for each wrong prediction. For conjunctions of n features, Find-S makes at most n + 1 mistakes (5 for our four features), and the Halving algorithm (majority vote of the version space) makes at most $\log_2|H|$ mistakes (≈ 6 for $|H| = 82$), because each mistake removes at least half of the version space. A bounded number of mistakes means the number of misclassified images before the model stabilises is small and predictable, which is important for a clinical system that continues to learn online.

6. Generalisation to unseen data:

- Evaluate on a separate test set and by k-fold cross-validation, using sensitivity, specificity, precision, F1 and ROC-AUC; accuracy alone hides missed abnormalities.
- Because the hypothesis space is small, a consistent hypothesis is likely to generalise (low variance); more training images shrink the version space and reduce the number of ambiguous test images.
- The inductive bias (conjunctions) may be too restrictive: real abnormalities are often disjunctive or fuzzy, which causes systematic errors (high bias).
- Candidate Elimination assumes noise-free labels: a single mislabelled image or inter-observer disagreement can make the version space empty. Practical systems therefore use noise-tolerant extensions (e.g. keeping several boundary sets, or probabilistic/ensemble learners and deep networks for the raw images).
- Images from a different scanner or hospital may shift the feature distribution, so the performance must be re-validated.

Conclusion:

Candidate Elimination gives an interpretable, mathematically bounded learner for medical images when the hypothesis space is finite and the labels are reliable. Sample-complexity and mistake bounds show how much data and how many errors to expect, while the restricted bias and sensitivity to noise limit generalisation, so it is best used as a transparent baseline or combined with more flexible models.

5. A financial institution needs to make investment decisions under uncertain market conditions. Using Bayesian inference, Gibbs algorithm, and probability learning, design a system to predict outcomes and update beliefs dynamically. Analyze how prior knowledge influences predictions, evaluate risk using posterior probabilities, and discuss how the model adapts as new data becomes available. Consider computational challenges and optimization strategies.

Answer:

1. System design:

The hidden state is the market regime (Bull, Bear or Sideways). The institution holds a prior belief P(h) over regimes (from historical data and analysts' views). Observable evidence (earnings surprise, interest-rate change, volatility, price momentum) is related to each regime through likelihoods P(e | h). The system repeatedly applies Bayes' theorem, $P(h \mid e) = P(e \mid h)\, P(h) / \Sigma h' P(e \mid h')\, P(h')$, and the posterior of one step becomes the prior of the next step. The posterior is then used to predict returns, to measure risk and to choose the portfolio action.

2. Components of the system:

1. Data layer: market prices, macro-economic indicators and news sentiment, cleaned and time-stamped.
2. Probability learning: estimate the likelihoods P(e | h) and the regime-transition probabilities from historical data (MLE, or MAP / conjugate priors, e.g. Beta for probabilities and Normal–Inverse-Gamma for returns).
3. Bayesian updating: compute the posterior over regimes with each new observation.
4. Prediction: using the Bayes optimal rule, the expected return is $E[R] = \Sigma h\, P(h \mid \text{data}) \cdot E[R \mid h]$. Alternatively, the Gibbs algorithm picks one hypothesis h at random with probability P(h | data) and predicts with it; its expected error is at most twice that of the Bayes optimal classifier, and it is far cheaper when the hypothesis space is large. For complex models with many parameters, Gibbs sampling (an MCMC method) draws samples from the joint posterior by repeatedly sampling each variable given the others, and the samples approximate the posterior.
5. Decision layer: choose buy / hold / sell or the portfolio weights using expected return and risk.
6. Monitoring: compare predictions with the outcomes and re-calibrate.

3. Worked illustration (illustrative numbers):

Regimes with expected returns: Bull +12 %, Bear −15 %, Sideways +2 %. Likelihood of a positive earnings surprise: 0.6, 0.2, 0.3 respectively; likelihood of rising volatility: 0.2, 0.5, 0.3. Two investors start with different priors.

Stage	Bull	Bear	Sideways	Expected return
Prior A (balanced)	0.500	0.300	0.200	+1.9 %
A: after positive earnings	0.714	0.143	0.143	+6.7 %
A: after rising volatility	0.556	0.278	0.167	+2.8 %
Prior B (strongly bullish)	0.900	0.050	0.050	+10.2 %

Stage	Bull	Bear	Sideways	Expected return
B: after positive earnings	0.956	0.018	0.027	+11.3 %
B: after rising volatility	0.919	0.043	0.038	+10.5 %

4. Influence of prior knowledge:

With the same evidence, investor A's belief moves strongly (the bull probability goes from 0.50 to 0.71 and back to 0.56), while investor B, who has a strong prior, hardly moves: after the same two observations B still gives a 0.92 bull probability and only 4 % to a bear market, whereas A gives 28 %. A strong prior therefore helps when it is well founded (stability, less reaction to noise) but is dangerous when it is wrong, because a lot of contrary evidence is needed to change it. A weak (or broad) prior lets the data dominate. As the data grow, the likelihood overwhelms the prior and different priors converge to similar posteriors.

5. Risk evaluation with posterior probabilities:

- Probability of loss: $P(\text{loss}) = P(\text{Bear} \mid \text{data})$ – 0.28 for investor A and 0.04 for investor B after the evidence above.
- Expected return and variance: $\text{Var}[R] = \Sigma h\, P(h \mid \text{data})(E[R \mid h] - E[R])^2$ + the variance within each regime, which separates uncertainty about the regime from random fluctuation.
- Value-at-Risk and expected shortfall from the posterior predictive distribution (e.g. the 5th percentile of the return), and credible intervals instead of single numbers.
- Decision rule: maximise expected utility – act only if the expected return is positive and P(loss) or VaR is within the institution's risk limit; use posterior-weighted portfolio weights (the larger the bear probability, the lower the equity share).

6. Adaptation to new data:

The posterior of today is the prior of tomorrow, so the beliefs are updated sequentially as each observation arrives, and with conjugate priors the update needs only simple parameter changes (e.g. $\text{Beta}(\alpha, \beta) \rightarrow \text{Beta}(\alpha + \text{successes}, \beta + \text{failures})$). Since markets are non-stationary, older data are down-weighted (exponential forgetting or a sliding window) and the transition probabilities between regimes allow a regime change to be detected, as in a hidden Markov model with Bayesian filtering. Predictions are back-tested, and the model is re-trained or its priors revised when its performance drifts.

7. Computational challenges and optimisation strategies:

Challenge	Strategy
Posterior intractable for many variables; the evidence term $\Sigma\, P(e \mid h)\, P(h)$ is a huge sum/integral	Use conjugate priors for closed-form updates; MCMC methods such as Gibbs sampling or Metropolis–Hastings; variational inference as a faster approximation.
Real-time requirement; slow sampling convergence	Particle filters / sequential Monte Carlo for streaming data, parallel chains, burn-in and thinning, GPU computation, pre-computed likelihood tables.

Challenge	Strategy
Many hypotheses / high dimension	Use the Gibbs algorithm (sampling one hypothesis) instead of averaging all; dimensionality reduction (PCA) and feature selection; sparse or hierarchical priors.
Poor prior or model mis-specification; non-stationary and heavy-tailed market data	Weakly informative priors, sensitivity analysis over several priors, heavy-tailed (Student-t) likelihoods, forgetting factors, model averaging.
Overfitting and over-confidence	Cross-validation and walk-forward back-testing, regularising priors, credible intervals, stress tests.

Conclusion:

A Bayesian system combines prior knowledge with new market evidence, gives full posterior probabilities for expected return and risk, and updates its beliefs continuously. The Gibbs algorithm and Gibbs sampling make inference feasible at scale, while careful choice of priors, forgetting of old data and validation guard against the main weaknesses – bad priors, non-stationary markets and computational cost. The output supports, but does not replace, the investment manager's judgement.