

Design and Analysis of algorithm

Lab 7

Name: Harsh Brahmecha

PRN: 20220802003

Topic: Dynamic Programming

1) Write a C code to implement Travelling salesman problem using dynamic programming method.

CODE:

```
#include <stdio.h>
int ary[10][10], completed[10], n, cost = 0;
void takeInput() {
    int i, j;
    printf("Enter the number of villages: ");
    scanf("%d", & n);
    printf("\nEnter the Cost Matrix\n");
    for (i = 0; i < n; i++) {
        printf("\nEnter Elements of Row: %d\n", i + 1);
        for (j = 0; j < n; j++)
            scanf("%d", & ary[i][j]);
        completed[i] = 0;
    }
    printf("\n\nThe cost list is:");
    for (i = 0; i < n; i++) {
        printf("\n");
        for (j = 0; j < n; j++) printf("\t%d", ary[i][j]);
    }
}
int least(int c) {
    int i, nc = 999;
    int min = 999, kmin;
    for (i = 0; i < n; i++) {
        if ((ary[c][i] != 0) && (completed[i] == 0))
```

```

    = ary[c][i];
    nc =
        i;
    }
}
}
if (min != 999) cost += kmin;
return nc;
}

void mincost(int city) {
    int i, ncity;
    completed[city] = 1;
    printf("%d--->", city + 1);
    ncity = least(city);
    if (ncity == 999) {
        ncity = 0;
        printf("%d", ncity + 1);
        cost += ary[city][ncity];
        return;
    }
    mincost(ncity);
}

int main() {
    takeInput();
    printf("\n\nThe Path is:\n");
    mincost(0);
    printf("\n\nMinimum cost is %d\n", cost);
    return 0;
}

```

OUTPUT:

Enter the number of villages: 4

Enter the Cost Matrix

Enter Elements of Row: 1

0 4 1 3

Enter Elements of Row: 2

4 0 2 1

Enter Elements of Row: 3

1 2 0 5

Enter Elements of Row: 4

3 1 5 0

The cost list is:

0 4 1 3

4 0 2 1

1 2 0 5

3 1 5 0

The Path is:

1—>3—>2—>4—>1

Minimum cost is 7