CARELINK AI: setup and demo commands

Repo: `git@github.com:harsha-4144/carelink.git` (HTTPS: `https://github.com/harsha-4144/carelink.git`)

Part 1. Push from this laptop (once)

```
cd /home/harsha/carelink
git status                      # should say "nothing to commit, working tree clean"
git remote add origin git@github.com:harsha-4144/carelink.git
git branch -M main
git push -u origin main
```

If `git remote add` says `remote origin already exists`:

```
git remote set-url origin git@github.com:harsha-4144/carelink.git
```

If the push says "Permission denied (publickey)"

The SSH URL needs an SSH key registered on GitHub. Either set up a key:

```
ssh-keygen -t ed25519 -C "harsha@dharanova.com"      # press Enter 3 times
cat ~/.ssh/id_ed25519.pub                            # copy the whole line
```

Then GitHub, Settings, SSH and GPG keys, New SSH key, paste, save. Test with:

```
ssh -T git@github.com                                # "Hi harsha-4144! You've successfully
authenticated"
git push -u origin main
```

Or skip SSH and use HTTPS (GitHub asks for a personal access token as the password):

```
git remote set-url origin https://github.com/harsha-4144/carelink.git
git push -u origin main
```

Pushing later changes

```
git add -A
git commit -m "describe the change"
git push
```

Part 2. Brand-new laptop with a fresh WSL (Ubuntu)

Run these inside the WSL terminal.

2.1 Install the tools (one time)

```
sudo apt update
sudo apt install -y git curl build-essential python3
curl -o- https://raw.githubusercontent.com/nvm-sh/nvm/v0.40.1/install.sh | bash
```

Close the terminal and open a new WSL terminal (so `nvm` loads), then:

```
nvm install 20
node -v          # must print v20.x or higher
npm -v
```

2.2 Get the project (clone into the Linux home, not /mnt/c)

```
cd ~
git clone https://github.com/harsha-4144/carelink.git
cd carelink
```

(Use the HTTPS URL on a new laptop unless you set up an SSH key there. If the repo is private, git asks for your GitHub username and a personal access token as the password.)

2.3 Install and run

```
npm install            # 1 to 2 minutes the first time
npm start              # seeds the demo data automatically on the first start
```

Open **http://localhost:3000** in the Windows browser (Chrome or Edge).

If that page does not load from Windows, find the WSL address and use it instead:

```
hostname -I            # then open http://<that-ip>:3000
```

2.4 Check that everything is healthy (optional)

```
npm test                                  # expect: 42 pass, 0 fail
curl localhost:3000/api/health            # expect: {"ok":true,...}
```

Part 3. Run the demo

Accounts (password for all: `demo1234`)

Role	Email
Patient	`asha@demo.test` (CL-1001), `ravi@demo.test`, `meera@demo.test`, `arjun@demo.test`, `sana@demo.test`
Guardian	`rohan@demo.test` (Asha's), `sunita@demo.test`, `anil@demo.test`, `lakshmi@demo.test`, `imran@demo.test`
Hospital staff	`kiran@demo.test` (Heartline), `priya@demo.test` (Riverside)

Staff sign-up code: `HACKHERS`. Patient IDs for the bystander: `CL-1001` to `CL-1005`.

Three windows

1. **Bystander:** http://localhost:3000/emergency.html (use a phone-size window if you like).
2. **Hospital:** http://localhost:3000/login.html, tap "Heartline staff".
3. **Guardian:** a second browser profile or an incognito window, http://localhost:3000/login.html, log in as `rohan@demo.test`. (Each browser profile holds one login, so use different profiles or incognito for different people.)

Script (about 2 minutes)

1. Bystander: tap **SOS**, then **Start now** (or wait 5 seconds).

2. Enter `CL-1001`, **Look up patient**, **Continue**.
3. Tap **Unconscious** and **Chest pain**, **Assess urgency**: shows **Critical**.
4. **Find best hospitals**: three cards with score breakdown; pick the first (Heartline).
5. **Confirm and alert**. Watch the hospital queue and guardian screen react.
6. Hospital: **Accept**, then **Preparing**, then **Ready**. Guardian: **I'm on my way**. The bystander screen shows both.
7. Bystander: **Patient arrived**. Show the timeline.

Extra moments: **False alarm**, refresh the page and **Resume emergency**, hospital **Decline** (bystander is re-matched), skip identification and let the hospital **Identify patient** (guardians then alerted), the bell, the patient's **Access log**, `/outbox.html` (simulated SMS), `/about.html`.

Reset between runs

Stop the server (Ctrl+C), then:

```
npm run seed          # resets patients, hospitals, accounts and history
npm start
```

Part 4. Show it on phones (HTTPS tunnel)

Camera (QR), microphone and location only work on `localhost` or HTTPS. For a phone, use a tunnel.

```
npm start                                  # terminal 1
```

Install cloudflared once (WSL, Ubuntu):

```
curl -L https://github.com/cloudflare/cloudflared/releases/latest/download/cloudflared-linux-amd64.deb -o
cloudflared.deb
sudo dpkg -i cloudflared.deb
```

Then in a second terminal:

```
cloudflared tunnel --url http://localhost:3000
```

It prints an `https://something.trycloudflare.com` address. Open it on the phone. Stop it with Ctrl+C when done.

Part 5. Useful options

```
MOCK_MODE=true npm start          # no internet used at all (route becomes a straight line)
PORT=4000 npm start               # different port
DEMO_MODE=false npm start         # hides demo-account buttons and the SMS log
STAFF_CODE=mysecret npm start     # change the hospital staff sign-up code
```

Optional AI refinement of triage: copy `.env.example` to `.env`, put your key after `ANTHROPIC_API_KEY=`, restart. Never commit `.env` (it is already git-ignored).

Browser walk-through of all personas (needs Playwright, installed only when you want it):

```
npm i --no-save playwright
npx playwright install chromium
# terminal 1:  RATE_LIMIT=off PORT=3997 npm start
# terminal 2:  BASE=http://localhost:3997 node scripts/e2e-flows.js
```

Part 6. Troubleshooting

Problem	Fix
`node: command not found` after installing nvm	Close and reopen the WSL terminal, then `nvm install 20`
`npm install` fails building `better-sqlite3`	`sudo apt install -y build-essential python3`, then `npm install` again
`EADDRINUSE: port 3000 already in use`	`PORT=3001 npm start`, or `fuser -k 3000/tcp`
Page does not open from Windows	Use `hostname -I` and open `http://<ip>:3000`
Map or QR scanner shows a "failed to load" message	No internet for the CDN. The rest of the flow still works. Type the ID instead of scanning
Camera, mic or location blocked	Use `http://localhost:3000` on the same machine, or the HTTPS tunnel on a phone
Page looks broken or old	Hard refresh: Ctrl+Shift+R
Too many login attempts message	Wait a few minutes, or restart the server
Want a totally clean start	`rm -rf data && npm start`
Slow or odd file errors	Make sure the project is under `~` (Linux), not `/mnt/c`

More: JUDGES_QA.md (answers to likely questions), `/about.html` in the running app, and `README.md`.