

QUESTIONS 1 / 10 completed

Queue Using Array ▾

QUEUE USING ARRAYS

Write a C program to implement a Queue using Arrays with operations such as insertion (enqueue), deletion (dequeue), display, and peek. The program should simulate a ticket booking counter where customers arrive in sequence and are served on a first-come-first-served basis. The queue should

PROGRAM EDITOR

C ▾

Run

Save

```

1 #include <stdio.h>
2 #define size 5
3
4 int front = -1, rear = -1;
5 int que[size];
6
7 void enqueue(int ele)
8 {
9     if (rear == size - 1)
10         printf("queue is full");
11     else
12     {
13         if (front == -1 && rear == -1)
14             front = rear = 0;
15         else
16             rear = rear + 1;
17
18         que[rear] = ele;
19     }
20 }
21

```

OUTPUT

30 20

INPUT

Your Input
here!

QUESTIONS 1 / 10 completed

Queue Using Array ▾

**QUEUE USING
ARRAYS**

Write a C program to implement a Queue using Arrays with operations such as insertion (enqueue), deletion (dequeue), display, and peek. The program should simulate a ticket booking counter where customers arrive in sequence and are served on a first-come-first-served basis. The program should

PROGRAM EDITOR

C ▾

Run

Save

```
21
22 void dequeue()
23 {
24     if (front == -1 && rear == -1)
25         printf("queue is empty");
26     else
27     {
28         if (front == rear)
29             front = rear = -1;
30         else
31             front = front + 1;
32     }
33 }
34
35 void display()
36 {
37     if (front == -1 && rear == -1)
38         printf("queue is empty");
39     else
40     {
41         for (int i = front; i <= rear; i++)
```

OUTPUT

30 20

QUESTIONS 1 / 10 completed

Queue Using Array ▾

**QUEUE USING
ARRAYS**

Write a C program to implement a Queue using Arrays with operations such as insertion (enqueue), deletion (dequeue), display, and peek. The program should simulate a ticket booking counter where customers arrive in sequence and are served on a first-come-first-served basis. The

PROGRAM EDITOR

C ▾

Run

Save

```
34
35 void display()
36 {
37     if (front == -1 && rear == -1)
38         printf("queue is empty");
39     else
40     {
41         for (int i = front; i <= rear; i++)
42             printf("%d ", que[i]);
43     }
44 }
45
46 int main()
47 {
48     enqueue(25);
49     enqueue(30);
50     enqueue(20);
51     dequeue(20);
52     display();
53     return 0;
54 }
```

OUTPUT

30 20