

Attribute Selectors

Attribute Selectors

Allows developers to select an element using attribute selectors

Types

1) has attribute

```
[href]{
  border: 5px solid blue;
}
[src]{
  border: 5px solid blue;
}
[controls]{
  border: 5px solid blue;
}
[dir]{
  border: 5px solid blue;
}
[type]{
  border: 5px solid blue;
}
```

2) attribute value equals to

```
[ target="_self" ] {
  border: 5px solid blue;
}

[ type="text" ] {
  border: 5px solid blue;
}
```

3) attribute value starts with

```
[name^="username"]{
  border: 5px solid blue;
}
[dir^="rtl"]{
  border: 5px solid blue;
}
[dir^="rtl"]{
  border: 5px solid blue;
}
[target^="_blank"]{
  border: 5px solid blue;
}
```

4) attribute value ends with

```
[href $='com']{
  font-size: xx-large;
}

[type $='xt']{
  font-size: xx-large;
}
```

5) attribute value contains

```
[target *= 'bl']{
  border: 5px solid blueviolet;
}
[alt *= 'ca']{
  width: 50%;
}
```

13 CSS Attribute

1. Attribute Selectors

1.1. Attribute Selectors Allows developers to select an element using attribute selectors Types

- 1) has attribute [href]{ border: 5px solid blue; } [src]{ border: 5px solid blue; } [controls]{ border: 5px solid blue; } [dir]{ border: 5px solid blue; } [type]{ border: 5px solid blue; }
- 2) attribute value equals to [target="_self"] { border: 5px solid blue; } [type="text"] { border: 5px solid blue; }
- 3) attribute value starts with [name^="username"]{ border: 5px solid blue; } [dir^="rtl"]{ border: 5px solid blue; } [dir^="rtl"]{ border: 5px solid blue; } [target^="_blank"]{ border: 5px solid blue; }
- 4) attribute value ends with [href \$='com']{ font-size: xx-large; } [type \$='xt']{ font-size: xx-large; }
- 5) attribute value contains [target *= 'bl']{ border: 5px solid blueviolet; } [alt *= 'ca']{ width: 50%; }

