

Data Preprocessing

- Major Tasks in Data Preprocessing: An Overview
- Data Cleaning
- Data Integration
- Data Reduction
- Data Transformation and Data Discretization
- Summary

Major Tasks in Data Preprocessing

- **Data cleaning**
 - Fill in missing values, smooth noisy data, identify or remove outliers, and resolve inconsistencies
- **Data integration**
 - Integration of multiple databases, data cubes, or files
- **Data reduction**
 - Dimensionality reduction
 - Data reduction
- **Data transformation and data discretization**
 - Normalization
 - Concept hierarchy generation

Data Cleaning

- Data in the Real World Is Dirty: Lots of potentially incorrect data, e.g., instrument faulty, human or computer error, transmission error
 - incomplete: lacking attribute values, lacking certain attributes of interest, or containing only aggregate data
 - e.g., *Occupation*=" " (missing data)
 - noisy: containing noise, errors, or outliers
 - e.g., *Salary*="−10" (an error)
 - inconsistent: containing discrepancies in codes or names, e.g.,
 - *Age*="42", *Birthday*="03/07/2010"
 - Was rating "1, 2, 3", now rating "A, B, C"
 - discrepancy between duplicate records
 - Intentional (e.g., *disguised missing* data)
 - Jan. 1 as everyone's birthday?

Incomplete (Missing) Data

- Data is not always available
 - E.g., many tuples have no recorded value for several attributes, such as customer income in sales data
- Missing data may be due to
 - inconsistent with other recorded data and thus deleted
 - data not entered due to misunderstanding
 - certain data may not be considered important at the time of entry
 - not register history or changes of the data
- Missing data may need to be inferred

How to Handle Missing Data?

- Ignore the tuple: usually done when class label is missing (when doing classification)—not effective when the % of missing values per attribute varies considerably
- Fill in the missing value manually: tedious + infeasible?
- Fill in it automatically with
 - a global constant : e.g., “unknown”, a new class?!
 - the attribute mean
 - the attribute mean for all samples belonging to the same class: smarter
 - the most probable value: inference-based such as Bayesian formula or decision tree

Noisy Data


- **Noise**: random error or variance in a measured variable
- **Incorrect attribute values** may be due to
 - faulty data collection instruments
 - data entry problems
 - data transmission problems
 - technology limitation
 - inconsistency in naming convention
- **Other data problems** which require data cleaning
 - duplicate records
 - incomplete data
 - inconsistent data

How to Handle Noisy Data?

- Binning
 - first sort data and partition into (equal-frequency) bins
 - then one can smooth by bin means, smooth by bin median, etc.
- Regression
 - smooth by fitting the data into regression functions
- Clustering
 - detect and remove outliers
- Combined computer and human inspection
 - detect suspicious values and check by human (e.g., deal with possible outliers)

Data Cleaning as a Process

- Data discrepancy detection
 - Use metadata (e.g., domain, range, dependency, distribution)
 - Check field overloading
 - Check uniqueness rule, consecutive rule and null rule
 - Use commercial tools
 - Data scrubbing: use simple domain knowledge (e.g., postal code, spell-check) to detect errors and make corrections
 - Data auditing: by analyzing data to discover rules and relationship to detect violators (e.g., correlation and clustering to find outliers)
- Data migration and integration
 - Data migration tools: allow transformations to be specified
 - ETL (Extraction/Transformation/Loading) tools: allow users to specify transformations through a graphical user interface
- Integration of the two processes
 - Iterative and interactive (e.g., Potter's Wheels)

-
- Data Preprocessing: An Overview
 - Major Tasks in Data Preprocessing
 - Data Cleaning
 - Data Integration 
 - Data Reduction
 - Data Transformation and Data Discretization
 - Summary

Data Integration

- **Data integration:**
 - Combines data from multiple sources into a coherent store
- Schema integration: e.g., $A.cust-id \equiv B.cust-\#$
 - Integrate metadata from different sources
- **Entity identification problem:**
 - Identify real world entities from multiple data sources, e.g., Bill Clinton = William Clinton
- Detecting and resolving data value conflicts
 - For the same real world entity, attribute values from different sources are different
 - Possible reasons: different representations, different scales, e.g., metric vs. British units

Handling Redundancy in Data Integration

- Redundant data occur often when integration of multiple databases
 - *Object identification*: The same attribute or object may have different names in different databases
 - *Derivable data*: One attribute may be a “derived” attribute in another table, e.g., annual revenue
- Redundant attributes may be able to be detected by *correlation analysis* and *covariance analysis*
- Careful integration of the data from multiple sources may help reduce/avoid redundancies and inconsistencies and improve mining speed and quality

Correlation Analysis (Nominal Data)

- **X² (chi-square) test**

$$\chi^2 = \sum \frac{(\text{Observed} - \text{Expected})^2}{\text{Expected}}$$

- The larger the X² value, the more likely the variables are related
- The cells that contribute the most to the X² value are those whose actual count is very different from the expected count
- Correlation does not imply causality
 - # of hospitals and # of car-theft in a city are correlated
 - Both are causally linked to the third variable: population

Chi-Square Calculation: An Example

	Play chess	Not play chess	Sum (row)
Like science fiction	250(90)	200(360)	450
Not like science fiction	50(210)	1000(840)	1050
Sum(col.)	300	1200	1500

- χ^2 (chi-square) calculation (numbers in parenthesis are expected counts calculated based on the data distribution in the two categories)

$$\chi^2 = \frac{(250 - 90)^2}{90} + \frac{(50 - 210)^2}{210} + \frac{(200 - 360)^2}{360} + \frac{(1000 - 840)^2}{840} = 507.93$$

- It shows that like_science_fiction and play_chess are correlated in the group

Correlation Analysis (Numeric Data)


- Correlation coefficient (also called **Pearson's product moment coefficient**)

$$r_{A,B} = \frac{\sum_{i=1}^n (a_i - \bar{A})(b_i - \bar{B})}{(n-1)\sigma_A\sigma_B} = \frac{\sum_{i=1}^n (a_i b_i) - n\bar{A}\bar{B}}{(n-1)\sigma_A\sigma_B}$$

where n is the number of tuples, \bar{A} and \bar{B} are the respective means of A and B , σ_A and σ_B are the respective standard deviation of A and B , and $\sum(a_i b_i)$ is the sum of the AB cross-product.

- If $r_{A,B} > 0$, A and B are positively correlated (A 's values increase as B 's). The higher, the stronger correlation.
- $r_{A,B} = 0$: independent; $r_{AB} < 0$: negatively correlated

Visually Evaluating Correlation



Scatter plots showing the similarity from -1 to 1.

Correlation (viewed as linear relationship)

- Correlation measures the linear relationship between objects
- To compute correlation, we standardize data objects, A and B , and then take their dot product

$$a'_k = (a_k - \text{mean}(A)) / \text{std}(A)$$

$$b'_k = (b_k - \text{mean}(B)) / \text{std}(B)$$

$$\text{correlation}(A, B) = A' \bullet B'$$

Covariance (Numeric Data)

- Covariance is similar to correlation

$$Cov(A, B) = E((A - \bar{A})(B - \bar{B})) = \frac{\sum_{i=1}^n (a_i - \bar{A})(b_i - \bar{B})}{n}$$

Correlation coefficient: $r_{A,B} = \frac{Cov(A, B)}{\sigma_A \sigma_B}$

where n is the number of tuples, \bar{A} and \bar{B} are the respective mean or **expected values** of A and B , σ_A and σ_B are the respective standard deviation of A and B .

- **Positive covariance:** If $Cov_{A,B} > 0$, then A and B both tend to be larger than their expected values.
- **Negative covariance:** If $Cov_{A,B} < 0$ then if A is larger than its expected value, B is likely to be smaller than its expected value.
- **Independence:** $Cov_{A,B} = 0$ but the converse is not true:
 - Some pairs of random variables may have a covariance of 0 but are not independent. Only under some additional assumptions (e.g., the data follow multivariate normal distributions) does a covariance of 0 imply independence.

Co-Variance: An Example


$$Cov(A, B) = E((A - \bar{A})(B - \bar{B})) = \frac{\sum_{i=1}^n (a_i - \bar{A})(b_i - \bar{B})}{n}$$

- It can be simplified in computation as

$$Cov(A, B) = E(A \cdot B) - \bar{A}\bar{B}$$

- Suppose two stocks A and B have the following values in one week:
(2, 5), (3, 8), (5, 10), (4, 11), (6, 14).
- Question: If the stocks are affected by the same industry trends, will their prices rise or fall together?
 - $E(A) = (2 + 3 + 5 + 4 + 6) / 5 = 20/5 = 4$
 - $E(B) = (5 + 8 + 10 + 11 + 14) / 5 = 48/5 = 9.6$
 - $Cov(A, B) = (2 \times 5 + 3 \times 8 + 5 \times 10 + 4 \times 11 + 6 \times 14) / 5 - 4 \times 9.6 = 4$
- Thus, A and B rise together since $Cov(A, B) > 0$.

Chapter 3: Data Preprocessing

- Data Preprocessing: An Overview
 - Data Quality
 - Major Tasks in Data Preprocessing
- Data Cleaning
- Data Integration
- Data Reduction 
- Data Transformation
- Summary

Data Reduction Strategies

- **Data reduction:** Obtain a reduced representation of the data set that is much smaller in volume but yet produces the same (or almost the same) analytical results
- Why data reduction? — A database/data warehouse may store terabytes of data. Complex data analysis may take a very long time to run on the complete data set.
- Data reduction strategies
 - **Dimensionality reduction**, e.g., remove unimportant attributes
 - Principal Components Analysis (PCA)
 - Feature subset selection, feature creation
 - **Numerosity reduction** (some simply call it: **Data Reduction**)
 - Regression and Log-Linear Models
 - Histograms, clustering, sampling
 - Data cube aggregation

Principal Component Analysis (Steps)

- Given N data vectors from n -dimensions, find $k \leq n$ orthogonal vectors (*principal components*) that can be best used to represent data
 - Normalize input data: Each attribute falls within the same range
 - Compute k orthonormal (unit) vectors, i.e., *principal components*
 - Each input data (vector) is a linear combination of the k principal component vectors
 - The principal components are sorted in order of decreasing “significance” or strength
 - Since the components are sorted, the size of the data can be reduced by eliminating the *weak components*, i.e., those with low variance (i.e., using the strongest principal components, it is possible to reconstruct a good approximation of the original data)
- Works for numeric data only

Attribute Subset Selection

- Another way to reduce dimensionality of data
- Redundant attributes
 - Duplicate much or all of the information contained in one or more other attributes
 - E.g., purchase price of a product and the amount of sales tax paid
- Irrelevant attributes
 - Contain no information that is useful for the data mining task at hand
 - E.g., students' ID is often irrelevant to the task of predicting students' GPA

Data Reduction

- Reduce data volume by choosing alternative, *smaller forms* of data representation
- **Parametric methods** (e.g., regression)
 - Assume the data fits some model, estimate model parameters, store only the parameters, and discard the data (except possible outliers)
 - Ex.: Log-linear models—obtain value at a point in m -D space as the product on appropriate marginal subspaces
- **Non-parametric** methods
 - Do not assume models
 - Major families: histograms, clustering, sampling, ...


Parametric Data Reduction: Regression and Log-Linear Models

- **Linear regression**
 - Data modeled to fit a straight line
 - Often uses the least-square method to fit the line
- **Multiple regression**
 - Allows a response variable Y to be modeled as a linear function of multidimensional feature vector

Types of Sampling


- **Simple random sampling**
 - There is an equal probability of selecting any particular item
- **Sampling without replacement**
 - Once an object is selected, it is removed from the population
- **Sampling with replacement**
 - A selected object is not removed from the population
- **Stratified sampling:**
 - Partition the data set, and draw samples from each partition (proportionally, i.e., approximately the same percentage of the data)
 - Used in conjunction with skewed data

Sampling: With or without Replacement




Sampling: Cluster or Stratified Sampling


Raw Data



Cluster/Stratified Sample



Chapter 3: Data Preprocessing

- Data Preprocessing: An Overview
 - Data Quality
 - Major Tasks in Data Preprocessing
- Data Cleaning
- Data Integration
- Data Reduction
- Data Transformation 

Data Transformation

- A function that maps the entire set of values of a given attribute to a new set of replacement values s.t. each old value can be identified with one of the new values
- Methods
 - Smoothing: Remove noise from data
 - Attribute/feature construction
 - New attributes constructed from the given ones
 - Aggregation: Summarization, data cube construction
 - Normalization: Scaled to fall within a smaller, specified range
 - min-max normalization
 - z-score normalization
 - Discretization: Concept hierarchy climbing

Data Normalization

- **Min-max normalization:** to $[new_min_A, new_max_A]$

$$v' = \frac{v - min_A}{max_A - min_A} (new_max_A - new_min_A) + new_min_A$$

- Ex. Let income range \$12,000 to \$98,000 normalized to [0.0, 1.0]. Then \$73,000 is mapped to $\frac{73,600 - 12,000}{98,000 - 12,000} (1.0 - 0) + 0 = 0.716$

- **Z-score normalization** (μ : mean, σ : standard deviation):

$$v' = \frac{v - \mu_A}{\sigma_A}$$

- Ex. Let $\mu = 54,000$, $\sigma = 16,000$. Then $\frac{73,600 - 54,000}{16,000} = 1.225$

ACTIVITY-5

Investigate the Handling of Redundancy in Data Integration.

Explore the usage of correlation analysis and covariance analysis towards eliminating the redundant attributes along with relevant computations and scenario analysis.