

# CS60075

# Natural Language Processing

# Autumn 2020

Module 4: Part 1  
Classification tasks in NLP


Sep 23 2020

# The text classification problem


- Given a text  $\mathbf{d} = (w_1, w_2, \dots, w_T) \in V^*$
- choose a label  $c_i \in C$
- Some applications
  - Sentiment Analysis  $\{\text{pos, neg, neutral}\}$
  - Spam filtering
  - Language identification
  - Age/gender identification
  - Authorship identification

# Who wrote which Federalist papers?

- 1787-8: anonymous essays try to convince New York to ratify U.S Constitution: Jay, Madison, Hamilton.
- Authorship of 12 of the letters in dispute
- 1963: solved by Mosteller and Wallace using Bayesian methods



James Madison



Alexander Hamilton

# Male or female author?

1. By 1925 present-day Vietnam was divided into three parts under French colonial rule. The southern region embracing Saigon and the Mekong delta was the colony of Cochinchina; the central area with its imperial capital at Hue was the protectorate of Annam...
2. Clara never failed to be astonished by the extraordinary felicity of her own name. She found it hard to trust herself to the mercy of fate, which had managed over the years to convert her greatest shame into one of her greatest assets...

# Positive or negative movie review?



- unbelievably disappointing



- Full of zany characters and richly applied satire, and some great plot twists



- this is the greatest screwball comedy ever filmed
- It was pathetic. The worst part about it was the boxing scenes.




# What is the subject of this article?

## MEDLINE Article



## MeSH Subject Category Hierarchy

- Antagonists and Inhibitors
- Blood Supply
- Chemistry
- Drug Therapy
- Embryology
- Epidemiology
- ...



# Classification Methods:

## Supervised Machine Learning

- *Input:*

- a document  $d$
- a fixed set of classes  $C = \{c_1, c_2, \dots, c_J\}$
- A training set of  $m$  hand-labeled documents  
 $(d_1, c_1), \dots, (d_m, c_m)$

- *Output:*

- a learned classifier  $\gamma: d \rightarrow c$

# The bag-of-words

- One challenge: the sequential representation  $(w_1, w_2, \dots, w_T)$  may have a different length  $T$  for every document.
- The bag-of-words is a fixed-length representation, which consists of a vector of word counts:
  - $w$  = It was the best of times, it was the worst of times
  - $x$  = [aardvark, ..., best, ..., it, ..., of, ..., zyther]
- The length of  $x$  is equal to the size of the vocabulary,  $V$ .



# Bayes' Rule Applied to Documents and Classes

- For a document  $d$  and a class  $c$

$$P(c | d) = \frac{P(d | c)P(c)}{P(d)}$$

# Naïve Bayes Classifier (I)

$$c_{MAP} = \operatorname{argmax}_{c \in C} P(c \mid d)$$

MAP is “maximum a posteriori” = most likely class

$$= \operatorname{argmax}_{c \in C} \frac{P(d \mid c)P(c)}{P(d)}$$

Bayes Rule

$$= \operatorname{argmax}_{c \in C} P(d \mid c)P(c)$$

Dropping the denominator

# Naïve Bayes Classifier (II)

$$c_{MAP} = \operatorname{argmax}_{c \in C} P(d | c)P(c)$$

$$= \operatorname{argmax}_{c \in C} P(x_1, x_2, \dots, x_n | c)P(c)$$

Document  $d$   
represented as  
features  $x_1..x_n$

But where will we get these probabilities?

# Multinomial Naïve Bayes Independence Assumptions

$$P(x_1, x_2, \dots, x_n \mid c)$$

- Bag of Words assumption
  - Assume position doesn't matter
- Conditional Independence
  - Assume the feature probabilities  $P(x_i \mid c)$  are independent given the class  $c$ .

$$P(x_1, \dots, x_n \mid c) = P(x_1 \mid c) \bullet P(x_2 \mid c) \bullet P(x_3 \mid c) \bullet \dots \bullet P(x_n \mid c)$$

# Multinomial Naïve Bayes Classifier

$$c_{MAP} = \operatorname{argmax}_{c \in C} P(x_1, x_2, \dots, x_n | c) P(c)$$

$$c_{NB} = \operatorname{argmax}_{c \in C} P(c_j) \prod_{x \in X} P(x | c)$$

↑  
This is why it's naïve!

[Jurafsky and Martin]

# Learning the Multinomial Naïve Bayes Model

- Maximum likelihood estimates
  1. simply use the frequencies in the data

$$\hat{P}(c_j) = \frac{\text{doccount}(C = c_j)}{N_{doc}}$$

$$\hat{P}(w_i | c_j) = \frac{\text{count}(w_i, c_j)}{\sum_{w \in V} \text{count}(w, c_j)}$$

# Parameter Estimation

$$\hat{P}(w_i | c_j) = \frac{\text{count}(w_i, c_j)}{\sum_{w \in V} \text{count}(w, c_j)}$$

fraction of times word  $w_i$  appears  
among all words in documents of topic  $c_j$

- Create mega-document for topic  $j$  by concatenating all docs in this topic
  - Use frequency of  $w$  in mega-document

# Problem with Maximum Likelihood

- What if we have seen no training documents with the word ***fantastic*** and classified in the topic **positive** ?

$$\hat{P}(\text{"fantastic"} \mid \text{positive}) = \frac{\text{count}(\text{"fantastic"}, \text{positive})}{\sum_{w \in V} \text{count}(w, \text{positive})} = 0$$

- Zero probabilities cannot be conditioned away, no matter the other evidence!

$$c_{MAP} = \operatorname{argmax}_c \hat{P}(c) \prod_i \hat{P}(x_i \mid c)$$



# Laplace Smoothing

$$\hat{P}(w_i | c) = \frac{\text{count}(w_i, c)}{\sum_{w \in V} (\text{count}(w, c))}$$

$$\hat{P}(w_i | c) = \frac{\text{count}(w_i, c) + 1}{\sum_{w \in V} (\text{count}(w, c) + 1)}$$

$$= \frac{\text{count}(w_i, c) + 1}{\left( \sum_{w \in V} \text{count}(w, c) \right) + |V|}$$

# Multinomial Naïve Bayes: Learning

- From training corpus, extract *Vocabulary*

- Calculate  $P(c_j)$  terms

- For each  $c_j$  in  $C$  do

$docs_j \leftarrow$  all docs with class  $= c_j$

$$P(c_j) \leftarrow \frac{|docs_j|}{|\text{total \# documents}|}$$

- Calculate  $P(w_k | c_j)$  terms

- $Text_j \leftarrow$  single doc containing all  $docs_j$

- For each word  $w_k$  in *Vocabulary*

$n_k \leftarrow$  # of occurrences of  $w_k$  in  $Text_j$

$$P(w_k | c_j) \leftarrow \frac{n_k + \alpha}{n + \alpha |Vocabulary|}$$

# Naive Bayes

- Very fast, low storage requirements
- Robust to irrelevant features
- A good, dependable baseline for text classification
  - But other classifiers give better accuracy