- Getting started with cuML's accelerator mode

Using accelerated hardware

- Train a CNN to classify handwritten digits on the MNIST dataset using Flax NNX API
- Train a Vision Transformer (ViT) for image classification with JAX
- Text classification with a transformer language model using JAX

Featured examples

- Train a miniGPT language model with JAX AI stack
- LoRA/QLoRA finetuning for LLM using Tunix
- Parameter-efficient fine-tuning of Gemma with LoRA and QLoRA
- Loading Hugging Face transformers checkpoints
- 8-bit integer quantisation in Keras
- Float8 training and inference with a simple transformer model
- Pretraining a transformer from scratch with KerasHub
- Simple MNIST convnet
- Image classification from scratch using Keras 3
- Image classification with KerasHub

```
import numpy as np
import matplotlib.pyplot as plt
price = np.array([50,100,80])
qty = np.array([2,1,3])
total = np.sum(price*qty)
discount = total*0.10
tax = (total-discount)*0.05
bill = total-discount+tax
print("Total Bill =", bill)
item = ["Item1","Item2","Item3"]
plt.figure(figsize=(12,4))
plt.subplot(131)
plt.bar(item,price*qty)
plt.title("Bar")
plt.subplot(132)
plt.pie(price*qty,labels=item,autopct='%1.1f%%')
plt.title("Pie")
plt.subplot(133)
plt.hist(price*qty,bins=3)
plt.title("Histogram")
plt.tight_layout()
plt.show()
```

```
Total Bill = 415.8
```