

Name: A Harsha Mukundha

Reg-No: 192324070

29. Write a C program to simulate the solution of Classical Process Synchronization Problem

Aim:

To simulate the solution to the Classical Process Synchronization Problem (e.g., Producer-Consumer or Dining Philosophers) using C programming and demonstrate the correct functioning of process synchronization.

Algorithm (Dining Philosophers Example):

1. Initialize the state of philosophers as "thinking."
2. Use semaphores to control access to shared resources (chopsticks).
3. Define `pickup()` and `putdown()` functions to manage chopsticks.
4. A philosopher alternates between thinking and eating.
5. Ensure no deadlock or starvation occurs using a synchronization mechanism.

Procedure:

1. Create threads to represent philosophers.
2. Use semaphores for chopstick access.
3. Implement synchronization logic to prevent deadlock (e.g., wait-and-signal operations).
4. Run the program and observe how philosophers alternate between thinking and eating.

Code:

```
#include <pthread.h>
```

```
#include <semaphore.h>
```

```
#include <stdio.h>
```

```
#include <unistd.h>
```

```
#define N 5
```

```
sem_t chopstick[N];
```

```
pthread_t philosopher[N];
```

```
void* dine(void* arg) {  
    int id = *(int*)arg;  
  
    while (1) {  
        printf("Philosopher %d is thinking.\n", id);  
        sleep(1);  
  
        sem_wait(&chopstick[id]);  
        sem_wait(&chopstick[(id + 1) % N]);  
  
        printf("Philosopher %d is eating.\n", id);  
        sleep(1);  
  
        sem_post(&chopstick[id]);  
        sem_post(&chopstick[(id + 1) % N]);  
  
        printf("Philosopher %d finished eating and starts thinking.\n", id);  
    }  
}  
  
int main() {  
    int id[N];
```

```

for (int i = 0; i < N; i++) {

    sem_init(&chopstick[i], 0, 1);

    id[i] = i;

}

```

```

for (int i = 0; i < N; i++)

    pthread_create(&philosopher[i], NULL, dine, &id[i]);

```

```

for (int i = 0; i < N; i++)

    pthread_join(philosopher[i], NULL);

```

```

return 0;


```

```

}

```

output



```

OnlineGDB
online compiler and debugger for c/c++

Welcome, Harsha Aripaka

Create New Project
My Projects
Classroom new
Learn Programming
Programming Questions
Upgrade
Logout

main.c
24 sem_wait(&chopstick[(id + 1) % N]);
25 }
26

Philosopher 0 is thinking.
Philosopher 1 is thinking.
Philosopher 2 is thinking.
Philosopher 3 is thinking.
Philosopher 4 is thinking.
Philosopher 1 is eating.
Philosopher 3 is eating.
Philosopher 1 finished eating and starts thinking.
Philosopher 1 is thinking.

```

