

Experiment 12 b): End-to-End Communication at Transport Layer (UDP)

AIM:

To implement a **UDP-based Echo (Ping) Client-Server** program using socket programming that measures **Round Trip Time (RTT)** for each packet and demonstrates **end-to-end communication** at the Transport Layer.

PROGRAM CODE

```
# -----  
  
# Title: UDP Ping (Echo) Client-Server Program  
  
# -----  
  
# Name:  
  
# Roll No:  
  
# Date:  
  
# -----  
  
  
import socket  
  
import time  
  
import sys  
  
  
# -----  
  
# UDP Ping Server  
  
# -----  
  
def udp_ping_server(host="127.0.0.1", port=12000):  
    server_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)  
    server_socket.bind((host, port))  
    print(f"[SERVER] Listening on {host}:{port}")  
  
    while True:  
        msg, client_address = server_socket.recvfrom(1024)  
        print(f"[SERVER] Received '{msg.decode()}' from {client_address}")  
        # Echo the same message back to client
```

```

server_socket.sendto(msg, client_address)

# -----
# UDP Ping Client
# -----

def udp_ping_client(server_host="127.0.0.1", server_port=12000, count=5):
    client_socket = socket.socket(socket.AF_INET, socket.SOCK_DGRAM)
    client_socket.settimeout(1) # 1 second timeout

    for i in range(1, count + 1):
        msg = f"Ping {i} {time.time()}"
        start = time.time()
        client_socket.sendto(msg.encode(), (server_host, server_port))

        try:
            data, _ = client_socket.recvfrom(1024)
            end = time.time()
            rtt = (end - start) * 1000
            print(f"Reply from {server_host}:{server_port} | {data.decode()} | RTT = {rtt:.2f} ms")
        except socket.timeout:
            print(f"Request {i} timed out")

    client_socket.close()

# -----
# Run as server or client
# -----

if __name__ == "__main__":
    if len(sys.argv) > 1 and sys.argv[1] == "server":

```

```
    udp_ping_server()
else:
    udp_ping_client()
```

SAMPLE INPUT AND OUTPUT

Step 1: Run the Server

```
$ python udp_ping.py server
```

Server Output:

```
[SERVER] Listening on 127.0.0.1:12000
[SERVER] Received 'Ping 1 1728575342.123' from ('127.0.0.1', 60642)
[SERVER] Received 'Ping 2 1728575343.125' from ('127.0.0.1', 60642)
[SERVER] Received 'Ping 3 1728575344.127' from ('127.0.0.1', 60642)
```

Step 2: Run the Client

```
$ python udp_ping.py
```

Client Output:

```
Reply from 127.0.0.1:12000 | Ping 1 1728575342.123 | RTT = 0.52 ms
Reply from 127.0.0.1:12000 | Ping 2 1728575343.125 | RTT = 0.47 ms
Reply from 127.0.0.1:12000 | Ping 3 1728575344.127 | RTT = 0.49 ms
Reply from 127.0.0.1:12000 | Ping 4 1728575345.129 | RTT = 0.54 ms
Reply from 127.0.0.1:12000 | Ping 5 1728575346.131 | RTT = 0.50 ms
(If the server doesn't reply in time, it shows "Request timed out.")
```

RESULT:

The **UDP Echo (Ping) Client-Server** program was successfully implemented. The client sent multiple ping messages to the server, and the server echoed them back. Round Trip Time (RTT) was measured for each message, demonstrating **unreliable but connectionless communication** at the **Transport Layer (UDP)**.