Prompt 1: Initial Code Generation

Write a beginner-friendly C++ console program that generates funny roast messages.
The program should ask the user to enter their name.
Store at least 10 roast templates using a {name} placeholder.
Randomly select one roast each time the program runs.
Replace {name} with the actual user input.
Handle empty input properly and display an error message.
Add comments in the code so that beginners can understand it easily.

** Prompt 2: Code Improvement / Refinement**

Improve the previous C++ roast generator program.
Make sure that if {name} appears multiple times in a roast template, it is replaced everywhere.
Also make the code cleaner, readable, and beginner-friendly.

** Prompt 3: Bug Identification**

My C++ roast generator program is not replacing {name} correctly in all cases.
Sometimes only one occurrence is replaced.
Why is this happening?

** Prompt 4: Bug Fix Request**

Fix the issue in my C++ program where {name} is not replaced everywhere in the string.
Modify the code so that all occurrences of {name} are replaced correctly.
Explain the fix in simple terms.

ChatGPT

Free offer ×

Prompt 1 (top)

```
Write a beginner-friendly C++ console program that generates funny roast messages.
The program should ask the user to enter their name.
Store at least 10 roast templates using a {name} placeholder.
Randomly select one roast each time the program runs.
Replace {name} with the actual user input.
Handle empty input properly and display an error message.
Add comments in the code so that beginners can understand it easily.
```

AI Response (Code below prompt)

C++

```cpp
#include <iostream>
#include <vector>
#include <cstdlib>  // For rand() and srand()
#include <ctime>    // For time()
using namespace std;

// Function to replace {name} with actual user input
string personalize(string roast, string name) {
    size_t pos = roast.find("{name}");

    if (pos != string::npos) {
        roast.replace(pos, 6, name); // Replace only st occurrence
    }
```

Ask anything

C++

```cpp
    }

    return roast;
}

int main() {
    string name;

    // Ask user for input
    cout << "Enter your name: ";
    getline(cin, name);

    // Handle empty input
    if (name.empty()) {
        cout << "Error: Name cannot be empty!" << endl;
        return 0;
    }

    // Store roast templates
    vector<string> roasts = {
        "{name}'s code runs so slowly that even dial-up internet feels fast.",
        "If laziness had a brand ambassador, it would be {name}.",
        "{name} doesn't debug code — they negotiate with bugs.",
        "{name}'s coding speed makes glaciers look fast.",
        "Even a calculator gets confused by {name}'s logic.",
        "{name} writes code like it's a suspense thr r — nothing works till the end.",
        "If errors were money, {name} would be a bil aire.",
        "{name}'s keyboard deserves an award for suffering.",
        "{name} writes code so bad, even AI asks for help.",
```

Ask anything

C++

```cpp
        "{name} writes code so bad, even AI asks for help.",
        "{name}'s bugs have bugs."
    };

    // Initialize random seed
    srand(time(0));

    // Generate random index
    int index = rand() % roasts.size();

    // Personalize roast
    string finalRoast = personalize(roasts[index], name);

    // Display output
    cout << finalRoast << endl;

    return 0;
}
```

OUTOUT

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Warning: PowerShell detected that you might be using a screen reader and has disabled PSReadLine for compatibility purposes. If you want to re-enable it, run 'Import-Module PSRea
dLine'.

PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual> cd "c:\Users\Nikita\OneDrive\Desktop\focp2-lab manual\" ; if ($?) { g++ tempCodeRunnerFile.cpp -o tempCodeRunnerFile } ; if
($?) { .\tempCodeRunnerFile }
Enter your name: HARSHIT
If errors were money, HARSHIT would be a billionaire.
PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual>
```

Prompt 2 (top)

```
Improve the previous C++ roast generator program.
Make sure that if {name} appears multiple times in a roast template, it is replaced everywhere.
Also make the code cleaner, readable, and beginner-friendly.
```

AI Response (Improved Code)

C++

```cpp
#include <iostream>
#include <vector>
#include <cstdlib>
#include <ctime>
using namespace std;

// Function to replace ALL occurrences of {name}
string personalize(string roast, const string& name) {
    size_t pos = 0;

    // Loop to replace every occurrence of "{name}"
    while ((pos = roast.find("{name}", pos)) != string::npos) {
        roast.replace(pos, 6, name);
        pos += name.length(); // Move forward after ...cement
    }

    return roast;
```

C++

```cpp
}

int main() {
    string name;

    // Ask user for input
    cout << "Enter your name: ";
    getline(cin, name);

    // Handle empty input
    if (name.empty()) {
        cout << "Error: Name cannot be empty!" << endl;
        return 0;
    }

    // Roast templates (some contain multiple {name})
    vector<string> roasts = {
        "{name}, your code is so slow that even {name}'s shadow arrives earlier.",
        "If laziness had a face, it would look exactly like {name}.",
        "{name} doesn't debug code — {name} just hopes the bugs fix themselves.",
        "{name}'s coding speed makes glaciers look fast.",
        "Even a calculator gets confused by {name}'s logic.",
        "{name} writes code like a mystery — even {name} doesn't know what it does.",
        "If errors were money, {name} would be a billionaire.",
        "{name}'s keyboard deserves an award for suffering.",
        "{name} writes code so bad, even AI asks {name} for help.",
        "{name}'s bugs have bugs — and they blame {name}."
    };
```

```cpp
};

// Initialize random seed for different output each run
srand(time(0));

// Select random roast
int index = rand() % roasts.size();

// Personalize selected roast
string finalRoast = personalize(roasts[index], name);

// Display result
cout << finalRoast << endl;

return 0;
}
```

OUPUT

```
PROBLEMS   OUTPUT   DEBUG CONSOLE   TERMINAL   PORTS

Warning: PowerShell detected that you might be using a screen reader and has disabled PSReadLine for compatibility purposes. If you want to re-enable it, run 'Import-Module PSRea
dLine'.

PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual> cd "c:\Users\Nikita\OneDrive\Desktop\focp2-lab manual\" ; if ($?) { g++ tempCodeRunnerFile.cpp -o tempCodeRunnerFile } ; if
($?) { .\tempCodeRunnerFile }
Enter your name: HARSHIT
HARSHIT doesn't debug code ΓÇö HARSHIT just hopes the bugs fix themselves.
PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual>
```

Prompt 3: Bug Identification

Prompt:

```
My C++ roast generator program is not replacing {name} correctly in all cases.
Sometimes only one occurrence is replaced.
Why is this happening?
```

AI Response:

```
This issue happens because your program is using the find() function only once.

The find("{name}") function returns the position of the first occurrence of "{name}" in the string.

After replacing it, your code does not continue searching for other occurrences.

So if "{name}" appears multiple times in a roast template, only the first one gets replaced.

The remaining occurrences stay unchanged.

To fix this, you should use a loop (such as a while loop).

The loop will repeatedly search for "{name}" and rep... it until no more occurrences are found.
```

Prompt 4: Bug Fix Request

Prompt:

```
Fix the issue in my C++ program where {name} is not replaced everywhere in the string.
Modify the code so that all occurrences of {name} are replaced correctly.
Explain the fix in simple terms.
```

AI Response:

C++

```cpp
// Fixed function to replace ALL occurrences of {name}
string personalize(string roast, const string& name) {
    size_t pos = 0;

    // Keep replacing until no {name} is left
    while ((pos = roast.find("{name}", pos)) != string::npos) {
        roast.replace(pos, 6, name);
        pos += name.length(); // Move forward after replacement
    }

    return roast;
}
```

AFTER FIXING ALL BUGS

CODE

```
#include <iostream>
#include <vector>
#include <cstdlib>
#include <ctime>

using namespace std;

// Function to replace {name} with actual user input
string personalize(string roast, string name) {
   size_t pos = roast.find("{name}");
   if (pos != string::npos) {=
      roast.replace(pos, 6, name);
   }
   return roast;
}

int main() {
   string name;

   cout << "Enter your name: ";
   getline(cin, name);

   // Handle empty input
   if (name.empty()) {
      cout << "Please enter a valid name!" << endl;
      return 0;
   }
```

```
    // Roast templates
    vector<string> roasts = {
        "{name} writes code so slow that even a turtle switched to Python.",
        "If procrastination were an Olympic sport, {name} would win gold.",
        "{name}'s debugging style is staring at the screen until the bug leaves.",
        "{name}'s code runs so slowly that dial-up internet feels fast.",
        "If laziness had a brand ambassador, it would be {name}.",
        "{name} doesn't debug code — they negotiate with bugs.",
        "{name}'s code has more errors than a broken calculator.",
        "{name} types so slow, even autocorrect gave up.",
        "{name}'s logic is like WiFi — weak and unstable.",
        "Even AI refuses to fix {name}'s code."
    };

    // Seed random generator
    srand(time(0));

    int index = rand() % roasts.size();

    string finalRoast = personalize(roasts[index], name);

    cout << "\n🔥 Roast Generator 🔥 " << endl;
    cout << finalRoast << endl;

    return 0;
}
```

OUTPUT

```
PROBLEMS    OUTPUT    DEBUG CONSOLE    TERMINAL    PORTS                                                    Code

Warning: PowerShell detected that you might be using a screen reader and has disabled PSReadLine for compatibility purposes. If you want to re-enable it, run 'Import-Module PSRea
dLine'.

PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual> cd "c:\Users\Nikita\OneDrive\Desktop\focp2-lab manual\" ; if ($?) { g++ tempCodeRunnerFile.cpp -o tempCodeRunnerFile } ; if
($?) { .\tempCodeRunnerFile }
Enter your name: harshit

=f0Ñ Roast Generator =f0Ñ
harshit's code has more errors than a broken calculator.
PS C:\Users\Nikita\OneDrive\Desktop\focp2-lab manual>
```