





| | 6 1 | 5 l | 4 7 3 | l 2 l 1 |
|---------------|----------|----------|---|---|
| | <u> </u> | <u> </u> | PARTS LIST | |
| | ITEM | QTY | PART NUMBER | DESCRIPTION |
| | 1 | 1 | K24_0_128_5032244006 | |
| | 2 | 1 | Spur Gear1 | |
| D | 3 | 1 | Spur Gear2 | D |
| | 4 | 2 | SKF_7200 BEP | BA1_001_101-Angular contact ball bearings, single row |
| | 5 | 1 | nut1 | |
| | 6 | 1 | Bottom Clutch Sleve | |
| | 7 | 1 | Middle seperators | |
| | 8 | 1 | Spring Clutch | |
| | 9 | 2 | Bearing Slleve | |
| | 10 | 1 | Cover Plate | |
| | 11 | 1 | Cover Plate 2 | |
| | 12 | 1 | Bearing Plate | |
| | 13 | 4 | Support Beams | |
| | 14 | 8 | ANSI B18.2.3.4M - M5 x 0.8x8 | Metric Hex Flange Screws |
| | 15 | 8 | ANSI B18.3.4M - M4 x 0.7 x 16, BHSBHCSM | Broached Hexagon Socket Button Head Cap Screw - Metric |
| | 16 | 3 | ANSI B18.3.4M - M3 x 0.5 x 3, BHSBHCSM | Broached Hexagon Socket Button Head Cap Screw - Metric |
| | 17 | 1 | Rotary plate hoder | |
| | 18 | 1 | rotary plate | |
| | 19 | 1 | top plate | |
| \rightarrow | 20 | 2 | Support Beams Short | € |
| | 21 | 4 | ANSI B18.3.4M - M4 x 0.7 x 8, BHSBHCSM | Broached Hexagon Socket Button Head Cap Screw - Metric |
| | 22 | 1 | HEDS-9100#A00 Incremental Encoder Optical | |
| | 23 | 2 | Encoder Stand | |
| | 24 | 1 | Pusher Rotary Holder | |
| | 25 | 1 | Pusher | |
| В | 26 | 9 | IFI - I0.138 - 32, HFNI(1) | Hex Flange Nut |
| | 27 | 4 | ANSI B18.6.7M - M3x0.5 x 5, CRPHMSTIM(1) | Cross Recessed Pan Head Machine Screw - Type I - Metric |
| | 28 | 2 | Pusher Ends | |
| | 29 | 2 | IFI 513 - M2x0.4 x 5, CRFCHMSTIM(1) | Cross Recessed Flat Countersunk Head Machine Screw - |
| | | | | Type I - Metric |
| | 30 | 2 | ANSI B18.6.3 - No. 2 - 56 - 3/8, CRPHMSTII(1) | Cross Recessed Pan Head Machine Screw - Type IA |
| | 31 | 2 | ASME B18.6.3 - 2-56 | Chamfered Bottom Hex Machine Screw Nuts |
| | 32 | 1 | Spring | |
| | 33 | 2 | ANSI B18.6.7M - M2x0.4 x 5, CRPHMSTIM(1) | Cross Recessed Pan Head Machine Screw - Type I - Metric |
| | 34 | 4 | ANSI B18.6.7M - M4x0.7 x 8, CRPHMSTIM(1) | Cross Recessed Pan Head Machine Screw - Type I - Metric |
| | 35 | 1 | 110204_AMAX26_EB_4_5W_SL_2WE | |
| Α | | | Designed by | Checked by Approved by Date 6/23/2023 |
| | | | ASUS | 0/23/2023 |
| | | | | FMD Project 02-1 Edition Sheet 2 / 2 |
| | 6 | <u> </u> | 4 1 3 | 2 1 |
| | · | • | T | · |