

727. Minimum Window Subsequence Premium

Hard Topics Companies Hint

Given strings `s1` and `s2`, return *the minimum contiguous substring part of `s1`, so that `s2` is a subsequence of the part*.
If there is no such window in `s1` that covers all characters in `s2`, return the empty string `""`. If there are multiple such minimum-length windows, return the one with the **left-most starting index**.

Example 1:

Input: `s1 = "abcdebddde", s2 = "bde"`
Output: `"bcde"`
Explanation:
"bcde" is the answer because it occurs before "bdde" which has the same length.
"deb" is not a smaller window because the elements of `s2` in the window must occur in order.

Example 2:

Input: `s1 = "jmeqksfrsdcmsiwvaovztaqenprpvnbstl", s2 = "u"`
Output: `""`

Constraints:

- `1 <= s1.length <= 2 * 104`
- `1 <= s2.length <= 100`
- `s1` and `s2` consist of lowercase English letters.

Seen this question in a real interview before? 1/5

Yes No

Accepted 93.8K | Submissions 215.5K | Acceptance Rate 43.5%

Topics

StringDynamic ProgrammingSliding Window

Companies

0 - 6 months

Google2eBay2

6 months ago

Meta4

Hint 1

Let `dp[j][e] = s` be the largest index for which `S[s:e+1]` has `T[:j]` as a substring.

Similar Questions

Minimum Window SubstringHard

Longest Continuous Increasing SubsequenceEasy

Discussion (6)