

759. Employee Free Time Premium

Hard Topics Companies Hint

We are given a list `schedule` of employees, which represents the working time for each employee.

Each employee has a list of non-overlapping `Intervals`, and these intervals are in sorted order.

Return the list of finite intervals representing **common, positive-length free time** for *all* employees, also in sorted order.

(Even though we are representing `Intervals` in the form `[x, y]`, the objects inside are `Intervals`, not lists or arrays. For example, `schedule[0][0].start = 1`, `schedule[0][0].end = 2`, and `schedule[0][0][0]` is not defined). Also, we wouldn't include intervals like `[5, 5]` in our answer, as they have zero length.

Example 1:

Input: `schedule = [[[1,2],[5,6]], [[1,3]], [[4,10]]]`
Output: `[[3,4]]`
Explanation: There are a total of three employees, and all common free time intervals would be `[-inf, 1]`, `[3, 4]`, `[10, inf]`. We discard any intervals that contain `inf` as they aren't finite.

Example 2:

Input: `schedule = [[[1,3],[6,7]], [[2,4]], [[2,5],[9,12]]]`
Output: `[[5,6],[7,9]]`

Constraints:

- `1 <= schedule.length , schedule[i].length <= 50`
- `0 <= schedule[i].start < schedule[i].end <= 10^8`

Seen this question in a real interview before? 1/5

Yes No

Accepted **156.1K** | Submissions **215.8K** | Acceptance Rate **72.3%**

Topics

ArraySortingHeap (Priority Queue)

Companies

0 - 3 months

Pinterest2Roblox2

0 - 6 months

Google6Airbnb2

6 months ago

DoorDash2GE Healthcare2

Hint 1

Take all the intervals and do an "events" (or "line sweep") approach - an event of (x, OPEN) increases the number of active intervals, while (x, CLOSE) decreases it. Processing in sorted order from left to right, if the number of active intervals is zero, then you crossed a region of common free time.

Similar Questions

Merge IntervalsMedium

Interval List IntersectionsMedium

Discussion (15)