## 359. Logger Rate Limiter Premium



Design a logger system that receives a stream of messages along with their timestamps. Each **unique** message should only be printed **at most every 10 seconds** (i.e. a message printed at timestamp t will prevent other identical messages from being printed until timestamp t + 10).

All messages will come in chronological order. Several messages may arrive at the same timestamp.

Implement the Logger class:

- Logger() Initializes the logger object.
- bool shouldPrintMessage(int timestamp, string message) Returns true if the message should be printed in the given timestamp, otherwise returns false.

## Example 1:

```
Input
["Logger", "shouldPrintMessage", "shouldPrintMessage",
"shouldPrintMessage", "shouldPrintMessage",
"shouldPrintMessage", "shouldPrintMessage"]
[[], [1, "foo"], [2, "bar"], [3, "foo"], [8, "bar"], [10,
"foo"], [11, "foo"]]
Output
[null, true, true, false, false, false, true]
Explanation
Logger logger = new Logger();
logger.shouldPrintMessage(1, "foo"); // return true, next
allowed timestamp for "foo" is 1 + 10 = 11
logger.shouldPrintMessage(2, "bar"); // return true, next
allowed timestamp for "bar" is 2 + 10 = 12
logger.shouldPrintMessage(3, "foo"); // 3 < 11, return false</pre>
logger.shouldPrintMessage(8, "bar"); // 8 < 12, return false</pre>
logger.shouldPrintMessage(10, "foo"); // 10 < 11, return false</pre>
logger.shouldPrintMessage(11, "foo"); // 11 >= 11, return
```

## Constraints:

- 0 <= timestamp <= 10<sup>9</sup>
- Every times tamp will be passed in non-decreasing order (chronological order).

true, next allowed timestamp for "foo" is 11 + 10 = 21

