256. Paint House

Medium · 🏷 Topics · 🏢 Companies

There is a row of `n` houses, where each house can be painted one of three colors: red, blue, or green. The cost of painting each house with a certain color is different. You have to paint all the houses such that no two adjacent houses have the same color.

The cost of painting each house with a certain color is represented by an `n x 3` cost matrix `costs`.

- For example, `costs[0][0]` is the cost of painting house `0` with the color red; `costs[1][2]` is the cost of painting house 1 with color green, and so on...

Return *the minimum cost to paint all houses*.

Example 1:

```
Input: costs = [[17,2,17],[16,16,5],[14,3,19]]
Output: 10
Explanation: Paint house 0 into blue, paint house 1 into green,
paint house 2 into blue.
Minimum cost: 2 + 5 + 3 = 10.
```

Example 2:

```
Input: costs = [[7,6,2]]
Output: 2
```

Constraints:

- `costs.length == n`
- `costs[i].length == 3`
- `1 <= n <= 100`
- `1 <= costs[i][j] <= 20`

Seen this question in a real interview before?   1/5

Yes   No

Accepted **217.5K** | Submissions **345K** | Acceptance Rate **63.0%**

🏷 Topics ⌃

Array   Dynamic Programming

🏢 Companies ⌃

0 - 6 months

LinkedIn ⑤   Uber ②

6 months ago

Google ②

🗒 Similar Questions ⌃

House Robber	Medium
House Robber II	Medium
Paint House II 🔒	Hard
Paint Fence 🔒	Medium
Minimum Path Cost in a Grid	Medium

💬 Discussion (13) ⌄