

Homework 7
HUID: 71238520

Out: April 10, 2017
Due: April 21, 2017 (4:59 pm)

1 Problem 1

If we restrict the problems we look at, sometimes hard problems like counting the number of independent sets in a graph become solvable. For instance, consider a graph that is a line on n vertices. (That is, the vertices are labelled 1 to n , and there is an edge from 1 to 2, 2 to 3, etc.) How many independent sets are there on a line graph? Also, how many independent sets are there on a cycle of n vertices? (Hint: In this case, we want to express your answer in terms of a family of numbers like For n vertices the number of independent sets is the n th prime. And that's not the answer.)

Similarly, describe how you could quickly compute the number of independent sets on a complete binary tree. (Here, just explain how to compute this number.) Calculate the number of independent sets on a complete binary tree with 127 nodes. (Warning: it's a pretty big number.)

1.1 Solution

2 Problem 2

Consider the problem MAX- k -CUT, which is like the MAXCUT algorithm, except that we divide the vertices into k disjoint sets, and we want to maximize the number of edges between sets. Explain how to generalize both the randomized and the local search algorithms for MAX CUT to MAX- k -CUT and prove bounds on their performance.

2.1 Solution

To generalize the MAXCUT randomized algorithm to MAX- k -CUT, we randomly assign vertices to the k disjoint sets, by using a random number generator.

The probability that a given edge crosses sets is $1 -$ the probability that both its vertices are in the same set, which is $1 - k(\frac{1}{k} \cdot \frac{1}{k}) = 1 - \frac{1}{k} = \frac{k-1}{k}$. This means that on average, a fraction of $\frac{k}{k-1}$ of the total edges will cross between sets. Since the most we could have is for all edges to cross between sets, this random assignment will be, on average, within a factor of $\frac{k-1}{k}$ of the optimum.

For local search algorithms, we select an edge E and move

3 Problem 3

Prove that if there exists a polynomial time algorithm for approximating the maximum clique in a graph to within a factor of 2, then there is a polynomial time algorithm for approximating the maximum clique in a graph to within a factor of $(1 + \epsilon)$ for any constant $\epsilon > 0$. The degree of the polynomial may depend on ϵ . Hint: for a starting graph $G = (V, E)$, consider the graph $G \times G = (V, E)$, where the vertex set V of $G \times G$ is the set of ordered pairs $V = V \times V$, and $\{(u, v), (w, x)\} \in E$ if and only if

$$[\{(u, w)\} \in E \text{ or } u = w] \text{ and } [\{(v, x)\} \in E \text{ or } v = x]. \quad (1)$$

If G has a clique of size k , then how large a clique does G have?

3.1 Solution

4 Problem 4

We consider the following scheduling problem, similar to one that we studied before: we have two machines, and a set of jobs $j_1, j_2, j_3, \dots, j_n$ that we have to process. We place a subset of the jobs on each machine. Each job j_i has an associated running time r_i . The load on the machine is the sum of the running times of the jobs placed on it. The goal is to minimize the completion time, sometimes called the *makespan*, which is the maximum load over all machines.

Consider the following local search algorithm. Start with any arbitrary assignment of jobs to machines. We then repeatedly *swap* a single job from

one machine to another, if that swap will *strictly reduce* the completion time. (We won't make a move if the completion time stays the same, and only one job moves in each swap.) If a swap is not possible, we are in a stable state. For example, suppose we had jobs with running times 1, 2, 3, 4, and 5, and we started with the jobs with running times 1, 2, and 3 on machine 1, and the jobs with running times 4 and 5 on machine 2. This is a stable state, but it is not optimal; the minimum possible completion time is 8, and this stable state has completion time 9.

Prove that the local search algorithm always terminates in a stable state, and that the completion time is within a factor of $4/3$ of the optimal.

4.1 Solution

Given that we have a set of jobs $j_1, j_2, j_3, \dots, j_n$, and two machines M_1 and M_2 . We use local search to find an optimum assignment of jobs to M_1 or M_2 . The solution space S can be represented by an array of length n that contains 1 or 2, where S_i corresponds to the machine assignment of j_i . There are therefore 2^n solutions in the solution space. If for some job assignment,

Even for the best possible solution, the *makespan* is at least as big as the biggest job, or at least as big as half the sum of the jobs. [From PSET3.]