

## TCP OUTPUTS:

### client.c :

```
#include <arpa/inet.h> // inet_addr()
#include <netdb.h>
#include <stdio.h>
#include <stdlib.h>
#include <string.h>
#include <strings.h> // bzero()
#include <sys/socket.h>
#include <unistd.h> // read(), write(), close()
#define MAX 80
#define PORT 8080
#define SA struct sockaddr
void func(int sockfd)
{
    char buff[MAX];
    int n;
    for (;;) {
        bzero(buff, sizeof(buff));
        printf("Enter the string : ");
        n = 0;
        while ((buff[n++] = getchar()) != '\n')
            ;
        write(sockfd, buff, sizeof(buff));
        bzero(buff, sizeof(buff));
        read(sockfd, buff, sizeof(buff));
        printf("From Server : %s", buff);
        if ((strncmp(buff, "exit", 4)) == 0) {
            printf("Client Exit...\n");
            break;
        }
    }
}

int main()
{
    int sockfd, connfd;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
```

```

        printf("Socket successfully created..\n");
        bzero(&servaddr, sizeof(servaddr));

        // assign IP, PORT
        servaddr.sin_family = AF_INET;
        servaddr.sin_addr.s_addr = inet_addr("127.0.0.1");
        servaddr.sin_port = htons(PORT);

        // connect the client socket to server socket
        if (connect(sockfd, (SA*)&servaddr, sizeof(servaddr))
            != 0) {
            printf("connection with the server failed...\n");
            exit(0);
        }
        else
            printf("connected to the server..\n");

        // function for chat
        func(sockfd);

        // close the socket
        close(sockfd);
    }

```

## server.c :

```

#include <stdio.h>
#include <netdb.h>
#include <netinet/in.h>
#include <stdlib.h>
#include <string.h>
#include <sys/socket.h>
#include <sys/types.h>
#include <unistd.h> // read(), write(), close()
#define MAX 80
#define PORT 8080
#define SA struct sockaddr

// Function designed for chat between client and server.
void func(int connfd)
{
    char buff[MAX];
    int n;
    // infinite loop for chat
    for (;;) {
        bzero(buff, MAX);

```

```

        // read the message from client and copy it in buffer
        read(connfd, buff, sizeof(buff));
        // print buffer which contains the client contents
        printf("From client: %s\t To client : ", buff);
        bzero(buff, MAX);
        n = 0;
        // copy server message in the buffer
        while ((buff[n++] = getchar()) != '\n')
            ;

        // and send that buffer to client
        write(connfd, buff, sizeof(buff));

        // if msg contains "Exit" then server exit and chat ended.
        if (strncmp("exit", buff, 4) == 0) {
            printf("Server Exit...\n");
            break;
        }
    }
}

```

// Driver function

int main()

```

{
    int sockfd, connfd, len;
    struct sockaddr_in servaddr, cli;

    // socket create and verification
    sockfd = socket(AF_INET, SOCK_STREAM, 0);
    if (sockfd == -1) {
        printf("socket creation failed...\n");
        exit(0);
    }
    else
        printf("Socket successfully created..\n");
    bzero(&servaddr, sizeof(servaddr));

    // assign IP, PORT
    servaddr.sin_family = AF_INET;
    servaddr.sin_addr.s_addr = htonl(INADDR_ANY);
    servaddr.sin_port = htons(PORT);

    // Binding newly created socket to given IP and verification
    if ((bind(sockfd, (SA*)&servaddr, sizeof(servaddr))) != 0) {
        printf("socket bind failed...\n");
        exit(0);
    }
}

```

```

    }
    else
        printf("Socket successfully binded..\n");

    // Now server is ready to listen and verification
    if ((listen(sockfd, 5)) != 0) {
        printf("Listen failed...\n");
        exit(0);
    }
    else
        printf("Server listening..\n");
    len = sizeof(cli);

    // Accept the data packet from client and verification
    connfd = accept(sockfd, (SA*)&cli, &len);
    if (connfd < 0) {
        printf("server accept failed...\n");
        exit(0);
    }
    else
        printf("server accept the client...\n");

    // Function for chatting between client and server
    func(connfd);

    // After chatting close the socket
    close(sockfd);
}

```

```
stud_user@stud:~$ cd Desktop
stud_user@stud:~/Desktop$ gcc client.c -o client
stud_user@stud:~/Desktop$ ./client
Socket successfully created..
connected to the server..
Enter the string : Welcome to the lab
From Server : Have a good day
Enter the string : exit
From Server : exit
Client Exit...
stud_user@stud:~/Desktop$
```

```
stud_user@stud:~$ cd Desktop
stud_user@stud:~/Desktop$ gcc server.c -o server
stud_user@stud:~/Desktop$ ./server
Socket successfully created..
Socket successfully binded..
Server listening..
server accept the client...
From client: Welcome to the lab
        To client : Have a good day
From client: exit
        To client : exit
Server Exit...
stud_user@stud:~/Desktop$
```