

Wireshark filters

ARP FILTER

Wireshark interface showing an ARP filter applied to the packet list. The filter bar contains 'arp'. The packet list shows several ARP requests and replies. The packet details pane shows the structure of an ARP request.

No.	Time	Source	Destination	Protocol	Length	Info
7	4.964043	fa:40:ed:4b:59:13	HonHaiPrecis_14:3a:...	ARP	42	Who has 192.168.92.102? Tell 192.168.92.198
8	4.964080	HonHaiPrecis_14:3a:...	fa:40:ed:4b:59:13	ARP	42	192.168.92.102 is at 34:68:95:14:3a:e7
432	25.797022	fa:40:ed:4b:59:13	HonHaiPrecis_14:3a:...	ARP	42	Who has 192.168.92.102? Tell 192.168.92.198
433	25.797058	HonHaiPrecis_14:3a:...	fa:40:ed:4b:59:13	ARP	42	192.168.92.102 is at 34:68:95:14:3a:e7
447	77.420602	HonHaiPrecis_14:3a:...	fa:40:ed:4b:59:13	ARP	42	Who has 192.168.92.198? Tell 192.168.92.102
448	77.434102	fa:40:ed:4b:59:13	HonHaiPrecis_14:3a:...	ARP	42	192.168.92.198 is at fa:40:ed:4b:59:13
449	77.919340	fa:40:ed:4b:59:13	HonHaiPrecis_14:3a:...	ARP	42	Who has 192.168.92.102? Tell 192.168.92.198
450	77.919377	HonHaiPrecis_14:3a:...	fa:40:ed:4b:59:13	ARP	42	192.168.92.102 is at 34:68:95:14:3a:e7
723	99.935137	fa:40:ed:4b:59:13	HonHaiPrecis_14:3a:...	ARP	42	Who has 192.168.92.102? Tell 192.168.92.198
724	99.935160	HonHaiPrecis_14:3a:...	fa:40:ed:4b:59:13	ARP	42	192.168.92.102 is at 34:68:95:14:3a:e7

Frame 450: 42 bytes on wire (336 bits), 42 bytes captured (336 bits) on interface \Device\NPF...
> Ethernet II, Src: HonHaiPrecis_14:3a:e7 (34:68:95:14:3a:e7), Dst: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13)
> Address Resolution Protocol (reply)

0000 fa 40 ed 4b 59 13 34 68 95 14 3a e7 08 06 00 01 :@.KY:4h ...
0010 08 00 06 04 00 02 34 68 95 14 3a e7 c0 a8 5c 664h @.i.%
0020 fa 40 ed 4b 59 13 c0 a8 5c c6 :@.KY:4h ...

UDP FILTER

Wireshark interface showing a UDP filter applied to the packet list. The filter bar contains 'udp'. The packet list shows a large number of UDP packets. The packet details pane shows the structure of a UDP packet.

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	87	443 → 65426 Len=25
2	0.000640	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	87	443 → 65426 Len=25
3	0.018686	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	87	443 → 65426 Len=25
4	0.135294	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	905	443 → 65426 Len=843
5	0.137705	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	339	443 → 65426 Len=277
6	0.137965	2409:40d6:1004:690b:...	2404:6800:4002:825:...	UDP	99	65426 → 443 Len=37
7	0.182959	2409:40d6:1004:690b:...	2404:6800:4002:816:...	UDP	91	54162 → 443 Len=29
8	0.197444	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	86	443 → 65426 Len=24
9	0.234829	2404:6800:4002:816:...	2409:40d6:1004:690b:...	UDP	88	443 → 54162 Len=26
12	0.933580	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	142	443 → 56532 Len=80
13	0.949031	2409:40d6:1004:690b:...	2404:6800:4002:825:...	UDP	95	56532 → 443 Len=33
14	1.042775	2409:40d6:1004:690b:...	2404:6800:4002:816:...	UDP	91	54162 → 443 Len=29
15	1.089309	2404:6800:4002:816:...	2409:40d6:1004:690b:...	UDP	88	443 → 54162 Len=26
16	1.136504	2409:40d6:1004:690b:...	2404:6800:4002:825:...	UDP	91	56532 → 443 Len=29
17	1.194205	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	88	443 → 56532 Len=26
18	1.403960	2409:40d6:1004:690b:...	2404:6800:4002:825:...	UDP	91	56532 → 443 Len=29
19	1.453543	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	88	443 → 56532 Len=26
20	1.606955	2409:40d6:1004:690b:...	2404:6800:4002:824:...	UDP	91	51792 → 443 Len=29
21	1.669535	2409:40d6:1004:690b:...	2404:6800:4002:825:...	UDP	91	56532 → 443 Len=29
22	1.671294	2404:6800:4002:824:...	2409:40d6:1004:690b:...	UDP	87	443 → 51792 Len=25
23	1.719301	2404:6800:4002:825:...	2409:40d6:1004:690b:...	UDP	88	443 → 56532 Len=26

Frame 1: 87 bytes on wire (696 bits), 87 bytes captured (696 bits) on interface \Device\NPF...
> Ethernet II, Src: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13), Dst: HonHaiPrecis_14:3a:e7 (34:68:95:14:3a:e7)
> Internet Protocol Version 6, Src: 2404:6800:4002:825:1200e, Dst: 2409:40d6:1004:690b:8825:678f
> User Datagram Protocol, Src Port: 443, Dst Port: 65426
> Data (25 bytes)

0000 34 68 95 14 3a e7 fa 40 ed 4b 59 13 86 dd 68 00 4h...@.KY:4h...
0010 00 00 00 21 11 3a 24 04 68 00 40 02 08 25 00 00 ...:.\$ h@.i.%
0020 00 00 00 00 20 0e 24 09 40 d6 10 04 69 0b 88 25:\$. @.i.%
0030 67 8b 35 27 e1 13 01 bb ff 92 00 21 fb f9 49 13 g.5'.....!..4:
0040 7d 49 f1 7f e2 8e 1f 12 80 ce 71 9a 18 34 84 95 }I.....q:~4:
0050 61 d9 29 e5 71 e0 e4 a~.q~

ICMPv6 FILTER

*Wi-Fi 2

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

icmpv6

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	fe80::f840:edff:fe4...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b:8825:678b:3527:e113 from fa:40:ed:4b:59:13
2	0.000299	2409:40d6:1004:690b...	fe80::f840:edff:fe4...	ICMPv6	86	Neighbor Advertisement 2409:40d6:1004:690b:8825:678b:3527:e113 (sol, ovr) is at 34:68:95:14:3a:e7
3	0.006646	2409:40d6:1004:690b...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b::69 from 34:68:95:14:3a:e7
4	0.009516	2409:40d6:1004:690b...	2409:40d6:1004:690b...	ICMPv6	78	Neighbor Advertisement 2409:40d6:1004:690b::69 (rtr, sol)
4971	21.248724	fe80::f840:edff:fe4...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b:8825:678b:3527:e113 from fa:40:ed:4b:59:13
4973	21.248795	2409:40d6:1004:690b...	fe80::f840:edff:fe4...	ICMPv6	86	Neighbor Advertisement 2409:40d6:1004:690b:8825:678b:3527:e113 (sol, ovr) is at 34:68:95:14:3a:e7
60000	41.470157	fe80::f840:edff:fe4...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b:8825:678b:3527:e113 from fa:40:ed:4b:59:13
60001	41.470198	2409:40d6:1004:690b...	fe80::f840:edff:fe4...	ICMPv6	86	Neighbor Advertisement 2409:40d6:1004:690b:8825:678b:3527:e113 (sol, ovr) is at 34:68:95:14:3a:e7
1099...	62.463437	fe80::f840:edff:fe4...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b:8825:678b:3527:e113 from fa:40:ed:4b:59:13
1099...	62.463516	2409:40d6:1004:690b...	fe80::f840:edff:fe4...	ICMPv6	86	Neighbor Advertisement 2409:40d6:1004:690b:8825:678b:3527:e113 (sol, ovr) is at 34:68:95:14:3a:e7
1457...	85.758746	fe80::f840:edff:fe4...	2409:40d6:1004:690b...	ICMPv6	86	Neighbor Solicitation for 2409:40d6:1004:690b:8825:678b:3527:e113 from fa:40:ed:4b:59:13
1457...	85.758857	2409:40d6:1004:690b...	fe80::f840:edff:fe4...	ICMPv6	86	Neighbor Advertisement 2409:40d6:1004:690b:8825:678b:3527:e113 (sol, ovr) is at 34:68:95:14:3a:e7

> Frame 1: 86 bytes on wire (688 bits), 86 bytes captured (688 bits) on interface \Device\NPF...
> Ethernet II, Src: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13), Dst: HonHaiPrecis_14:3a:e7 (34:68:95:14:3a:e7)
> Internet Protocol Version 6, Src: fe80::f840:edff:fe4b:5913, Dst: 2409:40d6:1004:690b:8825:678b:3527:e113
> Internet Control Message Protocol v6

0000 34 68 95 14 3a e7 fa 40 ed 4b 59 13 86 dd 60 00 4h...: @ KY...
0010 00 00 00 20 3a ff fe 80 00 00 00 00 00 f0 40 ...:@
0020 ed ff fe 4b 59 13 24 09 40 d6 10 04 69 0b 88 25 ...: KY\$: i...%
0030 67 8b 35 27 e1 13 87 00 33 2d 00 00 00 24 09 g 5'... 3...\$
0040 40 d6 10 04 69 0b 88 25 67 8b 35 27 e1 13 01 01 @... i...% g 5'...
0050 fa 40 ed 4b 59 13 @ KY

Internet Control Message Protocol v6 Protocol

Packets: 153568 - Displayed: 12 (0.0%) - Dropped: 536 (0.3%) Profile: Default

17°C Sunny 20:18 12-02-2025

TLS FILTER

*Wi-Fi 2

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

tls

No.	Time	Source	Destination	Protocol	Length	Info
188	8.199712	204.79.197.203	192.168.92.102	TLSv1.3	345	Server Hello, Application Data
189	8.200657	192.168.92.102	204.79.197.203	TLSv1.3	128	Application Data
190	8.200800	192.168.92.102	204.79.197.203	TLSv1.3	146	Application Data
192	8.201153	192.168.92.102	204.79.197.203	TLSv1.3	1144	Application Data
194	8.233516	204.79.197.203	192.168.92.102	TLSv1.3	116	Application Data
195	8.233791	192.168.92.102	204.79.197.203	TLSv1.3	85	Application Data
197	8.237212	204.79.197.203	192.168.92.102	TLSv1.3	85	Application Data
210	8.477504	204.79.197.203	192.168.92.102	TLSv1.3	964	Application Data
216	8.487815	204.79.197.203	192.168.92.102	TLSv1.3	147	Application Data
218	8.487964	204.79.197.203	192.168.92.102	TLSv1.3	273	Application Data
223	8.531923	204.79.197.203	192.168.92.102	TLSv1.3	341	Application Data
229	8.532163	204.79.197.203	192.168.92.102	TLSv1.3	286	Application Data
231	8.532268	204.79.197.203	192.168.92.102	TLSv1.3	134	Application Data
237	8.532521	204.79.197.203	192.168.92.102	TLSv1.3	1334	Application Data, Application Data, Application Data
240	8.532655	204.79.197.203	192.168.92.102	TLSv1.3	498	Application Data
244	8.558590	204.79.197.203	192.168.92.102	TLSv1.3	217	Application Data
248	8.561391	204.79.197.203	192.168.92.102	TLSv1.3	203	Application Data
269	8.627799	204.79.197.203	192.168.92.102	TLSv1.3	285	Application Data
271	8.627971	204.79.197.203	192.168.92.102	TLSv1.3	135	Application Data
272	8.627971	204.79.197.203	192.168.92.102	TLSv1.3	91	Application Data
276	8.628052	204.79.197.203	192.168.92.102	TLSv1.3	285	Application Data

> Frame 24: 1292 bytes on wire (10336 bits), 1292 bytes captured (10336 bits) on interface \Dev...
> Ethernet II, Src: HonHaiPrecis_14:3a:e7 (34:68:95:14:3a:e7), Dst: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13)
> Internet Protocol Version 6, Src: 2409:40d6:1004:690b:8825:678b:3527:e113, Dst: 2404:6800:4000:4000:0000:0000:0000:0000
> User Datagram Protocol, Src Port: 57877, Dst Port: 443
> QUIC IETF

0000 fa 40 ed 4b 59 13 34 68 95 14 3a e7 86 dd 60 07 :@ KY 4h ...
0010 6c 05 04 d6 11 3f 24 09 40 d6 10 04 69 0b 88 25 1...? \$: @... i...%
0020 67 8b 35 27 e1 13 24 04 68 00 40 03 0c 04 00 00 g 5'... \$: h...@...
0030 00 00 00 00 00 54 e2 15 01 bb 04 d6 7f 28 c5 00 ...: T...: (...
0040 00 00 01 88 7c 54 de 95 ce 9f 0d 41 00 40 47 00 ...: [T... : A @...
0050 ab e6 20 e1 b5 a5 5a 16 01 a5 70 de 70 81 c2 ec ...: Z...: p...
0060 04 a9 04 ca f2 9a d1 4f 7e e2 c1 b8 5a e3 b1 86 ...: ...O...: Z...
0070 54 b3 e9 66 7a 01 75 cb f3 14 5e 2c 0d 1f 1c 29 T...fz...: u...: (...
0080 1f 6c 1b cd 98 56 3c c1 51 3e 87 b2 0d b2 23 90 :...V<...: Q...: #...
0090 38 7f f8 5a f1 da 44 74 ed 7c c7 a2 b0 db b7 3b #...Z...: Dt...: (...
00a0 23 98 43 7b 12 2f 56 70 2f 81 9b 43 c9 ea 90 e5 # C.../Vp...: /...: C...
00b0 17 f4 eb 72 82 eb cd 7e cd 62 99 a6 1d 08 a0 40 ...: ...: b...: @...
00c0 a0 33 4a b1 93 7a e6 6b 71 70 be ec bd 56 b3 18 :J...: z...: k qp...: V...

Frame (1292 bytes) Decrypted QUIC (1123 bytes)

wireless_Wi-Fi_25KVQ12.pcapng

Packets: 153568 - Displayed: 18790 (12.2%) - Dropped: 536 (0.3%) Profile: Default

17°C Sunny 20:21 12-02-2025

HTTP FILTER

Wi-Fi 2

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

http

No.	Time	Source	Destination	Protocol	Length	Info
2892	21.230750	192.168.92.102	65.61.137.117	HTTP	531	GET / HTTP/1.1
2962	21.621236	65.61.137.117	192.168.92.102	HTTP	709	HTTP/1.1 200 OK (text/html)
2970	21.716497	192.168.92.102	65.61.137.117	HTTP	449	GET /style.css HTTP/1.1
2973	21.717236	192.168.92.102	65.61.137.117	HTTP	501	GET /images/logo.gif HTTP/1.1
2998	22.040286	65.61.137.117	192.168.92.102	HTTP	252	HTTP/1.1 200 OK (text/css)
3003	22.040767	192.168.92.102	65.61.137.117	HTTP	507	GET /images/header_pic.jpg HTTP/1.1
3004	22.040899	192.168.92.102	65.61.137.117	HTTP	502	GET /images/home1.jpg HTTP/1.1
3005	22.041031	192.168.92.102	65.61.137.117	HTTP	502	GET /images/home2.jpg HTTP/1.1
3006	22.041151	192.168.92.102	65.61.137.117	HTTP	502	GET /images/home3.jpg HTTP/1.1
3012	22.047752	65.61.137.117	192.168.92.102	HTTP	151	HTTP/1.1 200 OK (GIF89a)
3015	22.193045	192.168.92.102	65.61.137.117	HTTP	504	GET /images/pf_lock.gif HTTP/1.1
3016	22.229410	192.168.92.102	65.61.137.117	HTTP	505	GET /images/gradient.jpg HTTP/1.1
3039	22.392673	65.61.137.117	192.168.92.102	HTTP	503	HTTP/1.1 200 OK (JPEG JFIF image)
3044	22.399933	65.61.137.117	192.168.92.102	HTTP	1067	HTTP/1.1 200 OK (JPEG JFIF image)
3055	22.407267	65.61.137.117	192.168.92.102	HTTP	446	HTTP/1.1 200 OK (JPEG JFIF image)
3060	22.518238	65.61.137.117	192.168.92.102	HTTP	354	HTTP/1.1 200 OK (GIF89a)
3067	22.616080	65.61.137.117	192.168.92.102	HTTP	1175	HTTP/1.1 200 OK (JPEG JFIF image)
3081	22.734900	65.61.137.117	192.168.92.102	HTTP	1094	HTTP/1.1 200 OK (JPEG JFIF image)
3092	22.797920	192.168.92.102	65.61.137.117	HTTP	497	GET /favicon.ico HTTP/1.1
3144	23.173710	65.61.137.117	192.168.92.102	HTTP	768	HTTP/1.1 404 Not Found (text/html)

> Frame 2892: 531 bytes on wire (4248 bits), 531 bytes captured (4248 bits) on interface \Device
> Ethernet II, Src: HonHaiPrecis_14:3a:e7 (34:68:95:14:3a:e7), Dst: fa:40:ed:4b:59:13 (fa:40:ed:
> Internet Protocol Version 4, Src: 192.168.92.102, Dst: 65.61.137.117
> Transmission Control Protocol, Src Port: 50246, Dst Port: 80, Seq: 1, Ack: 1, Len: 477
> Hypertext Transfer Protocol

0000 fa 40 ed 4b 59 13 34 68 95 14 3a e7 08 00 45 00 :@KY:4hE-
0010 02 05 1d 62 40 00 80 06 f3 cf c0 a8 5c 66 41 3d :...@.....:fa=
0020 89 75 c4 46 00 50 aa dd 14 7a 42 89 bb 21 50 18 :..u.FP...zB..lP-
0030 01 02 00 c5 00 00 47 45 54 20 2f 20 48 54 54 5c :.....GE T / http
0040 74 65 73 74 66 69 72 65 2e 6e 65 74 6d 0a 43 6f :.testfire.net/Co
0050 6e 6e 65 63 74 69 6f 6e 3a 20 6b 65 65 70 2d 61 :nnection : keep-a
0060 6c 69 76 65 6d 0a 55 70 67 72 61 64 65 2d 49 6e :live/Up grade-In
0070 73 65 63 75 72 65 2d 52 65 71 65 73 74 73 3a :secure-R equests:
0080 20 31 0d 0a 55 73 65 72 2d 41 67 65 6e 74 3a 20 :1:User -Agent:
0090 4d 6f 7a 69 6c 6c 61 2f 35 2e 30 28 57 69 6e :Mozilla/ 5.0 (win
00a0 64 6f 77 73 20 4e 54 20 31 30 2e 30 3b 20 57 69 :dows NT 10.0; Wi
00b0 6e 36 34 30 20 78 36 34 29 20 41 70 70 6c 65 57 :n64; x64) AppleW
00c0 65 62 4b 69 74 2f 35 33 37 2e 33 36 20 28 4b 48 :ebKit/53.7.36 (KH

Hypertext Transfer Protocol: Protocol

Packets: 3379 - Displayed: 20 (0.6%) - Dropped: 0 (0.0%)

Profile: Default

20-27
12-02-2025

Ip.addr FILTER

Wi-Fi 2

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

Ip.addr = 218.248.13.200

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	192.168.92.215	218.248.13.200	TCP	55	1070 -> 443 [ACK] Seq=1 Ack=1 Win=8328 Len=1 [TCP segment of a reassembled PDU]
2	0.004390	218.248.13.200	192.168.92.215	TCP	66	443 -> 1064 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
3	0.009035	218.248.13.200	192.168.92.215	TCP	66	443 -> 1064 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
4	0.009518	218.248.13.200	192.168.92.215	TCP	66	443 -> 1070 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
5	0.201832	2409:40d6:28:69d5:3...	2404:6800:4002:021::...	TCP	75	8835 -> 80 [ACK] Seq=1 Ack=1 Win=256 Len=1
6	0.233413	2404:6800:4002:021::...	2409:40d6:28:69d5:3...	TCP	86	80 -> 8835 [ACK] Seq=1 Ack=2 Win=1051 Len=0 SLE=1 SRE=2
7	0.481174	2409:40d6:28:69d5:3...	2a04:4e42:0e::684	TCP	74	24346 -> 80 [FIN, ACK] Seq=1 Ack=1 Win=258 Len=0
8	0.575330	2409:40d6:28:69d5:3...	2600:1901:0:38d7::...	TCP	75	2874 -> 80 [ACK] Seq=1 Ack=1 Win=256 Len=1
9	0.604510	2600:1901:0:38d7::...	2409:40d6:28:69d5:3...	TCP	86	80 -> 2874 [ACK] Seq=1 Ack=2 Win=1050 Len=0 SLE=1 SRE=2
10	0.715423	2409:40d6:28:69d5:3...	2600:1901:0:38d7::...	TCP	75	2873 -> 80 [ACK] Seq=1 Ack=1 Win=255 Len=1
11	0.738697	2600:1901:0:38d7::...	2409:40d6:28:69d5:3...	TCP	86	80 -> 2873 [ACK] Seq=1 Ack=2 Win=1050 Len=0 SLE=1 SRE=2
12	0.777594	192.168.92.215	99.86.51.238	TCP	55	8847 -> 80 [ACK] Seq=1 Ack=1 Win=254 Len=1
13	0.792543	192.168.92.215	99.86.51.238	TCP	55	8848 -> 80 [ACK] Seq=1 Ack=1 Win=254 Len=1
14	0.804173	99.86.51.238	192.168.92.215	TCP	66	80 -> 8847 [ACK] Seq=1 Ack=2 Win=131 Len=0 SLE=1 SRE=2
15	0.824131	99.86.51.238	192.168.92.215	TCP	66	80 -> 8848 [ACK] Seq=1 Ack=2 Win=131 Len=0 SLE=1 SRE=2
16	1.382434	2409:40d6:28:69d5:3...	2a04:4e42:0e::684	TCP	74	24345 -> 80 [FIN, ACK] Seq=1 Ack=1 Win=258 Len=0
17	1.507417	192.168.92.215	40.126.17.135	TCP	54	27773 -> 443 [FIN, ACK] Seq=1 Ack=1 Win=258 Len=0
18	1.570870	40.126.17.135	192.168.92.215	TCP	54	443 -> 27773 [FIN, ACK] Seq=1 Ack=2 Win=16381 Len=0
19	1.570934	192.168.92.215	40.126.17.135	TCP	54	27773 -> 443 [ACK] Seq=2 Ack=2 Win=258 Len=0
20	1.511541	2409:40d6:28:69d5:3...	2504:6429:0a:1c84...	TCP	74	[TCP Retransmission] 24346 -> 80 [FIN, ACK] Seq=1 Ack=1 Win=258 Len=0
21	2.333414	192.168.92.215	192.168.92.198	DNS	76	Standard query 0x11e8 AAAA dns.msftncsl.com
22	2.337789	192.168.92.198	192.168.92.215	DNS	104	Standard query response 0x11e8 AAAA dns.msftncsl.com
23	2.393908	2409:40d6:28:69d5:3...	2404:6800:4002:02b::...	TCP	75	2874 -> 80 [ACK] Seq=1 Ack=1 Win=256 Len=1
24	2.416042	2404:6800:4002:02b::...	2409:40d6:28:69d5:3...	TCP	86	80 -> 2874 [ACK] Seq=1 Ack=2 Win=1050 Len=0 SLE=1 SRE=2
25	3.682268	2409:40d6:28:69d5:3...	2404:6800:4002:02c::...	UDP	129	Command Prompt

> Frame 1: 55 bytes on wire (440 bits), 55 bytes captured (440 bits) on interface 0
> Ethernet II, Src: Chongqin_7b:87:09 (c0:b5:d7:7b:87:09), Dst: fa:40:ed:4b:59:13 (fa:40:
> Internet Protocol Version 4, Src: 192.168.92.215, Dst: 218.248.13.200
> Transmission Control Protocol, Src Port: 1070, Dst Port: 443, Seq: 1, Ack: 1, Len: 1

0000 fa 40 ed 4b 59 13 c0 b5 d7 7b 87 09 00 00 45 00 :@KY:4hE-
0010 00 29 58 40 00 80 06 cb 36 c0 a8 5c d7 da f8 :))X.....6'....
0020 0d c0 04 2e 01 bb c5 ee 46 43 60 cb a1 35 50 10 :.....FC'..SP-
0030 20 88 74 ef 00 00 00 :t....

Microsoft Windows [Version 10.0.19044.1288]
(c) Microsoft Corporation. All rights reserved.
C:\Users\CONITK>ping nitw.ac.in
Pinging nitw.ac.in [218.248.13.200] with 32 bytes of data:
Request timed out.
Request timed out.
Request timed out.
Request timed out.
Ping statistics for 218.248.13.200:
Packets: Sent = 4, Received = 0, Lost = 4 (100% loss),
C:\Users\CONITK>

Invalid filter: "-" was unexpected in this context.

Type here to search

NIFTY -0.28%

1401
11-02-2025

ip.dst FILTER

Wireshark capture showing IP destination filter: `ip.dst == 218.248.13.200`

Packet List (Selected Packet 1000):

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	192.168.92.215	218.248.13.200	TCP	55	1070 → 443 [ACK] Seq=1 Ack=1 Win=8328 Len=1 [TCP segment of a reassembled PDU]
78	4.859473	192.168.92.215	218.248.13.200	TCP	55	1038 → 443 [ACK] Seq=1 Ack=1 Win=2082 Len=1 [TCP segment of a reassembled PDU]
465	9.949675	192.168.92.215	218.248.13.200	TCP	55	1063 → 443 [ACK] Seq=1 Ack=1 Win=517 Len=1 [TCP segment of a reassembled PDU]
721	9.369580	192.168.92.215	218.248.13.200	TCP	55	8821 → 443 [ACK] Seq=1 Ack=1 Win=258 Len=1 [TCP segment of a reassembled PDU]
748	9.464651	192.168.92.215	218.248.13.200	TCP	55	8820 → 443 [ACK] Seq=1 Ack=1 Win=258 Len=1 [TCP segment of a reassembled PDU]
750	9.480484	192.168.92.215	218.248.13.200	TCP	55	8823 → 443 [ACK] Seq=1 Ack=1 Win=258 Len=1 [TCP segment of a reassembled PDU]
967	9.633919	192.168.92.215	218.248.13.200	TCP	55	8824 → 443 [ACK] Seq=1 Ack=1 Win=2082 Len=1 [TCP segment of a reassembled PDU]
995	9.820283	192.168.92.215	218.248.13.200	TCP	55	1069 → 443 [ACK] Seq=1 Ack=1 Win=4803 Len=1 [TCP segment of a reassembled PDU]
1000	9.913753	192.168.92.215	218.248.13.200	TCP	55	1063 → 443 [ACK] Seq=1 Ack=1 Win=8328 Len=1 [TCP segment of a reassembled PDU]
1010	10.009095	192.168.92.215	218.248.13.200	TCP	55	[TCP Spurious Retransmission] 1064 → 443 [ACK] Seq=0 Ack=1 Win=4164 Len=1 [TCP segment of a reassembled PDU]
1018	10.024012	192.168.92.215	218.248.13.200	TCP	55	[TCP Spurious Retransmission] 8819 → 443 [ACK] Seq=0 Ack=1 Win=2078 Len=1 [TCP segment of a reassembled PDU]
1023	10.085968	192.168.92.215	218.248.13.200	TCP	55	[TCP Keep-Alive] 1070 → 443 [ACK] Seq=1 Ack=1 Win=8328 Len=1
1120	10.736136	192.168.92.215	218.248.13.200	TLSv1.2	564	Ignored Unknown Record
1123	10.736737	192.168.92.215	218.248.13.200	TLSv1.2	78	Application Data
1124	10.736775	192.168.92.215	218.248.13.200	TCP	54	1070 → 443 [FIN, ACK] Seq=536 Ack=1 Win=8328 Len=0
1133	10.762419	192.168.92.215	218.248.13.200	TLSv1.2	480	Ignored Unknown Record
1134	10.768904	192.168.92.215	218.248.13.200	TLSv1.2	476	Ignored Unknown Record
1135	10.769292	192.168.92.215	218.248.13.200	TLSv1.2	494	Ignored Unknown Record
1136	10.769487	192.168.92.215	218.248.13.200	TLSv1.2	497	Ignored Unknown Record
1152	10.802133	192.168.92.215	218.248.13.200	TLSv1.2	78	Application Data
1153	10.802167	192.168.92.215	218.248.13.200	TCP	54	1069 → 443 [FIN, ACK] Seq=452 Ack=1 Win=4803 Len=0
1154	10.802260	192.168.92.215	218.248.13.200	TLSv1.2	78	Application Data
1155	10.802323	192.168.92.215	218.248.13.200	TCP	54	1070 → 443 [FIN, ACK] Seq=452 Ack=1 Win=4803 Len=0
1157	10.802602	192.168.92.215	218.248.13.200	TLSv1.2	78	Application Data
1158	10.802651	192.168.92.215	218.248.13.200	TCP	54	1070 → 443 [FIN, ACK] Seq=452 Ack=1 Win=4803 Len=0

Packet Details (Selected Packet 1000):

- Frame 1: 55 bytes on wire (440 bits), 55 bytes captured (440 bits) on interface 0
- Ethernet II, Src: Chongqin_7b:87:89 (c0:b5:d7:7b:87:89), Dst: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13)
- Internet Protocol Version 4, Src: 192.168.92.215, Dst: 218.248.13.200
- Transmission Control Protocol, Src Port: 1070, Dst Port: 443, Seq: 1, Ack: 1, Len: 1

Packet Bytes (Selected Packet 1000):

```
0000 fa 40 ed 4b 59 13 c0 b5 d7 7b 87 89 08 00 45 00  @ KY...{....E
0010 00 29 29 58 40 00 00 06 cb 36 c0 a8 5c d7 da f8  )X@...6...
0020 0d c8 94 2e 81 bb c5 ee 46 43 60 cb a1 35 50 10  .t.....FC...SP
0030 20 88 74 ef 00 00 00 00 00 00 00 00 00 00 00 00  t.....
```

ip.src FILTER

Wireshark capture showing IP source filter: `ip.src == 218.248.13.200`

Packet List (Selected Packet 1000):

No.	Time	Source	Destination	Protocol	Length	Info
2	0.004390	218.248.13.200	192.168.92.215	TCP	66	443 → 1064 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
3	0.009035	218.248.13.200	192.168.92.215	TCP	66	443 → 8819 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
4	0.009518	218.248.13.200	192.168.92.215	TCP	66	443 → 1070 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
83	4.953916	218.248.13.200	192.168.92.215	TCP	66	443 → 1038 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
585	9.862616	218.248.13.200	192.168.92.215	TCP	66	443 → 1063 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
797	9.499370	218.248.13.200	192.168.92.215	TCP	66	443 → 8821 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
896	9.541971	218.248.13.200	192.168.92.215	TCP	66	443 → 8820 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
916	9.572224	218.248.13.200	192.168.92.215	TCP	66	443 → 8823 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
986	9.718681	218.248.13.200	192.168.92.215	TCP	66	443 → 8824 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
1003	9.917184	218.248.13.200	192.168.92.215	TCP	66	443 → 1069 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
1014	9.998589	218.248.13.200	192.168.92.215	TCP	66	443 → 1063 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
1026	10.103766	218.248.13.200	192.168.92.215	TCP	66	[TCP Dup ACK 281] 443 → 1064 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
1027	10.107486	218.248.13.200	192.168.92.215	TCP	66	[TCP Dup ACK 381] 443 → 8819 [ACK] Seq=1 Ack=1 Win=501 Len=0 SLE=0 SRE=1
1037	10.107276	218.248.13.200	192.168.92.215	TCP	66	[TCP Keep-Alive] 443 → 1070 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=1 SRE=2
1172	10.825844	218.248.13.200	192.168.92.215	TCP	66	[TCP Dup ACK 481] 443 → 1070 [ACK] Seq=1 Ack=2 Win=501 Len=0 SLE=536 SRE=537
1192	10.832846	218.248.13.200	192.168.92.215	TCP	66	443 → 1070 [ACK] Seq=1 Ack=512 Win=501 Len=0 SLE=536 SRE=537
1193	10.832846	218.248.13.200	192.168.92.215	TCP	1334	443 → 1070 [ACK] Seq=1 Ack=512 Win=501 Len=1268 SLE=536 SRE=537 [TCP segment of a reassembled PDU]
1194	10.832846	218.248.13.200	192.168.92.215	TCP	1334	443 → 1070 [PSH, ACK] Seq=1269 Ack=512 Win=501 Len=1268 SLE=536 SRE=537 [TCP segment of a reassembled PDU]
1195	10.832846	218.248.13.200	192.168.92.215	TLSv1.2	683	Application Data
1200	10.839762	218.248.13.200	192.168.92.215	TCP	54	443 → 1070 [ACK] Seq=3154 Ack=537 Win=501 Len=0
1201	10.840462	218.248.13.200	192.168.92.215	TCP	54	443 → 1070 [FIN, ACK] Seq=154 Ack=537 Win=501 Len=0
1210	10.860283	218.248.13.200	192.168.92.215	TCP	54	443 → 1069 [ACK] Seq=1 Ack=428 Win=501 Len=0
1219	10.860283	218.248.13.200	192.168.92.215	TCP	1334	443 → 1070 [ACK] Seq=1 Ack=512 Win=501 Len=1268 SLE=536 SRE=537 [TCP segment of a reassembled PDU]
1220	10.860283	218.248.13.200	192.168.92.215	TCP	1334	443 → 1070 [ACK] Seq=1 Ack=512 Win=501 Len=1268 SLE=536 SRE=537 [TCP segment of a reassembled PDU]
1221	10.860283	218.248.13.200	192.168.92.215	TCP	1334	443 → 1070 [ACK] Seq=1 Ack=512 Win=501 Len=1268 SLE=536 SRE=537 [TCP segment of a reassembled PDU]

Packet Details (Selected Packet 1000):

- Frame 2: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface 0
- Ethernet II, Src: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13), Dst: Chongqin_7b:87:89 (c0:b5:d7:7b:87:89)
- Internet Protocol Version 4, Src: 218.248.13.200, Dst: 192.168.92.215
- Transmission Control Protocol, Src Port: 443, Dst Port: 1064, Seq: 1, Ack: 1, Len: 0

Packet Bytes (Selected Packet 1000):

```
0000 c0 b5 d7 7b 87 89 fa 40 ed 4b 59 13 08 00 45 00  ...@...KY...E
0010 00 34 00 00 00 2f 06 45 84 da f8 0d c8 c0 a8  4-@./-E.....
0020 5c d7 81 b6 04 28 67 b9 e6 4e dd 22 d9 ab 80 10  \....(g"-N.....
0030 01 f5 f9 31 00 00 01 01 05 0a dd 22 d9 aa d2  1.....
0040 d9 ab
```

SMTP FILTER

The screenshot shows a network analyzer window titled "Wi-Fi". The main pane displays a list of captured packets. The first packet is an SMTP message. The details pane on the right shows the packet structure: Ethernet II, Internet Protocol Version 4, and Transmission Control Protocol. The packet data is displayed in hexadecimal and ASCII format.

No.	Time	Source	Destination	Protocol	Length	Info
129	10.323493	172.16.48.32	142.250.27.27	SMTP	56	C: \003\b\b
135	10.729589	142.250.27.27	172.16.48.32	SMTP	220	S: 502-5.5.1 Unrecognized command. For more information, go to 502 5.5.1 https://support.google.com/a/answer/3221692 a640c23a62f3a-aba...
305	21.227792	172.16.48.32	142.250.27.27	SMTP	56	C: hi
308	21.616838	142.250.27.27	172.16.48.32	SMTP	220	S: 502-5.5.1 Unrecognized command. For more information, go to 502 5.5.1 https://support.google.com/a/answer/3221692 a640c23a62f3a-aba...
333	24.643871	172.16.48.32	142.250.27.27	SMTP	56	C: hello
336	25.032968	142.250.27.27	172.16.48.32	SMTP	220	S: 502-5.5.1 Unrecognized command. For more information, go to 502 5.5.1 https://support.google.com/a/answer/3221692 a640c23a62f3a-aba...

Frame 129: 56 bytes on wire (448 bits), 56 bytes captured (448 bits) on interface 0
> Ethernet II, Src: Chonglin_7b:87:89 (c8b5:d7:7b:87:89), Dst: ExtremeN_1d:87:d0 (00:04:96:1d:87:d0)
> Internet Protocol Version 4, Src: 172.16.48.32, Dst: 142.250.27.27
> Transmission Control Protocol, Src Port: 22623, Dst Port: 25, Seq: 4, Ack: 1, Len: 2
> [4 Reassembled TCP Segments (5 bytes): #92(1), #109(1), #121(1), #129(2)]
> Simple Mail Transfer Protocol

0000 00 04 96 1d 87 d0 c8 b5 d7 7b 87 89 08 00 45 00E
0010 00 2a fa 1a 40 00 00 06 7a 6d ac 10 30 20 8e fa ..*..zm..
0020 1b 1b 58 5f 00 19 c7 f6 a5 dc ab d3 52 9b 50 18 ..X.....R.P.
0030 01 02 56 be 00 00 0d 0a ..V.....

Frame (56 bytes) Reassembled TCP (5 bytes)
Simple Mail Transfer Protocol: Protocol

Packets: 447 · Displayed: 6 (1.3%) · Dropped: 0 (0.0%) Profile: Default

tcp.options FILTER

The screenshot shows a network analyzer window titled "Wi-Fi 2". The main pane displays a list of captured packets. The details pane on the right shows the packet structure: Ethernet II, Internet Protocol Version 4, and Transmission Control Protocol. The packet data is displayed in hexadecimal and ASCII format.

No.	Time	Source	Destination	Protocol	Length	Info
2770	20.651212	2409:40d6:1004:690b...	2404:6800:4002:80e...	TCP	86	50247 → 443 [SYN] Seq=0 Win=64320 Len=0 MSS=1340 WS=256 SACK_PERM
2773	20.657380	192.168.92.102	4.241.22.149	TCP	66	50248 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2786	20.699562	192.168.92.102	65.61.137.117	TCP	66	50249 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2790	20.704938	2404:6800:4002:80e...	2409:40d6:1004:690b...	TCP	86	443 → 50247 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1300 SACK_PERM WS=256
2805	20.767623	65.61.137.117	192.168.92.102	TCP	66	443 → 50244 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2825	20.877482	4.241.22.149	192.168.92.102	TCP	66	443 → 50248 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1300 SACK_PERM WS=1024
2834	20.925271	65.61.137.117	192.168.92.102	TCP	66	80 → 50246 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2835	20.925271	65.61.137.117	192.168.92.102	TCP	66	80 → 50245 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2841	20.964345	192.168.92.102	4.241.22.149	TCP	66	50250 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2848	21.019156	65.61.137.117	192.168.92.102	TCP	66	443 → 50249 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2875	21.172688	4.241.22.149	192.168.92.102	TCP	66	443 → 50250 [SYN, ACK] Seq=0 Ack=1 Win=64240 Len=0 MSS=1300 SACK_PERM WS=1024
2969	21.716284	192.168.92.102	65.61.137.117	TCP	66	50251 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2971	21.716802	192.168.92.102	65.61.137.117	TCP	66	50252 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2972	21.717098	192.168.92.102	65.61.137.117	TCP	66	50253 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2974	21.717529	192.168.92.102	65.61.137.117	TCP	66	50254 → 80 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
2992	22.040064	65.61.137.117	192.168.92.102	TCP	66	80 → 50254 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2993	22.040064	65.61.137.117	192.168.92.102	TCP	66	80 → 50253 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2996	22.040286	65.61.137.117	192.168.92.102	TCP	66	80 → 50251 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
2999	22.040286	65.61.137.117	192.168.92.102	TCP	66	80 → 50252 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM
3090	22.772593	192.168.92.102	65.61.137.117	TCP	66	50255 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM
3127	23.096686	65.61.137.117	192.168.92.102	TCP	66	443 → 50255 [SYN, ACK] Seq=0 Ack=1 Win=8192 Len=0 MSS=1300 WS=256 SACK_PERM

Frame 2875: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface DeviceNPF
> Ethernet II, Src: fa:40:ed:4b:59:13 (fa:40:ed:4b:59:13), Dst: HonhaiPrecis_14:3a:e7 (34:68:95:14:3a:e7)
> Internet Protocol Version 4, Src: 4.241.22.149, Dst: 192.168.92.102
> Transmission Control Protocol, Src Port: 443, Dst Port: 50250, Seq: 0, Ack: 1, Len: 0

0000 34 68 95 14 3a e7 fa 40 ed 4b 59 13 08 00 45 00 4h...@..KY...E
0010 00 34 00 00 40 00 2b 06 17 30 04 f1 16 95 c0 a8 4...@+...0.....
0020 5c 66 01 bb c4 4a e7 17 67 02 93 a8 f1 9d 80 12 \f...J...g.....
0030 fa f0 a2 b2 00 00 02 04 05 14 01 01 04 02 01 03
0040 03 0a ..

wire shark_Wi-Fi 2XIXOK12.pcapng

Packets: 3379 · Displayed: 83 (2.5%) · Dropped: 0 (0.0%) Profile: Default

Eth.type == 0x0806 FILTER

The screenshot shows a Wireshark capture of network traffic filtered by the expression `Eth.type == 0x0806`. The capture is on interface `eth0` and shows a series of ARP requests from various hosts to the broadcast address `ff:ff:ff:ff:ff:ff`. The first packet is an ARP request from `192.168.1.100` to `192.168.1.1`. The packet details pane shows the Ethernet II header, Internet Protocol Version 4 header, and Address Resolution Protocol (request) section. The packet bytes pane shows the raw data in hexadecimal and ASCII.

No.	Time	Source	Destination	Protocol	Length	Info
20	1.338469	Universa_a6:9b:a3	Broadcast	ARP	60	Who has 172.16.48.254? Tell 172.16.49.160
29	2.252458	Extremeh_id:87:d0	Broadcast	ARP	60	Who has 172.16.48.181? Tell 172.16.49.254
35	4.816628	Dell_c8:b6:a0	Broadcast	ARP	60	Who has 172.16.48.251? Tell 172.16.48.45
45	7.680457	Zhejiang_76:22:9c	Broadcast	ARP	60	Who has 172.16.48.219? Tell 172.16.48.205
46	7.680545	Zhejiang_76:22:9c	Broadcast	ARP	60	Who has 172.16.48.224? Tell 172.16.48.205
47	7.680591	Zhejiang_76:22:9c	Broadcast	ARP	60	Who has 172.16.48.228? Tell 172.16.48.205
48	7.680633	Zhejiang_76:22:9c	Broadcast	ARP	60	Who has 172.16.48.232? Tell 172.16.48.205
74	11.775950	50:5a:65:9e:2f:85	Broadcast	ARP	60	Who has 172.16.48.73? Tell 172.16.48.59
75	11.776067	50:5a:65:9e:2f:85	Broadcast	ARP	60	Who has 172.16.49.254? Tell 172.16.48.59
90	13.622751	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.33? Tell 172.16.48.27
91	13.824799	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.35? Tell 172.16.48.27
92	14.028506	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.37? Tell 172.16.48.27
93	14.130539	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.38? Tell 172.16.48.27
96	14.643843	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.39? Tell 172.16.48.27
98	14.949741	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.42? Tell 172.16.48.27
99	15.058114	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.43? Tell 172.16.48.27
100	15.155467	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.44? Tell 172.16.48.27
107	15.257436	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.45? Tell 172.16.48.27
108	15.257494	50:5a:65:9e:2f:85	Broadcast	ARP	60	Gratuitous ARP for 172.16.48.59 (Request)
110	15.359781	HewlettP_ce:09:bc	Broadcast	ARP	60	Who has 172.16.48.46? Tell 172.16.48.27
133	16.384216	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.235? Tell 0.0.0.0
134	16.384266	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.235? Tell 0.0.0.0
136	17.006215	50:5a:65:9e:2f:85	Broadcast	ARP	60	Gratuitous ARP for 172.16.48.59 (Request)
137	17.013645	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.218? Tell 0.0.0.0
138	17.100343	Extremeh_id:87:d0	Broadcast	ARP	60	Who has 172.16.48.15? Tell 172.16.49.254
142	16.944807	Extremeh_id:87:d0	Broadcast	ARP	60	Who has 172.16.48.124? Tell 172.16.49.254
143	19.353606	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.236? Tell 0.0.0.0
144	19.356418	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.236? Tell 0.0.0.0
146	19.663521	Zhejiang_ff:fb:6c	Broadcast	ARP	60	Who has 172.16.48.203? Tell 172.16.48.218
148	20.274871	Extremeh_id:87:d0	Broadcast	ARP	60	Who has 172.16.48.158? Tell 172.16.49.254
149	20.587822	ITFP-VRRP-VRID_01	Broadcast	ARP	60	Gratuitous ARP for 172.16.48.201 (Request)

Eth.type == 0x0800 FILTER

The screenshot shows a Wireshark capture of network traffic filtered by the expression `Eth.type == 0x0800`. The capture is on interface `eth0` and shows a series of network packets, including UDP, TCP, and TLS. The first packet is a UDP packet from `142.250.178.10` to `172.16.48.32`. The packet details pane shows the Ethernet II header, Internet Protocol Version 4 header, and User Datagram Protocol section. The packet bytes pane shows the raw data in hexadecimal and ASCII.

No.	Time	Source	Destination	Protocol	Length	Info
1	0.000000	142.250.178.10	172.16.48.32	UDP	204	443 → 51133 Len=162
2	0.000495	172.16.48.32	142.250.178.10	UDP	75	51133 → 443 Len=33
3	0.011346	23.53.42.66	172.16.48.32	TCP	60	80 → 9830 [ACK] Seq=1 Ack=1 Win=502 Len=0
4	0.011662	23.53.42.66	172.16.48.32	HTTP	241	HTTP/1.1 200 OK (text/plain)
5	0.011845	172.16.48.32	23.53.42.66	TCP	54	9830 → 80 [FIN, ACK] Seq=1 Ack=188 Win=258 Len=0
6	0.012407	23.53.42.66	172.16.48.32	TCP	60	80 → 9830 [FIN, ACK] Seq=188 Ack=1 Win=502 Len=0
7	0.012463	172.16.48.32	23.53.42.66	TCP	54	9830 → 80 [ACK] Seq=2 Ack=189 Win=258 Len=0
8	0.205675	23.53.42.66	172.16.48.32	TCP	60	80 → 9830 [ACK] Seq=189 Ack=2 Win=502 Len=0
10	0.341019	172.16.48.32	20.90.152.133	TLSv1.2	155	Application Data
11	0.509565	20.90.152.133	172.16.48.32	TLSv1.2	225	Application Data
12	0.560329	172.16.48.32	20.90.152.133	TCP	54	1448 → 443 [ACK] Seq=102 Ack=172 Win=257 Len=0
13	0.645173	172.16.48.75	255.255.255.255	UDP	70	52373 → 22222 Len=28
14	0.645304	172.16.48.75	255.255.255.255	UDP	125	10004 → 10004 Len=83
15	0.645612	172.16.48.75	255.255.255.255	UDP	60	52379 → 3289 Len=14
16	0.645907	172.16.48.75	255.255.255.255	UDP	70	52377 → 22222 Len=28
17	0.646125	172.16.48.75	255.255.255.255	UDP	70	52374 → 22222 Len=28
18	0.646206	172.16.48.75	255.255.255.255	UDP	70	52378 → 22222 Len=28
19	0.747984	172.16.48.75	255.255.255.255	UDP	125	10004 → 10004 Len=83
20	0.748097	172.16.48.75	255.255.255.255	UDP	60	52381 → 3289 Len=14
21	0.748148	172.16.48.75	255.255.255.255	UDP	60	52382 → 3289 Len=14
22	1.250227	172.16.48.32	142.250.179.229	TLSv1.2	93	Application Data
24	1.641391	142.250.179.229	172.16.48.32	TCP	60	443 → 9804 [ACK] Seq=1 Ack=40 Win=487 Len=0
25	1.641391	142.250.179.229	172.16.48.32	TLSv1.2	93	Application Data
26	1.693198	172.16.48.32	142.250.179.229	TCP	54	9804 → 443 [ACK] Seq=40 Ack=40 Win=258 Len=0
27	1.771925	172.16.48.75	255.255.255.255	UDP	125	10004 → 10004 Len=83
28	1.771999	172.16.48.75	255.255.255.255	UDP	125	10004 → 10004 Len=83
29	1.873889	172.16.48.75	255.255.255.255	UDP	70	52495 → 22222 Len=28
30	1.873956	172.16.48.75	255.255.255.255	UDP	60	52501 → 3289 Len=14
31	1.874111	172.16.48.75	255.255.255.255	UDP	70	52499 → 22222 Len=28
32	1.976333	172.16.48.75	255.255.255.255	UDP	60	52503 → 3289 Len=14
33	2.079579	172.16.48.75	255.255.255.255	UDP	70	49804 → 22222 Len=28

OSCP FILTER

Wireshark capture of OSCP traffic. The filter bar shows 'oscp'. The packet list displays 10 packets, all of which are OSCP requests and responses between 172.16.48.32 and 142.250.195.3. The packet details pane shows the selected packet (No. 1764) as an OSCP Request. The packet bytes pane shows the raw data of the selected packet.

No.	Time	Source	Destination	Protocol	Length	Info
1764	9.934323	172.16.48.32	142.250.195.3	OSCP	492	Request
1815	10.012749	142.250.195.3	172.16.48.32	OSCP	756	Response
1922	10.168276	172.16.48.32	2.22.70.32	OSCP	494	Request
1923	10.168412	172.16.48.32	2.22.70.32	OSCP	494	Request
1927	10.172831	172.16.48.32	142.250.195.3	OSCP	492	Request
1947	10.264233	142.250.195.3	172.16.48.32	OSCP	756	Response
2037	10.427331	2.22.70.32	172.16.48.32	OSCP	242	Response
2080	10.439454	2.22.70.32	172.16.48.32	OSCP	241	Response
2095	11.581235	172.16.48.32	142.250.195.3	OSCP	491	Request
2899	11.663430	142.250.195.3	172.16.48.32	OSCP	755	Response

Udp.port == 53 FILTER

Wireshark capture of traffic filtered by 'udp.port == 53'. The filter bar shows 'udp.port == 53'. The packet list displays 306 packets, all of which are DNS queries and responses. The packet details pane shows the selected packet (No. 80) as a DNS Standard query response. The packet bytes pane shows the raw data of the selected packet.

No.	Time	Source	Destination	Protocol	Length	Info
80	4.358095	172.16.48.32	172.16.0.1	DNS	89	Standard query 0xa385 A img-getpocket.cdn.mozilla.net
81	4.358155	172.16.48.32	172.16.0.1	DNS	76	Standard query 0xa47ca A dns.msftncsl.com
82	4.361440	172.16.0.1	172.16.48.32	DNS	200	Standard query response 0xa385 A img-getpocket.cdn.mozilla.net CNAME img-getpocket-cdn.prod.mozaws.net CNAME img-prod.pocket.prod...
83	4.361440	172.16.0.1	172.16.48.32	DNS	92	Standard query response 0xa47ca A dns.msftncsl.com A 131.107.255.255
85	4.362191	172.16.48.32	172.16.0.1	DNS	100	Standard query 0x5813 A img-prod.pocket.prod.cloudops.mozcp.net
86	4.360240	172.16.0.1	172.16.48.32	DNS	116	Standard query response 0x5813 A img-prod.pocket.prod.cloudops.mozcp.net A 34.120.237.76
87	4.360918	172.16.48.32	172.16.0.1	DNS	100	Standard query 0xa070 AAAA img-prod.pocket.prod.cloudops.mozcp.net
88	4.374298	172.16.0.1	172.16.48.32	DNS	128	Standard query response 0xa070 AAAA img-prod.pocket.prod.cloudops.mozcp.net AAAA 2600:1981:0:e988::
275	6.340233	172.16.48.32	172.16.0.1	DNS	91	Standard query 0xb596 A www.aggarsainpublicschool.ac.in
276	6.340233	172.16.48.32	172.16.0.1	DNS	72	Standard query 0x193b A www.nasa.gov
277	6.340233	172.16.48.32	172.16.0.1	DNS	75	Standard query 0xb0f3 A www.youtube.com
278	6.340233	172.16.48.32	172.16.0.1	DNS	76	Standard query 0xd236 A drive.google.com
279	6.340317	172.16.48.32	172.16.0.1	DNS	85	Standard query 0x13d0 A colab.research.google.com
280	6.340458	172.16.48.32	172.16.0.1	DNS	77	Standard query 0xb40d A www.indiatoday.in
281	6.340461	172.16.48.32	172.16.0.1	DNS	80	Standard query 0x429a A classroom.google.com
282	6.340461	172.16.48.32	172.16.0.1	DNS	75	Standard query 0xb0fc A www.mozilla.org
283	6.340491	172.16.48.32	172.16.0.1	DNS	71	Standard query 0xb75c A www.vox.com
284	6.340494	172.16.48.32	172.16.0.1	DNS	75	Standard query 0x8e23 A restofworld.org
285	6.340580	172.16.48.32	172.16.0.1	DNS	80	Standard query 0xe941 A www.atlasobscura.com
286	6.340769	172.16.48.32	172.16.0.1	DNS	77	Standard query 0xafbc A www.thenation.com
287	6.340790	172.16.48.32	172.16.0.1	DNS	77	Standard query 0xbd8f A www.newyorker.com
288	6.340817	172.16.48.32	172.16.0.1	DNS	74	Standard query 0x2aa1 AAAA www.nitw.ac.in
295	6.403609	172.16.0.1	172.16.48.32	DNS	317	Standard query response 0xb0f3 A www.youtube.com CNAME youtube-ui-1.google.com A 142.250.179.238 A 142.250.180.14 A 142.250.187.20...
296	6.403609	172.16.0.1	172.16.48.32	DNS	92	Standard query response 0xd236 A drive.google.com A 142.250.200.46
299	6.404682	172.16.48.32	172.16.0.1	DNS	76	Standard query 0xe49b A drive.google.com
300	6.404682	172.16.48.32	172.16.0.1	DNS	83	Standard query 0x2f97 A youtube-ui-1.google.com
301	6.407695	172.16.0.1	172.16.48.32	DNS	173	Standard query response 0x13d0 A colab.research.google.com CNAME colab-alv.research.google.com A 216.239.34.100 A 216.239.36.100 A...
302	6.407695	172.16.0.1	172.16.48.32	DNS	96	Standard query response 0x429a A classroom.google.com A 142.250.180.14
303	6.407695	172.16.0.1	172.16.48.32	DNS	124	Standard query response 0x875c A www.vox.com CNAME n.sni.global.fastly.net A 146.75.73.91
304	6.407695	172.16.0.1	172.16.48.32	DNS	121	Standard query response 0x193b A www.nasa.gov CNAME nasa.gov-vip.net A 192.0.66.108
305	6.408362	172.16.48.32	172.16.0.1	DNS	80	Standard query 0x307b A classroom.google.com
306	6.408362	172.16.48.32	172.16.0.1	DNS	70	Standard query 0xb40d A www.indiatoday.in

The screenshot displays the Wireshark network protocol analyzer interface. The top menu bar includes File, Edit, View, Go, Capture, Analyze, Statistics, Telephony, Wireless, Tools, and Help. The toolbar contains icons for various functions like opening files, saving, and analyzing. The main window is divided into three panes: Packet List, Packet Details, and Packet Bytes.

Packet List: Shows a list of captured packets. The selected packet is #134, a BROWSER packet (243 bytes) from 172.16.49.12 to 172.16.49.255, identified as a Host Announcement (DESKTOP-DTPRR6P, Workstation, Server, NT Workstation).

Packet Details: Displays the structure of the selected packet. The Ethernet II section shows the source MAC address as 48:48:48:48:48:48 and the destination MAC address as ff:ff:ff:ff:ff:ff (Broadcast). The Internet Protocol section shows the source IP as 172.16.49.12 and the destination IP as 255.255.255.255. The User Datagram Protocol section shows the source port as 54321 and the destination port as 67. The DHCP section shows the transaction ID as 0x98d2e9d1 and the message type as Discover.

Packet Bytes: Shows the raw data of the packet in hexadecimal and ASCII. The data starts with the Ethernet II header (08 00 54 00 00 00) followed by the Internet Protocol header (45 00 00 00 00 00) and the User Datagram Protocol header (00 00 00 00 00 00).

The status bar at the bottom indicates that 1342 packets were displayed, with 204 (6.5%) dropped and 0 (0.0%) filtered. The profile is set to Default.

The screenshot displays the Wireshark network protocol analyzer interface. The top menu bar includes File, Edit, View, Go, Capture, Analyze, Statistics, Telephony, Wireless, Tools, and Help. The toolbar contains icons for various functions like opening files, saving, and capturing. The main window is divided into three panes:

- Packet List:** Shows a list of captured packets. The first packet is selected, showing its details in the packet details pane.
- Packet Details:** Displays the hierarchical structure of the selected packet. It shows an Ethernet II frame, an Internet Protocol Version 4 packet, and a User Datagram Protocol (UDP) packet. The details of the UDP packet are expanded, showing the Simple Network Management Protocol (SNMP) request. The community string is 'public' and the request ID is 1.
- Packet Bytes:** Shows the raw data of the selected packet in hexadecimal and ASCII. The ASCII column shows the text representation of the data, including the community string 'public' and the request ID '1'.

The status bar at the bottom indicates that 333 packets are displayed, with 3 (0.8%) dropped. The profile is set to 'Default'.

DNS FILTER

The image shows a Wireshark capture of DNS traffic. The filter bar at the top is set to 'dns'. The packet list pane shows several DNS queries and responses. The packet details pane shows the structure of a DNS query packet, including the Ethernet II header, Internet Protocol Version 4 header, User Datagram Protocol header, and Domain Name System (query) header. The packet bytes pane shows the raw data of the packet.

No.	Time	Source	Destination	Protocol	Length	Info
51	4.046575	172.16.48.32	172.16.0.1	DNS	76	Standard query 0xf4d1 AAAA drive.google.com
52	4.046580	172.16.48.32	172.16.0.1	DNS	89	Standard query 0xa990 AAAA colab-alv.research.google.com
53	4.052694	172.16.0.1	172.16.48.32	DNS	104	Standard query response 0xf4d1 AAAA drive.google.com AAAA 2404:6800:4002:82e1:200e
54	4.052694	172.16.0.1	172.16.48.32	DNS	201	Standard query response 0xa990 AAAA colab-alv.research.google.com AAAA 2001:4860:4802:38::180 AAAA 2001:4860:4802:36::180 AAAA 2001:4860:4802:36::180
55	4.064088	172.16.48.32	172.16.0.1	DNS	89	Standard query 0x9c8a A img-getpocket.cdn.mozilla.net
58	4.179145	172.16.0.1	172.16.48.32	DNS	132	Standard query response 0x2c75 A www.mozilla.org CNAME www.mozilla.fastly-edge.com A 146.75.75.19
59	4.180636	172.16.0.1	172.16.48.32	DNS	121	Standard query response 0x6e9d A www.nasa.gov CNAME nasa.gov.go-vip.net A 192.0.66.108
60	4.180740	172.16.48.32	172.16.0.1	DNS	87	Standard query 0xc189 A www.mozilla.fastly-edge.com
61	4.182075	172.16.48.32	172.16.0.1	DNS	79	Standard query 0x375e A nasa.gov.go-vip.net
62	4.195418	172.16.0.1	172.16.48.32	DNS	141	Standard query response 0x340a A www.aggarsainpublicschool.ac.in CNAME aps-frontend.web.app A 199.36.158.180
63	4.195544	172.16.0.1	172.16.48.32	DNS	108	Standard query response 0xf79f AAAA classroom.google.com AAAA 2a00:1450:4009:821::200e
67	4.211809	172.16.0.1	172.16.48.32	DNS	200	Standard query response 0x9c8a A img-getpocket.cdn.mozilla.net CNAME img-getpocket.cdn.prod.mozaws.net CNAME img-prod.pocket.prod...
68	4.212867	172.16.48.32	172.16.0.1	DNS	100	Standard query 0x833b A img-prod.pocket.prod.cloudops.mozcp.net
72	4.228880	172.16.48.32	4.2.2.2	DNS	74	Standard query 0x9987 AAAA www.nitw.ac.in

> Frame 68: 100 bytes on wire (800 bits), 100 bytes captured (800 bits) on interface 0
> Ethernet II, Src: Chongqin_7b:87:89 (c0:b5:d7:7b:87:89), Dst: ExtremeM_Id:87:d0 (00:04:96:1d:87:d0)
> Internet Protocol Version 4, Src: 172.16.48.32, Dst: 172.16.0.1
> User Datagram Protocol, Src Port: 51841, Dst Port: 53
> Domain Name System (query)

0000 00 04 96 1d 87 d0 c0 b5 d7 7b 87 89 00 00 45 00{....E
0010 00 56 40 a0 00 00 00 11 71 b5 ac 10 30 20 ac 10 Vg.....q...
0020 00 01 ca 81 00 35 00 42 42 cd 03 3b 01 00 00 01S B B :...
0030 00 00 00 00 00 00 69 6d 67 2d 70 72 6f 64 06i mg-prod
0040 70 6f 63 6b 65 74 04 70 72 6f 64 06 63 6c 6f 75 pocket p rod clou
0050 64 6f 70 73 06 6d 6f 7a 67 63 70 03 6e 65 74 00 dops-moz gcp net
0060 00 01 00 01

TCP FILTER

The image shows a Wireshark capture of TCP traffic. The filter bar at the top is set to 'tcp'. The packet list pane shows several TCP segments. The packet details pane shows the structure of a TCP segment, including the Ethernet II header, Internet Protocol Version 4 header, and Transmission Control Protocol header. The packet bytes pane shows the raw data of the packet.

No.	Time	Source	Destination	Protocol	Length	Info
69	4.213507	172.16.48.32	34.120.237.76	TCP	66	22656 → 443 [SYN] Seq=0 Win=64240 Len=0 MSS=1460 WS=256 SACK_PERM=1
74	4.239470	34.120.237.76	172.16.48.32	TCP	66	443 → 22656 [SYN, ACK] Seq=0 Ack=1 Win=65535 Len=0 MSS=1250 SACK_PERM=1 WS=256
75	4.239516	172.16.48.32	34.120.237.76	TCP	54	22656 → 443 [ACK] Seq=1 Ack=1 Win=66048 Len=0
76	4.240093	172.16.48.32	34.120.237.76	TCP	1304	22656 → 443 [ACK] Seq=1 Ack=1 Win=66048 Len=1250 [TCP segment of a reassembled PDU]
77	4.240093	172.16.48.32	34.120.237.76	TCP	1304	22656 → 443 [ACK] Seq=1251 Ack=1 Win=66048 Len=1250 [TCP segment of a reassembled PDU]
78	4.240093	172.16.48.32	34.120.237.76	TLSv1.3	76	Client Hello
82	4.262994	34.120.237.76	172.16.48.32	TCP	60	443 → 22656 [ACK] Seq=1 Ack=1251 Win=268544 Len=0
83	4.263054	34.120.237.76	172.16.48.32	TCP	66	[TCP Dup ACK 82#1] 443 → 22656 [ACK] Seq=1 Ack=1251 Win=268544 Len=0 SLE=2501 SRE=2523
84	4.263054	34.120.237.76	172.16.48.32	TCP	60	443 → 22656 [ACK] Seq=1 Ack=2523 Win=267520 Len=0
97	4.342525	34.120.237.76	172.16.48.32	TLSv1.3	266	Server Hello, Change Cipher Spec, Application Data
98	4.343966	172.16.48.32	34.120.237.76	TLSv1.3	118	Change Cipher Spec, Application Data
100	4.344949	172.16.48.32	34.120.237.76	TLSv1.3	146	Application Data
101	4.345072	172.16.48.32	34.120.237.76	TLSv1.3	478	Application Data
102	4.345554	172.16.48.32	34.120.237.76	TLSv1.3	319	Application Data

> Frame 69: 66 bytes on wire (528 bits), 66 bytes captured (528 bits) on interface 0
> Ethernet II, Src: Chongqin_7b:87:89 (c0:b5:d7:7b:87:89), Dst: ExtremeM_Id:87:d0 (00:04:96:1d:87:d0)
> Internet Protocol Version 4, Src: 172.16.48.32, Dst: 34.120.237.76
> Transmission Control Protocol, Src Port: 22656, Dst Port: 443, Seq: 0, Len: 0

0000 00 04 96 1d 87 d0 c0 b5 d7 7b 87 89 00 00 45 00{....E
0010 00 34 2b a5 40 00 00 06 e3 29 ac 10 30 20 22 78 4+@....)0 "x
0020 ed 4c 58 00 01 bb 24 65 6f 93 00 00 00 00 00 02 LX...\$e o.....
0030 fa f0 99 f6 00 00 02 04 05 04 01 03 03 00 01 01
0040 04 02

TELNET FILTER

Wi-Fi

File Edit View Go Capture Analyze Statistics Telephony Wireless Tools Help

telnet

Expression...

No.	Time	Source	Destination	Protocol	Length	Info
2518	29.911894	213.136.8.188	172.16.48.32	TELNET	60	Telnet Data ...
2520	30.143728	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2643	36.583816	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2878	46.580581	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2883	46.914646	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2905	47.728496	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2920	48.175558	213.136.8.188	172.16.48.32	TELNET	1042	Telnet Data ...
2922	48.246651	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2924	48.315916	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2928	48.382253	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2929	48.412264	213.136.8.188	172.16.48.32	TELNET	256	Telnet Data ...
2932	48.514903	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2934	48.580614	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2935	48.588142	213.136.8.188	172.16.48.32	TELNET	518	Telnet Data ...
2937	48.714474	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2939	48.764828	213.136.8.188	172.16.48.32	TELNET	780	Telnet Data ...
2942	48.851839	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2947	48.921895	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2952	48.980866	213.136.8.188	172.16.48.32	TELNET	518	Telnet Data ...
2954	49.049140	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2962	49.123751	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2966	49.183177	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2967	49.205217	213.136.8.188	172.16.48.32	TELNET	256	Telnet Data ...
2969	49.316347	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2971	49.378938	213.136.8.188	172.16.48.32	TELNET	780	Telnet Data ...
2973	49.580853	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2974	49.517598	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2976	49.585182	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2977	49.610425	213.136.8.188	172.16.48.32	TELNET	256	Telnet Data ...
2985	49.718708	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
2988	49.787778	213.136.8.188	172.16.48.32	TELNET	1304	Telnet Data ...
3080	49.783081	213.136.8.188	172.16.48.32	TELNET	518	Telnet Data ...

> Frame 2518: 60 bytes on wire (480 bits), 60 bytes captured (480 bits) on interface 0

> Ethernet II, Src: ExtremeM_id:87:00 (00:04:96:1d:87:00), Dst: Chongqin_7b:87:89 (c0:b5:d7:7b:87:89)

> Internet Protocol Version 4, Src: 213.136.8.188, Dst: 172.16.48.32

> Transmission Control Protocol, Src Port: 23, Dst Port: 10158, Seq: 1, Ack: 1, Len: 6

0000 c0 b5 d7 7b 87 89 00 04 96 1d 87 d0 08 00 45 00 ...{.....E-

0010 00 2e 18 20 40 00 2b 06 7d 35 d5 88 08 bc ac 10 ...@+;5.....

0020 30 20 00 17 27 ae 6e 3f 1a ef 4d 37 bd 7f 50 18 0 ...n? .H? p

0030 01 f6 78 f0 00 00 1b 5b 48 1b 5b 4a ...x...[H[]

Telnet: Protocol

Packets: 3371 - Displayed: 78 (2.3%) - Dropped: 0 (0.0%)

Profile: Default

Type here to search

17°C Haze 1043 13-02-2025