RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS

A2

Started on	Saturday, 10 October 2026, 1:48 PM
State	Finished
Completed on	Saturday, 10 October 2026, 1:49 PM
Time taken	48 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n, k;
    scanf("%d", &n);

    int A[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }

    scanf("%d", &k);

    int i = 0, j = 1;

    while (i < n && j < n) {
        int diff = A[j] - A[i];

        if (i != j && diff == k) {
            printf("1");
            return 0;
        }

        if (diff < k) {
            j++;
        } else {
            i++;
            if (i == j) {
                j++;
            }
        }
    }

    printf("0");
    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS

A2

Started on	Saturday, 10 October 2026, 1:46 PM
State	Finished
Completed on	Saturday, 10 October 2026, 1:47 PM
Time taken	1 min 55 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Given an array A of sorted integers and another non negative integer k, find if there exists 2 indices i and j such that A[j] - A[i] = k, i != j.

Input Format:

First Line n - Number of elements in an array

Next n Lines - N elements in the array

k - Non - Negative Integer

Output Format:

1 - If pair exists

0 - If no pair exists

Explanation for the given Sample Testcase:

YES as 5 - 1 = 4

So Return 1.

For example:

Input	Result
3 1 3 5 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>

int main() {
    int n, k;
    scanf("%d", &n);

    int A[n];

    for (int i = 0; i < n; i++) {
        scanf("%d", &A[i]);
    }

    scanf("%d", &k);

    int i = 0, j = 1;

    while (i < n && j < n) {
        int diff = A[j] - A[i];

        if (i != j && diff == k) {
            printf("1\n");
            return 0;
        }
        else if (diff < k) {
            j++;
        }
        else {
            i++;
            if (i == j) {
                j++;
            }
        }
    }

    printf("0\n");

    return 0;
}
```

	Input	Expected	Got	
✔	3 1 3 5 4	1	1	✔
✔	10 1 4 6 8 12 14 15 20 21 25 1	1	1	✔
✔	10 1 2 3 5 11 14 16 24 28 29 0	0	0	✔
✔	10 0 2 3 7 13 14 15 20 24 25 10	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS

A2

Started on	Saturday, 12 September 2026, 2:30 PM
State	Finished
Completed on	Saturday, 12 September 2026, 2:30 PM
Time taken	36 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array
2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
    int n1, n2;

    if (scanf("%d", &n1) != 1) return;
    int *arr1 = (int *)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &arr1[i]);
    }

    if (scanf("%d", &n2) != 1) {
        free(arr1);
        return;
    }
    int *arr2 = (int *)malloc(n2 * sizeof(int));
    for (int i = 0; i < n2; i++) {
        scanf("%d", &arr2[i]);
    }

    int i = 0, j = 0;
    int first = 1;

    while (i < n1 && j < n2) {
        if (arr1[i] == arr2[j]) {
```

```
            if (!first) {
                printf(" ");
            }
            printf("%d", arr1[i]);
            first = 0;
            i++;
            j++;
        } else if (arr1[i] < arr2[j]) {
            i++;
        } else {
            j++;
        }
    }
    printf("\n");

    free(arr1);
    free(arr2);
}

int main() {
    int t;
    if (scanf("%d", &t) != 1) {
        return 0;
    }

    while (t--) {
        solve();
    }

    return 0;
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS A2

Started on	Saturday, 12 September 2026, 2:27 PM
State	Finished
Completed on	Saturday, 12 September 2026, 2:28 PM
Time taken	43 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find the intersection of two sorted arrays.

OR in other words,

Given 2 sorted arrays, find all the elements which occur in both the arrays.

Input Format

· The first line contains T, the number of test cases. Following T lines contain:

1. Line 1 contains N1, followed by N1 integers of the first array

2. Line 2 contains N2, followed by N2 integers of the second array

Output Format

The intersection of the arrays in a single line

Example

Input:

1

3 10 17 57

6 2 7 10 15 57 246

Output:

10 57

Input:

1

6 1 2 3 4 5 6

2 1 6

Output:

1 6

For example:

Input	Result
1 3 10 17 57 6 2 7 10 15 57 246	10 57

Answer: (penalty regime: 0 %)

```
#include <stdio.h>
#include <stdlib.h>

void solve() {
    int n1, n2;

    // Read the size and elements of the first array
    if (scanf("%d", &n1) != 1) return;
    int *arr1 = (int *)malloc(n1 * sizeof(int));
    for (int i = 0; i < n1; i++) {
        scanf("%d", &arr1[i]);
    }

    // Read the size and elements of the second array
    if (scanf("%d", &n2) != 1) {
        free(arr1);
        return;
    }
    int *arr2 = (int *)malloc(n2 * sizeof(int));
    for (int i = 0; i < n2; i++) {
        scanf("%d", &arr2[i]);
    }
```

```
    }

    // Two-pointer intersection logic
    int i = 0, j = 0;
    int first = 1; // Flag to format space-separated output properly

    while (i < n1 && j < n2) {
        if (arr1[i] == arr2[j]) {
            if (!first) {
                printf(" ");
            }
            printf("%d", arr1[i]);
            first = 0;

            i++;
            j++;
        } else if (arr1[i] < arr2[j]) {
            i++; // Advance pointer for smaller element
        } else {
            j++; // Advance pointer for smaller element
        }
    }
    printf("\n");

    // Clean up memory for the current test case
    free(arr1);
    free(arr2);
}

int main() {
    int t;
```

	Input	Expected	Got	
✔	1 3 10 17 57 6 2 7 10 15 57 246	10 57	10 57	✔
✔	1 6 1 2 3 4 5 6 2 1 6	1 6	1 6	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS

A2

Started on	Saturday, 12 September 2026, 2:26 PM
State	Finished
Completed on	Saturday, 12 September 2026, 2:27 PM
Time taken	53 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int main() {
    int n;

    // Read the total number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 0;
    }

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
            return 0;
        }
    }

    // Floyd's Cycle Detection (Tortoise and Hare)
    // Start both at the beginning position
    int tortoise = arr[0];
    int hare = arr[0];

    // Phase 1: Find the intersection point inside the cycle
    do {
        tortoise = arr[tortoise];       // Moves 1 step
        hare = arr[arr[hare]];          // Moves 2 steps
    } while (tortoise != hare);

    // Phase 2: Find the entrance to the cycle (the duplicate number)
    tortoise = arr[0];                  // Reset tortoise to the start
    while (tortoise != hare) {
        tortoise = arr[tortoise];       // Both move 1 step now
        hare = arr[hare];
    }

    // The entry point of the cycle is the duplicate value
    printf("%d\n", tortoise);

    // Clean up memory
    free(arr);
    return 0;
}

```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course

RAJALAKSHMI ENGINEERING COLLEGE

A Harshita 251801098-2025-AIDS

A2

Started on	Saturday, 12 September 2026, 2:25 PM
State	Finished
Completed on	Saturday, 12 September 2026, 2:26 PM
Time taken	36 secs
Marks	1.00/1.00
Grade	**10.00** out of 10.00 (**100**%)

Question 1 | Correct Mark 1.00 out of 1.00

Find Duplicate in Array.

Given a read only array of n integers between 1 and n, find one number that repeats.

Input Format:

First Line - Number of elements

n Lines - n Elements

Output Format:

Element x - That is repeated

For example:

Input	Result
5 1 1 2 3 4	1

Answer: (penalty regime: 0 %)

```c
#include <stdio.h>
#include <stdlib.h>

int main() {
    int n;

    // Read the number of elements
    if (scanf("%d", &n) != 1 || n <= 0) {
        return 0;
    }

    int *arr = (int *)malloc(n * sizeof(int));
    for (int i = 0; i < n; i++) {
        if (scanf("%d", &arr[i]) != 1) {
            free(arr);
            return 0;
        }
    }

    // Floyd's Cycle Detection (Tortoise and Hare)
    // Start both at the first element index
    int tortoise = arr[0];
    int hare = arr[0];

    // Phase 1: Find the intersection point inside the cycle
    do {
        tortoise = arr[tortoise];       // Moves 1 step
        hare = arr[arr[hare]];          // Moves 2 steps
    } while (tortoise != hare);

    // Phase 2: Find the entrance to the cycle (the duplicate number)
    tortoise = arr[0];                  // Reset tortoise to start
    while (tortoise != hare) {
        tortoise = arr[tortoise];       // Both move 1 step now
        hare = arr[hare];
    }

    // The entry point is the duplicate value
    printf("%d\n", tortoise);

    // Clean up memory
    free(arr);
    return 0;
}

```

	Input	Expected	Got	
✔	11 10 9 7 6 5 1 2 3 8 4 7	7	7	✔
✔	5 1 2 3 4 4	4	4	✔
✔	5 1 1 2 3 4	1	1	✔

Passed all tests! ✔

Correct

Marks for this submission: 1.00/1.00.

Back to Course