


Internet Control Message Protocol (ICMP)


Introduction

- The IP protocol has no error-reporting or error correcting mechanism.
- What happens if something goes wrong? What happens if a router must discard a datagram because it cannot find a router to the final destination, or because the time-to-live field has a zero value?
- These are examples of situations where an error has occurred and the IP protocol has no built-in mechanism to notify the original host.

Position of ICMP in the network layer



ICMP encapsulation




ICMP

- ICMP messages are divided into two broad categories:
 - error-reporting messages
 - query messages.
- The error-reporting messages report problems that a router or a host (destination) may encounter when it processes an IP packet.
- The query messages, which occur in pairs, help a host or a network manager get specific information from a router or another host.


Table 9.1 *ICMP messages*

<i>Category</i>	<i>Type</i>	<i>Message</i>
Error-reporting messages	3	Destination unreachable
	4	Source quench
	11	Time exceeded
	12	Parameter problem
	5	Redirection
Query messages	8 or 0	Echo request or reply
	13 or 14	Timestamp request or reply

General format of ICMP messages



ICMP Parameter Message Format




Type	Code	Meaning
0	0	Echo Reply
3	0	Net Unreachable
	1	Host Unreachable
	2	Protocol Unreachable
	3	Port Unreachable
	4	Frag needed and DF set
	5	Source route failed
	6	Dest network unknown
	7	Dest host unknown
	8	Source host isolated
	9	Network admin prohibited
	10	Host admin prohibited
	11	Network unreachable for TOS
	12	Host unreachable for TOS
	13	Communication admin prohibited
4	0	Source Quench (Slow down/Shut up)

Type	Code	Meaning
5	0	Redirect datagram for the network
	1	Redirect datagram for the host
	2	Redirect datagram for the TOS & Network
	3	Redirect datagram for the TOS & Host
8	0	Echo
9	0	Router advertisement
10	0	Router selection
11	0	Time To Live exceeded in transit
	1	Fragment reassemble time exceeded
12	0	Pointer indicates the error (Parameter Problem)
	1	Missing a required option (Parameter Problem)
	2	Bad length (Parameter Problem)
13	0	Time Stamp
14	0	Time Stamp Reply
15	0	Information Request
16	0	Informaiton Reply
17	0	Address Mask Request
18	0	Address Mask Reply
30	0	Traceroute (Tracert)


Note

ICMP always reports error messages to the original source.

Error-reporting messages



Contents of data field for the error message



Destination-unreachable format

Type: 3	Code: 0 to 15	Checksum
Unused (All 0s)		
Part of the received IP datagram including IP header plus the first 8 bytes of datagram data		

Note

Destination-unreachable messages with codes 2 or 3 can be created only by the destination host.

Other destination-unreachable messages can be created only by routers.

Source-quench format

Type: 4	Code: 0	Checksum
Unused (All 0s)		
Part of the received IP datagram including IP header plus the first 8 bytes of datagram data		

Note

A source-quench message informs the source that a datagram has been discarded due to congestion in a router or the destination host.

The source must slow down the sending of datagrams until the congestion is relieved.

Note

One source-quench message is sent for each datagram that is discarded due to congestion.

Note

Whenever a router decrements a datagram with a time-to-live value to zero, it discards the datagram and sends a time-exceeded message to the original source.

Note

When the final destination does not receive all of the fragments in a set time, it discards the received fragments and sends a time-exceeded message to the original source.

Time-exceeded message format

Type: 11	Code: 0 or 1	Checksum
Unused (All 0s)		
Part of the received IP datagram including IP header plus the first 8 bytes of datagram data		

Note

In a time-exceeded message, code 0 is used only by routers to show that the value of the time-to-live field is zero.

Code 1 is used only by the destination host to show that not all of the fragments have arrived within a set time.


Note

A parameter-problem message can be created by a router or the destination host.

Parameter-problem message format

Type: 12	Code: 0 or 1	Checksum
Pointer	Unused (All 0s)	
Part of the received IP datagram including IP header plus the first 8 bytes of datagram data		

Redirection concept



Note

A host usually starts with a small routing table that is gradually augmented and updated.

One of the tools to accomplish this is the redirection message.

Redirection message format

Type: 5	Code: 0 to 3	Checksum
IP address of the target router		
Part of the received IP datagram including IP header plus the first 8 bytes of datagram data		

Note

A redirection message is sent from a router to a host on the same local network.

Note

***An echo-request message can be sent
by a host or router.***

***An echo-reply message is sent
by the host or router that receives
an echo-request message.***

Note

Echo-request and echo-reply messages can be used by network managers to check the operation of the IP protocol.

Note

***Echo-request and echo-reply messages
can test the reachability of a host.***

***This is usually
done by invoking the ping command.***

Echo-request and echo-reply message

Type 8: Echo request

Type 0: Echo reply

Type: 8 or 0	Code: 0	Checksum
Identifier		Sequence number
Optional data Sent by the request message; repeated by the reply message		

Timestamp-request and timestamp-reply message format

Type 13: request

Type 14: reply

Type: 13 or 14	Code: 0	Checksum
Identifier		Sequence number
Original timestamp		
Receive timestamp		
Transmit timestamp		

Note


Timestamp-request and timestamp-reply messages can be used to calculate the round-trip time between a source and a destination machine even if their clocks are not synchronized.

Note

The timestamp-request and timestamp-reply messages can be used to synchronize two clocks in two machines if the exact one-way time duration is known.

Example of checksum calculation

Figure shows an example of checksum calculation for a simple echo-request message. We randomly chose the identifier to be 1 and the sequence number to be 9. The message is divided into 16-bit (2-byte) words. The words are added together and the sum is complemented. Now the sender can put this value in the checksum field.



8 & 0	→	00001000	00000000
0	→	00000000	00000000
1	→	00000000	00000001
9	→	00000000	00001001
T & E	→	01010100	01000101
S & T	→	01010011	01010100
Sum	→	10101111	10100011
Checksum	→	01010000	01011100

DEBUGGING TOOLS

We introduce two tools that use ICMP for debugging: ping and traceroute.

✓ Ping

✓ Traceroute

Example

We use the ping program to test the server fhda.edu. The result is shown below:

```
$ ping fhda.edu
PING fhda.edu (153.18.8.1) 56 (84) bytes of data.
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=0    ttl=62    time=1.91 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=1    ttl=62    time=2.04 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=2    ttl=62    time=1.90 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=3    ttl=62    time=1.97 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=4    ttl=62    time=1.93 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=5    ttl=62    time=2.00 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=6    ttl=62    time=1.94 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=7    ttl=62    time=1.94 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=8    ttl=62    time=1.97 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=9    ttl=62    time=1.89 ms
64 bytes from tiptoe.fhda.edu (153.18.8.1): icmp_seq=10   ttl=62    time=1.98 ms

--- fhda.edu ping statistics ---
11 packets transmitted, 11 received, 0% packet loss, time 10103 ms
rtt min/avg/max = 1.899/1.955/2.041 ms
```


Example

For the second example, we want to know if the adelphia.net mail server is alive and running. The result is shown below: Note that in this case, we sent 14 packets, but only 13 have been returned. We may have interrupted the program before the last packet, with sequence number 13, was returned.

```
$ ping mail.adelphia.net
PING mail.adelphia.net (68.168.78.100) 56(84) bytes of data.
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=0    ttl=48    time=85.4 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=1    ttl=48    time=84.6 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=2    ttl=48    time=84.9 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=3    ttl=48    time=84.3 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=4    ttl=48    time=84.5 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=5    ttl=48    time=84.7 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=6    ttl=48    time=84.6 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=7    ttl=48    time=84.7 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=8    ttl=48    time=84.4 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=9    ttl=48    time=84.2 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=10   ttl=48    time=84.9 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=11   ttl=48    time=84.6 ms
64 bytes from mail.adelphia.net (68.168.78.100): icmp_seq=12   ttl=48    time=84.5 ms

--- mail.adelphia.net ping statistics ---
14 packets transmitted, 13 received, 7% packet loss, time 13129 ms
rtt min/avg/max/mdev = 84.207/84.694/85.469
```

The traceroute program operation



Example

We use the traceroute program to find the route from the computer `voyager.deanza.edu` to the server `fhda.edu`. The following shows the result.

```
$ traceroute fhda.edu
```

```
traceroute to fhda.edu (153.18.8.1), 30 hops max, 38 byte packets
```

1	Dcore.fhda.edu	(153.18.31.25)	0.995 ms	0.899 ms	0.878 ms
2	Dbackup.fhda.edu	(153.18.251.4)	1.039 ms	1.064 ms	1.083 ms
3	tiptoe.fhda.edu	(153.18.8.1)	1.797 ms	1.642 ms	1.757 ms

Example

In this example, we trace a longer route, the route to xerox.com. The following is a partial listing.

```
$ traceroute xerox.com
```

```
traceroute to xerox.com (13.1.64.93), 30 hops max, 38 byte packets
```


1	Dcore.fhda.edu	(153.18.31.254)	0.622 ms	0.891 ms	0.875 ms
2	Ddmz.fhda.edu	(153.18.251.40)	2.132 ms	2.266 ms	2.094 ms
3	Cinic.fhda.edu	(153.18.253.126)	2.110 ms	2.145 ms	1.763 ms
4	cenic.net	(137.164.32.140)	3.069 ms	2.875 ms	2.930 ms
5	cenic.net	(137.164.22.31)	4.205 ms	4.870 ms	4.197 ms
6	cenic.net	(137.164.22.167)	4.250 ms	4.159 ms	4.078 ms
7	cogentco.com	(38.112.6.225)	5.062 ms	4.825 ms	5.020 ms
8	cogentco.com	(66.28.4.69)	6.070 ms	6.207 ms	5.653 ms
9	cogentco.com	(66.28.4.94)	6.070 ms	5.928 ms	5.499 ms

Network Layer – Routing Protocol




Anand Baswade
anand@iitbhilai.ac.in

Sources



Computer Networking: A Top-Down Approach




TCP/IP Protocol Suite

Network Layer: Internet

host, router network layer functions:

network
layer



Routing/Forwarding Table Example


Network Destination	Netmask	Gateway	Interface	Metric
101.25.67.0	255.255.255.0	10.0.0.2	eth3	1
default	0.0.0.0	10.0.0.1	eth0	0
192.25.67.0	255.255.255.0	10.0.0.3	eth5	10

Routing Protocol

Routing protocols

Routing protocol goal: determine “good” paths (equivalently, routes), from sending hosts to receiving host, through network of routers


- **path:** sequence of routers packets traverse from given initial source host to final destination host
- **“good”:** least “cost”, “fastest”, “least congested”
- routing: a “top-10” networking challenge!



Cont..

- Today, the Internet is so large that one routing protocol cannot handle the task of updating the routing tables of all routers. For this reason, the Internet is divided into autonomous systems.
- An autonomous system (AS) is a group of networks and routers under the authority of a single administration. Routing inside an autonomous system is called intra-domain routing. Routing between autonomous systems is called inter-domain routing

Autonomous systems




Legend

- AS Autonomous System
- Ethernet switch
- Point-to-point WAN
- Inter-system connection


AS140033 – Indian Institute of Technology Bhilai		
Country	 India	
Website	iitbhilai.ac.in	
Hosted domains	2	
Number of IPs	256	
ASN type	Education	
Allocated	2 years ago on May 16, 2020	
IP Address Ranges		
		IPv4 Ranges IPv6 Ranges
NETBLOCK	COMPANY	NUM OF IPS
103.147.138.0/24	 Indian Institute of Technology Bhilai	256

Popular routing protocols



RIP: Routing Information Protocol
OSPF: Open Shortest Path First
BGP: Border Gateway Protocol

Graph abstraction: link costs



$c_{a,b}$: cost of *direct* link connecting a and b

e.g., $c_{w,z} = 5$, $c_{u,z} = \infty$

cost defined by network operator:
could always be 1, or inversely related
to bandwidth, or inversely related to
congestion

graph: $G = (N, E)$

N : set of routers = $\{ u, v, w, x, y, z \}$

E : set of links = $\{ (u,v), (u,x), (v,x), (v,w), (x,w), (x,y), (w,y), (w,z), (y,z) \}$

Routing algorithm classification

