

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline Anti-Wear Hydraulic Oils VG 32, 46, 68, 100, 150, 220, 320

PRODUCT DESCRIPTION

Valvoline Anti-Wear Hydraulic Oils are high viscosity index, chemically stable, good quality mineral base oils which have been further fortified with anti-oxidant, anti-corrosion, anti-wear and anti-foam additives. They comply with the requirements of high pressure systems and also applications where high pump speeds are experienced.

APPLICATIONS

Valvoline Anti-Wear Hydraulic Oils are recommended as fluid media for hydraulic systems operating under moderate to severe operating conditions in stationary & mobile equipments where high pressure gear & vane pumps are used. These oils are also recommended for circulation, splash, ring oiling system of the bearings (both plain & antifriction), gears of industrial machinery, metal working equipments, servo controls and air compressor applications.

PERFORMANCE STANDARDS

DIN 51524 Part I

PERFORMANCE BENEFITS

- Outstanding anti-wear characteristics.
- High chemical stability to ensure long & trouble free service life.
- Excellent foam resistance.
- Good protection against rust & corrosion.
- Right viscosity to satisfy the requirement of hydraulic pumps & designed systems

TYPICAL CHARACTERISTICS

VALVOLINE ANTI-WEAR HYDRAULIC OILS

ISO VG	32	46	68	100	150	220	320
Kinematic Viscosity, cSt @ 40°C	32	46	68	100	150	220	320
Viscosity Index,min	95	95	95	95	90	90	90
Flash Point, COC, °C	220	220	228	238	230	242	256
Pour Point, °C,	-12	-12	-12	-9	-6	-6	-6
Rust Test D665, A&B, 24 hrs.	Pass	Pass	Pass	Pass	Pass	Pass	Pass
Emulsion Test, D-1401, 40-40-0, Minutes	15	15	25	25	25	25	30

Available Pack: Consult your Valvoline Representative

2/2017



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

