

PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

Valvoline AWH EHVI 46 & 68

PRODUCT DESCRIPTION

Valvoline AWH EHVI Oils are formulated from hydrocracked base stocks with inherent oxidation and thermal stability. The products are further fortified with antioxidant, antirust, antifoam and anti-wear additives, plus a special shear stable viscosity index improver which assists in maintaining viscosity under continuous use & severity of operation.

APPLICATIONS

Valvoline AWH EHVI Oils are recommended for all hydraulic applications including critical systems in industrial and mobile equipment using high pressure vane, gear & piston pumps. Valvoline AWH EHVI Oils are suitable for use in various types of earthmoving equipment.

Valvoline AWH EHVI Oils are recommended for all kinds of hydraulic systems & equipment's working onsite which are subjected to extreme temperature variation.

Valvoline AWH EHVI Oils are specially recommended for Excavators and other civil engineering, agriculture, marine, transport and other industrial application.

PERFORMANCE STANDARDS

- Denison HF-0, HF-1, HF-2
- DIN 51524 Part III
- ASTM D6158 HV
- Eaton Lubricant Specification EFDGN-TB002-E
- ISO 11158 HV

PERFORMANCE BENEFITS

- A shear-stable viscosity modifier ensures correct viscosity at operating temperatures.
- Wide temperature range of operation.
- Excellent anti-wear properties.
- Excellent resistance to oxidation.
- Good demulsibility.
- Good protection against rust & corrosion.
- Long service life.

TYPICAL CHARACTERISTICS

ISO VG	46	68
Kinematic Viscosity, cSt @ 40°C	46	68
Viscosity Index	155	151
Flash Point, COC, °C	224	210
Pour Point, °C	-33	-33
FZG Test, Pass Stages	11	12
Rust Test D665, A&B, 24 hrs.	Pass	Pass
Emulsion Test, D-1401, 40-40-0, minute	15	15

Available Pack: Consult your Valvoline Representative.

9/2021



Valvoline Cummins Pvt. Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins India Ltd.
3rd Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299
Visit us at: www.valvolinecummins.com

